
AD-A179 196 1/4 UNCLASSIFIED NL



. .

,

AD-A179 196

9 Ai - 1367

OPERATING LOCATION - A USAFETAC Air Weather Service (MAC)



REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS

MCCONNELL AFB KS MSC #724505 N 37 37 W 097 16 ELEV 1371 FT KIAB

PARTS A - F HOURS SUMMARIZED: 0000 - 2300 LST

PERIOD OF RECORD:

HOURLY OBSERVATIONS: JAN 77 - DEC 86

SUMMARY OF DAY DATA: DEC 53 - DEC 86

TIME CONVERSION GMT TO LST -6

"Approved for public release; FEDERAL BUILDING Distribution Unlimited." ASHEVILLE, N.C. 28801 - 2723



REVIEW AND APPROVAL STATEMENT

USAFETAC/DS-87/016, Mcconnell AFB KS RUSSWO April 1987, is approved for public release. There is no objection to unlimited distribution of this document to the public at large, or by the Defense Technical Information Center (DTIC) to the National Technical Information Service (NTIS).

This document has been reviewed and is approved for publication.

FOR THE COMMANDER

WALTER S. BURGMAN Scientific and Technical Information Program Manager

REPORT DOCUMENTATION PAGE

- Report Security Classification: UNCLASSIFIED la.
- 3. Distribution/Availability of Report: Approved for public release; Distribution unlimited.
- 4. Performing Organization Report Number: USAFETAC/DS-87/016.
- 5. Monitoring Organization Report Number: USAFETAC/DS-87/016.
- 6a. Name of Performing Organization: USAFETAC/OL-A
- Office Symbol: 6b.
- 6c. Address: Federal Building, Asheville, NC 28801-2723.
- 11 Title: (RUSSWO) Mcconnell AFB KS
- 12 Personal Author(s):
- 13a Type of Report: Data Summary
- 13b Time Covered: Dec 53-Dec 86.
- 14 Date of Report: Apr 87
- 15 Page Count: 312
- 16 Supplementary Notation:
- 17 COSATI Codes: Field--04, Group--02
- *climatology; *weather; meteorological conditions; winds; 18 <u>Subject Terms:</u> *climatology; *weather; meteorological conditions; winds; precipitation; temperature; visibility; barometric pressure; relative humidity; sky cover; psychrometric data; ceiling; Revised Uniform Summary of Surface Weather Observations (RUSSWO); Mcconnell AFB; Kansas; Wichita; USKS724505.
- 19 Abstract: A six-part statistical data summary of surface weather observations for: Mcconnell AFB KS. Summary consists of: PART A, Weather Conditions and Atmospheric Phenomena; PART B, Precipitation; PART C, Surface Winds; PART D, Ceiling and Visibility; PART E, Psychrometric Summaries; PART F, Pressure Summaries. See USAFETAC/TN-83/001 (ADAl 32186), An Aid for Using the Revised Uniform Summary of Surface Weather Observations (RUSSWO) for complete description of contents and instructions for use.
- 20 Distribution/Availability of Abstract: Same as report.
- 21 Abstract Security Classification: UNCLASSIFIED.
- Name of Responsible Individual: Marianne L. Cavanaugh Telephone: (618)256-2625 22a
- 22ъ
- 22c Office Symbol: USAFETAC/LDD

DD FORM 1473

UNCLASSIFIED

The number that identifies the station in this summary is an AWS Master Station Catalog number. This number is comprised of the WMO number with the addition of a suffix zero; or, in cases where there is no designated WMO number, a 5-digit number created in agreement with WMO rules, plus a sixth qualifying digit. These numbers (also referred to as DATSAV or USAFETAC numbers) uniquely identify each of more than 15,000 reporting stations around the world. This is the provenance of the number (e.g., MSC 999999) which will appear on future OL-A standard products.



NTIS	our led	X () ()	
By Drit ib	ation [
٨	vailability	Codes	
Dist A-1	Avail au Speci	d for al	
" /	Chi		

U S AIR IFFEE BINTROMBITAL TICHISTAL AFFILICATION FEBRIFIA

REVISED UNIFORM SUMMARY

OF SURFACE WEATHER OBSERVATIONS

HOURLY OBSERVATIONS

Hourly wheere I me are defined as those record or precard-special observations recorded at accorded hourly intervals.

DAILY OBSERVATIONS

itsity observations are selected from all data recorded on rejuriting force and combined into Summery of the Day observations. (Gelected from record-spueint, local, superry of the day, remarks, sic.)

DESCRIPTION OF SUMMARIES

Proceeding each section is a brief description of the data comprision curb part of the Sevissé Uniform Summary of Surface Veather Observations and the enterior of prescription. Telephone are prepared from lourly and vally observations recorded by stations operated by the U. U. Bervices and some turning stations using stations using stations using stations.

) ecu 01	iso maked the following somewrites are includ	ed for this election	
PART A	WEATHER CONDITIONS	PALLE	CARLT MAR, MIN, & MEAN TEMP
	ATMOSPHERIC PHENOMERA		FILLEME MAX & MIN TEMP
7 A 2 1 8	PRECIPITATION		FST CHEOMETRIC DET VS WET BULL
	INOWFALL		MEAN & STO DEV .
	!NOW DEPTH		CET BULB, WET BULB, & DEW POINTS
	SURFACE WINDS		ELLATIVE HUMIDITY
PARTO	CEILING VERSUS VISIBILITY	****	STA! OH PRESSURE
	IXYCOVER		STA LEVEL PRESSURE

STANDARD J.HOUR GROUPS

Att energy requiring diarnot variations are experied in etg. ()-low periods corresponding to the following sets of howely observative a consequency, 0; co-0701, coccomm, compliant, execution, 15co-1710, theorem, 21 to 2) to bear a local standard time.

MISSING HOUR GROUPS Commery wheels are unitted when stations eministing limited observing entending and not remort cartain three-hour particular

wonth during the available period of observations.	f record . How bearing events are it	eled below, and are applicable to all	evamentes prepared from hourly
. WHURHY	ACCIL		or.lonx
FEBRUARY	MAT	A 2 - 2 -	MONTHUM
INICH	/ 	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	WITHU

0392	3	M DOWN APB KANSAS		1: 3		. 404 - 10 17 - 16	1371	IAB]	WMO NUMPER
		STATION LOCATION	A NC	ND II	NSTRU	MENT	ATION	HISTO	RY	···
CAT-ON		Up CHARM UAL COTATION & NAME	TEPE OF STATION	AT THIS I	CCATION TO	er rupt	CONGITUDE	ELEVATION /	BOVE MSL	OBS PER DAT
1 2 3 4 5 6 7,	Me orane dame anne danc danc danc dame dame dame dame	ell A, wichita Kansas	APP same same same same same same same	Nov 53 Apr 55 Apr 58 Apr 59 Cet 61 Apr 64 Apr 69 Jan 74 Jan 79	Mar 55 Mar 59 .ep 61 Mar 64 Mar 69 Dec 73 Dec 76 May	i. 37 37 ame fame fame ame ame ame ame	W 097 16 Same Same Same Same Same Same Same	1	1384 1388 Same 1352 1355 1381 1357 Same Same	24 24 24 24 24 24 24 24
wp[p	DATE	SURFACE WIND	EGUIPMENT	INFORMATION		!	\			
CATION	CHANTE	LOCATION		TYPE OF TRANSMITT	*** CF	HT ABOVE	REMARKS, AC	DITIONAL EQUIPMI	INT OR REA	SON FOR CHA!
1	15.8 53 5 Apr 55	blde.	eration		a.e	70 ft 70 ft				
	1 - 2 54 1 - 34 : 6 1	Invoated 100 ft H of wx strict parachute tower. Invoated 5700 ft H of wx strict of approach end of m life ft H of centerline of w.	tn, 30 nwy 301	A5√39,	- il	50 ft				
5	: Apr 64	<pre>mal instrumented :- 1/cated approach and :-</pre>	•		- 1 ₆ 3 - 11 - 1-2	1	ı			
	TAC FURW	Located approach end	or rnw,	ame		16 ft				

STATION	HAMMUZ MC Se	Mar N NAME		CATIT	uce ,	CAST OF	FIELD ELEV	(FT) CAL	LSIGN	WMO NUMPER
0392	23	MI SHELL AFB KANSAS		№ 3	7 37	∷ J •7 16	1371		IAB	
		STATION LOCATION	A NC	ND II	NSTRU	JMENT	TATION	HIS	TORY	
NUMBER TE LOCATION		JEWORAPH JAL COTATION & MARKE	TYPE OF STATION	AT THIS I	LOCATION	, ATHTUDE	LONGITUDE	ELEVA FIELD (FT	TION ABOVE MSL	JBS PER DAT
1 2 3 4 5 6 7 8 9	MecConne Same Same Same Same Same Same Same	all Acc, Wichita Kansas	Same Same Same Same	Mov 53 Apr 55 Apr 58 Apr 59 Oct 61 Apr 64 Apr 69 Jan 74 Jan 79	Mar 55 Mar 58 Mar 59 Sep 61 Mar 64 Mar 69 Dec 73 Dec 76 Mar 67	: 37 37 same same same same same same same	W 097 16 Same Same Same Same Same Same Same	1362 1374 1371 Same Same Same Same Same	1384 1388 Same 1352 1355 1381 1357 Same Same	24 24 24 24 24 24 24 24 24
· Maga	DATE	SURFACE WIND	EGUIPMENT	INFORMATION						
LOCATION	OHANGE	LOCATION		TYPE OF TRANSMITT	1796 GF E+ RECORER	HT ABOVE	REMARKS. AE	DITIONAL ED	DUIPMENT OR RE	ASON FOR CHANGE
1 2	Nov 53 5 Apr 55	Located on roof of HQ blde Located on top of base open blder.		AN/GM,	,-1 ·e	70 ft 70 ft	·			
į.	3 4; r 50	incated 100 ft % of wx str of parachute tower.	n on to	ame		50 Et	-			
.;	. Au + 6 -	Excated 5700 ft 8 of wx st ft 8 of approach end of rn 11 3 ft 8 of centerline of	гму Зы	1	- ili	la £t				
5	3 Apr 64		of r nwy	11.7.34,	(, = 2/1	: Is it	<u>.</u>			
		2. Located approach end	of rnwy	ļ		16 ft	<u>.</u>			

CLATINUED ON REVERSE SIDE

USAFETAC FORM S 9 TOLAL PRESTUS TOTAL AM ALL A

ER	DATE	SURFACE WIND EQUIPMENT INF				
10M	OF CHANGE	LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	REMARKS. ADDITIONAL EQUIPMENT. OR REASON FOR CHANGE
_		18				
-	21 Apr69	Dual Instrumented		,		
- {	- }	1. Same	A11/3000-2	0 RC-363	13 ft	
	1	2. Same	AN/014, ~20	}	16 ft	
1	Jan 71	Dual Instrumented	}			
- 1	ſ	1. Located 1100 ft E of centerlin	e Jame	Same	13 ft	
1)	3355 ft from end of rnwy 36R.	(
- 1		2. Located 550 ft E of centerline	, ame		16 ft	
-	ł	1400 ft from end of rnwy 18L.	į			
	Dec 78	1. Same	Same	Same	13 ft	
		2. Same	Same		16 ft.	
1	Mar 87	1. Same	Same	Same	13 ft	
1	}	2. Same	Same]	16 ft	
-	1					
	1			}		
1	j					
1	1		ļ	1		•
1	1		}	i	·	
1	1		}	}		
1			1	 	}	
-	Í		}		{	
1	1		1	ĺ		
ł	1		ſ	1		{
ł	ł		l .]		
ì	1		}	})	
1	1			}	}	
١	j			Ì		
1	}		l	l		
1	}		ļ	1	[
ı	}		1	1		
1	1		1	ł		
1	j			·		
1	ļ		1	[.		
ł	ŀ		1	[
1	ł		1]		
1	1		1	}]	
1	ì		1			
Ţ	j		1			
Į	j		1	1		
1	j		Ĭ	j !		
1	1]	ļ i		
J	į.		1	1		

US AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

A

PART A

WEATHER CONDITIONS

This summary is a percentage frequency occurrence of various atmospheric phenomena and obstructions to vision, derived from hourly observations, and is presented in two tables as follows:

- 1. By month and annual, all hours and years combined.
- 2. By mouth, all years combined, by stendard 3-hour groups.

A percent value of ".0" in these tables indicates less then .05 percent, which is usually only one occurrence. The various phenomena included in each category on the forms are listed below:

Thunderstorms - All reported occurrences of thunderstorm, tornado, and waterspout.

Rain and/or drizzle - All liquid precipitation, falling to the ground, not freezing.

Freezing rain and/or freezing drizzle (glaze) - Precipitation falling in liquid form, but freezing on contact with an unheated surface.

Snow and/or sleet (ice pellets) - Included are snow, snow pellets, sleet, snow grains, ice crystals, and ice pellets from Jan 68 ami later. (Snow pellets also known as soft hail)

Hail - Occurrences of hail and small hail are included.

Percentage of observations with precipitation - Included in this category are the observations when one or more of the above phenomena occurred. Since more than one type of precipitation may be reported in the same observation, the sums of the individual categories may exceed the percentages of the observations with precip.

Fog - Included are fog, ice fcg, and ground fog.

Smoke and/or haze - Occurrences of smoke, haze, or combinations of smoke and haze are included.

Blowing snow - Occurrences of blowing snow (also drifting snow when reported from non-WRAN sources).

Dust and/or sand - Included are blowing dust, blowing sand, and dust.

Continued on Reverse

Blowing spray - This item if reported, is not shown in a separate category on this form but is included in the computation Percentage of Observations with Obstructions to Vision, below.

Percentage of observations with obstructions to vision - Included in this category are the observations when one or more of the above obstructions to vision occurred. Since more than one type of obstruction may be reported in the same observation, the sums of the individual categories may exceed the percentage total columns. Also, although precipitation may reduce visibility, it is not considered an obstruction to vision for purposes of this summary; therefore, the percentage total of obstructions to vision need not reflect the total observations with reduced visibility.

PART A

The state of the s

THE REPORT OF THE PARTY OF THE

ATMOSPHERIC PHENOMENA

This summary is a presentation of the percentage of days with occurrence of various atmospheric phenomena. These data are obtained from all recorded information on the reporting force or from hourly data and to make into a daily observation.

The descriptions of the phenomena in the Weather Conditions Summary shove also apply for the categories summarized in these daily tabulations. However, it should be noted that in this summary the columns headed "# OF OBS WITH PRECIP" and "# OF OBS WITH OBST TO VISION" show the percentage of days rather than the percentage of observations. Since more than one type of precipitation or more than one type of obstruction may occur in the same daily observation, the sum of the values in the individual categories may differ from the total columns.

A percent value of ".0" in the table indicates less than .05 percent, which is usually only one occurrence.

This presentation is by month with annual totals, and is prepared with all years combined.

- NOTES: (1) A day with rain and/or drizzle was not separately reported in the WBAN data prior to year 1949.
 Therefore, percentages in this column are restricted to the period Jan 1949 and later.
 - (2) A day with freezing rain and/or freezing drizzle is also properly reported as a day with rain and/or drizzle.
 - (3) A day with dust and/or sand is included in this summary anly when visibility is reduced to less than 5/8 mile.

φ •, ·	HCURS ↓1.1	THUNDER STORMS	RAIN AND OR ERIZZIE	FREEZING RAIN & TR CRIZZLE		MAIL	OF GREWITH PRECIP	FOG.	SMOKE ANT OR MAIE	BLC WING SNOW	DUST AND OP SANO	S. OF OBS WITH OBST TO VISION	1014L NO 11 OF
•			•	,			•	•					
				•	٠			•	. •	•	• :		
							• .	. •	•	•			
	-			•			•	• .	•	٠			
		•	•				. •		•		•		
		•					. •	٠.	•	•	•		
							• .	1	•				
			٠				•	. •	•	. •			
											·		
							1 1					± ±	

WEATHER CONDITIONS

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	°= OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND DE SAND	CE THE WITH OBST TO VICTOR	· · · ·
		• 1	· • •				:. •		• .				
		<u> </u>	4.	1			· · · · ·		·•				-
				1.				. ,	<u> </u>	 .		•	٠
										. •	,		
	1 -:	• 1	4					•	••			· · .	••
	: -:				•			1.41					•
		•	ч.:	•	• 4			1: •					-
	1-43		1	• i	·		, i.i.	1	. •	•			•
			+··-										
		·					·· !-			-			
			:				=1===	.,				, ,	
TOTALS			4.					. •	•		•		÷

NAVWEASERVCOM

•

The second secon

V 10	4	THE POLICE OF TH	** ** **: *	1411 N. 16 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	\$4 - 5 - 25 2			# *! 	* * *	2	# # \ # 1	
											• •	
											•	
			•			•	•	•				
			,				•	•		٠		
			,			٠	•	•		•	· • .	
		-				•	•				•	
		•	•				. •	•		•	· · · .	
		•	•				•				. : .	

TOTALS

A TITAL DO NOT SEE

WEATHER CONDITIONS

STATION NAME

STATION NAME

YEARS

TO A STEER SECTION OF THE COLUMN AND LIFE AND THE COLUMN AND THE COLUMN ASSETS THE COLUMN ASSETS TO SECTION ASSETS.

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	8LOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBS! TO VISION	* 1.* A. N * F
	. ·		• •						•				
		1.0	···						-				
		1.4	1				,	• *					
	1		• .				•		. •			•	
	4 - 7 ,	•						• .					
	1	1.	. . •			• '	. · .	٠.			٠		
		•						•				. · .	
	1-1,	. •	. ••		• ,		. •		, •		•	· .	,
			•				•						
		•											
	•	· · -	•						-				,
	.	·		*:=:	,		, ,		:				1
TOTALS		<u> </u>	. 4			•	•	. •	. •				

STATION NAME

YE 4 85

MONTH

MONTH	HOURS LST	THUNDER STORMS	RAIN AND OR ORIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	PAIL	OF OBS WITH PRECIP	fOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	° OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
								•	. •				
									. •				
		•				•	•	. •	•				÷
	- ,	. • •	• •				-	•	٠				
			•				•	• •	٠				
			•				•	•	-		-		
	. •	• •					•	•	• •			· ·	
	. ! -		•	-		•	• .	•	•		-	•	-
	-											•	
	٠	÷									•		
	•	-									-		
TOTALS	•				•			. 1		t 1		•	

CONTRACTOR IN AL

WEATHER CONDITIONS

STATION	STATION NAME	RS
	For Constant (Fig.) and the property of the constant of the c	

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	° OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
	- 1,2	•1					. • .				<u>.</u> :		
-	<u>-</u>	• •			,		. • .	• 1	1.				
	· -	<u> </u>	• -					• • •		. ,			
	1							•					
	1 - '	· · ·	•,					•	•				
	'		. • "					•	•		=		
	`.	• • •						•	. •			· .	
	1 = 2	•	. •				•	•					
							•				•		
	•	• .											
	•	•			1		1 4		:	1 :		ş ,	
TOTALS		<u> </u>						• .			•		

WEATHER CONDITIONS

•		,	
STATION	STATION NAME		TEARS

(a) 1860. Find a Community of the Community

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	PAIL	OF OBS WITH PRECIP	500	SMOKE AND OR HAZE	BLOWING	DUST AND SP SAND	1 (24 185 With 185* TO VI (180	7 - 1 A
,								• .					
		·	. •••					•	٠.				
		1.						•			•		
	- 11		•				• .	• .				•	
		• **	•				•	•					
	-		•				•						
	-		• •				•	• 1	•				
		4	• •					٠	•				
													,
	•												
									t			. :	,
TOTALS			<u> </u>									•	

	· ·		
5161 8	STAT M NAME	****	• •
	•		

W -NTH	HOURS (ST		7#12212	PREEZING PAINS OF 2718		1.00		****	• •	414	The second secon
	-				,				-		-· •
			•			•	•				
			•			• .	•				
	. - .	. •	•				•	•			
						•	• •	•			•
								•			
										•	
						•				•	•
1											
, -											
TOTALS											

w. h.te		STORMS	19 ZZ:r	FREEZ NOV. 1984 1984 RAINA HOLAND 1997 1987 2748	e A	B value		M. HE AN IN HAZE	Pro A No. 1		14 - 185 We the 1585 to 1 150	
							•					
	-		•							•		
		. •	-									
							٠	•			•	
		٠	•					•		•		
		. • :					-	•		• •	• .	
		•						•				
		•	•				٠	•				
												,
•												•
,	•			•	•	•		•	••		•	,
totais				• •			. •				* *	1

STATION NAME

YEARS

NORTH

CONTACT FOR CONTRACTOR CONTRACTOR

HTMCM	HOURS LST,	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	°+ OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
	<u>.</u> - '		• *!					1_ •	• 4	*	•••	1 .	
		••	11.1				. •	: • 5_	·	· ·	•		2
			• •		٠.	-		. • 5	<u></u>			· ··	
		• 1.	. •				· · .	• •				. • .	:
	·	·`.						•	• •		•	1	
	- 1	. • • •					· · · .	. •	,			. `**	7,
		. 1.1	• .,				· · · .	• /	. •		•	· · ·	:
	. :	. 1			-		• .	1. • :	•	_			
		•										• • • •	
	•	•											
	••	÷			•				•		n	-	
TOTALS	† 5	1.3	• (- •			_1			. . ;		,	~

Single Motivity Assessment Type Single Main

WEATHER CONDITIONS

STATION NAME

i - -

CONTRACT FREEDOM CONTRACTOR CONTR

MONTH	HOURS L.S.T :	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	° OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
			· - :		• : .			•	. • .				,
		<u>-</u>		· · .	• .		. • .	i •. •.	. : •				
		· .	1				• ,		<u></u>				. ,
	-11	. •			• • •		· · ·	. • 1	. • .			, ,	
	1 -	· ·						: •				. , .	
	'	•	11.	. · .			. : .	. • ~				. : · .	
		•						1	. •			1 - •	-
	. 1.7.	• •	•:'		· · ·		. • .	1 - • -		-	•	! • •	
		•		•									
	•												
				··	····•				•	····			
<u>-</u>		, 	 -	! +					parteurusene s	** =======	rezi iliz		=
TOTALS	<u> </u>	•	• ;	1 • .				: •;			- 1	· · ·	7 .

Agencia de la companya de la company

WEATHER CONDITIONS

1 to 1	7 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	;		
STATION	STATION HAME		YEARS	монте
		S. F. L. F. B. L. S. A. 220		

MONTH	HOURS (L.S.T.)	THUNDER- STORMS	RAIN AND: OR ORIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	°c OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
		<u> </u>	. 4				: • •	1		i •			
	· -			<u> </u>						<u> 1 </u>			
_		• 1			***				1 • "	·		****	
							1	· •					
	1 -1	• 1		· ·	٠.			1 - • *				· · · · · · · · · · · · · · · · · · ·	
	.:				•••			•					•
				+ • · · · .	٠.			1	•	· • <u>:</u>		<u> </u>	
-	:	· i			· · ·			1				· ·	
		-•			-								
		•						-				• • •	
	•	·		.						·	,		= :
s=	· • ••••••	+		ali and an	a-42 = 1.		and a reason		* ====================================	r mary	·=	1 = = 1	. <u>.</u>
TOTALS		1			•		. 1 .	17.1	~ •	1.1			۽ د

WEATHER CONDITIONS

, -	Control of the Contro	1		. t
STATION	STATION NAME		YEARS	MCATH

The first of the second of the

MONTH	HOURS LST.:	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	PAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OES
			• •				•		•	· • · · · ·			1.4
		·			•		. • • .	• •		•		•	2
		<u>.</u>				•		1 • •		. •	•	. : •	
			ē			•					• .	. 1	,
		<u> </u>	. •			•							
								• ,					
								. •	•			•	7 12
		1	. •										<u>-</u>
								• "				. :	?
		+			,		. · .	: .				1	7
٠.		•										1 .	,
:		• • • • • • • • • • • • • • • • • • • •						:	•			1	. :
TOTALS		. •					• .	.1.	• .		• 1	1	~ ~

ENVIRONMENTAL TECHNICAL APPLICATIONS CENTER

U S AIR FORCE

PART B

PRECIPITATION, SNOWFALL & SNOW DEPTH

This part of the Uniform Summary coasists of eight summaries derived from daily observations as follows:

- 1. The first set presents, in three tables, the percentage irequency of various daily amounts of PRECIPITATION, SNOWFALL, and SNOW DEPTH. The daily amount summary is prepared by month and annual, all years combined, and includes percent of days with measurable amounts; percent of days having none, traces, and given amounts; and means, greatest and least monthly amounts. (The last three statistics are omitted from the snow depth summary because of their doubtful and limited value.) A total count of valid observations is given for months and manual. Stations are included in which a portion or all of the period may contain months with missing days. This will be noted on the summary pages. A percent value of ".0" in these daily amount tables indicates less than .05 percent which is usually only one occurrence.
- 2. The second set of three tables presents the extreme daily amounts, by individual year and month, of PRECIPITATION, SNOWFALL, and SNOW DEFTH for the entire period of record available. Also provided are the means and standard deviations for each month and annual (all months) and the total valid observation count. An asterisk (*) is printed in any year-month block when the extreme value is based on an incomplete month (at least one day missing for the month). When a month has valid observations reported but no occurrences, zeros are given in the tables as follows:

EXTREME DAT	LLY	PRECIPITATION	۳.	.00"	equals	none	for	Lhe	month	(hundredths)
EXTREME DAT	LLY.	SNOWFALL	".	.0"	equals	none	for	the	month	(tenths)
EXTREME DAI	I.Y	SNOW DEPTH	"0)"	equals	none	for	the	month	(whole inches)

3. The third set of two tables provides the total monthly computes of FRECIPITATION and SNOWFALL for each year-month and annual. Also prepared are the means, standard deviations, and total number of valid observations for each month and annual (all months). An asterisk (*) is printed in each data block if one or more days are missing for the month. No occurrences for a mouth are indicated in the same mauner as in the extreme tables above. If a trace becomes the extreme or monthly total in any of these tables it is printed as "TRACE."

Continued on Reverse Side

Values for means and standard deviations do not include measurements from incomplete months,

NOTES:

- (1) The above studies may also be prepared for stations operating for less than full months for portions or all of the period of record. This may include stations operating 5 or 6 days a week and those with only random days missing. An asterisk (*) in the data blocks will give an indication that a month is incomplete. Please refer to Station History at front of book and observation counts in each summary to evaluate the amounts of data missing.
- (2) Hail was included in snowfall occurrences in the summary of day observations prior to Jan 56, but these occurrences have been removed from snowfall category and counted as Hail in these summaries.
- (3) Snow Depth was recorded and punched at various hours during the period available from U. S. operated stations. The hours used by each service for each period are as follows:

Air Force Stations:

U. S. Navy and National Weather Service (USWB)

Beginning thru 1945	at 08001ST	beginning thru Jun 52	at 0030GMT
Jan 46-May 57	at 1230GMT	Jul 52-May 57	at 1230GM0'
Jun 57-present	at 1200GMT	Jun 57-present	at 1200GMT

DI SAU CLIMATOLOGY HANCH DELTAC 1 DEAT E SERVICE MAC

DAILY AMOUNTS

PERCENTAGE FREQUENCY OF FOLITIFITY (FROM DAILY OBSERVATIONS: +

TOUR TO TOURNELL AFBIRS 1,3-56

						AMO	OUNTS (II	NCHES					PERCENT		MON	THLY AMO	DUN'S
- 9 2 6	NONE	TRACE	٥٠ .	02 05	00 10	11 25	26 50	51 1 00	1 01 2 50	2 4: 5 00	5 C1 + 0 00	10 01 20 00 OVER 20		TOTAL NO		INCHES	
SHO HEAL	NONE	TRACE	0:04	0.5 4	1524	2534	3 5 4 4	4504	6 5 10 4	10 5 '5 4	15 5 25 4	25 5 50 4 OVER 50	ALE A CLUB	OF OBS	MEAN	GREATES"	.EAS*
->0 * -16"#	NONE	TRACE	1	2	3	46	7 12	13 24	25 36	37 48	49.60	61 120 OVER 12	c AMTS		,		
JAN	3.3	19.0	1 • 7		₹• ९	3.1	1 • *	1.2	. 4				17.5	1023	• c	-12	TRAC
r E B	7.1	19.9	1 •	5.5	2.1	3.4	2.6	2.0	• 5				1	- 1	1. 4	76	, * # A C
₩ A R	. 7	17.0	1 .	4 • ė	2.	3.7	4.9	5 • 4	2.2	• 1			23.	1 23	2	1. • ^{6.} 7	
APR	• 1	14.2		4.6	3.8	4.5	3.7	4.4	2.3	• .			7 • 7	772	3 • 1	7.20	4
MAY	^ · :	15.6	2.6	5.8	2.3	0.5	c . 6	J • 3	3.9	• .			73.1	1 23	4.		.40
JUN.	5.	14	7.3	4 . 3	3.5	4.0	· 4	5.3	4.1	•	• 1		y	ų.	4.4"	1 -7	• •
·uι	5	11.8	1 • •	3 • 2	2.1	4.7	3.3	4.5	7.2	• .			2	1023	3 • - c	° • 1 -	TRAC
AυG	5.	11.0	2 • 1	4 - 1	2.2	3.9	5.4	3.2	2.4	•	• 1		24.,	1027	3.24	1: • 4 6	••
SEP	2.:	.1.7	2.4	4.5	2 • 5	4.2	4.0	4 . 3	7.4	. 4			21.5		3.7	7	• : •
oct .	6 . 7	د ۱۰۰۰	7 . 3	4.5	2 • 2	3.5	2.7	• 6	2.0	• =			77.0	1023	3.1	.70	TRAC
NOV	6	12	1.5	5.2	1.7	3.	2.6	3 • 3	1.2	• ¿			7.	940	1 3		. 5
DEC	5.7	19	2.2	6.0	2.5	4 • 3	2.6	1.3	.6				1 . 4	1.54	1	7.54	
ANNUAL	. 2	14.5		4.5	2.6	4.1	7.7	5.4	2 • 3	• 2	• 5		27.3	120 3	33. 12	• ·	

USAFETAC FORM 0.15.5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOHAL CEIMATOLOGY BRANCH USATETAC AIR WEATHER SERVICE/MAC

EXTREME VALUES OF PRECIPITATION (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFRIKS

PERIOD OF FECURO: 53-86

					24		*0UNTS IN						
YEAR	JAN	Fto	MA R	APS	#A Y	-M-0	-N-Т-Н 5- JUL	Auι	SEP	0(1	404	E E C	ALL PORTH
53	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	•••••	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • • •	• • • • • • • •		• • • • • • • •
54 1	.12	1.24	1.00	1.20	1.60	.16	.04	. 64	1.33	. 74		.10	1.6
55 1	.56	1.42	.35	. 3.7	2.18	1.49	1.50	. 54	1.84	4.41	• • • •	• 43	
56 1	.15	. 2 9	1.07	.66	. 6 1	.65	• • 1	3	-12	1.13	.50	1	1.1
57	.16	1	1.06	1.11	2.30	1.67	1.34		2.21	5.6	.66	.43	2.3
5a i	54	.46	1.21	.61	1.92	. 5 1	2.33	1.35	2,	TRACE	.01	16	
59		.66	.48	.85	1.68	.67	4.34	. 61	1.07	2.65	.37	. 74	
60 1	.73	. 19	.37	.23	1.45	. 90	2.64	6.90	. 6 7	2.19	.26	1.37	6.9
61	9	1.08	.67	1.97	2.12	1.41	2	2.53	1	1.46	1.34	.56	7.1
62 1	. 4 8	.27	.47	.36	. 34	1.40	2.45	1.45	1.06	. 4 8	1 - 1 9	. 30	
63 1	1.32	TRACE	. b A	.14	2.12	1.68	7	1.58	1.10	1.48	. 6 !	. 10	1
54 1	.45	.53	. 7 U	1.73	2.63	1.34	. 6.2	2.23	1.19	1.6.	87	.53	
65 I	.56	•.73	.06	1.46	1.98	5.06	2.51	1.30	2.52	. 3.	.33	1.54	٠
10 1	-11	1.05	• 1/5	.00	.17	.61	1.0.	.76	. 50	.31	.15	1	1.7
67 !	. 37	. J 7	. 8 2	1.24	. 6 C	1.72	2.12	. 4 4	1.19	1.35	. 5 3	• 35	7.1
68	.11	. 17	-51	1.63	1.46	1.44	.61	.99	2.30	1.21	1.72	1.27	2.1
69 1	.07	- 7 4	1-24	2.7#	1.71	1.26	2.63	1.04	1.91	آدي د ا	.3 5	. 60	7
7.3	.18	.17	. 3 9	2.60	.99	0	. C q	• 7 8	1.35	1.65	.0 5	-50	4
71 1	1.24	. 8 .	TRACE	1.29	1.27	1.23	1.46	. A O	1.21	2 - 51	1.15	.50	2.3
72 1	-12	. Z h	.27	1-11	.65	.59	1.44	1 - 1 3	.12	. 75	1.26	. 4 *	1.4
73	.86	. 4 .	4 1	- 8 °	. 11	. 10	1.45	1.13	2.79	2.30	•50	• 5 5	2.1
74	.46	. 3 7	1 7	2.03	1.05	1.39	• u l	1.76	-61	1.55	2.11	. 71	2.1
75 I	.98	.80	. 8 9	1.62	2 - 1 5	1.94	TRACE	1-61	-65	• G 1	- 76		2.1
76	-10	-17	.35	1.97	1.00	1.77	2.08	• 3	5.41	. 6 4	.22	• 1 1	7.4
77	. 2 4	-13	1.82	1-68	2.01	1.95	. 0 3	2.47	. 9 •	٠6٣	1,18	• 1 1	2.4
78	. 35	1.55	1 + 2 8	3.25	1.82	1.97	2.48	-56	1.88	- 15	.6.3	. 29	3.2
79 1	.90	. 4 1	1.67	1.29	1 - 4 3	1.30	1.44	.53	2.25	1 - 21	2.19	1.03	5.3
AD 1	1.27	.9.	1.58	.64	2.25	.61	. 6 5	3 - 1 .	. 6 3	. 6 7	. 6 0	2.16	7.1
81	•06	• 21	•15	. 8 4	06	1 - 1 7	1.99	- 5 5	.93	1.47	1.19	. 1 3	2.0
82	1.48	• • 0	1.80	.6 5	1.63	1.41	. 13	. 4 5	1.68	. 49	.54	.94	1.9

NOTE . . TRASED ON LESS THAN FULL MONTHST

CONTINUED ON REXT PAGE....

GLOHAL CLIMATOLOGY BRANCH USAFLTAC ALR WEATHER SERVICE/MAC

EXTREME VALUES OF PRECIPITATION IFROM DAILY OBSERVATIONS!

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS

PER100 OF RECORD: 53-86

	•-				24	HUUR AF	100412 10	1 THICHES				******	ALL
YEAR I	MAL	FEB	- ,	APP	MAY	JUN	-W-7-H-S JUL	AUG	SEP	0.1	NOV	(t C	MONTHS
93 94 95 96	.66 ,18 ,35 30AN	.76 -55 -66	1 4 2.02 .63 .67	1.36 1.31 1.38 .71	1.00 1.12 1.98 1.05	2.19 3.50 2.21 1.66	2.42 .43 1.69 2.37	1.27 1.40 1.23 2.47	1.55 2.23 1.47 3.37	1.23 .74 2.86 1.45	1.20 .38 .62	. 72 2.37 .48 .88	3.50 7.86 3.37
MEAN S.D. IL OBS	.451 .464 1023	.593 .399	.978 .646	1.243 .688 990	1.492 .680 1023	1.598 .964 990	1.512 .990 1023	1.403 1.247 1023	1.538 .815 990	1.288 .956 1023	.804 .725 990	.e 20 .531 1654	2.68 1.69 1268

NOTE . (BASED ON LESS THAN FULL MONTHS)

GLUBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

MONTHLY PRECIPITATION (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724565 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-R6

1					IUIAL N		-N-T-H-S	TION IN I -	MCHt 5				ALL
YEAR I	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	061	NOV	CFC	MONTH
53 [••••	• • • • • • •	• • • • • • • •	• • • • • • •	•••••	• • • • • • • •	• • • • • • •	• • • • • • • • •	• • • • • • •	• • • • • • • •	•••••	1.31	• • • • • • •
54 1	.12	1.24	1.43	2.10	3.76	.60	- 08	2.33	1.72	1.74	.00	.21	15.3
55	.83	1.98	. 64	-67	4.62	5.09	3.43	-82	3.25	6.35	.33	.04	27.5
56 I	.63	• 5 D	1.44	1.11	2.26	1.28	2.50	.97	.16	2.28	.81	.69	14.6
57 1	.12	1.19	c . b b	5.37	6.69	10.07	1.93	.82	5.18	1.92	2.02	• 5 9	39.1
5 a	1.18	1.16	5.06	1.28	3.76	2.63	6.63	2.10	5.94	TRACE	1.24	.71	31.6
59	.57	-71	.94	2.07	6 - 17	2.33	9.10	4.97	3.58	9.70	.15	2.11	42.4
ea I	1.28	1.94	1.39	.59	4.22	3.53	9.01	10.46	2.34	7.15	.28	2.16	44.3
61 1	.09	1.98	2.95	5.49	6.48	3.32	7.75	5.62	4.94	4.93	3.50	1.11	46.1
62 1	1.37	.49	.59	.17	1.00	4.03	6.90	2.45	7.53	.98	1 - 6 1	-60	28.5
63 [1.57	TRACE	1.78	. 4 4	5.08	4.36	3.95	2.39	3.58	2.34	.88	.81	27.1
64 1	.54	. 9 4	.89	3.93	5.19	2.68	1.52	6.08	3.54	2.22	7.79	1.04	36.2
65 I	.25	#2.10	.83	4.71	6.42	7.81	4.81	3.29	9.27	. 37	•02	2.20	*42.0
66 [. 3 3	1.30	• 05	2.13	.45	1.10	1.75	1.93	.63	•57	-15	.48	10.8
67	.61	.07	1.20	2.60	1.72	7.14	6.42	1.75	2.63	4 - 23	.47	.88	29.7
68 1	. Z B	. 1 7	1.09	4.27	6.43	3.55	2.43	4.37	3.28	2.58	2.71	2.31	33.9
69	.26	1.34	2.25	6.05	5.09	5.06	6.85	2.07	4.63	3.06	•06	1.71	38.4
70 I	. 32	.12	2.85	5.65	1.37	6.25	1.01	1.18	4.54	2.83	.07	• 5 c	26.6
71 1	1.77	2.76	TRACE	3.48	2.99	2.96	6.33	1.97	2.29	6 • 62	2.72	1.49	35.3
72	. 35	.46	.70	3.88	1.72	1.44	5.52	2.68	1.43	2.62	4.33	1.12	26.4
73 I	3.12	1.10	10.57	3.21	.99	1.10	3.18	1.73	9.25	4.05	.78	1.57	40.6
74	.78	.45	2.90	4.58	3.60	2.92	•02	6.06	1.18	5.23	3.90	2.22	33.8
75	2.05	1.85	1.75	1.77	7.47	6.22	TRACE	3 - 73	1.56	-01	1.98	-06	28.4
76 I	.13	. 34	1.50	7.20	3.84	4.24	7 7	.42	5.06	1 • 33	.29	.17	31.7
77 1	.43	.23	3 . 4 4	4.78	9.02	4.25	3.23	9.29	3.36	1.28	2.42	- 14	41.8
78	1.09	2.29	2.47	4.80	4.64	5.44	4.00	2.11	5.02	- 15	3.18	.71	35.9
79	2.27	.49	5 - 2 7	3.56	3.44	7 - 4 4	2.33	1.31	2.56	1.90	3.81	1.44	35.8
80	2.11	1.34	4.42	1.37	4.36	1.84	•63	4.93	.96	1.51	.83	2.55	26.8
A) j	.11	. 30	2.64	1.12	7.63	3.59	3.62	2.34	3.47	4.90	3 - 8 7	• 28	33.8
82 I	1.78	.94	3.54	1.12	7.87	6.37	1.29	1.33	1.33	1.56	1.12	2.05	30 - 1

NOTE . (BASED ON LESS THAN FULL MONTHS!

CONTINUED ON NEXT PAGE....

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

MONTHLY PRECIPITATION
(FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-86

	t						ONTHLY PI M-0	-N-T-H-S		1				ALL
YEAP		JAN	FE6	MAR	APR	MAY	NUL	JuL	AUG	SEP	001	NOV	1 E C	HONIHS
83	1	1.47	1.64	6.65	4.01	3.60	10.03	3.43	1.95	3.61	3.73	2.35	1.43	43.90
8.4	1	• 32	1.49	10.29	5 - 6 4	3.55	6 • 28	.64	2.13	2.69	3.36	1.59	3.54	41.72
8.5	1	•52	2.10	1.97	4.10	3.65	5.40	3.20	3.27	5.42	6.58	.91	.73	37.85
86	1	TRACE	1.12	1.54	2.39	5.55	5 . 38	6.98	7.52	5 - 8 7	4.09	.82	1.67	43.13
ME AN	٠;٠٠	.886	1.060	2.657	3.159	4.383	4.416	3.859	3 - 2 3 8	3.697	3.101	1.724	1.201	33.139
5.D.	i	.710	.737	2 • 51 5	1.832	2.170	2.435	2.706	2.449	2.241	2.337	1.730	. 647	6.686
AL OBS	į.	1023	931	1023	990	1023	990	1023	In23	990	1023	990	1654	12083

NOTE . (BASED ON LESS THAN FULL MONTHS)

UEGERE CLIMATOLOGY BRANCH EXTREME VALUES OF SNOWFALL USAFFIXAC IFROM (VALUE OBSERVATIONS).

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB MS

PERIOD OF HEIGHUI NE ME

						HOUR AM	1-1-H 5-	• • • • • • •					4
YEAR L	JAN	ffb	MAR	APE	MAY	JUN	Jul	Airt	et b		No. V	.1 -	رز 1 رون ₩
									<i></i>		.		
.3 1													
έμ (1.3	THACE	THALE	• Fr	• 0	• 0	•	• 1.	• 1				
45	1 - 3	1.8	1.5	• 0	• f*	• 0	• 3	• L	• 0	• "	. '	- 1	
56 [2.2	5.6	2.8	TRACE		• C	• U	. (• 15			1.1	
7 1	2.0	3.4	1.0	. 6	• 0	.0	. 0	• t.			• .:	14261	
* A	5.0	3.9	5.7	• 0	• C	• t°	•	• 1.	•	•	1.8	4.1	
59 1	6.8	. 5	. 9	1.4	• f)	• 0	• 11	• f.	• 0	• .	4.45	. •	
eu f	1.9	4.0	2.8	TRACE	• C	. 0	• J	• (• (*	THALE	. '	1. *	٠.
61 1	. 8	4.6	5.6	TRACE	.0	٠ ٥	- C	• 0	• 1			• • *	٠.
62 1	4.8	• 3	TRACE	.0	• U	• 0	. (• C	• 7		. 1	3	4.
63 1	4 - 1	TRACE	TRALE	• (i	• 0	• 13	• U	• 33	٠.٠	• •			4.
64	TRACE	2.6	THACE	• ^	• 0	• 0	• (• G	• 3		THACE	4.7	٠.
65 1	1.8	07.4	*THALE	• n	• C	• 0	• 0	• 1.	• "	• **	•	4	
66 1	2.0	. 5	THACE	. C	٠,٢	• C	• 6	•	• 1.	• (TRACE	•	•
67	5.7	TRACE	. 5	.0	.0	• 0	• 3	• ! -	• P	TRACE	THACE	1.6	١.
68 (TRACE	. 4	TRACE	• D	• 0	• (1	• 0	- (. 5	• "	. '	- 1	
69	TRACE	2 - 1	• 7	• C	• 0	• 0	• (• (• 11	• P	THALE	1. '	٠.
7 U [2.1	TRACE	1 (+ 1)	. 4	• 0	D.	• 7	• 1	• .	TPAL	TRACE	'	111
71 1	• 2	A . 3	THALE	• fi	• 0	• U	• L	• t	• O	١.	4.7	1	7 •
72 1	1.1	2.9	2 • €	• 0	• 0	• 0	;	• 0	• 2	• 0	3.6	1.0	
73 1	3.0	TRACE	• ()	2 • C	• 0	. 0	• Ú	• C	• 9	• 1		1. •	
74	. 9	. 1	1.6	TRACE	• 0	• 0	• 43	• L	• ()	• 11	1. '	1.4	
75	6.6	4.6	8.8	. 4	• D	• 0	• U	• C	• 1	• 1"	1.6	. 4	
76 1	1.0	1.7	TRACE	• U	• 0	• 0	• U	• 6	•	• i*	1.4	THALF	
77	. 8	TRACE	TRACE	TRACE	• 0	• C	• 0	• ()	• 3		13861	TRACE	
7 â	3.5	2.7	. 1	.0	.0	• 0	٠٠	• t,	. 1	. "	THACE		
79	4.0	. 8	. 3	4 . 3	• 6	• 0	• 0	٠.	. 0	TRALE	TRACE	1 4 & C E	٩.
AU 1	. 3	9.2	TRACE	• 0	• 0	• 0	• 0	• C	.0	TRALE	THALE	. 4	٠.
81 1	TRACE	2 • 1	.5	• e	• 0	٠.0	. i.	• 6	• •	• 0	TRACE	4.3	

NOTE . IRASED ON LESS THAN FULL MONTHS?

(MNTINUER ON REST FAST....

TOPAL STMATILUSE HEANTH COAFSTAL CAFSTAL AIR WEATHER SERVICESHAL Exterme values of security.

(FEDE CALL Conceptation)

CTATION SOMELET TRASCS STATION NAME: MCCCHNELL AFE FO

and the second of the second of the second

					. 4	HOUSE AM	3014 to \$4	i i National					
1						M U	No. 3 House						A v 3
¥ C. & D	JF≜ N	+1+	444	A F C	MAT	JUN	Jes	Acc	٠, ١	. (*	% C V	. •	Harry
- 1												*	• • • • • • • • • • • • • • • • • • • •
+9 İ		1. 1	· (•	•	•							
~ 1	5 . H	5 . 12	THALL	THACE	, it	• •						i -	1
+6 1	. 3	1.5	THACE	• '	• 12	• • 3	• •	• •	• *	• *	1 = 4 ()	• • *	١.
MI AN I	2.19	2.45	1.62		,00			(• • • • • • • • • • • • • • • • • • •			1.13	4.4.
1.0.1	1.477	2.5 14	3.151	. 4 4 4	.000	.0.0	. He to	.cor	. 1 6 8	. 1 . 5	1.445	1.45.	ι, ι,
TAL Sec. 1	1721	911	1521	99(14.23	940	1 4 5	1.62.1	993	1 1	34.7	43.53	1

NOTE . . CRASED ON LESS THAN FULL MONTHS L

. IF 1941 ST TMATULUGY HEANCH -SAFETAC -AIM HEATHER SERVICE/MAC

MONTHLY SNOWFALL LEROM DATEY OBSERVATIONS:

TION NUMBER: 774505 STATION NAME: MCCONNELL AFRIKS

PERIOD OF RECOFU: 51-86

1						- M - O - I	V-Y-H-5-						ALL
VEAR 1	JAN	FEE	MA ₽	APR	MAY	JUN	JUL	*UG	SEP	(-C 1	NUy	CFC	MONTH
5.3	• • • • • • • •				• • • • • • • •	•••••	• • • • • • •	• • • • • • • •					
5.4	1.3	TRACE	THACE	• 6	• 0	٠.0	• 0	• C	• 0	• 13	• 3	. 3	1 .
55 F	2.0	2.4	1.5	• 0	• ()	٠.0	• D	• 0	• n	• 0	. 5	. 1	٠.
55]	R.5	3.4	5.7	TRACE	• 0	.0	• J	۵.	• 0	• 0	• 0	6	2∟•
57 [7.1	3.4	1.4	٠,	• 0	• U	• 0	• C	• 0	. A	• 2	TRACE	13.
48 1	6 • 8	7.1	17.8	• C	• O	. D	• 0	٠.	• 0	• 0	1.8	7.A	4 i .
59 [1.9	. 4	٠,	1.5	• D	.0	• 0	• C	• 0	• (1)	2-1	. 7	13.
60 1	3.4	16.9	9 • 0	TRACE	• 0	• U	• 0	• 0	• 0	TRACE	• 3	3.3	31.
61 1	. A	9.2	7.3	TRACE	• 0	• 0	• 0	• 0	• 3	• D	. 7	4.9	23.
62 1	12.3	• 2	THACE	• 0	• 0	• 0	• 0	• 0	• D	• f1	• 2	i • 0	14.
63 1	5.3	TRACE	TRACE	• 17	• 0	• 0	• 0	.0	• 0	.0	• 0	7.6	1
64 1	TRACE	2.6	TRACE	٠,٠	• 0	• 0	• D	• 0	• 0	.0	TRACE	4.7	7.
55 [1.6	•2.4	*TRACE	.0	• D	•0	• 0	•0	• 0	• C	• 3	4 . 4	• t .
66 1	4 • 2	. 7	THACE	. 0	• 0	• 0	٠ 0	نا •	• 0	.0	TRACE	4	• I •
67 [3.7	TRACL	. 6	• 0	.0	.0	. 0	• C	• 0	TRACE	TRACE	2.5	7.
64 1	TRACE	. 8	TRACE	• 0	.0	•0	.0	• D	.0	• D	• 3	- 1	1.
69	TRACE	2 - 8	. 4	• 0	• 0	• 0	• G	• G	• 0	.0	TRACE	3.8	7.
ru l	3 - 1	TRACE	1 R. 3	• 6	•0	• 0	• 0	• C	• 0	TRACE	TRACE	è • 5	24.
71 1	• 2	18.6	TRALE	• 0	• 0	• D	• 0	• C	• 0	• 0	4.5	1.9	55.
12	2.4	4.4	2.0	• 0	.0	• 0	• 0	• 0	• 0	• 0	7.5	1.5	17.
73 J	8.0	TRACE	• 0	2.0	. 0	• C	. 0	.0	.0	•0	• 0	2 . 8	1
74	1.7	. 5	2.9	TRACE	• 0	• 0	٠.0	•0	. 0	•0	1.0	2	۰.
75 I	7.3	11.4	9.4	- 4	• 0	• 0	• 0	• D	• D	.0	4 . 4	. 4	33.
76	1.3	1.4	TRALE	• n	• 0	• 0	• 0	• 0	• 0	• 0	2.3	TRACE	5.
77 (2.3	TRACE	TRACE	TRACE	•0	• 0	• 0	• 0	• 0	• 0	TRACE	TRACE	
78 1	10.7	9.9	. 8	. D	• 0	•0	• 0	.0	• 0	• 0	TRACE	7.6	24.
79	14.3	. 8	.5	4.3	• 0	.0	• 0	• 0	.0	TRACE	TRACE	TRACE	15.
8 J	. 9	12.8	TRACE	• G	• 0	•0	• 0	•0	•0	TRACE	TRACE	. 4	14.
91 1	TRACE	2 . 2	. 5	• 0	• 0	• O	• 0	• 0	• 0	• 0	TRACE	1.4	4 .

NOTE . + EBASED ON LESS THAN FULL MONTHS)

CONTINUED ON KEXT PAGE....

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

MONTHLY SNOWFALL IFROM DAILY OBSERVATIONS!

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 57-86

_					TOTAL			L IN INC	HE S				
ť						-M-0-	N-T-H-S-						∆ L L
YEAR 1	JAN	FξB	MAR	APR	MAY	JUN	JUL	100	SEP	0.1	NOV	LŧC	MONTHS
										• • • • • • •	· · · · · · · · ·		• • • • • • • • •
83 1	13.3	10.3	• 6	TRACE	• 0	.0	• 0	•0	• 0	• []	3.6	t • 5	36 - 3
84	4.0	1.5	3.9	.0	• 0	- 0	• 0	.0	• 0	• tì	5.3	5.1	23.8
85	4.4	4.0	TRACE	TRACE	•0	.0	• 0	• 0	• 0	• 0	. 5	3.4	13
86	• 0	3 . 2	TRACE	• 0	• 0	• 0	٠ ل	• 0	• 0	• 0	TRACE	1.5	4.7
MEAN 1	4.21	4.46	2.58	.29	.00	.00	.00	.00	.00	.02	1.05	2.86	15.84
5.0.	4.154	5.271	4.792	.850	•00n	.000	• 000	.00C	•000	139	1.907	2.724	16.659
AL OBS 1	1023	931	1021	990	1023	990	1023	1023	990	1023	998	1653	12 u A ú

NOTE . (BASED ON LESS THAN FULL MONTHS)

A COLMATRES AND PATORS SERVICE MAC

DAILY AMOUNTS

PERCENTAGE FREQUENCY OF

(FROM DAILY OBSERVATIONS)

THE CONFIDENCE FOR ME

YEARS

						AM	OUNTS :	NCHES:							PERCENT	TOTAL	MON	THLY AMO	UNTS
121	No. No.	*@A_F		11 ::	36 13	. 25	26 50	e as	J. 2 50	2 5° 5 GC	5 (110 00	:c c	25 OU OV	ER 20.00	OF DAYS	NO		(INCHES)	
Sec. Prof.	NONE	TRA1.E	. 4	0 t 4	124	2 5 3 4	3344	4:04	05.04	10.515.4 	15 5 25 4	25.5	50 4 O	VER 50 4	MEASUR.	OF OB5	MEAN	GREATEST	LE AST
:	NO.	TRA I		2	3	4.5		:3 74	21.36	37.46	49 60		25 0	VER 120	AMTS			-	
, A %		, . 7	7.1	4.3	• 5	7	1.							_		1 -	•	•	
+ f B	: •	/ • • ·	4.7	4.4	' • 1	4.	7.4												
~ A.B	•	4.1	1.	1.2	• *	1.0	. • •						_	_		1 8			
¥ c 5	÷ .	•	. ì	• 1												,			• >
MAY	7.						-									.50		•	•
	7.										-		• -						
J.				-			• · -								.	1 .			
456												.		-		:07			
< ę p																		-	
oc*	r, c		•			•						_			• •	1 1	•	•	
VGM	5.0	1.2	•	• 5		. 4		<u> </u>								i, i			
DEC	2.	5.7	1 . 1	3.2	1.	1.2			-	.	francis de la constante de la	-£				10.4			•
ANNUAL	•	2 . 4	1.7	1.2	. 7	1.	5	 .)	:			-			. 4	1. 4		•	

USAFETAC $^{FORM}_{OCT.75}$ 0.15.5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

EXTREME VALUES OF SNOW DEPTH (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PEPIOU OF RECORD: 53-86

	• • • •	• • • • • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • •	ÜA	ILY SNOW	DEPIH I	N INCHES		• • • • • • •	• • • • • • •	• • • • • • • •	
		1						v-1-H-S-						ALL
ΥE	AP !	MAL	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	0 C T	NOV	(£ C	MONTHS
••••••	3		• • • • • • • •	• • • • • • • • •	• • • • • • • • •	• • • • • • • •	•••••	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
	4	,	C C	G	0	0	0	0	۵	0	a	0	TRACE	1
	5		ž	2	n	ő	ő	ü	ŭ	Ö	c	0	TRACE	;
	6	, ,	ú	ì	ň	ū	ň	ŭ	ñ	ō	ő	ä	1	ű.
	7	,	,	ī	i	ñ	n	a	ū	ā	1	TRACE	TRACE	5
	в.	, ,	2		ō	ŏ	Ö	ō	ő	o o	Ď	2	5	7
	9	6	7	TRACE	0	n	0	C	D	o	0	2	TRACE	7
	o i	4	8	9	n	ő	ō	o o	o	ō	ō	TRACE	2	Ģ
	1	1	6	5	TRACE	Ō	Ö	ō	Ō	o	0	0	2	ь
6	2 1	11	TRACE	C	n	0	0	C	0	0	ñ	ຄ	2	11
	3	5	TRACE	TRACE	0	ō	Ø	0	0	a	0	õ	ь	b
6	4	0	2	0	ō	0	0	0	0	0	Ō	0	r ₅	5
6	5 !	1	2	ō	0	0	0	0	0	Ö	0	0	1	
6	6	2	1	0	0	O	٥	Ð	۵	D	D	O	3	3
6	7	3	O	0	0	0	0	0	C	c	0	0	1	3
6	8 1	0	1	0	D	0	0	a	0	0	a	3	1	1
6	9	1	4	4	0	Ð	0	o	ס	0	0	0	2	4
7	0 1	3	0	10	Ō	0	O	0	0	0	0	0	1	10
	1 1	0	1 4	1	0	0	0	0	C	a	0	4	2	14
	2	2	4	TRACE	0	0	O	0	0	0	0	4	1	4
	3	6	TRACE	0	TRACE	0	0	0	0	0	0	a	2	6
	4	5	2	2	0	0	0	O	0	0	0	0	1	5
	5	6	6	9	TRACE	0	0	ū	0	0	0	4	TRACE	. 9
	6	1	ı	O.	0	0	0	0	C	O	σ	1	O	1
	7	2	TRACE	O	C	0	0	O	0	0	0	0	0	2
	8	7	8	TRACE	0	0	0	Ü	o	0	0	0	3	6
	9 1	9	8	TRACE	2	0	0	0	0	0	0	0	0	y
	0	TRACE	11	1	0	0	0	0	0	ū	0	0	1	11
	1	TRACE	3	0	0	0	0	0	0	0	0	0	1	3
8	2	TRACE	10	۵	D	D	0	0	0	D	٥	TRACE	7	10

NOTE . BASED ON LESS THAN FULL MONTHS!

CONTINUED ON NEXT PAGE....

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PEPIOD OF RECOPD: 53-86

•••••	• • • •	• • • •	•••••		• • • • • • • •	• • • • • • • •		ILY SNOW				•••••	• • • • • • • •	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
		ł						- M - O -	N-T-H-S-	-					ALL
	YEAR	-	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	0 C T	NOV	CEC	MONTHS
• • • • • •	83	• • • •		12	TRACE	0	******	•••••	•••••	•••••			• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
	נמ		4	1 2	IKALE	U	U	U	υ	U	U	U	,	6	12
	84	- 1	4	ົບ	1	C	0	0	0	0	0	0	2	3	4
	85	1	4	3	TRACE	TRACE	O	0	O	O	0	C	TRACE	2	4
	86	1	0	4	0	0	0	0	0	C	0	٥	0	TRACE	4
	EAN	· ; · ·	3.1	3.9	1.6	••••••••••••••••••••••••••••••••••••••	•0	.0	.0	.0	.0	.0		1.7	5.8
5	.D.	1	2.843	3.908	2.905	. 384	.000	.000	•DU0	.000	.000	.174	1.315	1.697	3.496
TOTAL	082	1	1023	932	1023	990	1023	990	1023	1023	990	1023	990	1654	12684

NOTE . (BASED ON LESS THAN FULL MONTHS)

U S AIR FORCE
ENVIRONMENTAL 1 ECHNICAL
APPLICATIONS JENIER

PART C

1

SUFFICE THE

Presented in this part are various tabulations of some author as follow

*1. Extreme Values - Peak Gusts: Derived from daily diservations and presented by individual year and more for the entire period of record available. Specia are presented in knots, while directions are given 16 compass points from the beginning of record through June 1968, and in tens of degrees starting in 3 1968. The extreme is selected and printed from available peak gusts for each year-worth, however an asterisk () is printed in the data block if less than a king on more missing observations) of the peak gusts are valiable for the month. An ALL MONTHS value is presented when every month of the year has valid observations. Hears and standard deviations are also proted when every month and ALL MONTHS.

NOTE: According to Federal Meteorological Handbook No. 1 specification of formerly Circular N), "peak data are recorded only at stations with continuous instantaneous with tespecificacretic recorders."

*2. Bivariate percentage frequency tabulations: Derived from horrly observations, these tabulations are a percentage frequency of wind directions to 16 compass points and calm by wind speeds (knots) in increments of Beaufort classifications. Percentages are shown by both directions and appeal, and in addition the many wind speed is given for each direction.

A separate category is provided on the form for variable winds, which are reported in some data sources. In these cata where light and variable winds are reported with no directions but with speeds given, the speeds will be summarized in the appropriate groups opposite the column headed VERL.

- a. Three tables are prepared for ALL WEATHER surface wints, all years a mbined, by: (1) Annual elahours combined, (2) By month all hours combined, said the standard 3-bour groups.
- b. A sep rate annual table is also presented for surface while setting INSTITUTED CLASS conditions as follows: Ceiling 200 through 1400 feet inclusive with definiting equal to or greater than 1/2 mile, and/or visibility 1/2 through 2-1/2 miles inclusive with the first to or greater than 200 feet.

NOTE: A percentage frequency of ".0" in these tables to the confirmation to less than ".05" percent.

*Values for meins and standard deviations do not include a global menths.

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

EXTREML VALUES OF SURFACE WINDS
(FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 60-P6

· · · · · · · · · · · · · · · · · · ·				K GUSTS IN KNOTS -N-T-H-S-			ALL
YEAR I	JANI FEBI	MARI APRI		JUL AUG	• • • • • • • • • • • • • • • • • •	l teci	MONTHS
60 I	l (1 1	1 1		31 NNW 32 WNW 37	IN 351	
61 1				HNH 52 N +26 N		Nw #45	h 50
62		NNE 39 NW 36		NNW 441 NNW 421 ESE	*321 N 331 N 33	N 341	NN# #49
63 1		INN 140 IS 38 I				NW #48	tem
54]			SE 42 S 43			I N 401	55W 52
65 l	N 451 N 431	l NW 441 SE 391	S 66 NNE 48	H *40 S 29 SW	461 ESE 371 S +35	SS#####	5 66
66 [\$ 381 E 381 NNE		I N 361	t. m 48
67		SSE 47 S 44		N 391 ESE 391 SE		N +391	1. 40
6.8				20/ 401 23/ 511 30/			h 53
69				19/ 351 17/ 301 20/			337 58
70 l				2P/ 40 1/ 36 9/			9/ 72
71				33/ 491 31/ 361 18/			307 64
72				32/ 55] 23/ 35 19/			27/ 55
73				32/ 461 33/ 491 18/			21/ 58
74				18/ 35 20/ 60 35/			501 60
75				22/ 291 34/ 841 2/			34/ 84
76				3/ 33 25/ 33 16/			33/ 52
77				24* 36 31/ 46 20/			13/ 52
78 1				22/ 561 25/ 361 26/			22/ 50
79 1	36/ 41 35/ 44	34/47 19/ 38	17/ 421 20/ 401	1/ 461 20/ 481 36/	441 13/ 451 19/ 35	1 187 361	201 46
80 [36/ 42 16/ 40 19/			187 42
81 1	36/ 33 36/ 44	3/38 18/35	36/ 45 19/ 39	15/ 47 20/ 50 31/	41 33/ 37 29/ 39	1 35/ 381	207 50
82 1				1* 501 22/ 491 19/			29 € 53
83 (34/ 33 35/ 35	33/ 35 36/ 43	31/ 5D 28/ 38	19/ 301 32/ 291 36/	391 17/ 361 33/ 38	1 1/ 331	317 55
84 1	1/ 33 28/ 38	36/ 341 26/ 471	20/ 34 15/ 56	18/ 301 22/ 261 18/	461 18/ 401 18/ 40	4/341	15/ 50
85 [337 251 127 401 187			201 44
86	32/ 371 35/ 46	24/47 16/48	17/ 441 19/ 461	32/ 40 4/ 32 18/	371 17/ 321 36/ 37	1 17/ 291	16/ 48
MEAN 1	39.61 41.6	43.71 43.81	42-11 44-31	40.3 41.8 3	9.81 39.31 39.7	36.31	55.4
5.0. 1	5.6141 6.9831	6.691 5.755	7.944 7.009	R.353 12.349 8.	0781 5.3661 7.467		10.170
SEC TATE	7941 7281	PU11 7771	8011 7741	7841 8101	7921 B231 795	1 6201	9499

NOTES * (BASED ON LESS THAN FULL MONTHS)
S (BASED ON LESS THAN FULL MONTHS AND +100 KNOTS)

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS
PERIOD OF MCCORD: 77-86
MONTH: JAN HOURS(LST): 0000-0200 WIND SPEED IN KNOTS DIRECTION 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL MEAN (DEGREES) 1 1 WIND N 1.4 4.7 5.4 5.1 2.3 • 2 • 2 19.2 10.1 **.** 1 NNE • 5 2.3 2.2 2.3 . 4 7.7 9.2 ΝE .6 1.8 1.2 • 6 4.3 6.6 ENE 2.6 5.0 3.0 E 1.5 . 9 5.6 .6 ESE .9 1.6 2.9 4.4 2.6 5.2 SE 1.1 .6 • 6 . 2 9.2 SSE 1.2 2.2 1.5 .6 6.2 5 1.5 3.5 4.0 • 5 • 3 11.5 8.0 SSW 1.3 1.9 1.3 5.1 6.3 54 . 9 3.7 5.4 MSW . 1 5.4 1.0 1.5 . 3 2.9 4.6 . 1 . 3 .5 . 1 1.7 7.4 KNU .6 . 1 9.0 W . 3 .6 .6 .2 2.3 NNH 1.1 2.2 6.7 VARIABLE CALM 14.4 ///// TOTALS 23.3 4.7 . 2 100.0 6.8

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTION FROM MOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

PERIOU OF RECORD: 77-86
MONTH: JAN HOURS(EST): JSUG-0566
wIND SPEED IN KNOTS
7-10 11-16 17-21 22-27 28-33 3N-40 41-47 48-55 GE 56 TCTAL HEAD STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB MS DIPECTION I IDEGREES) 1 10.8 NNE 1.2 2.2 2.0 2.3 . 2 • 2 4.1 A . H ΝE . 2 2.0 1.8 . 2 4.3 6.5 1.1 . 3 FNE . 8 . 6 2 . R 6.6 £ . 9 1.7 . 5 . 3 1.4 5.4 FSE . 5 1.0 . 6 2.2 5.6 ٠.9 1.3 SE . 3 . 6 . 1 2.4 2.5 SSE . 8 1.3 1.1 . 8 6.3 9.0 \$ 1.7 2.7 1.7 3.1 1.1 10.3 9.2 6.0 4.4 2.3 1.0 . 3 SW . 4 6.0 4.0 **65** . 2 4.0 1.1 1.5 2 . R 1.3 . 6 . 4 2.5 1.9 .5 LNE .5 1.1 . 1 2.3 6.1 N. . 3 . 9 1.6 1.0 .5 14.2 NNu 1.4 VARIABLE 1 CALM 13.4 ///// TOTALS 18.1 1.0 100.0 7.2

GLOBAL CLIMATOLOGY BRANCH AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SHEED FROM HOUNLY OBSERVATIONS

STATION NUMBER: 7245U5 STATION NAME: MCCONNELL AFB KS
PERIOD OF PECORD: 77-86
MONTH: JAN HOURS(LST): 0600-0600 WIND SPEED IN KNOTS DIRECTION 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL 1 - 3 7-10 11-16 4 - 6 MEAN COEGREES! 1 LINU 1.0 .1 10.7 1.5 21.1 1.3 6.1 1.7 A . 5 9.5 PINE . 8 2.7 2.4 1.0 1.4 3.9 t. E .6 1.3 . 4 . 1 6.8 . 9 1.2 ENE 1.2 . 9 . 5 6.2 £ 1.3 1.5 . 2 FSE 1.0 . 2 . 1 2.4 4.3 1.0 1.C 3.1 5.5 SE 1.1 . 1 1.1 . 9 2.2 1.9 9.5 SSE . 1 6.1 1.4 2.2 2.2 2.2 1.3 9.6 10.0 S 1.2 1.5 554 1.0 .5 4.2 6.1 SW •6 1.0 1.1 . 3 3.0 6.3 W 5 W . 3 1.3 . 4 2.0 5.1 1.0 1.3 • 1 .6 . 3 • 2 1.9 5.2 1.5 4.1 7.6 NW .6 1.1 NNW . 3 2.7 2.3 9.4 1.6 . 3 CALM 12.9 ///// TOTALS 18.3 4.4 1.4 - 1 100.0 7.3

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PEPCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEFD FROM HOURLY ORSERVATIONS

1						VD SPEED	IN ANOTS		• • • • • • • •	••••	•••••		••••
IRECTION OFUREESI	1-3	4-6	7-10				28-33		41-47		GE 56	TCTAL %	ME AN
<u>ا</u>	1.0	3.2	6.8	8.5	2.3	.8				•••••	••••••	22.7	11.3
NNE !	.4	1.6	2.4	2.0	.6	• 1						1.7	9.7
NE !	- 1	1.8	1.5	. 8	. 3							4.5	8.2
ENE	. 3	• 5	1.0	. 3	. 1							2.3	P • 1
t !	.6	1.3	1.2		.2							*.3	6.8
FSE !	•2	. 4	1.2	.4								2.3	8.3
SF	. 4	- 8	1.7									3.1	6.A
.21	.6	2.2	1.4	2.8	. 4							7.4	9.3
s	1.7	1.5	2.3	3 - 3	1.3	. А						10.9	11.0
'Su !	۰,8	1.8	2.3	1.8	.4							7.1	A.B
Sw	• 3	1.5	1.7	. 8								4.3	7.5
¥5¥	.9	1.0	. 3									2.2	4,4
- !	.6	1.6	.6	. 1								3.0	5.3
	.5	•5	.5	. 3								1.9	5.8
Nu	• 3	• 6	. e	1.9	.1							3.7	9.6
NA I	.6	1.2	2.9	3.4	. 4	- 1						8 - 7	10.3
ARIAPLE I	•••••	• • • • • • •		• • • • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • • •		• • • • • • •	• • • • • • • •	• • • • • • • •	•••••
ALM 1,	(////////	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	11111111	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	5.5	111111

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86 MONTH: JAN HOURS(LST): 1203-1410 | WIND SPEED IN KNOTS
DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL IDEGREES) | -IND 7.0 12.0 NNE 1.1 3.1 1.6 . 9 10.1 3.0 8.6 • 3 ENE . 4 . 5 . 8 - 1 2.6 8.3 1.0 . 4 . 3 Ĺ .6 2.4 6.0 ESE • 6 1.1 . 5 2.4 A.5 . 1 SE . 1 1.1 1.1 . 3 - 1 2.1 8.3 1.5 2.2 . 2 SSE • 2 1.4 . 2 5.7 5 . 5 2.4 3.7 2.9 2.0 . 5 . 2 12.3 11.4 10.8 1.0 . 1 4.6 10.0 . 8 3.1 1.2 - 4 . ì 5.6 6.2 2.2 1.6 . 1 4.3 6.2 WNW 1.2 . 4 . 1 . 1 9.1 • 3 2.6 . 5 1.1 1.1 1.1 . 2 . 2 N. ii 4.2 9.1 NN9 1.5 3.2 3.9 . 6 10.6 11 - 3 CALM 2.0 ///// TOTALS . 4 3.1 100.0 9.9

SEOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WIND SEES.

FROM HOURLY UNSERVATIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 7245US STATION NAME: MCCONNELL AFB NS FURIOU OF HECORD: 17-NO MONTH: JAN HOURGESTO: 25-00 370

				•••••					: M140M			112 2536 	• • • • • • • •
IPECTION E DEURLEST (1 - 3	4 ~ 6.	7-10	11-16			28-33		41-47	48-55	uf se	10 1 A c	#8 A % #1 % c
N I	1.7	2.7	5.6	6.9	2.0	.5					•••••	1	41.
NNF I	. 8	1.7	2.4	3.1	. 3							R . 4	٠.٠
NF I	.5	• 5	1.2	. h	. 3							1.2	F. 7
FNE	.5	1.2	.6									2.4	1.2
	.5	1.2	1.1	. 3								4.1	***
rsr	• ?	.9	. 8	. 3								• • .	7.
SE	- 3	.9	1.0	.5								2.1	7.=
SSE		1.7	1.6	1.3	.5							4.2	9.7
s	.4	1.4	4.1	3.4	1.3	. 6						11.7	11-1
KSW	.9	1.9	2.9	2.0	. 4							A	٠, ١
S₩ Ì	. 9	.9	1.1	.9								1.7	7.:
wsw	.5	1.7	1.5	. 4	. 1							4.3	7.1
• [.4	1.2	1.2	. 3								5.1	t t
LNU .	1 - 1	. 9	1.1	- 1	. 1	• 2						5.4	7. 1
Nw	. 3	1.2	1.6	1.0	- 3	• 2						4.4	9.7
PiNia	. A	1.8	2.4	4.8	1.5	, p		- 1				17.7	1 *
VARIABLE I	• • • • • • • • • • • • • • • • • • • •			• • • • • • •						•••••	•••••	• • • • • • • • • •	
i i	(1)(1)(1)	////////			1111111	///////	,,,,,,,,	1111111	,,,,,,,	///////	,,,,,,,,	3.1	111111
TOTALS 1	9.1	21.7	30.5	26.0	7.0	2.4		. 1				169.0	4.4

C. LAS OLIMATICUS OF REACH PERCENTAGE FILL
 AFITAS

PROCENTAGE FOR SCENCY OF OLLOWING CO. OF EACH WENCE COMPLETE A WINCOMPLETE A WINCOMPLETE AND ACCORDED TO THE CONTRACT OF THE PROCESS OF THE CONTRACT OF THE CO

Alm BEATHER SERVICE/MAC.

REPART OF BEING HE WAS ARRESTED FOR SALES TATTING NUMBERS TOUSES STATION NAMES MECONNESS AFE H. #186 SEED IN MNOTS
#186 FID IN Adding to 1 300, 1 • 7 . • n 3.9 1.6 . 4 ٠.٠ ,, . 3 1.9 1.6 . 1 , , · * - 1 $t \sim t$, 1.5 . 4 ٠. . . . 1.4 . . 5 ٠.. ٠ ١ 4.1 . 5 1.54 . 1 1.2 . # . 3 ٠, ٠, ٦, • .* • A ٠.٠ 156 1.0 . . C 2.1 1.6 . 1 3.1 2.1 1.5 . . 4 ٠, ٩ 1 - " i • 0 4. ٠. 1.0 . 5 4. ٠. . 8 . 2 4. . 1. . 4 % H .. . ' 1 - 1 + A ٠.. 1.5 . , *** . 4 2.3 ٠. ١ to as • 5 . 9 • b *** ٠. ٠ VARIABLE | CALM 14.5 ///// TOTAL " 21.3 24.9 0.1 . 9 1...... 6.7

TOTAL NUMBER OF CREENVATIONS: 930

SESSAL CELMATUEDOV BRANCH SAFETAL AIR WEATHER SERVICEZMAC PERCENTAGE FREQUENCY OF OLCUPHINGS OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOUSELY OBSERVATIONS.

ATTOM NUMBER	#: 7245U5	STATION	NAME:	MCCONNELL	AFR HS				PERIOD MONTH:		0: 77- HOURS(LS1	-86 }: 21J0-	23(0
: 1FE (11UN - FUE UNE ES)		4 b		11-16	=1 N	D SPEED	IN KNOTS 28-33		41-47	4 H - 5 S	6F 56	fi TAL	ME AN NINE
*		5.0	4.4		1.6			• • • • • •	• • • • • • • •	• • • • • • •	••••••	16.2	1(.1
PINE	2.2	?	2.0	5.0	. 3	. 1						9 . A	F.4
NI.		?	. 4,	. 6								4.2	6.2
1046		1.0	. 9	- 1								2.4	5.1
•	1 1 - 2	1.9	1.0									4.3	5.2
Fire	.5	. 9	1.5									2.9	€.4
,1		1.2	. 0	. 1								2.1	5.P
* 5£		1.7	2.4	1.7	. 1							6 • ⁴ ;	+.7
	1 3.7	3.5	4.,	1.1	. 9							13.1	7.1
45#	1.3	٠.	1.0	.5								4.5	1.0
5.	.5	1.5	- 1									÷.:	4.4
₩ '5 ₩	.2	1.0	• .'									1.4	5.6
•	1.3	٠,	. н									1.1	٠.٠
h fe in		. 2	• .									. 6	4.1
N to		1.6	1.3	. 1								3.7	6.5
NNW	1.3	2.3	2.3	2.5	• 5							P.7	9.0
VAH 1 A HL F	· !	•••••	• • • • • •	•••••					•••••		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • •	
CALM	 <i> </i>	///////	,,,,,,	,,,,,,,,,,	1111111	,,,,,,,	///////////////////////////////////////	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	15.4	111111
TOTALS	1 1 16.5	. 5.a	24.5	15.3	3.7	. 9						100.0	1.6

SLUHAL CLIMATOLOGY BRANCH USAFLTAC AIR WEATHER SERVICE/MAC

PEPCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER	7: 724505	STATION	NAME :	MCCONNELL	. AFB KS				PERIOD MONTH:	OF RECOR	0: 17- HOURS(LS)		L
	• • • • • • • • • •	•••••	• • • • • •	•••••		n speen	IN KNOTS		• • • • • • • •	•••••	•••••	• • • • • • • •	•••••
DIRECTION OEGREESE		4 - 6	1-10	11-16			28-33		41-47	48-55	GE 56	TETAL	ME AN WIND
N	1,2	3.6	5.6	6.5	2.0		.1	• • • • • •		•••••		19.7	10.8
NNE	.9	1 - 8	2.5	2.3	.5	. 1						8.1	9.2
NE.	.5	1.6	1.3	.5	•1							3.9	7.2
ENE	.5	1 • D	. 8	. ?	•0							2.5	6.3
Ł	.8	1.6	. 9	• 2	•0							3.5	5.9
171	.4	1.0	. 8	• 2								2.4	6.3
Sf	.5	1.0	1.0	. 3	• 0							2.7	6.6
.71	.6	1.5	2 • C	1 • 8	.4	• 0						6.4	٥. و
١ ،	1.8	2+5	3.3	2 - 4	1.1	.4	•0					11.5	9.4
55 g	.9	1 - 7	1.7	1.0	• 2	- 1						5.6	7.8
SW	.6	1.2	. 9	-6	• 0							3.4	6.8
WSw	.7	1.5	. 6	• 1	•0							2.8	5.5
-	.9	1 - 3	. 7	-1								3.0	5.2
날리날	.5	• A	.6	-1	1.	• 0						2.1	6.5
NW	.5	• 9	1.1	1.0	• ?	- 1	•0					3.7	8.8
Mem	.7	1 - 6	2.6	3.0	.6			• 0)			R . 7	10.2
VARIA-LE			• • • • • •	• • • • • • • • • • • • • • • • • • • •		• • • • • • • •	•••••	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	•••••			
· ·	ı	11111111	,,,,,,,	//////////	,,,,,,,,	,,,,,,,,	,,,,,,,,,	,,,,,,,				9.9	111111
TOTALS	l 12.0		26.5		5.4	1.5	. 1	•0				100.0	7.8
IOTAL S	1 12.0	24.4	20.5	20.2	3 • 4				, 			100.0	r • · ·

GLOBAL CLIMATOLOGY BRANCH

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS

PEPLOU OF RECORD: 77-86
MONTH: FEB HOURS(LST): 0040-02(0
WIND SPEED IN MNOTS
7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-41 67 DIRECTION ! I (23 38830) N 15.4 1.8 NNE 1.3 1.7 2.1 7.9 8.5 • 6 1.1 1.4 .9 ٠,١ 6.4 NE . 7 4 - 3 ENE . 8 . 9 . 5 2.4 . 1 5.8 . 4 Ł . 9 . 9 . 2 . 1 . 1 2.7 7.6 FSE . 9 1.3 .6 2.8 5.0 SE . 9 4.5 6.2 SSE 2.8 8.5 6.4 2.7 S 5.3 8.7 16.8 1.3 . 7 SSW 1.2 6.7 1 - 1 4.3 . 7 . 9 5.1 SW . 6 . 1 2 - 4 WSW 1.1 • 7 2.1 4.1 .4 . 7 . 1 . 5 1.7 7.3 . 2 MNW . 5 . 2 . 9 4.5 NW 1.1 • 5 2.5 e.9 NNW VARIABLE CALM

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): 0300-0500 STATION NUMBER: 724505 STATION NAME: MCCONNELL AF 8 KS wind speed in knots DIRECTION | 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL PEAN IDEGREES! 1 ı. WIND - 1 2.6 4 - 1 6.6 2.2 18.0 10.5 HNE 1.7 1.9 2.0 1.4 . 1 7.1 7.0 ٨F . 7 1.1 1.4 • 8 4.0 7.7 ENE . 5 . 9 . 7 . 1 2.2 6.3 £ .6 . i 3.0 6.2 . 7 FSE . 4 2.1 5.7 .9 SE 1.7 1.5 . 1 4.5 5.8 1.2 9.6 SSE 1.9 3.5 3.4 .6 • 1 6.4 s 2.7 1.9 4.4 3.5 . 4 12.9 8.6 SSW 1.9 ٠l 4.7 SH . 1 . 1 1.3 4.5 WSW . 4 2.5 1 - 1 7.2 • 2 • 8 7.0 • 6 • 1 NW 1.8 1.1 . 2 3.9 9.7 . 1 . 7 NNW 2.0 2.5 .6 6.5 13.5 ///// TOTALS 100.0 t.9 3.9 21.0

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

1

PERIOU OF RECORD: 77-86

#ONTH: FEB HOURS(LST): 06U0-06CU

#IND SPEED IN KNOTS

DIRECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 28-50 ... N 1.8 2.7 7.2 5.2 2.7 . 8 - 1 20.6 11.0 1.3 2.8 2.0 . 9 7.7 7.4 NNE • 6 NE . 7 1.2 . 9 . 8 3.7 7.3 ENE . 5 . 2 E .7 6.2 . 9 2.1 4.0 ESE . 9 . 2 SE 1.1 1.8 1.7 . 7 5.2 6.4 1.5 7.2 SSE 2.5 2.2 1.6 . 1 8.2 S 3.0 3.2 4.4 3.3 . 8 . 2 14.9 8.2 SSW . 8 . 4 . 1 3.1 6.4 • 1 7.0 • 6 5.7 . 2 - 1 1.8 •6 WNW . 1 . 8 5.6 • 6 . 1 А.В Na . 5 1.3 3.1 NNW 2.1 VARIABLE CALM TOTALS . 1 100.0 26.0 18.0 4 . 7 1.2 7.7

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFLED FROM HOURLY ORSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): G900-1100 WIND SPEED IN KNOTS
DIFECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL MEAN (DEGREES) 1 HINDN 3.8 1.7 7.1 20.1 13.1 2.4 2.8 1.3 . 4 7.4 NNE .6 8.4 ΝE . 9 2.1 1.5 . 8 5.4 6.8 FNE 1.1 1.3 2.7 6.3 Ĺ 1.1 1.5 .6 3.3 7,9 ESE 1.1 . 4 1.7 6.1 . 1 . 7 5.7 SE "SE 1 - 7 2 . 8 3.8 .5 . ? 10.5 • 2 5.9 15.7 5 2.6 3.9 1.8 10.8 1.2 1.4 . 9 SSW 2.1 2.0 ٠ ١ 8.3 6.6 . 5 . 5 2.6 8.5 S¥ • 6 . 8 . 1 - 1 • 7 . 5 . 1 . 1 2.0 6.0 . 1 • 2 - 1 2.5 8.0 7.9 - 1 . 9 • 1 7.0 NW - 1 • 7 NNW 1.3 2.2 12.1 CALM 6.0 ///// 150.0

GLUBAL CLIMATOLOGY BRANCH AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTIONS

STATICH NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORDS: 77-86
MONTH: FEE: HOURS(CST): 1230-1460 NIND SPEED IN KNOTS

DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 45-55 OE 56 TCTAL MEAN 22-21 28-33 34-40 41-47 48-55 UE 56 1 123340301 ı wI*L 5.9 . 4 1.8 4.3 2.5 1.3 16.5 12.8 5.2 NNE .6 . 9 2.8 3.5 • 2 1::1 NE . 8 . 9 . 5 - 1 2.7 7.9 • 7 7.7 • 2 . 9 ۹., . 1 ESE . 1 6.9 • 2 1.1 . 7 • 5 1.1 SE • 2 • 7 7.7 1.2 ₹ S E 1.2 1.9 1 - 1 1.2 0.5 1.3 S 3.2 2.5 2.7 5.0 15.5 11.8 55% . 4 2 - 7 2.6 4 . 3 1.3 11.2 Sil . 8 2.1 1.4 .5 ٤.4 - 1 • 6 ٠2 . 2 .6 t.7 1 - 1 . 4 10.1 NW .2 . 9 1.3 . 9 . 5 1.4 ψ. s, 1.2 NNW 1.4 2.4 11.7

2.7

11.0

3.1 //////

10.1

160.0

TOTAL NUMBER OF OBSERVATIONS:

28.0

CALM

GEORAL CEIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

AIR MEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): 1500-1700

LIND SPEED IN KNOTS
7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN DIPECTION | (DEGREES) 1 615b 6.0 2.1 16.3 12.0 7.1 10.2 NNE .5 . 9 NE 6.9 1.1 ENE .6 7.4 . 9 1.5 3.3 • 2 -6 1.9 FSE .6 • 5 - 6 • 2 6.1 SE . 7 1.2 1.1 .6 . 2 3.8 7.4 .5 1.1 3.1 . 9 7.4 11-3 2.0 1.7 1.5 2.4 10.6 ٠ که **۵** . 6 .6 • 2 • 8 2.2 3.4 5.8 - 8 . 1 • 2 . 5 4.0 6.5 1.1 . 9 1.4 . 1 . 9 . 4 3.4 9.7 1.1 969 - 1 . 9 1.1 1.2 1.1 . 8 4.7 9.8 VARIABLE ! CALM 2-1 ///// 100.0 4.9

SERBAL CLIMATOLIGY READON PERCENTAGE FREQUENCY OF OCCURRENCE OF JUPEACE WIND SINECTION VEHICLS AFELD CHARLES FROM HOUSELF OF SERVICEZHAC.

• • • • • • • • • • • • • • • • • • • •	• • • • • • • •	• • • • • • • •		• • • • • • • •					• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	
1 PECTION CEBURGES	1 - 4	4 - 6			17-21	22-21	1% #NUTS	\$ 4 - 4 ()	41-47		UE 56	TL TAL	ME AN
١	1.1	3 - 4	6.4	4.5	3.4	.*	• • • • • • • •		• • • • • • • •	• • • • • • •	•••••	19-1	10.5
P.N.F. I		1.4	2.0	1.5	. 4							6.6	F.5
Nt [.6	1-2	. •	.4								1.1	6.9
rw. I	. 5	i. •		. 4								3.0	6.5
E I	.7	1.9	1 - 4	. 4								4.1	5.9
ا ادا	1.1	1.5	. 9	•.*	- 1							7.7	6.0
51	1.5	2.4	1.2	. 1								٠.,٢	5.0
1 152	1 - 2	1.5	1.9	1.2	• 1	.,							A
5	1 - *	4.1	4.5	4,5	٠,٠							16.6	A.3
•5•	.,	1.5	1. !	. 1								4.5	1.:
· .	.,	. 7	.•	. 4								1.7	۴.9
1 	.,	. •	. 7									1.4	٠.،
	.7											1 . '	1.3
#5m	.2	. •	• •	:	. 1							1.7	*,4
	. 4	1.1	1.3	1 - 1	• •							4.5	A . *
No.	. •	,	1.7	1.4		• 1						٠.	¢.1
*#HIAGLE	• • • • • • • • • • • • • • • • • • • •	•••••		•••••		• • • • • • • •		• • • • • • • • • • • • • • • • • • • •	••••••		•••••	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
	,,,,,,,,,,	,,,,,,,	,,,,,,,	11111111	,,,,,,,	,,,,,,	.,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	i 1 - 1	,,,,,,
TOTAL: 1	1'.1	21.0	25.4	11.1	4.6	.,						160.0	7.1

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR #FATHER SERVICE/MAC PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER	P: 724505	STATION	NAME:	MCCONNEL	L AFB KS	•			PERIOD MONTH:	OF RECOR FEB	D: 77- HOURS(LS)		2300
	- • • • • • • • • • • • • • • • • • • •	•••••	• • • • • • •	• • • • • • • • •	uln	D SPEED	IN KNOT	· · · · · · · · · · · · · · · · · · ·	• • • • • • • • •	• • • • • • • •	• • • • • • • •	•••••	• • • • • • • •
DIRECTION (4 - 6	7-10	11-16	17-21				41~47	48-55	GE 56	TOTAL	ME AN
N	1.3	2.0	5.9	5.1	2.1	.4	• • • • • • •	•••••	• • • • • • • •	•••••	•••••	16.8	10.9
NNE	.8	2.4	2.8	1.4	.7	• 1						9.3	8.8
NE	.8	1.1	. 8	• 2								3.0	5.9
FNE	.8	1.3	. 6	• 2								3.2	5.5
L	.9	1.8	• 9	.4								4.0	5.6
ESE	.9	. 9	1.5	• 2								3.5	6.0
SE	.9	1.9	1.4	.4								4.6	6.1
55F	1.2	3+0	2.5	1.9								8.4	7.1
S	1 • 2	2.6	3.4	5.4	• 5							13.1	5.6
55# 	1 - 1	1 • 3	1.8	.7	• 1							5.0	6.9
Sw	.2	• 7	•5									1.4	5.4
154 I	1 .7	- 1	•2	• 2								1.3	5.5
	.2	•5	• 2	•2								1.2	6.3
UNU	! .6 !	•6	• 2	• 2								1.7	5.9
NW	l .4	1.2	. 8	.4								2.7	6.9
NNW 1	, 6 I	1.2	1.5	1.2	•6	• 2						5.3	10.1
VARIABLE		•••••	• • • • • •	• • • • • • • • •	• • • • • • •	•••••	• • • • • •	•••••	• • • • • • • •	• • • • • • • •	• • • • • • • •	•••••	• • • • • • • •
CALM	 /////////	,,,,,,,	//////	,,,,,,,,	,,,,,,,	1111111	,,,,,,,		(//////	,,,,,,,,	,,,,,,,,	16.5	111111
TOTALS	12.6	22.5	25.5	10.1	4.0	.7						100.0	6.9

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): ALL #IND SPEED IN KNOTS 17-21 22-27 28-33 DIFECTION ! 7-10 11-16 4-6 34-40 48-55 GE 56 TUTAL MEAN IDEGREES) 1 ı FIND N .1 1.3 5.3 5.8 2.2 2.4 • 6 17.R 11.4 1.0 1.9 2.3 NNE 1.9 • 0 . 4 7.5 8.6 NE . 7 1.3 1.1 -6 - 0 3.7 7.0 .5 ENE 1.0 . 8 . 3 2.6 6.4 Ĺ .6 1.3 1.2 •0 • 0 FSE . 7 • 0 ٠D 5.7 • 8 . 9 SE 1.5 1.3 . 3 .0 4 - 1 6.2 558 1.2 2.1 2.3 . 4 • 1 8.0 8.3 s 1.9 3.9 . 3 2 . 8 4.8 1.2 14.9 9.7 . 9 5.5 W 1.4 • 0 1.9 1.6 . 3 6.0 6.6 SK . 5 . 7 . 8 • 5 •0 • 0 2.5 7.2 **45**W .6 ٠0 .5 . 9 6.6 . 1 • 6 • 0 8.2 Ne . 3 . 9 1.2 . 8 . 2 3.4 8.8 1.5 1.7 2.2 1.0 • O 10.5 9.9 /////

. 2

100.0

8.0

6.2

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUBSECT WIND DIRECTION VEHSUS WIND SPEED FROM HOUSELY OBSERVATIONS

AIR MEATHER SERVICE/MAC

COFGREES) 1 1 BINL 1.9 1.7 . ? 12.6 10.4 NNE 1.0 2.4 1.9 ٠, . 4 . 1 4.1 6.0 2.0 .5 . 3 5.1 1.3 NE . 8 . 3 ٠. ۵ ENE 1.5 2 . 7 1.3 6. 2.2 . 9 £ 1.7 2.0 4. . 4 4.6 1.1 . 3 ESE 1.5 1 . 7 1.0 4.9 1.5 SE 1.6 1.1 10.3 1.9 3.0 4.2 . 5 10.0 SSE . 6 11 - " 1.9 1.0 12.7 S . 9 2.7 2.2 4.1 4.9 55# . 8 1.0 1.3 1.0 . 5 4.5 . 8 514 - 1 • 2 . 1 6.3 WSW . 3 . 1 1.9 4.9 • 5 . 1 5.7 .4 •6 . 1 . 3 1.7 9.2 • 2 . 2 1.0 . 9 1.8 .6 1.8 . 2 NNW .5 1.6 11.3 VARIABLE 10.2 ///// TOTALS . 1 100.0 7.8 23.3 22.5 21.3 6 • 6

GLOBAL CLIMATOLOGY RRANCH USAFETAC PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS AIR MEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS

PERIOD OF RECORD: 77-86 MONTH: MAR HOURS(LST): 03J0-05CU | WIND SPEED IN KNOTS | DIFFCTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 6 56 TETAL PEAN CUEUREISI I 3 BINL 2.0 1.7 . 4 17.9 10.5 MINE . 9 1.9 2.2 1.1 . 3 . 2 6.6 8.2 . 2 Nf . 6 1.5 1.8 . 6 4.0 7.7 ENE 1.6 1 . 7 1.9 • 6 5.9 6.5 . 9 ŧ 2.4 1.9 £ .] FSE 1.3 . 6 • 5 7.9 6.5 1.0 4.8 8.1 < 5 F . 9 2.3 2.9 1.7 . 5 9.3 4.6 1.5 2.5 4 4 2.9 S 2.4 13.9 . 2 11 - 2 1.9 < 5 H . 3 . 4 . 8 . 1 3 . ". 7.5 . 5 SW . 4 .5 . 1 2.4 7.2 .5 • 2 . 4 4.8 . 5 . 4 • 2 1.5 . 3 6.2 .5 • 2 . 1 • 6 1.6 7.8 . 3 1.5 . 3 2.2 . 3 4.9 11.0 . 3 2.5 */** 1.5 1.0 . 2 1.1 . 3 6.6 11.8 CALM 11.6 ///// 21.9 100.0

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS

MEMILOU OF MECURU: 77-86 MONTH: MAR HOURS (EST): UNUC-06CC MIND SPEED IN ANDIS 7-10 11-16 17-71 22-27 28-33 34-40 41-47 48-55 GF 56 1775 DIFECTION ! 1 - 3 MEAN LDEGREES) I 6.0 11.1 PIPE E . 3 4.7 • 6 . 4 5.2 NE 1.1 1.6 1.6 . 1 h . 4 FNE 2.5 1.5 1.1 4. . 7 . 6 1.: 2.5 1.0 7.4 1.1 Ł 1.4 . . 6 FSE . 3 1.3 1.2 . 1 2.4 1.4 . 5 SE 1.3 1.8 1.0 . 1 4.7 H . I SSF 1.0 . 8 . 1 111. 1.4 2.7 11... < 5 w 1.0 1.2 . 3 ٠., . 6 - 1 . . ٠.٠ . 8 . 4 . 2 . 3 1.7 . 3 . 3 . 1 1.4 4 . H WSW . 6 - 1 . 5 . 2 . ? . 1 1.7 1.4 . P 7.4 . 6 . 4 . 4 1.4 1.1 1.5 ٠1 . 2 9.4 VARIABLE CALM 7.7 ///// 130.0 TOTALS 1.7

GLUHAL CLIMATOLOGY BRANCH PROCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECT FROM HOURLY ORSERVATIONS

AIR WEATHER SERVICE/MAC STATION NUMBER: 7245U5 STATION NAME: MCCONNELL AFB KS PERIOD OF MECORD: 77-86
MONTH: MAR HOURS(LST): G9JO-1100 WIND SPEED IN KNOTS UIFECTION 1 22-27 28-33 34-40 41-47 48-55 GE 56 1 - 5 4 - 6 7-10 11-16 TUTAL MEAN . INU IDEGREES) 1 2 12.7 . 4 15.2 . 5 1 - 3 4.1 6.0 2.8 1.1 4 . A A.5 1.NE 1.7 1.3 . 1 . 6 1.0 9.7 NF .6 . 9 1.5 . 4 4 . 4 ENE 1.6 2.2 1.0 . 2 5.4 8.2 . 5 1.9 2.5 . 5 5.6 7.2 1.1 7.5 ESE . 3 . 5 9.5 4.2 SF . 5 1.9 1.5 . 2 158 . 3 1.4 7.1 4.4 1.7 . 3 10.9 11.9 13.8 5.2 14.6 s .5 . 9 3.4 2.9 1.6 7.0 11.9 554 1.2 2.0 2.0 1.0 . 5 8.9 • 5 1.0 . 2 . 3 . 1 2.6 10.0 1.0 . ? • 2 6.4 • 6 10.7 . 3 1.0 . 4 . 1 *** . 6 . 4 . 2 3.7 12.4 - 1 . 3 1.2 1 - 4 . 4 fe w NNW 1.7 1.6 2.5 1.0 . 6 . ? 8.0 12.2 VARIABLE I CALM 1.9 ///// 100.0 TOTAL 28.1 30.1 11.9 4.0 10.A

GLUBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SEELD FROM HOURLY OBSERVATIONS

STATION NUMBER	724505	STATION	NAME:	MECONNELL	AF8 KS	•			PERIOD :	OF PECORS): 77- HOURS (LST		400
	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • •	• • • • • • • • • • •		D SPEED			• • • • • • • •				• • • • • • • • • • • • • • • • • • • •
DIRECTION IDEGREES)	l	4-6	7-10	11-16	17-21	22-21	28-35	34-40				TOTAL	ME AN Hinu
N [.5	1.7	3.8	5.7	2.6	.4	•••••	• • • • • • •	• • • • • • • •		••••••	14.7	12.3
NNE I	•2	.8	1.6	1.5	. 1							4.2	9,8
NE I	•2	• 8	1 . 3	1.5								3.8	9.5
ENE	.5	•5	- 8	.9	. 1							2.8	8.1
٤	.6	1.4	1.7	• 4	-1							4.3	7.1
ese i		. 9	1.6	.4								2.9	H.5
SE	.5	1.4	1.2	. 9								4.0	7.6
382	.5	1.2	2 • 2	3.8	1.8	.6						10.1	12.6
s	.3	1.1	2.7	5 • 5	4.0	2.8	.4					16.8	15.4
SSW !	.4	• 8	1.9	2 • 2	1.3	1 - 3	- 1					9.0	13.5
SW	-1	1.2	1.0	1 - 4	-2							3.9	9.8
พรพ	.9	1.0	. 9	.6	-1							3.4	7.0
¥	.3	•5	. 8	•5	•6							2.8	10.9
WNW	•1	. 4	• 9	.4	• 3	• 2						2.4	11.9
NW	• 3	• 9	1 - 1	1 - 4	.8	. 1						4.5	1 . • 4
NNW 1	.4	1.2	1.9	4 - 1	1.5	.5	. 3					10.0	13.0
VARIARLE		•••••	• • • • • •			• • • • • • •	•••••	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • • •	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •
i	ĺ	,,,,,,,,	,,,,,,	,,,,,,,,,,	1111111	1111111	11111111	,,,,,,	11111111	((((())	,,,,,,,,	1.5	111111
FOTALS !	5.1	15.6	25.2	31.2	13.5	6.0	. 9						11.6
										• • • • • • •			• • • • • • • • • • • •

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

100.0

11.5

AIR WEATHER SERVICE/MAC

PERIOD OF RECORD: 77-86 MONTH: MAR HOURS(LST): 1500-1700 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS | WIND SPEED IN KNOTS
DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL MEAN IDEGREES) 1 m I N L N 11.5 PINE . 4 1.1 1.6 1.6 4 . P 9.2 NE - 1 3.1 R.5 FNE . 9 . 4 1.0 9.6 . 2 . 2 2.7 1.7 . 1 Ł 1.2 3. 0 6.6 f SE . 5 . 9 1.0 1.6 . 1 8 • C SE . 3 1.0 1.3 3.0 9.3 SSE . 3 1.1 2.7 3.9 1.0 s 3.3 1.3 6.5 14.9 . 3 18.1 55 W 1.3 1.3 • I 2.8 1.0 14.4 SW • 2 . 9 1.6 . 6 - 1 3.4 8.3 . ? 1.3 . 3 U.S.W • 3 . 8 . 1 3.0 10.4 . 9 1.4 . 1 . 3 -٠2 . 8 1.9 . 4 . ? 12.0 1.0 10.4 NIVE . 1 12.4 VARIABLE CALM

FOTAL NUMBER OF ORSERVATIONS: 930

TOTALS

GLUBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
MONTH: MAR HOURS(LST): 18U0-2000 | WIND SPEED IN KNOTS | DIRECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 TUTAL (DEGREES) ! ı WIND 3.5 5.2 1.0 16.0 9.7 . 3 7.3 8.5 NNE 1.0 1.2 + 8 . 4 3.2 6.8 ΝE . 8 . 1 . 5 1.2 . 5 3.5 7.5 FNE . 2 1 - 1 .9 1.1 5.2 6.5 Ł 1.7 1.5 3.3 8.1 ESE . 9 1.8 . 3 . 1 SE . 3 1.5 1.6 . 3 • 3 4.1 8.1 SSE . 9 2.3 4.5 2.1 .9 . 1 11.3 4.3 1.7 18.5 10.7 1.3 B.5 55 W 5.6 1.0 • 2 • 2 SW - 1 . 3 . 4 . 3 . 1 1.2 5.7 MSM 2.4 5.5 . 6 1.1 . 4 - 1 . 1 2.6 UNU • 2 . 3 1.1 • 6 . 3 10 • 3 . 9 1.3 1.0 . 1 • 2 3.7 9.8 NNW 10.5 VARIABLE I CALM 6.8 /////

TOTALS 28.0 6.2 1.5 100.0 8.4

TOTAL NUMBER OF OBSERVATIONS:

930

GLOBAL CLIMATOLOGY BRANCH USAFLTAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

											RIOD OF RECORD: 77-86 ONTH: MAR HOURS(LST): 2100-2300					
 DIPECTION IDEGREES)	1-3	4-6	7-10	11-16	WIA 17-21	D SPEED 22-27	IN KNOTS 28-33	34-40	41-47		GE 56	TCTAL	ME AN WINU			
	1.6	2 • 4	3.0	3.3	.5	.4	• • • • • • • •	•••••		• • • • • • • •	•••••	11.3	9.5			
NNE	1 - 1	2.3	2.2	1.8	•6	. ?						8 • 2	9.2			
NE I	1.8	1.2	1.5	1.0								5.5	6.1			
ENE	1.0	1.2	1.1	•5								3.8	6.3			
L	1.7	1.5	2.8	.9	. 3							7.2	7.2			
FSE	.6	1.4	1.3	.5								3.9	6.8			
SE	.8	1.4	2.6	1.8								6.6	8.3			
SSE	1.0	2 • 7	4.7	2.9	. 4	. 3						12.0	9 - 1			
s į	2.3	2.4	1.7	5.4	2.0	• 5						14.3	10.8			
SSW .	. 4	•6	.8									1.9	6.0			
Sw	. 4	• 2	• 1	• 1								.9	·, • 0			
WSW	• 3	•5	• 2									1.1	4.6			
u į	. 9	• 5	. 8	• 1								2.7	6.2			
unu		• 5	. 3	- 1	. 4							1.4	10.7			
NW	•1	- 8	.6	. 4	. 5							2.5	9.7			
NNW I	.4	1.0	1.7	2.0	•6	.4						6.2	11.1			
VARIABLE	• • • • • • • • •		• • • • • • •	• • • • • • • •	*******	• • • • • • •	• • • • • • • • •	•••••	• • • • • • • •	•••••	•••••	•••••	•••••			
CALM I	////////	///////	///////	'''''	///////	///////	,,,,,,,,	,,,,,,	,,,,,,,	///////	11111111	11.3	/////			
TOTALS	14.3	20.5	25.4	21.0	5.6	1.9						100.0	7.8			

GLOBAL CLIMATOLOGY BRANCH USAFLTAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

		• • • • • • • •	• • • • • • •	• • • • • • • •			IN KNOTS		• • • • • • • •	•••••	• • • • • • •		
TRECTION DEGREES!		4-6	7-10		17-21	22-21	28-33	34-40			•-	TCTAL	ME AN BIND
N	1.2	2 - 3	3.2	5.2	1.5	. 4	• • • • • • • •	•••••		•••••		15.4	11.0
NNE	.7	1.5	1.8	1.5	. 3	. 1	• 0					5.9	8.9
NE	.8	1.3	1.3	.9	. 1							4.4	7.7
FNE	.9	1.4	1.4	. 7	. 1							4.4	7.1
	1 • 2	1.8	2.1	. 7	• 1							5.9	t.1
ESE	.5	1.2	1.3	.5	•0							3.5	7.1
3.5	.6	1.1	1 • 8	1.1	. 1							4.5	B + 2
SSE	. 7	1.9	3.2	3.4	1.0	• 3						10.4	10.5
s ¦	1.1	2.1	2.9	5.0	3.1	1.1	- 1					15.3	12.5
\$\$w	.4	1.0	1.2	1 • 3	•6	. 3	•0					4.8	11.2
SW	. 4	•6	.6	.4	. 1	• 0						2+1	7.8
ESH	•5	•5	.5	. 3	• 1	• 0						1 - 4	7.4
•	.5	- 8	.6	. 3	-1	•0						2.4	7.6
WWW (•2	• 5	. 7	. 5	• 3	• 1						2.2	1(+2
Ny	. 3	.9	. 9	1.3	.4	- 1						4.0	11.0
NNW !	.4	1.2	1.7	2.9	.9	. 4	• 1					7.6	11.9
ARIABLE !	•••••		• • • • • • •		•••••	• • • • • • • •	•••••	•••••	• • • • • • • •	•••••	•••••	• • • • • • • • • • • • • • • • • • • •	
ALM !	,,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	6.9	111111
IOTALS I	10.2	19.9	25.2	26.0	8.9	2.9	• 2					160.0	٧.,

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTIONS

PERIOD OF FECORU: 77-86
MONTH: APR HOURS(EST): DOJO-02CO STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

3,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		•							MONTH:	APR	HOURSILST	1: 0000-	0.40	
DIRECTION (DEGREES)		4-6	7-10	11-16	=IA 17-21		IN KNOTS 28-33	34~40	41-47	48-55	UF 56	TCTAL 2	ME AN HIND	•••
N	.9	ن	3.0	1.3	.1	• • • • • • •		• • • • • • •			•••••	7.7	7.9	• • •
NNE	.9	1.7	1.2	. 6	. 3							4.7	7.4	
NE 1	l 1 1.1	7.2	.9	. 8	. 3							5.3	6.8	
ENE I	1.6	2-1	1.4	. 7	. 1							5.9	6.4	
i [1 1.4	2.4	2.6	1.6	• 1	- 1						8.2	7.5	
ESE	.7	1.9	1.3	. 9	• 1	. 1						4.9	7.5	
5F	. 8	1.6	.н	.9	. 3	. 1						4.4	7.7	
551 I	1.4	3.2	2.3	3.3	. 3	- 1	. 7					11.0	٧.0	
) S I	.9	2.6	3.4	5.9	1.9	. 4						15.0	11.0	
* S w = 1	. 7	. 4	1.2	1.1	. 1							3.6	9.8	
	.2	. 1	. :	.9								1.6	9.7	
 	l .4	. 9	. 4	. 1								1.9	5.4	
•	. 5	1.0	. 6	.2								2.1	5.8	
e fra i	.4	. 7		.6	. 1	.2						2.2	9.6	
N₩ 1	 • 1	. 9	1.0	1.1	1.2	. A						5.3	12.8	
1994 1994		1.6	1.7	1.7	. А	. 1						6.1	10.1	
	! ! • • • • • • • • •	· · · · · · · ·			• • • • • •									. .
VAHIAHLE I	i													
I	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							1111111	,,,,,,,	,,,,,,,,	11111111		111111	
TCTAL* (1 17.4 I	25.6	22.4	21.3	5.9	2.0	. ?					140.0	7,9	
	. .													

GLOZAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELF.
FROM HOURLY OPSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOU OF RECORD: 77-86 MONTH: APF HOURS (LST): UTVICES

									MONTH:	APF	HOURSILS	The Civile	
IPECTION OEGREES)	1-3	4-6	7-10	11-16	17-21	22 - 2 7	IN KNOTS 28-33	54-4 U	41-47	46-45	GE 56	T(TA)	ME AA.
N	.6	3-2	3.1	2.6	. 3	. 1	******	• • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	4.4	• • •
NNE I	.6	2.1	1.3	.9	• 2	- 1							٠.
NE	1.0	2 • 1	1.1	.7								4.3	٠.
ENE	1 - 1	1.0	1.9	1.2								• •	٠.
E !	1.7	3.2	2.0	. 3								1.3	٠.
ESE	.9	1.0	1.8	. 7	•2							4.6	٠.
SE .	.6	1.3	1.3	1.8	• 2	. 1						٠.,	٠.
SSE	.9	2.2	2.2	2.9	. 4	•2	- 1					¥.	٠.
s į	1 • 3	2.4	3.0	6.1	2.0	. 1						15.	
SSN	.4	•8	1 - 7	. 3	- 1							٠.٠	٠.
su	.6	•6	• 6									1.	٠.
wsw !	.4	. 4	• 9	. 3	.1							2.2	٠.
	. 9	1.2	.7	. 3								3.1	٠.
END :	.8	• 7	.8	•2	. 1							•	٠.
NW I	. 3	1.0	1.1	1.0	.9							4.7	
NNE	• 3	1.8	2.3	1 • 1	1.1	.6						1.3	
VARIABLE 		· · · · · · · · · · · · · · · · · · ·											
TOTALS 1	12.3	25•1	25.8	20.4	5.8	1.2	•1	,,,	,,,,,,	,,,,,,,			
IVIALS I	12.3	25-1	25.8	20.4	5.8	1.7	• 1					141.	,.

LE MARTINE EL MERGER DE L'ESTRATA LE CARLINGENCE DE L'ESTRATE DE L'ESTRAT D'ARTINE DE MERGER DE

										and you to we have the control of th						
• • • • • • • • • •		• • • • • •		• • • • • •	· · · · · · · · · · ·				 .		• • • • • • •	• • • • • • • • • •				
i de la transferiore. Esta porte de la transferiore.		; *	• •			· · · i	The second second	* 4 W (4 * 1	A SE	1	#4 8 % # (% c			
			1	•		, ,										
, \$5, 4		;.		1.7	. •	. :							٠.٠			
*, \$. 7										٠.				
1.147		. •		. '	1.5							• . •	٠.٠			
	:	i • '		1.*								٠, •	• . •			
1.0		! •		i. '	. •							* . *	٠. •			
			. •	1		. 4	• P					•				
+ + 1		. •	. 1		٠.		. *					~.•				
	÷	. *		1.5	٠	. *	. 4					•				
•		.*	1.9	1.4								*	٠.			
. •	1		. •	. •									. •			
. 5.	:	. •			•							• 1	* . *			
•			. •		. •											
60 a	1	- 1	. •	. 9	. 1							. •	٠.			
·• •	1			1.•		• •	• •					٠.				
*. 4 •	ŧ	• -	!	. •	. •	. •	•					٠. ـ				
### A m c f				• • • • • •	• • • • • • • • • •	• • • • • •	,		<i></i>	•••••			• , ,			
4, 4	1,,	,,,,,,	1111111	//////		111111		1 - 1 - 1 - 1			***	٠.٠				
Trial	i	9.4	/1.4			n. 4						,				

TOTAL NUMBER OF ORSENVATIONS: NO

ATH MEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPPLACE WIND DIRECTION VERSUS WIND SHEED FROM HOUNLY OFSERVATIONS

STATICH NUMBER: 724565 STATION NAME: MCCGNNELL AFP HS PERIOD OF PECUPO: Coromers) | -150 1.1 11.7 . . p 15.7 . • . 1.0 1.7 ٠., ٠. ٧ 2.0 - 1 6 . 1 ٠,٠ 2. . . . 1 4.6 7.8 1.1 6.46 1.3 2.1 r ... 7.9 . 6 . 6 - 1 1 - 2 . 7 2.5 , • . 1 4, . 5 1.3 63,6 1.4 13.0 - 1 1.7 . 1 10.0 1.4 . . 4 1.6 11. 10.0 14.0 . 9 1.6 7.4 1.4 . 4 4 . 1 15. - 6 1.4 . . 5 1.0 . 4 . . . 11.4 1.0 ٠.4 . • = - 1 1.6 1.1.9 • 1. 2.4 B . B • . , .+ . 1 2.3 11-5 ... 1.1 1.1 . 1 1.4 ٧... 4.1 ٠. . 1 1.7 . 1 11. . . , 10.6 1.4 10.9 . 1 100.0 41.3

TO THE MINISTER OF CHSERVATIONS

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND STRECTION VERSUS WIND STEED USAFETAC

AIR BEATHER SERVICE/MAC STATION NUMBER: 724565 STATION NAME: MCCONNELL AFRIKS PERIOD OF RECORD: PERIOD OF RECORD: 77-86

MONTH: APP HOURS (LST): 12J0-14L0

WIND SPEED IN KNOTS

UIFECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 UE 56 TUTAL PEAN
(DEGREES) | (DEGREES) I -140 1.9 12.7 MNE . 7 1.0 1.2 . 3 3.7 10.1 1.0 NF 1.6 . 3 1.0 μ., FNE - 1 1.3 2.3 1.0 ŧ . 1 ٠.١ . 7 ESE - 8 1.3 1.2 7.9 SF . 3 2.1 2.2 1.4 - 1 6.2 9.4 :58 . 8 . 9 1.6 2.7 1.8 . 6 8.2 6.0 1.3 4.0 1.7 ٠1 . 7 • 3 12.0 . 3 9.0 NS H . 9 1.2 1.1 - 1 4.0 10.8 . > . 7 . 9 12.3 1.1 . 1 3.5 10 Po 10 - 1 . 4 . 2 . 9 1.9 . 1 5.1 15.6 NW . 6 PIN W 3.3 1.7 12.7 VARIABLE CALM 1.3 ///// TOTALS 6.3 . 2 100.0 25.1 32.6 15.3 11.9

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC FROM HOURLY OBSERVATIONS
AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOU OF RECORD: 77-86 MONTH: APP HOURS(LST): 15J0-17CG PERIOD OF RECORD: MONTH: APR HOL | WIND SPEED IN KNOTS
DIFFCTION | 1-5 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL MEAR IDEGREES) 1 LINL .7 .2 2.7 5.8 12.9 12.5 NNE . 3 1.3 1.4 . 1 1.4 10.4 • 2 Νŧ . 2 1.0 1.1 1.1 . 3 5.9 9.4 . 3 F faF 1.3 • 3 - 6 2.6 7.4 Ł . 8 1.7 3.4 1.2 7.3 8.2 FSE 1.7 8.3 . 1 10.4 3.4 12.7 2.1 6.7 . 3 . 8 4.6 17.3 15.7 2.6 . 3 2.9 1.0 1.7 . 8 7.1 14.5 5 W - 1 . 7 1.1 . 9 . 1 . 1 3.0 9.9 • 3 . 6 . 3 . 2 ٠1 1.7 11.3 1.2 . 7 . 3 • 2 11.6 -. 9 . 8 . 7 14.0 2.9 . 1 . 2 5.2 12.6 11.8 1.0 150.0 12.0

ULUBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEEL FROM HOURLY ORSERVATIONS
AIR WEATHER SERVICE/MAC

STATION NUMBER: 124505 STATION NAME: MCCONNELL AFR KS PERIOD OF RECORD: 17-86 MONTH: APR HOURS(LST): 1800-2666 #IND SPEED IN ANOTS

7-10 11-16 17-21 22-27 28-33 34-40 41-47 4E-55 UE 56 TCTAL MEAN DIPECTION I 1-5 4 - 6 COESPEESE ! + 1 ML ı N 1.0 17.4 41.5 PINE . 8 1.4 2.4 1.2 4, . 9 7.4 . 9 2.0 . 1 41 1.1 . 1 4.4 1 . 4 . 4 FNE 1 - 1 1.6 1.6 . ? 5.2 7.: L 1.0 2.1 2.0 . 9 . i . ? ESE ٠,9 1.4 1.9 1.0 SE . 1 • 2 1.4 ..0 * 5 E 1.2 in.a 1 - 1 11 . * s 2.5 2.5 ..0 6.5 . 4 1 - 1 1. . * < 5 w . 6 1.2 1.3 1.6 . 2 4.4 H . 4 . 2 SW . 2 . 8 . 1 1.6 ٠.٠ 4 . 2 .8 . 1 1 . 2 11.1 48 • 2 . 1 1.5 . 3 • 7 . 3 4.4 1 * - 1 . . NA. 1.6 1.7 . 3 CALM 4.9 1/1/1/ 1.9 100.0

SCHEAL SEIMATOLOGY HRANCH STAFETAC AIM WEATHER SERVICEZMAC

PERCENTAGE EREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSOS WING SELECTIONS

STATION NUMBER	Fi 1245U5	514110N	NAME :	MCCONNEC	LAFRE	•			PERIOU HONTH:	APH COF		-86 	231.0
	<i>.</i>	• • • • • • • •	• • • • • • •	• • • • • • • • •			IN ANDIS		• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • • • • •
DIFFCTION (OFGREES)		4 6	7 - 10	11-16		22 21	28-33	54-46		48-55	6E 56	TETAL	ME AN
N	1.2		3.0	1.4						• • • • • • • •	• • • • • • • •	۷.6	8.2
NNI	1 1.1	2.2	1.1	1.9	. 1							6.8	7.9
NI	1.1	i. •	. 6	.,	.2							4.4	t . i.
ENE	1 1.4	1.8	2.2	. 4								5 . H	1.1
	1.8	4.7	2.9	1.1		. 4						10.4	٠.٠
£5£	1 1-1	1.4	1.6	. 1	. 1							4.4	6
51	1 1.0	2.2	1.4	. 9	. 1							6.1	6.4
•4	1 1 1	1.6	2.9	1.4	1.0	. ?	. 1					19.3	11. • 4
		1.3	3.4	4 . 7	1.8	. 4						12.6	11.7
٠. پور	1 J	.,	1.4	.6								2.1	F.5
'. .		. 1	. •	. 1		. 1						. 9	7.9
W5#	! !	•6	.,		. 1							1.2	6.2
•	1 1.0	. 9			.1							2.2	9.2
6.Na	.,	.•	• 2	. 1	. 6	. 1	. 1					2.1	12.9
**		. 6	. •	1 - 4	. 1		. 1	. 1				3.7	13.4
1.44	! . 9	1.8	. 6	1.8								5.7	9.2
VANIAHLE	; •• 	• • • • • • • •	• • • • • •			•••••							
(ALM	 ,,,,,,,	,,,,,,,	,,,,,,	,,,,,,,,,	,,,,,,,	1111111	,,,,,,,,	,,,,,,		,,,,,,,,	,,,,,,,	11.6	111111
tetal 5	; 1 14.2	24.4	23.1	10.0	5.7	1.#	. 1	.1				100.0	7.6

PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTIONS

#IND SPEED IN KNOTS

UIPECTION | 1-5 4-6 7-10 11-16 17-71 22-57 70-17 77 PEAN IDEURLEST 1 1 - IN.h 2.1 3.3 3.7 . 9 • 2 • 1) 11.3 10.5 4.1 NNE . 9 1.4 1.5 1.2 . 2 • 0 F . 7 ENE . 8 .0 1 - 2 7... Ł 4.5 1.1 1.51 . 7 1.2 1.6 . 1 .0 1.4 . 2 5.3 SF . 5 1.4 1.6 **.** C 4.3 556 . 9 1 - 8 2.1 5.1 1.1 . 3 . 1 9.4 s 2.7 5.9 3.2 1.1 - 0 15.1 11.5 956 . 3 . 8 • 6 11. . 7 SW . 6 • 3 • 0 . 3 • 0 15 N - 6 H . A . 4 . 9 . 6 . 1 - 1 • 0 2.9 . 6 . 7 . 3 . ? 2.9 . 3 • 7 . 6 • 0 10.8 WNW . 9 . 3 4.4 12.3 N LE • 2 . 7 1.6 .6 - 1 - 0 NNE 2.3 1.0 . 3 7.3 11.1 VARIABLE ! CALM 6.2 ////// . 3 - 0 100.0 9.5 TOTALS 20.4 26.9 3.5

PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY ORSERVATIONS

#IND SPEED IN KNOTS

UIFECTION 1 1-5 4-6 7-10 11-16 17-21 22--- ----ME A 44 COLUBERS) | 6 | NoN 1.8 1.1 1.6 1.5 . 3 4.1 1.0 . l NN(1 - 5 . . 3 1.1 5.4 h . 1 ٩f 1.8 ..0 4.5 4.1 1.9 . . 5 4. . 7 . . 4 ENE . 6 11.6 4. 1 ŧ 2.8 4.6 2.4 ... ٠., ESE 1.9 . 3 1.7 . . 4 2.5 51 1.8 3.2 1.3 H . H f . 5 156 5.5 2.9 11.4 F . 4 . 9 3.4 . 8 5 3.0 2.5 4.2 1.4 11. 4.1 SSE 1.2 3.5 1. ٠, 4 . 2 • 6 454 . 5 . 6 1.4 , , 1 1.6 4.4 .6 • 6 . 5 . 2 . 1 1.1 6.3 -. 4 . 1 1.5 NH . 3 • 5 . • . 2 t . * NNW 1.1 1. VAH I ARLE LALM 12.4 ///// 20.5 2.1 . 2 Local in TOTALS 14.2

TOTAL NUMBER OF OBSERVATIONS:

930

GELHAL CLIMATOLOGY BRANCH GSAFLTAC ATR HEATHEN SERVICEZMAC

PERCENTAGE FFEQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEFE FROM HOURLY ORSERVATIONS

STATION NUMBER	7: 124565	STATION	NAME:	MCCONNEL	L AFR KS				PER10U MONTH:	UF FECOR		86 1: 0300-0	1560
		• • • • • • • •	• • • • • •	• • • • • • • • •			IN KNOTS	• • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • •	•••••	
01FECTION CUTUME(5)		4 - 6	7 10	11-16					41-47	48-55	GE 56	TETAL	MEAN WING
N 1	2.9	1.9	1.6	1.4	.1			• • • • • • •		• • • • • • •		8.2	4.9
*. *s t	2.7		. 4	.5			• 1					5.9	5 . R
41	.5		. 4									٠.,	5.4
141	1.2	1.4	1.4	.5								4.5	6.7
t l	2.7 	1.3		.5								н.7	9.0
ESE	1.2	. • 6	1.6	.6								6.0	6.1
5 t i	1.0	2.1	H									7.4	6.1
* 5.F 1	1 1.2 1	4 - 1	1.5	2.9	• 6							12.4	٠.4
N 1	2.5	. • S	1.4	4.7	. 4	• ?						14.5	4.3
15 m 1	٧.	1.0	. *									:.1	4.5
5 a 1	• • • •	. 9	٠.									1.6	1.1
.	.5	.•	••									1.7	4. (1)
• !		1 - 4	. 6									2.4	5 . A
h N m j		. 5	. •									1.8	4.5
** • (. *	• •.			- 3						1.7	H, 9
Prince (. • !	1.1	. 4	1.1								4	7.7
WANTAPLE 1		•••••	• • • • • •			• • • • • • •							
C#1 4	,,,,,,,,,	,,,,,,,	,,,,,,	,,,,,,,,	,,,,,,,	//////	,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	13.7	111111
TOTAL!	14.5	20.0	22.1			٠,	•1					100.0	6.1

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOUNLY OBSERVATIONS

STATION NUMBER	R: 7245U5	STATION	NAME:	MCCONNELL	AFR KS				PERIOU :	F RECORU): 77- HOURSILST		DBC ("
		• • • • • • • •	• • • • • •	• • • • • • • • • •		O SPEED	IN KNOTS	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
UIRECTION (UFGREES)	l	4 - 6	1-10		17-21		2A-33		41-47	48-45	UE 56	TCTAL	ME AN WINL
N	1.1	1.9	2.6	3.1	. 9	•••••	• • • • • • • • •			• • • • • • •	••••••	9.6	۷.٬
MNE I	1.3	1.6	1.8	.8								e, • ,	f.3
NE	1 1 - 3	1.6	1.0	. 3								4.2	
ENE	.5	1.7	1.1	. 8								4.1	·
t	1.8	2.8	2 . B	.5								A .1.	+ • 0
ESE	1.0	1.8	1.3	.1	• 1							4. '	to
st	1-2	. 0	3.9	. 3								7.4	h.n
322	1.7	4.6	3.4	1.7	. 4							11.4	F.,
3	.9	2.5	5.7	5.7	2.2	.4						17.3	11.
°Sw .	.5	1.0	1.7	• .*	. 5							4	H . r
2 M	. 4 !	.5	• 2	. 4								1.6	7.1
wSw .	.5	. 4	. 3	. 1								1.4	50 g W
•	1.1	1.2	. 5										4.,
545	. 4	- 8	. 4									1.6	٠.,
New	.2	. •	1.2	. 4								2.1	1.4
PiN w	.9	1.3	1.7	• 5								4.4	K , R
VARIARLE	· · · · · · · · · · · · · · · · · · · ·	•••••	• • • • • •		• • • • • •	• • • • • • •		• • • • • • •			• • • • • • • •		
LALM I	,,,,,,,,,	/////////	/////	,,,,,,,,,	//////	//////	,,,,,,,,	,,,,,,,		1111111	1111111	٠.4	111111
TOTALS	14.3	26.1	29.1	15.1	4.5	.•						1.19.	7.1
	• • • • • • • • • •	<i>.</i>				• • • • • • •		• • • • • • • •	. 		· • • • • • • • • • • • • • • • • • • •		

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPFACE WIND DIRECTION VERSUS WIND SELECTIONS FROM HOURLY OBSERVATIONS

STATION NUMBER: 724565 STATION NAME: MCCONNELL AFRIKS PERIOD OF PECONU: 77-86 MONTH: MAY HOURSELSTE: 0903-110. STATION NUMBER: 724565 STATION NAME: MCCONNELL AFRIKS wind Speed in Anois 17-21 22-27 24-33 34-40 41-47 48-55 DIFECTION 11-16 ME A 1. TETAL uf 56 IDEGREES) | 6154 1 • 1 10.7 ... 1.5 4 . H ٠.: 1.6 1.6 ٠. ، 1.3 2.4 . 6 ŧ . . 9 1.9 1.3 # 5.E 1.5 2.2 1.4 51 1.3 1.6 . 4 . . . 151 1.7 ۷., ٠. ٠ 7.6 1.1 1. 1.5 1.6 . 1 . 4 . . 1.0 . 4 1.1 . . 1.1 . 4 . . . N = . 4 . . 1.44 WANTA LE I ... ICTAL: 11.9

TOTAL NUMBER OF DRIVERTION .: 22

DENCEMBER CERMANDE, IN GRANDRE DENCEMBA E PREQUENTA CE L'UL PRENTE DE SEA DI MUNICIPATION DE L'ULABERTA.

FRUM MILLE DE SEAST, IN
ACCUMENTATION DE MARCE PERCE

1411	n, n, mi	ι	7245.4	374 F108	54ME .	MUCCURRENT	A6 *			-	***		
	• • • • • •					· • • • • • • • • •	,		 				
		٠.	1 "	4 1	7 4	1. 1.				• •		•	•
				<i>.</i>				. 	 				
	٠.	,	- •	; . ·									
•	Pa 9		. 1	:•*		• *		•					
	••		1 -		:. '	. •							
	、			*		. •							
			. *	1.4									
,			,•	. •	•								
			. •										
			. •			-							
	. •		. •		. •	. :							
			•										
	•												
•	• * •		. •										
	••			*	. •								
	•			•	•								
•													
	• •			٠.									

THE RESERVATIONS OF THE PROPERTY OF THE PROPER

	4 1 N	****	M CONNECT	-				MONTH:			-86 1500-	1700	
				-15	SPEER	IN KNUTS				•••••	• • • • • • • •	• • • • • • • • • • •	••
			i *				34-40	41-47	48-55	GE 56	TCTAL	ME AN - I Nú	
4.4					.1				•••••		18.4	9.6	••
•	4										6.3	7.9	
	ų	.*		. '							5.1	7.5	
			. !								3.8	6.2	
	•		. 4								5.1	6.9	
											4.7	7.5	
			. "	. 4	• '						6.7	9.5	
		w.,		1.1	• 1	- 1					13.1	11.0	
			٠.٠	1,4	1						21.5	12.4	
			. •	. *	. •						5.5	11.8	
		. •	. •								2.4	7,7	
			. •		.;						1.6	9.9	
					• .						1.9	8.9	
											2.2	P.2	
•											2.5	7.6	
											4.2	9.7	
							• • • • • •			• • • • • • • • •	• • • • • • • • • •	• • • • • • • • • •	• • •
						11111111	,,,,,,	///////////////////////////////////////	///////	,,,,,,,,,	3.1	/////	
					. •	. '					100.0	9.5	
												• • • • • • • • •	

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SHEED FROM HOURLY OBSERVATIONS

	· · · · · · · · ·		• • • • • • • •			IN KNOTS						
			11-16		-						TCTAL	ME AN Linu
	. 6	3.5	2.6	•2	•••••	• • • • • • • •	•••••	•••••	•••••	•••••	10.4	7.9
, 9		1.5	.9	- 1							5.9	6.9
, . •		1.1	. 3								5.3	5.2
. *	, .r	. 8	- 1								5.2	4.2
	1.4	2.3	.5	. 1							8.8	5.8
	•	1.5	.9								6.7	6.0
	1.1	2.9	1 -4	. 4							9.5	7.3
	→ • **	5.1	4.3	. 8	• 1						15.3	9.3
	. •	3.4	4.8	1.3	•2						13.4	10.4
	. •	1."	?								2.2	7.1
		. :	. 4								1.7	7.2
			. 1		. 1						1.0	7.9
			- 1	-1							1.7	5.8
		. 4		.1							1.3	8.3
		. •		.1							1.5	8.7
		•									3.4	7.6
							• • • • • •	•••••		•••••	•••••	
					111/11/	.,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	6.8	,,,,,,
			,		. •						100.0	7.1

PERCENTAGE FREQUENCY OF OCCURRENCE UF SURFACE WIND DIRECTION VERSUS WIND SFLEU FROM HOURLY OBSERVATIONS

••••••	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •					MONTH:			11: 2100-	• • • • • •
IPECTION DEGREES 1	1-3	4-6	7-10	11-16			IN KNOTS 28-33		41-47	48-55	GE 56	TOTAL	ME AN WINU
N [2.0	3.7	2.5	1.4	.5	- 1	• • • • • • • •		••••••		•••••	10.2	7.2
NNE !	1 • 2	2.4	1.7	.6								5.9	6.2
NE I	1.9	2.0	. 2	.1								4.3	4.2
FNE	2.3	2.6	.6	. 1								5.6	4.1
E	3.2	3.8	2.3	.6	. 1							10.0	5.5
ESE !	2.5	1.8	1.4	• 5								6.2	5.2
SE I	7.2	3.9	3.1	1.2	.1							10.4	6.6
SSE	.9	3.9	4.5	3.0	.9	. 4						13.5	9.5
s	.9	2.4	2.3	4.5	. 8	• 1						10.9	10.1
ssw	.9	1.6	.6									2.1	5.4
SW I	. 3	.4	• 2	• 2								1.2	6.0
usu !	.4	• 2	. 1									. 4	3.7
- !	.4	.4	. 8									1.6	5.5
ANA	•2	. 1										. 3	2.1
NW .	.4	. 4	. 4		. 2							1.5	6.9
NN#	•5	• 1	• 2	. 8								1.6	F . 1
ARIAPLE !	••••••	•••••	• • • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • • • • •		• • • • • • • •	•••••	•••••	•••••	• • • • • •
ALM [/	,,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	13.2	/////
OTALS 1	19.8	29.7	21.0	13.1	2.6	. 6						145.1	٠.

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86 MONTH: MAY HOURS(LST): ALL

		• • • • • • •		•••••	I N		IN KNOTS		• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •
DIRECTION (DEGREES)		4~6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	GE 56	TETAL	MEAN WINU
N	1.4	2.5	2.6	2.6	.5	.1		•••••	• • • • • • • •	• • • • • • • •	• • • • • • • •	9.6	8.6
NNE	1.0	1.9	1.7	.8	.1	•0	•0					5.5	7.0
NE	1.2	1.9	1.1	. 3	.1							4.5	5.7
ENE	1.3	1.8	1.3	.4								4.8	5.7
Ĺ	1.9	3 • 1	2.2	. 8	.0							7.9	6.1
FSE	1 • 2	1.8	1.8	. 7	•0							5.5	6.5
SE	1.2	2.4	2.6	1.1	-1	.0						7.5	7.2
SSE		3 • 1	4.3	3.1	.7	•2	•0					12.2	9.3
s	1 1 • 2	2.6	4.5	6.0	2.0	. 7	•0					17.1	11.2
SSW	.5	1.2	1 - 3	.9	-5	1.						4.5	9,3
SW	.3	•6	.5	•5	. 1							2.0	7.9
WSW	-4	.4		• 3	•0	.0						1.5	7.1
	.6	- 8	.5	. 2	•0	•0						2.2	6.0
MNR		. 4	.5	. 3	.0							1.5	7.1
N. at	.3	.5	. B	. 4	.0	.0						2.1	7.9
1444	.6	. 9	1.1	1.0	- 1	•0						3.6	8.3
VARIAPLE	! !		• • • • • • • •			• • • • • • •			••••••	•••••	••••••	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
CALM		,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	8.1	/////
101465	1 14.2 	25.8	27.3	14.1	4.5	1.1	. 1					100.0	7.5

TOTAL NUMBER OF OPSERVATIONS: - FREE

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM MOUNLY OBSERVATIONS

724303	STATION		MCCONNELL						OF RECORU			0200
••••••	•••••	• • • • • • •	• • • • • • • • •				• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • • •	• • • • • • • • • • • •
1 - 7	4-6	7-10		17-21	22-27	28-33		41-47	48-55	GE 56	TOTAL	ME AN Binu
1.0	1.6			• • • • • • • •		• • • • • • • •	•••••	• • • • • • • •	• • • • • • • •		4.1	6,1
1.3	1.0	. 7	1.0	. 1							4.1	7.3
.8	2.1	.7	- 1	• 1	. 1						3.9	5.7
1.8	1.7	. 7	• 3								4.4	5.0
3.7	2.7	.6									6.9	3.9
1.9	2.4	.7									5.0	4.3
3.2	3.9	2.0	•2								9.3	4.8
2.4	4.0	5.7	3.3	• 2							15.7	7.7
2.6	5.2	6.6	9.1	1.8	•2						25.4	9.8
, 3	1-1	. 4	• 3								2.2	6.4
. 8	• 3	. 4	• 1					'			1.7	4.9
.4	•6										1.0	3.2
• 1			. 3								. 4	10.0
• 3	• 3	• 2	-1								1.0	6.4
- 1	. 3										.4	4.5
- 3	• 6	. 3	-1								1.3	6.2
	• • • • • • • •	• • • • • •	• • • • • • • • •	•••••	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • •
//////	,,,,,,,,	,,,,,,	,,,,,,,,,	1111111	,,,,,,,	,,,,,,,,	//////	,,,,,,,	(//////	,,,,,,,	13.0	/////
21.1	27.8	20.2	15.2	2 • 2	.4						100.0	6.1
	1-3 1.0 1.3 .8 1.8 3.7 1.9 3.2 2.4 2.6 .3 .8 .4 .1 .3 .1	1-3 4-6 1.0 1.6 1.3 1.0 .8 2.1 1.8 1.7 3.7 2.7 1.9 2.4 3.2 3.9 2.4 4.0 2.6 5.2 .3 1.1 .8 .3 .4 .6 .1 .3 .3 .1 .3 .3 .6	1-3 4-6 7-10 1.0 1.6 1.3 1.3 1.0 .7 .8 2.1 .7 1.8 1.7 .7 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 2.4 4.0 5.7 2.6 5.2 6.6 .3 1.1 .4 .8 .3 .4 .4 .6 .1 .3 .3 .2 .1 .3 .3 .6 .3	1-3 4-6 7-10 11-16 1.0 1.6 1.3 .1 1.3 1.0 .7 1.0 .8 2.1 .7 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 2.6 5.2 6.6 9.1 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .2 .1 .1 .3 .3 .2 .1	1-3 4-6 7-10 11-16 17-21 1.0 1.6 1.3 .1 1.3 1.0 .7 1.0 .1 .8 2.1 .7 .1 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .2 .1 .1 .3 .3 .2 .1	1-3 4-6 7-10 11-16 17-21 22-27 1.0 1.6 1.3 .1 .1 1.3 1.0 .7 1.0 .1 .8 2.1 .7 .1 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .2 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .3 .2 .1 .1 .3 .3 .3 .2 .1	1-3 4-6 7-10 11-16 17-21 22-27 28-33 1.0 1.6 1.3 .1 .1 1.3 1.0 .7 1.0 .1 .8 2.1 .7 .1 .1 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .2 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .3 .2 .1 .1 .3 .3 .3 .2 .1	1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 1.0 1.6 1.3 .1 .1 1.3 1.0 .7 1.0 .1 .8 2.1 .7 .1 .1 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .2 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .2 .1 .1 .3 .3 .2 .1 .1 .3 .3 .3 .2 .1	MONTH: 1-7	MONTH: JUN 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 1.0 1.6 1.3 .1 .1 1.3 1.0 .7 1.0 .1 .8 2-1 .7 .1 .1 .1 1.8 1.7 .7 .3 3.7 2.7 .6 1.9 2.4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .2 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .3 .6 .3 .1	MONTH: JUN HOURSILS: 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 1.0 1.6 1.3 .1 .1 1.3 1.0 .7 1.0 .1 .8 2-1 .7 .1 .1 .1 1.8 1.7 .7 .3 3.7 2-7 .6 1.9 2-4 .7 3.2 3.9 2.0 .2 2.4 4.0 5.7 3.3 .2 2.6 5.2 6.6 9.1 1.8 .2 .3 1.1 .4 .3 .8 .3 .4 .1 .4 .6 .1 .3 .3 .6 .3 .1	#ONTH: JUN HOURSILSTI: 00J0- ITAL SPEED IN KNOTS 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL 1.0 1-6 1-3 .1 .1 .1 .1 .1 .1 .1 .1 .1 .

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOUNLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 17-86

									HONTH:	JUN	HOURSILS	13: 0300-	3500
	• • • • • • • •	• • • • • • •	• • • • • • •	•••••			IN KNOTS		• • • • • • • •	•••••	• • • • • • •	• • • • • • • • •	• • • • • • • •
DIRECTION (DEGREES)	1-3	4-6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	GE 56	TCTAL 2	MEAN WIND
N j	2.1	1.6	. 8	.1	•••••		•••••	• • • • • • • •	• • • • • • • •	•••••	••••••	4.6	4.7
NNE	1.0	.9	1.9	.4								4.2	6.9
NE .	.8	2.3	. 8	•2								4.1	5.2
ENE]	1.7	2 • 4	. 4	.1								4.7	4.4
E	3.8	2.6	1.2	-1								7.7	4 - 1
ESE	2 • 3	2.0	.9	•1								5.3	4.4
SE	1 - 4	2.9	1.4									5.8	5.0
SSE	2.0	6.2	2.7	2.1	•2							13.2	6.8
s	2.9	4.0	6.9	9.9	1.2	- 1						25.0	9.7
SSN	1.0	• 3	. 3	.7	•2							2.6	7.6
SW	. 4	. 3	. 3	• 1								1.2	5.7
WSW	•2	• 1		- 1								.4	5 • 3
·	.9	•6	• 5									1.7	3.7
FNA	•1	• 3	- 1	• 1			• 1					.8	10-1
N⊯	• 2	•2										- 4	2.8
NNW	.4	•6	1.0	. 3								2.3	7.1
VARIABLE I	••••••	• • • • • • •				•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • • •	•••••	• • • • • • • • •	• • • • • • • •
CALM I		,,,,,,,,	,,,,,,,	,,,,,,,,	1111111	(//////	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,,	16.0	111111
TOTALS	21.3	27.3	19.0	14.4	1.7	. 1	• 1					100.0	5.7

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SHEED FROM HOUNLY OBSERVATIONS

TION NUMBER	: 724505	STATION			•				PERIOD Month:	OF RECOR		1): C600-	0800
DIRECTION 1 (DEGREES) (1-3	4-6	7-10	11~16	⊌I	ND SPEED	IN KNOTS 28-33		41-47	48-55	GE 56	TCTAL	ME AN WINL
N	1.1	2.6	2.0	.9	.1	• • • • • • • •	• • • • • • • • •			• • • • • • • •	•••••	6.7	6.8
NNE !	.9	1.3	.9	•6								3.7	6.5
યદ !	.8	2.1	1.1	.9								4.9	6.7
FNE !	1.6	1.7	1.6	• 2								5.0	5.6
Ł	3.3	2 • 8	1.0	-1								7.2	4.2
EZE	.9	2.1	.4									3.4	4.7
2E	1.6	1.8	2.1	. 4								5.9	6.1
558	1.7	3.1	4.3	2 • 2								11.3	7.5
2	2.1	4.1	8 • 2	10.8	5.0	• 3						27.6	10.4
ssn	1 • 2	1.2	1.1	2 • 4								6.0	8.2
2 4	•6	1.0	•1	-1								1.8	4.9
#2#	.7	. 1	. 1									. 9	3.6
4	.6	. 3	.1									1.0	4.0
WAW	. 3	- 1		.1								.6	4.6
NW)	•2	. 3	. 3									.9	5.8
NNW	.3	1.1	.6	. 4	•1	• 1						2.7	8.3
VARIARLE	•••••	•••••	• • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • •	••••••	• • • • • • • • • • • • • • • • • • • •	•••••	•••••	• • • • • • • • • • • • • • • • • • • •	•••••	•••••	•••••
CALM .	,,,,,,,,	,,,,,,,	//////	,,,,,,,,	//////	1111111	(((((()	///////	///////	,,,,,,,	,,,,,,,	10.6	111111
TOTALS	17.8	25.8	24.0	19.2	2 • 2	.4						100.0	6.8

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WING SFEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86

MONTH: JUN HOURS (LST): 0900-1160

									MONTH:	JUN	HOURS (LS	11: 0900-	1160
IPECTION 1 DEGREES) I		4-6	7-10	11-16	WIN 17-21	D SPEED 22-27	IN KNOTS 28-33	5 34-40	41-47	48-55	GE 56	TOTAL &	MEAN WINU
N I	. 8	1.7	1.6	1.8	••••••	•••••		• • • • • • • •	•••••	•••••	•••••	5.8	7.9
NNE .	1 - 1	1.0	1.4	.7								4.2	6.5
NE	.6	1.8	. 8	.7								3.8	6.8
ENE	1 - 2	2.2	1.2	.8								5.4	5.9
E	1.7	2 • 3	1.6	.4								6.0	5.5
ESE	. 8	1.8	1.7									4.2	5.7
SE	.6	1 • 3	1.1	.4	- 1							3.6	7.2
322	1.0	1.9	2.6	2.7	• 6							8.7	8.9
s	1 - 1	3.2	7.7	9.4	4.2	.8	.1					26.6	11.8
SSW	.6	1.4	5.1	4.0	1.6	. 3						13.0	11.0
SW	• 1	1.3	2.1	1-1	•2	. 1						5.0	9.3
wsw	• 3	•9	- 1									1 • 3	4.4
	. 8	1.0	• 1	- 1								2.0	4.3
UNU 1	•2	-1	• 1									. 4	4.0
NU I	.4	• 8	• 1	- 1								1.4	4.7
NNW	.4	•8	.6	1.0								2.8	8.1
VARIABLE	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	••••••	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • •	•••••	• • • • • • • •	• • • • • • • • •	
İ	,,,,,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	///////		,,,,,,,	///////	,,,,,,,,	5.8	/////
TOTALS	11.7	23.6	27.8	23.2	6.7	1.2	. 1					100.0	8.4

PEPCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

TION NUMBER:	724505	STATION							HONTH:	-	HQURS(LS	-86 T): 1200-	1400
DIPECTION (DEGREES)	1-3	4 ~6		11-16	dIN 17-21	22-27	IN KNOTS 28-33	34-40		48-55	GE 56	TOTAL 3	MEAN WIND
N !	1.6	1.8	1.7		• • • • • • •	•••••	• • • • • • •	•••••	• • • • • • •	• • • • • • •		6.7	7.7
NNE !	1.0	1.4	.9	•2	- 1							3.7	5.9
NE !	.8	1.6	.6	.4								3.3	5.9
FNE !	1 - 3	1.g	1.1	. 4								4.7	5.6
E	1 • 1	3.3	1.6	. 3								6.3	5.8
ESE !	.8	1.0	1.6	.8								4.1	7.1
SE !	.9	2.0	2.3	1.6								6.8	7.7
SSE	1 • 3	1.7	2.8	2.2	. 7							8.7	8.7
s	1.3	2.6	5 • 2	10.3	5 • 1	2.0						26.6	13.2
SSW	•2	1.8	3.3	4.4	. 8	.4						11.0	11.0
SW	.7	• 7	1.6	1 - 1	. 4							4.4	9.2
usu	.3	•6	•6	.7	• 1							2 • 2	9.0
w !	.4	.8										1.2	4.0
שמש	.3	•6	- 1									1.0	4.4
NW .	•2	• 2	. 1	•1	•1							.8	7.4
NNW I	.8	1.0	1.0	. 3	•1							3.2	6.4
VARIAPLE	•••••	•••••	• • • • • •	• • • • • • • • • • • • • • • • • • • •	•••••	• • • • • •		• • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • • • • •	
1	,,,,,,,,,,	,,,,,,,,	,,,,,,	,,,,,,,,,	///////	////////		.,,,,,,,	,,,,,,,,	,,,,,,,,	,,,,,,,,	5.3	111111
TOTALS I	13.1	22.7	24.3	24.7	7.4	2.4						100.0	8.8

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PÉRIOD OF RECORD: 77-86 Month: Jun Hours(LST): 1500-1700 UINO SPEED IN KNOTS
DIRECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TOTAL MEAN MINU (DEGREES) N 7.9 5.3 .9 1.7 1 • 3 1.4 4.9 7.5 .4 1.2 2.7 NNE .6 3.7 5.4 .9 1.4 NE 1.3 5.4 5.4 ENE 1.0 3.0 1.1 . 2 . 1 7.0 E 3.0 2.4 • 2 5.7 ESE .6 2.4 2.0 5.4 6.6 . 3 2.0 2.8 1.6 SE 4.7 . 7 13.1 . 8 2.1 4.8 • 1 10.0 SSE 1.3 26.8 13.4 4.7 10.7 6.2 . 1 s 2.6 1.2 7.0 2.2 1.7 1.0 . 1 10.1 SSW .6 1.4 7.8 2.9 SW • 2 1.0 1.0 .6 . 1 1.7 • l . 1 6.6 . 3 •6 . 3 1.2 5.2 WNW . 1 - 1 ٠ ١ .6 6.2 .6 • 7 . 3 •2 1.8 VARIABLE ! CALM 4.2 ///// 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM MOUNLY OBSERVATIONS

PERIOD OF RECORD:

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

HOURS(LST): 1800-2000 MUNTH: JUN WIND SPEED IN KNOTS DIRECTION 7-10 17-21 22-27 28-33 34-40 48-55 GE 56 MEAN IDEGREES) ! WIND N .8 1.7 7.1 . 7 1.9 NNE 1.8 . 7 • 2 5.2 7.3 NE 1.7 1.2 1.6 4.4 5.2 2.1 . 7 FNE 2.0 •2 5.0 4.6 3.9 2.4 Ł 4.1 . 1 10.6 4.7 6.7 ESE 2.0 2.7 1.9 • l 5.5 1.3 SE 2.7 3.0 1.6 8.6 7.2 SSE 1.0 4 . 7 7.2 6.2 1.0 20.1 9.5 s 4.7 8.2 3.2 . 7 1 - 1 2.6 11.9 .9 1.0 . 7 • 2 3.9 7.5 . 3 . 2 SW 1.0 5.9 WSW . 1 . 1 . 2 . 7 7.7 • 2 . 3 - 1 . 7 . 1 1.2 4.5 . 1 . 1 END . 2 7.5 NE - 1 . 4 . ı • 2 . 9 7.3 HNW VARIABLE CALM 5.8 TOTALS 100.0 7.6

TOTAL NUMPER OF OBSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SHEED FROM HOURLY OBSERVATIONS

STATION NUMBER	R: 724505	STATION	NAME:	MCCONNELL	AFB KS				PERIOD MONTH:	OF RECOR		86): 2100-2	2360
• • • • • • • • • • • • • • • • • • • •		•••••	• • • • • •	• • • • • • • • • •	u I N	n spren	IN KNOTS	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	•••••	••••••
DIRECTION (DEGREES)		4-6	7-10	11-16			28-33		41-47	48-55	GE 56	TOTAL	ME AN WINU
N	l •7	1.6	1.1	• ?	•••••	•••••	•••••		• • • • • • • •	• • • • • • •	• • • • • • • •	3.6	5.9
NNE	1.4	1.2	. 8	.4	•2							4 - 1	6.2
NE	1.4	2.2	1.1									4.8	4.8
ENE	1.7	2.0	1.0	•2								4.9	5 • 1
E	2.7	4.1	1.2	•2								8.2	4.7
ESE	3.3	2 • 3	2.1									7.8	4.7
35	2.9	3 + g	2.4	.9								10.0	5.6
SSE	2.1	5 • 7	8 • 1	5.0	. 4							21.3	8.3
S	1.6	3 • 6	4 • 2	7.3	2.0	• 1						18.8	10.4
\$ 5 W	l .8	- 1	.7	• 2	•1							1.9	6.6
SW	i I	• 3	- 1	•2	• 1							. B	9.4
WSW	•4 	• 3	• 2	• 1								1 - 1	4.8
u :	• 3	. 1										. 4	2.5
WNW	l •2	•1										• 3	3,7
NW	•1			• 2	•1							. 4	12.0
NNW	 	. 4	• 1	• 2								. 8	7,7
VARIAPLE		••••••	• • • • • •	• • • • • • • • • •	• • • • • • •	• • • • • • •		• • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	• • • • • • • •	
CALM	111111111	,,,,,,,,	111111	,,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	////////	,,,,,,,	10.8	/////
TOTALS	19.7	27.9	23.2	15.3	3.0	• 1						100.0	6.4
	, , , , , , , , , , , , , , , , , , , ,												

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPFACE WIND DIRECTION WERSUS WIND SHEEL FROM MOURCY OBSERVATIONS

PERIOD OF RECURD: 77-86

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB MS

STATICH NONDE									MONTH:	JUN	HOURS ILS	tti ac	ι
• • • • • • • • • • • • • • • • • • • •		• • • • • • • •	• • • • • • •	• • • • • • • •		n speen	IN KNOTS	• • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
OIPECTION (DEGREES)		4-6	7-10	11-16	17-21		28-33	34-40	41-47	48-55	uE 5t	TCTAL Z	ME AN WITE
N	1.1	1.6	1.4	.9	.0	.0	•••••			• • • • • • • •	•••••	5.0	6.0
NNE	1.0	1.2	1.4	.6	.1							4.1	f . R
NE	1.0	1.8	1.0	. 3	•0	• C						4 - 1	5.7
ENE	1.5	2.1	1.0	. 5	• 0							4.0	5+2
Ĺ	2.7	3.1	1.5	• 2								7.5	4.8
ESE	1.6	2.1	1 - 4	• 2								5.2	5 - 3
SE	1.5	2.5	2 • 2	. 8	.0							7 • 1	6.4
SSE	1.5	3.7	4.8	3.6	• 5	•0						14.0	н.4
s	1.7	3.5	6.0	9.5	3.2	. 7	• 0					24.6	11.4
SSW	.7	1.1	1.8	1.8	.5	• 1						5 • 9	٠.6
SW	. 9	.7	. 7	.4	. 1	• 0						2 - 3	7 . B
WSW	.4	.4	• 2	- 2	•0							1 • 7	6.0
4	.5	.5	- 1	- 1								1.2	4.4
WNW	•2	• 2	-1	- 1			•0					• 6	6.0
NW	•2	. 4	• 1	-1	•0							.9	6.2
NNE .	.4	• 7	. 7	. 4	•0	•0						2 - 1	7.3
VARIABLE		•••••	• • • • • • •	••••••	•••••		• • • • • • •	•••••			•••••	•••••	
CALM	! <i> </i>	,,,,,,,	///////	11111111	///////	////////	(1111111)	111111	,,,,,,,,,	,,,,,,,,,	,,,,,,,,	8.9	111111
TOTALS	 16.5	25.6	24.3	19.3	4.5	. 9	• 0					100.0	7.3
	,												


OCTOBE COMBECCO, THEBRAID PROCESS OF PROCESS OF THE COMMENT OF COMPANY OF THE COM

та∩ы марынары Тапы	F2 - \$245 U.S.	5 7 & 1 ^ N		₩ (અમાર્	(#*								
 15560 1104 1550 1865 1		• •	7 240		-15	SPEED 19	N. A. N. C. S.		4. 4.				
4	.t				• • • • • • • • •	• • • • • • • •		• • • • • •			• • • • • • • • • •		
NNE (. •		. •	:								٠.	1.4
M j	1.2	1. *	. t.										-
1 F4E 1	7.0	2.4	. 6									٠.	
t I	3.2	1.3	1-8										•.,
- FSE - 1	1.3	2.8										٠.٠	4.4
SE [1.3	2.4	2.2	. 1								4	٠.٠
, 2£ 1	2.7	4.3	6.2	5.4	.5							11.7	٠. ٠
\$	1.9	4 - 7	13.5	10.5	1 - 1							Vi. +	٠.،
1 w 2:	1.0	1-1	1.5	1.2	. 1							4.6	7.4
5 w 1	•?	.5	. 3	. 3								1.4	۴.4
15 w	-1	• 2	- 1									. 4	4.3
• I	.6		• ?									. 4	3.5
MNW	• 1	. 3	- 1	. 1								. 6	6.7
NH I	- 1	. 3	.1									. 5	5.2
NNW I	• ?	•5	-1									. 9	4,3
! 	•						• • • • • • •				• • • • • • • • • •		
VARIABLE													
1						'/////////	1111111	111111	,,,,,,,,,	//////			111111
TOTALS !	17.5	27.0	28.8	16.3	1.7							100.0	6.6

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OF SERVATIONS

TATE NO MARK	7.145.5	STATION	NAME :		-				MONTH:	JUL		-86 []: 0300-	05 00
	1 - 3	4 - e	1-10	11-16	17-21	22-27	IN KNOTS 28-33	34-40	41-47	48~55	GE 56	TOTAL	ME AN WIND
K !	1.0	1.4	. 6	. 2	.2			•••••	• • • • • • • •	• • • • • • • •	•••••	3.5	6.2
NNE	1.5	2.4	1 - C									4.6	4.9
× .	1.1	1.3	. P									3 - 1	4.7
FNE	1 - 2	1.9	- 1	• 2								3.4	4.7
Ł	1.7	3 - 1	. 8									5.6	4.6
! SF	.9	2.0	.4	• 1								3 . 4	¢, • 1
St	2.3	1.3	1.3	. 3								5.2	4. 8
327	3.5	3.9	3 • 8	1.4	.4							13.0	t.4
2	4 - 1	6.9	13.8	8.0	• 1							32.6	*.;
SSW	1.0	2.9	2.9	1.5	. 3							9.6	٠.٠
Sw	.4	• 5	. 1	- I	-1							1. '	٠
w2#	•2	• 1	. 3	- 1									
.	. 3	- 1	. 4										
unu !	. 3	• 3										. •	
NW !	• 3	• 2	• 2			. 1							
NNW I	•2	• 3	• 2	• 1									
VARIABLE !	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •		• • • • • • •		• • • • • • • • • • • • • • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •		
CALM /	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	//////	,,,,,,,,	1111111	,,,,,,,,				
TOTALS	19.8	28.7	26.8	12.3	1.2	.1							

. 7	AD-	179 1	96	MCCON! HEATHE	R OBS	ERUATI	SAS RI	UISED.	UNIFOR	M SUPER	MRY OF	SUMFACE	2/4
	LINC)	LASSIF	IED	USAFE!	AC DS	PLICA 87/01	TIONS	CENTER	SCOTT	À	67 APR	SURFACE 87 4/2	NL
					_								
Ì													
,													
_													



MERCICORY RESOLUTION 1831 - HART NATIONAL HORSAN OF TAN AND THE

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

							•		MONTH:			(LST): 0600
1		••••			WIN	ND SPEED) IN KNOTS	rs				
DIPECTION (DEGREES)		4-6	7-10			_	28-33		41-47	48-55	5 GE 5	56 TETAL
N	1,1	1.5				•••••	••••••	••••••	••••••	********	•••••	3.4
NNE	.8	2 • 7	1.7		• 1		-1					5.4
NE	. 8	1.9	• 5									3.2
ENE	.8	1.9	• 8	-1								3.5
E I	1.8	2.5	•5									4.9
E S E	1.0	1.7	. 4									3.1
SE İ	1 • 4	3.0	1.2	• 3								5.9
SSE	1.4	4 • 6	2.9	1 - 8	• 3	-1						11.2
s i	2.8	6•8			• 5							33.2
SSW I	1 • 2	2.2	4.3	2.5								10.1
SW 1	•2											1.6
WSW	.3		• 2	. 3								1 . 3
w	.8											1.7
WNW [. 3											.6
NW 1	• 3											. 9
NNW I	. 3	-8	• 3	• 1								1.5
VARIAPLE	,	•••••	•••••	,	•••••	•••••	•••••	•••••		•••••	•••••	· • • • • • • • • • • • • • • • • • • •
CALM	,,,,,,,,,	///////	11111111	,,,,,,,,,	11111111	//////	////////	//////	111111111	,,,,,,,,	//////	/// 8.0
TOTALS	15.2	31.9	27 0	16.3	1.0	. 1	. 1					100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: JUL HOURS(LST): 0900-1100 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS WIND SPEED IN KNOTS 17-21 22-27 28-33 34-40 DIRECTION ! TOTAL 7-10 MEAN (DEGREES) LINU 1.1 1.0 .8 4.2 6.5 NNE • 2 .6 1.3 1.6 3.8 6.5 5.9 NE 2.7 1.6 . 3 5.5 1 - 3 ENE . 8 1.5 1.1 - 1 3.4 5.5 E 1.9 2.2 . 3 5.2 6.6 ESE 2.5 SE 2.9 6.1 6.1 8.1 1 - 1 s 2.0 8.0 11.2 2.0 • 3 27.8 10.3 4.3 .5 55 W 2.8 5.3 8.4 1.5 18.5 1c.9 - 1 9.0 8.8 SW 1.0 2.3 3.1 2.5 . 1 WSW ٠5 • 5 1.8 8.2 . 2 . 3 1.8 5.9 KNW . 3 . 1 1.2 6.7 NW . 1 4.9 VARIABLE CALM 100.0 P . 3

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS JIND SFLED FROM HOURLY OBSERVATIONS

ATION NUMBER				MCCONNEL					MONTH:	JUL		11: 1200-	1400
					WI	ND SPEED	IN KNOT	5					
DIRECTION I IDEGREES 1		4-6		11-16						48-55	GE 56	TCTAL	FIND WE AN
N	.9	1-1	1.8		• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	•••••	•••••	••••	4.2	6.5
NNE !	1.1	. 9	1.3	.3								3.5	6.4
NE I	.8	1.6	1.7	• 1								4.2	5.7
ENE	1.3	2.5	1.5									5.3	5.2
ε	1.4	2.0	1.7	- 1								5.3	5.5
ESE	1.1	•6	1.0	. 4								3.1	6.1
SE	.3	1 - 7	. 9	.4	• 1							3.4	6.9
SSE	1 • 3	1.9	2.5	2.2	• 3							8 • 2	6.4
s i	1.5	2.9	9.1	15.6	3.0	• 6						32.8	11.6
SS# Ì	.8	2.4	2.5	5.9	2.2							13.7	11.6
SW 1	.8	1.5	1.4	1.4	• 5	- 1						5.7	9.3
usu i	•2	•8	1.3	.9								3.1	8.6
i	.6	• 1	• 1		- 1							1.0	5.2
WNW I	•2	• 5	• 2									1.0	5.2
N⊯ 1	•2	• 1										. 3	2.7
NNW I	.6	• 5	. 8	•2								2 • 2	5.7
VARIAPLE	••	•••••	• • • • • • •	• • • • • • • • •	• • • • • • •	•••••	• • • • • • • • •	• • • • • • •	••••••		•••••	• • • • • • • • •	• • • • • • • •
CALM !	/////////	,,,,,,,,	,,,,,,,	,,,,,,,,	//////	,,,,,,,	///////	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	3.1	111111
TOTALS	13.0	21.7	27.7	28.0	6.2	. 8						100.0	8.8

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86

MONTH: .ULL HOURS(LST): 1530-1700

		• • • • • • •				• • • • • • •	•••••			JUL		LST): 15J0	
IRECTION DEGREES)	1-3	4-6	7-10	11-16	u11 17-21	D SPEED 22-27	IN KNOTS 28-33	34-40	41-47	48-55	GE 5	6 TCTAL	ME AN W I N U
N .	1.1	.9	1.0	. 3	.1	•••••		• • • • • • •	• • • • • • • •	•••••	• • • • • •	3.3	6.4
NNE	.6	1.2	1.5	• 2								3.5	6.4
NE	1 • 6	2.0	1.7	. 1								5.5	5.4
FNE	1.2	2.4	1.7	• 2								5.5	5.9
E	1.1	3.8	2.6	- 3								7.7	6.0
ESE	1.3	1.5	1.9	. 3								5 • 1	6.0
SE	.8	2 • 5	1.7	.5								5.5	6.5
SSE	1 • 4	2 . 3	4.1	6.7	1.5	. 1						16.0	10.6
s	.5	1.9	8 • 2	14.9	3.7	• 6						29.9	12.4
SSW	1.0	•5	1.5	3.0	1.6							7.6	11.6
SW I	. 3	.4	• 6	1.3								2.7	9,9
WSW	•1	. 3	• 1	. 4	-1							1.1	9 • 2
.	•2	• 3	. 3	• 1								1.0	6.2
WAW	•5	. 9	• ?	- 1								1.0	5.9
NW I	•2	•1		• 1								. 4	5.5
NNW	.6	.4	. 3		• 1							1.5	5.1
VARIABLE	• • • • • • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • •	•••••	•••••	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •	•••••
i i	,,,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	////////	///////	,,,,,,,,	,,,,,,	,,,,,,	7// 2.7	//////
TOTALS !	12.3	21.0	27.5	28.7	7.1	. A						100.0	9.1

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER	724505	STATION							MONTH:		HOURS (LS1	-86 []: 18JD	2000
1	· • • • • • • • • • • • • • • • • • • •	••••••	• • • • • •	••••••			IN KNOTS		••••••	• • • • • • •	•••••		•••••
DIRECTION (DEGREES)		4-6		11-16		•						1	ME AN Binu
N	• 3	1.0	1.1		.2			• • • • • • • •		•••••	•••••	3.0	8.1
NNE	.5	1.1	1.6	•2								3.4	6.7
NE	.6	2.0	. 9	• 5	•1							4.2	6.6
ENE	2.0	2 • 8	1.9	• 2								7.0	5.2
٤	3.9	5 • 2	1.5	. 3								10.9	4.7
£2£	1.5	1.9	2.3	.4								6.1	6.2
SE	1.7	2.8	2.8	.9								8.2	6.6
SSE	1.3	3.5	10.3	9.8	1.2		• 1					26.2	10.3
s	1.4	2 • 4	6.5	8.5	1.9							20.6	10.8
#2?		•5	. 4	1.5	•2							2.7	11.2
sw		• 5	• 2	•2	.1							1.1	9 - 3
NSN	•2	• 3	• 2									. 8	5.3
u j	• 3		. 3	• 1								. 8	5.9
MNM	. 3		• 2	.1								• 6	5.2
Nat	• 1	•2		• 1								.4	6 • 3
NNW I	•2	• 5	. 1	•1								1.0	5.8
VARIABLE			• • • • • •	•••••	• • • • • •	• • • • • • • •	• • • • • • •			•••••	• • • • • • •		•
i		/////////	,,,,,,	//////////	,,,,,,,	(11/1/1/	,,,,,,,,,,	,,,,,,,,	,,,,,,,,,	,,,,,,,	,,,,,,,,	3.0	/////
TOTALS	14.5		30.3		3 • 8							100.0	8.1

PLRCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

1							IN KNOTS						
IPECTION DEGREES)	1-3	4-6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	GE 56	TOTAL	MEAN WING
N !	.8	-4	.2	.4								1.8	6.1
NNE !	.4	1.6	1.8	.4								4 . 3	7.2
NE I	1.3	1.8	1.1	- 1								4.3	5.2
FNE !	2.7	2.4	1.2	-1								6.3	4.6
L .	3.4	4.9	1.2									9.6	4.3
ESE	3.1	2.0	.9	• 2	.1							6.3	4.3
SE	1.6	3.2	3.4	.9								9.1	6.7
SSE	1 • 2	5.4	13.7	5.9	.5							26.7	8.6
s	1.5	2.8	7.1	8.1	1.0							20.4	10.1
SSW !		. 3	. 4	. 4								1 - 2	9.7
SW I	• 3	•1										. 4	2.5
NSN I		• 3										. 3	4.7
• i		. 3										. 3	5 - 3
KNA		• 1	• 2									. 3	F • 0
Nw i		• 1	• 1	-1								. 3	٥.0
HINW [- 1	- 1	. 1		.1							. 4	7.3
ARIABLE !	• • • • • • • •	•••••	• • • • • • •	•••••		******	• • • • • • • •	•••••	••••••	• • • • • • •	•••••	•••••	•••••
ALM	,,,,,,,,,	,,,,,,,	,,,,,,,	11111111	,,,,,,,	1111111	,,,,,,,,	,,,,,,,	,,,,,,,,,	,,,,,,,	,,,,,,,	7.7	111111

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTION FROM HOURLY OBSERVATIONS

STATION NUMBER	724505	STATION							HONTH:		10 URS (LST): ALL	
	• • • • • • • • •	•••••	• • • • • •	• • • • • • • • • •	HIN	SPEED.	IN KNOTS	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •
DIFLETION IDEGREES		4-6	-	11-16	17-21	22-27	28-33	34-40			GE 56	TOTAL	ME AN WIND
N I	.8	1.0	. 9		- 1	.0	******	••••			•••••	3.1	6.4
NNE	.8	1.7	1 - 4	• 2	•0		• 0					4 - 1	6.2
NE	1.1	1.8	1.1	• 2	•0							4 . 2	5 . 4
ENE	1.5	2.2	1 - 1	-1								4.9	5.1
£	7.2	3 • 3	1.5	• 1								7.2	5.0
ESE	1 - 3	1.7	.9	• 2	•0							4.2	5.3
SE	1.3	2+2	1.8	.5	•0							5.8	6 • 1
SSE.	1.7	3.4	5.7	4 - 1	• 6	- 1	•0					15.6	8.7
S	2.0	4 • 1	9.8	10.9	1.7	• 2						28.7	10.2
SSW	.7	1.6	2.4	3.1	. 7							8.4	10.0
SW	.4	• 8	. 8	.7	• 1	•0						2.9	8.6
WSW	•2	. 4	. 3	. 3	•0							1.2	7.7
w	. 5	. 3	•2	. 1	•0							1.0	5 • 1
พทษ	•2	• 3	• ?	.0	• 0							. 8	5.8
NW	• 2	• 2	. 1	. 1		• C						. 5	5.8
PINN	.4	• 5	. 3	- 1	•0							1.3	5.5
140740.5	•		• • • • • •	• • • • • • • • • •	•••••		•••••	• • • • • •				• • • • • • • •	
VARIAPLE	İ												
CALM 1	<i> </i>	/////////	,,,,,,	///////////////////////////////////////	'''''	,,,,,,,	11111111	,,,,,,	,,,,,,,	(1111111)	///////	6.1	/////
TOTALS	15.1	25.6	20.5	21.0	3 • 3	. 3	• ()					100.0	7.5
	· • • • • • • • •			• • • • • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • •		• • • • • • •	• • • • • • • •	• • • • • • •	

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS
PERIOD OF RECORD: 77-86
MONTH: AUG HOURS(LST): 0000-02C0 HIND SPEED IN KNOTS 17-21 22-27 28-33 34-40 DIRECTION I 1-3 7-10 11-16 41-47 48-55 GE 56 TETAL MEAN (DEGREES) | LINU t 5.9 N 3.2 NNE 1.5 1.3 - 1 . 1 3.9 6.1 2.2 NE 1 • 2 1.2 • 2 4.7 5.4 2.4 1.4 ENE 2.2 . 2 6.1 5.0 Ł 1.7 9.8 3.4 4.6 4.5 ESE 1.8 1.2 .6 . 2 4.8 4.7 ۶ŧ 1.5 4.0 1.8 - 1 5.5 SSE 2.3 4.4 5.2 7.3 s 4.0 6.7 6 - 8 . 5 26.3 7.9 1.3 .5 1.8 1.8 5.5 8.6 56 • 3 . 1 • 1 . 4 1.0 9.3 NS W . 1 - 1 • 2 A.5 • 2 . 4 . 1 WNW . 1 . 2 . 4 P . 3 NH . 4 . 1 1.0 4.1 NNW 7.6 VARIABLE | CALM TOTALS **.** 1 160.0 5.9

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION YERSUS WIND SFELD FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86

											• • • • • • • •	• • • • • • • • •	• • • • • • • •
IPECTION	1-3	4-6	7-10	11-16	₩IN 17-21	D SPELD 22-27	IN KNOTS 28-33	34-40	41-47	48-55	GE 56	TETAL	MEAN
DEGREES!												*	#INL
N	1.3	1.6	1.3	.4	•••••	• • • • • •	• • • • • • • •	•••••	• • • • • • • •	••••••	•••••	4.6	5.9
NNE !	1.0	2.6	. 8	. 4								4.7	5.7
NE !	1.1	2.2	. 8	•2	• 1							4.3	5.7
ENE [1.8	2.0	1.0	• 2								5 • 1	5.0
L	3.8	3.4	1.2	- 1								8.5	4.3
ESE !	2.0	2.0	1.1									5.2	4,4
SE !	1.4	2.4	1.5	. 1								5.4	5.3
55E	2.3	4.0	2.4	1.2								9.8	6.0
s !	3.7	6.1	10.3	4.2	. 8							27.0	7.6
SSW	1.5	1.8	2.0	.9								6.2	6.6
S# !	. 8	.2	•6									1.6	4 . R
usu i	•2	. 3	• 2	• 1								. 9	6.0
. !	.5	. 1										.6	3.2
- NMM	• 1	.1	• 3									.5	6.4
talu .	•2	. 3	• 5									1.1	5.9
tinu	.4	.6	• 2	•1								1.4	5.5
VARIABLE		•••••	· · · · · · ·			• • • • • • •		• • • • • •		• • • • • • • •	•••••	• • • • • • • • •	•••••
1	,,,,,,,,,,	11111111	,,,,,,	,,,,,,,,,	///////	1111111	111111111	///////	,,,,,,,,	11111111	///////	13.1	111111
TOTALS I	22.0		24.2		.9							100.0	5.3
	0			=									

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86 MONTH: AUG HOURS(LST): 0630-0600 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS WIND SPEED IN KNOTS DIRECTION I 1-3 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN (DEGREES) 1 WIND ıN 6.4 4.4 1.1 1.1 1.9 . 3 2.0 5 • 1 5.5 NNE 1.6 • 2 1 . 2 1.3 NE 1 - 1 2.3 • 1 4.7 5.3 4.9 FNE 1.5 2.4 1.0 . 2 5.1 E 3.1 3.3 1.8 4.7 FSE 2.0 5.3 1 - 3 2.0 2.4 SE . 5 6.5 1.4 6.6 1.8 10.3 7.1 SSE 4 - 1 1.2 7.9 3.3 8.2 10.8 6.5 29.4 S . 6 1.7 2.0 1.3 • 2 7.0 SSW 1.7 7.2 . 1 - 1 S₩ . 8 . 3 . 1 1.4 5.2 WSW . 3 • 3 . 3 4.9 2.7 • 2 WNW . 1 4.7 • 2 . 1 • 2 1.3 5 . 3 , 8 NW NNH . 6 - 1 1.7 6.4 VARIABLE CALM A.5 ///// 100.0 TOTALS 30.9 28.5 11.6 **6.**0

GLORAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURREN USAFETAC FROM AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPFACE WIND DIRECTION VERSUS WIND SFELD FROM HOURLY OBSERVATIONS

TION NUMBER	: 124505	21#1104	NAME:						MONTH:		HOURS (LS	1): 09J0- -86	11(C
		•••••	• • • • • • •		wIM	ID SPEED	IN KNOT	S		• • • • • • •	• • • • • • •	• • • • • • • • •	•••••
DIRECTION LOEGREES)	1 - 3	4-6	7-10				28-33					TETAL	ME AN Wind
N I	. 3	1 - 3	2.2	.9	•••••	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	••••••	4.6	7.9
NNE .	. 3	2.0	1.8	. 4								4.6	6.7
NE	.8	1.8	1.6									4.2	5.9
ENE	.6	2 • 2	1.3									4.1	5.5
E	1.9	3.1	1.7									6 8	5.C
FSE	.8	1.4	1.3	• 1								3.5	5.9
SE	• 5	1 • 7	1.4	.6								4.3	7.1
SSE	.8	2.2	4 - 1	3,4	• 1							10.5	4.1
s	1 • 2	4 • 1	8.9	9.4	1 - 1	• 3						24.9	10-1
SSW	. 9	2 • 7	3.8	7.7	1.4	-1						16.6	10.9
Sw i	1 • 2	1.2	1.1	1.0	• 2							4.6	7.4
WSW	.9	• 5	.9	• ?								2.5	5.8
• •	1.0	• 6	• 2	- 1								1.9	4.4
WNW 1	.6	• 3	- 1									1.1	3 • ⁶ 7
NW I	. 3	- 1	• 2	. 4								1.1	7.7
NNW	. 4	. 4	.6									1 • 6	¢, • ¢,
VARIABLE !	• • • • • • • • • • • • • • • • • • • •		• • • • • • •	• • • • • • • •		• • • • • • •	••••••	• • • • • • •	• • • • • • •			• • • • • • • • •	• • • • • • • •
CALM .	,,,,,,,,,	///////	,,,,,,,	,,,,,,,,	,,,,,,,	//////	11111111	1//////	,,,,,,,,	(11/1/1/	,,,,,,,	3 - 1	111111
TOTALS	12.5	25.7	31.2	24.3	2 • 8	. 4						100.0	4 - 1

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELECTION VERSUS WIND SELECTIONS

TATION NUMBER	: 724505	STATION							MONTH:	AUG		-86 I): 1250-	1466
DIRECTION CDEGREEST		4 - 6	7-10	11-16	17-21	D SPEED 22-27	IN KNOTS 28-33	34-40	41-47	48-55		J (T A L Z	ME AN WING
N .	.6	1.1	1.4	1.0	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • •	4.1	8.0
PNE [• ?	1.1	1.7	• 5	• 2							3.8	F . 4
NE	1 • 3	1 • 9	2.8	.5								6.5	6.6
FNF	1 • 2	1.0	1.1									9.2	5.2
. !	1 • 3	3 • 2	1.4	٠1								1.18	* • 1
ESE	. 9	- 9	1.5	. 3								3.4	6.3
SE !	1.0	1.7	2.3	• 3	. 1							4 • 6	4.9
*SE	1 - 1	1-8	3.A	3 • 8		• 1						10.8	9.1
5]	1.7	3.4	7.4	13.3	3.0	. 3						29+3	11.2
ZZM į	.5	2.0	3.7	4.8	1.3	- 1						12.5	1
SW !	.5	1.2	2.0	1 • 1	. 4							5.3	9.1
usw !	. 3	.4	. 3	. 4								1.5	1.2
w	.6	.3	. 3	. 5								l.b	५ . व
same !	. 3	•2	. 1									.6	5.4
NW I		. 4	. 4	• 1								1.0	7.3
Parkalan 1 Parkalan 1	.6	•5	. 5	. 4								2.2	6.3
VARIABLE	· · · · · · · · ·	• • • • • • • • •	• • • • • • •	• • • • • • • •		• • • • • • •	• • • • • • • •		• • • • • • •			• • • • • • • • •	•••••••
CALM !	,,,,,,,,,	,,,,,,,,	,,,,,,,	11111111	///////	//////	11111111	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,,	2.6	/////
TOTALS	12.5	21.5	30.A	27.1	5.1	.5						130.0	٠.٦

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF PECORD: 77-86 MONTH: AUG HOURS(LST1; 1580-1706 | WIND SPEED IN KNOTS DIPECTION I 17-21 22-27 28-33 34-40 GE 56 TOTAL MEAN IDEGREES) 1 # I N U 1.2 2.0 1.0 • 2 8.1 NNE • 3 1.4 2.7 1.0 5.4 8.1 ٨Ę 4.4 6.7 ENE .9 2.9 1.8 .5 6.1 6.1 2.5 3.0 1.1 . 4 ٤ • l 7.1 5.2 1.2 1.4 1.9 . 2 ESE 4.7 5.8 51 2 . 3 2.3 . 8 • 2 1.1 6.6 7.1 "SE . 9 3.3 4.0 6.1 1.2 . 2 15.7 9.8 1.3 4 • D 5.2 12.5 2.8 • 5 11.4 < S ¥ - 8 8.8 11.8 • 2 - 1 2.0 8.5 . 2 . 3 1.0 656 5.6 . 1 . 1 . 1 . 3 .6 B.7 . 3 . 2 White . 8 . 2 5.0 t. u ٠, ۲ . 5 • 2 1.3 e . o tite to .6 - 1 VARIABLE I CALM 2.7 ////// TOTALS 29.9 25.7 5.4 1.0 . 1 0.004 B.7

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOUNCY ORSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECOPD: 77-86
MONTH: AUG HOURS(LST): 1800-2000

WIND SPEED IN KNOTS

DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN
(DEGREES) | 8.1 N 1.7 . 5 . 1 4.0 1.4 1.1 . 3 . 1 3.0 7.1 NNE .6 1.6 . 2 4.8 5.7 NE 1.2 1.8 ENE 1.6 4.1 1.8 - 1 7.6 5 • 1 £ 4.9 1.7 .6 12.2 4.6 ESE • 2 6.2 4.6 1.0 . 2 6.3 SE 1.8 5.3 7.0 7.1 20.0 8.3 SSE .6 5.2 . 1 4.8 7.4 18.2 3.0 1.1 10.1 s 1.7 . 1 4.4 9.5 1.1 1.5 1.4 . 2 55# • 2 SW . 3 . 3 . 3 1.2 7.4 WSW . 1 . 1 . 2 8.0 . 3 . 1 . 6 6.3 . 1 .2 7.0 . 9 4.1 NW .6 • 1 NNW VARIABLE I *```* 3.9 ///// 100.0 7.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: AUG HOURS(LST): 2100-2300 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

•••••		• • • • • • • •		• • • • • • • •		ND SPEED	IN KNOTS	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	•••••
DIRECTION (DEGREES)	1-3	4-6	7-10	11-16		22-27	28-33		41-47	48-55	GE 56	TOTAL	MEAN WIND
N	.8	1.2	1.2	.6		• • • • • • •	• • • • • • • •	•••••		• • • • • • •		3.8	6.9
NNE	.8	1.5	1.4									3.7	5.8
NE	1.2	1.6	1.1	.4								4.3	5.8
FNE	2.5	2 • 7	1.1	. 1								6.3	4.2
£	3.5	6 • 3	2.6	• 3								12.8	4.9
ESE	1.9	3 • 5	.8	•2								6.5	4.8
SE	2.7	4 - 2	4.5	.6								12.0	6.0
SSE	1.9	5 • 8	8.4	2 • 2	• 1							18.4	7.4
s	2.6	3 • 7	7.1	6.1	.4							19.9	8.8
27₩	.3	. 9	. 4	1.0								2.6	8.1
SW	-1	. 3	- 1									.5	4.6
NSW													
¥	; !												
WNW				• 2								. 4	9.0
NW	j .4	• 2	• 2	• 2								1.1	6.2
NNW	.2	• 3	• 1									•6	4.7
VARIARLE	,	• • • • • • •	• • • • • • •		•••••	• • • • • • •	• • • • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	•
CALM	1,,,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	//////	///////	,,,,,,,,	1111111	,,,,,,,,	,,,,,,,	,,,,,,,	7.1	111111
TOTALS	 19.1 	32.3	28.9	12.0	• 5							100.0	6.1

PERGENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

IRECTION DEGREES)	1 - 3						IN KNOTS						
		4-6	7-10	11-16	17-21	22-27	28-33		41-47	48-55	GE 56	TCTAL *	ME AN WIND
N I	.7	1.3	1.5	.6	•0	• • • • • • • •	• • • • • • • •	•••••	•••••	• • • • • • •	•••••	4.2	7.2
NNE	.7	1.6	1.5	. 4	•0	.0						4.3	6.7
NE I	1 - 1	1.9	1.5	.3	•0							4.7	5.9
ENE	1.5	2.6	1.3	• 2								5.6	5.1
ε	3 • 1	4.0	1.7	• 2	•0							8.9	4.8
ESE !	1.6	1.9	1.2	• 2								4.9	5 • 1
SE !	1 • 4	2.9	2.4	• 5	. 1							7.3	6.3
55E	1.4	4.1	5.0	3.0	• 2	•0						13.7	8.1
s	2.4	5.1	7.9	8.3	1.3	. 2						25.1	9.4
SSW	.8	1.5	2.2	2.9	• 5	- 1		•0				7.9	9.8
SW .	.5	• 5	. 7	. 4	- 1							2.2	7.6
KSM	• 3	• ?	. 3	-1								.9	6.1
	.3	. 3	- 1	-1								. R	5.2
unu	• 2	• 2	• 1	- 1								.6	5.3
NW I	• 3	.4	• 3	- 1								1.1	6.2
NNW	• 3	.5	•5	- 1	•0	•0						1.4	6.5
ARIABLE [• • • • • • • • • • • • • • • • • • • •	•••••	• • • • • •	• • • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	•••••	• • • • • • • •	•••••	•••••	•••••	•••••
ALM /	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	//////	,,,,,,,	,,,,,,,	,,,,,,,	6.3	,,,,,,

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM MOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86 MONTH: SEP HOURS(LST): 0000-0200 WIND SPEED IN KNOTS
DIRECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 (DEGREES) I LIND 2.0 1.0 1.0 1 - 3 . 8 2.1 1.9 . 8 5.6 6.8 NNE 4.7 4.3 2.3 1.8 . 6 NE ENE 1.7 1.7 .6 3.9 4.2 4.5 7.6 2.7 3.3 1.6 £ 4.1 4.2 ESE 2.0 1.3 . 8 8.7 5.5 SE 1.7 4.9 1.8 . 3 17.0 7.5 SSE 2.1 6.2 5.1 3.2 • 3 27.4 s 5 • 3 8 - 8 8.7 1.3 9.5 . 2 3.7 10.0 SSW • 8 • 2 . 1 . 9 8.0 SW • 1 . 3 5.7 WSW - 1 . 1 - 1 5.5 . 7 - 6 . 1 . 1 . 1 4 . D WNW . 4 7.5 NU • 2 • 2 . 3 1.2 8.4 VARIABLE CALM 8.2 ////// . 7 100.0 TOTALS 16.0 2.1 6.7

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

í							IN KNOTS						
IPECTION DEGREESI	1-3	4-6	7-10	11-16	17-21	22-21	28-33	34-40			GE 56	TOTAL	ME AN Wind
N !	.7	1.7	1.9	1.0	•1	.2				<i></i>		5.6	8.2
NNE !	.7	2.1	1.4	1.0								5.2	7.1
NE	1 - 4	2.1	1.0									4.6	4.8
FNE	1.7	1.1	- 4									3.2	4.0
. !	2.8	3 • 1	1.4									7.3	4.5
E Z E	1.6	1.2	• 2									3.0	3.7
SE !	2.B	3.3	. 7	-1								6.9	4.2
SSE	3.7	4.3	2.7	3 - 3	• 1							14.1	6.9
5	4,4	6 • I	8.2	7.8	1.0							21.6	8,7
SSW	. 3	1.2	1.6	1.6	• 2	• 1						5.0	9,6
SW I	• 1	• 2	• 2									.6	6.4
LSW	•2	• 2	- 1									.6	4.0
• }	•?	• 3	- 1									. 7	4.7
was !	• 1											•1	2.0
NW \$	•2	. 3										.6	4.4
NNW I	.4	.9	. 8	.4	. 3							2.9	8.4
VARIABLE]	• • • • • • • •	•••••	• • • • • •	• • • • • • • •	• • • • • •	• • • • • • •					• • • • • • • •	• • • • • • • • •	• • • • • •
CALM 1/	11111111	,,,,,,,	///////	,,,,,,,,	///////	1111111	,,,,,,,,	1111111	,,,,,,,,	,,,,,,,,	,,,,,,,	12.2	111111

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86 MONTH: SEP HOURS(LST): 0600-0600 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS 41-47 (DEGREES) ! 6 I 14 U N 1.0 . 1 2 - 1 2.4 1.2 • 3 8.0 NNE .6 1 - 1 1.8 • 2 .8 4 - 4 6.2 NE 1.0 1.1 . 9 • 2 3.2 5.8 ENE 1.9 1.6 5.3 ٤ 2.3 7.7 4.9 ESE 2.0 .6 4.3 5.4 SE 2.9 1.0 1.4 5.6 • 2 5.1 SSE 4.1 2.3 3.8 2.1 - 1 17.4 7.1 6.0 S 1.7 10.0 8.8 2.0 . 2 29.7 9.7 . 9 55# . 4 1.6 1.3 . 2 SW - 1 • 3 • 2 . 7 ٠.3 WSW • 3 4.7 • 2 3.5 HNW 4.0 NW . 8 . 1 . 1 1.0 6.2 NNW . 6 . 3 3.6 7.2 VARIABLE

30.1 3.0 100.0 6.7

9.4 /////

TOTAL NUMPER OF OBSERVATIONS:

CALM

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFRIKS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS
PERIOD OF RECORD: 77-86
MONTH: SEP HOURS(LST): 09J0-1100 ⊾IND SPEED IN KNOTS 17-21 22-27 28-33 34-40 41-47 DIFECTION I 1-3 7-10 48-55 GE 56 4 - 6 11-16 TOTAL PEAN IDEGPEES) 1 MINL ı 7.7 9.9 . 8 1.6 . 3 1.0 2.4 . 2 KNE 1.4 5.4 9.3 1.1 2.9 NE • 2 + 8 . 8 8.2 6.3 ENE .6 1.4 1.4 - 1 3.6 2.3 £ 1.0 1.4 . 4 5.2 6.5 ESE . 8 1.4 .6 . 4 3.2 t • 1 SE . 4 2.2 . 3 7.0 . 9 A . 1 9.3 5 4.8 9.9 12.8 4.1 1.2 . 4 . 1 33.3 11.8 . 5 3.1 4.0 55W 1.7 2.2 - 1 11.4 11.8 SW 1 - 7 1.1 . 9 4.2 7.0 . 6 4 S W .6 . 9 . 2 . 1 1.8 5.0 . 7 . 3 1.0 3.2 LNE • 2 . 1 . 3 . 7 9.2 NW . 3 ٠, • 3 4.6 NNE VARIABLE CALM 100.0 31.4 9.3

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SHEED FROM HOURLY OBSERVATIONS

AIR BERTHER SERVICE/HAC

PERIOD OF RECORD: 77-86 MONTH: SEP HOURS(LST): 1200-14C0 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS WIND SPEED IN KNOTS DIFECTION | 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN IDEGREES! 1 **₩IN**U • 1 10.0 3.4 10.3 N 1.0 1.4 2.8 1.2 1.4 . 9 4.1 P.5 ENE 1.4 • 1 • 2 3.0 7.4 NE . 3 1.1 1.0 . 6 5.3 . 7 FNE • 2 1.9 2.8 1.0 1.4 1.6 . 3 4.3 6.2 ESE 1.3 SE 1.0 7.2 . ? 9.7 . 6 2.3 12.7 5 4.2 7.8 15.0 5.0 . 1 1.2 . 7 5 S W . 7 2.3 2.3 3.0 2.1 11.6 3.3 P - 1 . 8 1.0 5 🖦 • 3 1.1 . 1 5.4 2.2 WSW .6 1.0 .6 - 1 . 4 . 2 . 2 1.0 7.1 KNH • 3 4.2 • 3 . l .6 1.6 7.3 VARIABLE 2.3 ////// CALM TOTALS 3. 3 • 1 100.8

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM MOURLY OBSERVATIONS

!					WIN	D SPEED	IN KNOTS						
IPECTION DEGREES)	1-3	4 - 6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	GE 56	TOTAL	ME AN
N !	.7	1.6	2.2	2.8	.9	-1	• • • • • • • • •	•••••	•••••	•••••	•••••	8.2	10.
NNE .	.8	1.9	1.8	1.2	- 1							5.8	8 - 0
NE	• 9	1.4	1.0	. 7								3.9	6.6
ENF	•2	2.4	. 9									3.6	6.0
r į	1.4	2.1	1.9	• 2								5.7	5.
FSE	.6	• 7	. 9	. 3	• 1							2.6	1.
SE	.7	1.4	2.4	.7	- 1							5.3	7.4
SSE	. 4	1.3	5.7	4.8	1.1	• 2						13.9	10.
S [1 - 1	4 - 7	4.4	13.9	5.3	1.4	•3					31.1	12.5
SSW	. 7	1 - 7	1.7	2.8	1.0	. 3						8 • 1	11.
su i	.6	1.2	. 7	•6		•?						3.2	μ.
HSH	. 3	. 3	. 4	. 3								1.4	7.1
- [. 4	• 2									. 7	5.9
UNW		• 7	.2	• 1								.6	е.,
NW	• 3	• 2	• 1	. 7								1.3	۱. ۵
NN# 1	• 3	• 7	.6	. 9	• 1							2.6	9.1
ARIAPLE		• • • • • • •	• • • • • • •	•••••		• • • • • • •	• • • • • • • •	• • • • • •	••••••	••••	•••••		•••••
ALM /	,,,,,,,,	,,,,,,,	///////	,,,,,,,,	,,,,,,,	///////	,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	2.1	/////

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS

| MONTH: SEP HOURS(LST): 1800-2000

| MIND SPEED IN KNOTS
| DIPLOTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TETAL MEAN (UEUREES) | (DEGREES) | WIND ı . 3 8.7 . 8 1.9 2.3 2.1 7.4 2.2 1.7 1.1 . 1 NNE 6.3 7.3 1 • 2 . 9 . 2 5.4 NE 1.4 2.2 . 7 6.2 ENE 2.3 2.3 . 8 . I 5.6 4 . 4 Ł 1.6 3.0 2.2 . ? 7.0 5.7 1.0 ž • 1 5.1 4.0 2.9 9.8 SE 1.9 - 1 6.3 SSE 2.4 5.6 ٠, R. 4 20.6 10.7 S 1.7 5.0 7.2 2.6 3 . 7 . 4 954 . 3 3.4 7.6 1.7 . 9 . 3 . 2 SW . 4 - 1 • 1 . 7 8.7 WSW . 1 . 1 5.0 HNE N w 10.8 NAME 9.3 5.6 ///// 100.0

 GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

The service service in a

STATION NUMBER	?: 724505	STATION			_				MONTH:		HOURS (LS	-86 (1: 2130-	2300
DIPECTION (DEGREES)		4-6	7-10	11-16	wIt 17-21	ND SPEED 22-27	IN KNOTS 28+33	34-40	41-47	48-55		T(TAL	ME AN
N	. 4	2 - 3	1.8	1.4				• • • • • • •		•••••	••••••	6.0	1.7
NNE	.7	1.4	1.9	.8								4.8	7.3
₩E	1.0	2 • 7	1.2	.6								5.4	F 9
FNE	1.8	3.3	. 3									5.4	4.2
i	2.7	2.9	2.7	.4								8.7	4. 4
ESE	2.6	2.8	. 4	• 1								5.9	4.7
SF	1.6	5.4	2.6	.8								10.3	5.8
₹ 5 ₹	2.1	6.0	6.8	5.7	. 8							21.3	ų <u>, c</u>
5	2.1	2 • 8	6.0	8.0	2.1	.4						21.4	10.6
SSW .	•2	• 2	• 1		•2							. 6	9.0
SW	• 3	. 3	• 2									. 9	4.5
WSW	• 2												2.5
N/viii	•	. 1										• 1	6.0
le ta	.2		• 2	. 1								.6	7.4
NNw	•1		.6	-1	•1							. 0	4.6
VARIABLE (• • • • • • • • • • • • • • • • • • • •		• • • • • •		• • • • • •	• • • • • • •		• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	
(AL 4	/////////	,,,,,,,,	//////	,,,,,,,,	///////	(1)11111	,,,,,,,,	1111111	,,,,,,,,	,,,,,,,,	,,,,,,,	1.2	111111
TOTAL 5	16.0	3G.3	24.8	18.0	3.2	.4						156.0	7.5

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WING DIRECTION VERSUS WIND SELECTION FROM HOURLY DISFRVATIONS

PERIOD OF RECORD: 17-A6

MONTH: SEF HOURS(EST): ALL

UIRECTION | 1-3 4-6 7-10 11-16 17-71 22-27 39-31 70-00

UIRECTION | 1-3 4-6 7-10 11-16 17-71 22-27 39-31 70-00 (DEGFEES) 1 ı w 1 2 c N . 7 1 • 9 2.3 1.7 . 5 - 1 7.3 9.0 . 7 1.8 - 1 5.2 7.8 PINE 1 . 7 1.0 NE 1.3 1 . 7 1.0 . 4 • 0 4.1 ENE 1.2 2.0 . 8 • () 4.1 4.4 ٤ 1.9 5.3 2.6 • B . 1 .0 4.0 5.1 ESE 1.4 1.7 1.4 3.0 1.8 .5 • 0 6.7 4, 4 SF SSE A . 1, 1.9 4.4 3.7 . ì 14. " 3.8 .6 ٠, 1.9 4.7 7.5 10.2 2.9 . 9 . 1 29.2 1,... < 5 W . 4 1.4 1.4 1.7 . 7 . 2 6.0 11.6 S¥ • 7 . 4 . 3 ٠.0 . 0] . ^p 7.4 • 3 . 2 . 0 4. . 5 • 2 . 0 4.9 . 2 . 3 • 0 ٠. 1 ٠, . 1 . 1 .. 7.1 . 3 . 2 NW • 2 1,149 . 6 .5 . 1 4 . 4 CALM 6.3 ////// 7.9 TOTALS 25.R 20.9 5.0 1.3 • 1 160.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SELFU-FROM HOURLY OPSERVATIONS

<u>.</u>	• • • • • • • •	•••••	• • • • • • •	• • • • • • • •					• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •
IFECTION OFUREES)		4 - 6			17-21	22-27		34-40	41-47			1 (TAL	MEAN WIND
	2.9	3.5	2.0	3.1	.4	. 2			•••••	• • • • • • •		17.3	7.8
%%E]	1.0	2.0	1.1	. A								4.5	6.9
t _e E .	1.0	2.2	. 4	• 2								3.9	5.2
* h f	1.4	1.6	. 3	- 1								3.4	4.1
£ !	2.0	1.7	. 3									4.1	₹.₽
ESE	1.5	1.5	. e									3 • P	4.3
5£ !	1.5	3.2	1 - 4	.6	. 3							7.1	6.3
*5E	1.0	5 • 3	3.9	2.9	. 9							15.9	r. *
5 1	1.8	5 • 2	5.2	5.6	1.3	.6						19.7	٠.٠
	1 • 2	•6	.6	. 8	. 4							*.7	٠. ١
S=	. 4	. 8	• 2									1.4	4.7
- NS#	. 3	. 4	• 1										4.
-	.8	.5	. 1	. 3								1.7	·
tetre [1.0	. 1	• 6								1. '	*•:
١	• 2	• 6	. 6	• 2	• 2							1.9	* • *
100 mg	٠.	1.6	• •,	. 3								٠.	٠
VARIABLE 1	• • • • • • • •	• • • • • • • •	• • • • • • •	•••••	•••••	• • • • • • •		• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • • • •	
CALM 1	/////////	////////	11111111	.,,,,,,,	///////	1111111	11111111	,,,,,,	////////	////////	///////	17.9	111111
TOTALS	17.5	31.8	17.7	15.6	3.5	• 9							4

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

L AFB KS

PERIOD OF RECORD: 77-86

MONTH: OCT HOURS(LST): 0300-05CG

WIND SPEED IN KNOTS

17-21 22-27 28-33 34-40 41-47 46-55 GE 56 TCTAL HEA DIPECTION ! 1 - 3 7-10 11-16 MEAN (DEGREES) | Ł WIND .5 .2 N 3.8 2.4 1.8 2.8 11.5 ٧.0 1.2 1.3 1.2 NNE . 8 4.4 7.7 NE 1 - 4 1.5 . 2 • 3 3.4 4.4 ENE 1.0 . 1 2.5 4.0 Ł 2.3 2.5 4 . 1 ESE 1.3 1.2 .6 3.1 4.2 . 4 • 2 SE 2.6 1.7 1.6 6.6 5.5 3 - 4 2.6 2.4 . 8 SSE 1.7 . 1 11.0 8.1 \$ 2.5 6 . 7 4.3 6.5 1.2 . 5 21.6 8.9 SSW .6 1.3 . 9 .8 3.5 SW . 9 . 4 . 1 WSW . 3 • 2 . 1 • 3 . l 5.9 • 3 1.0 6.9 1.0 . 3 ٠2 NW . 6 2.8 7.1 NNW 2.5 1.0 7.1 2.2 VARIABLE CALM 13.7 ///// TOTALS 18.1 2.9 . 2 100.0 27.6 .6 6.3

GLOBAL CLIMATOLOGY BRANCH

PLACENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

#IND SPEED IN NOTS

| DIFFICITION | 1-3 | 4-6 | 7-10 | 11-16 | 17-21 | 22-27 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | 28-15 | IDEGREES) 1 12.7 6.4 . 5 3.0 3 • 1 8.6 5.1 . 9 1.1 1.5 1.2 . 4 NNE 4.5 5.5 2.0 . 3 1 - 1 NE 4.7 .2 1 - 1 • 6 ENE 1.3 2.2 .6 . 1 í 3.2 . 5 1.4 ESE 1.2 5.7 6.8 . 3 1.6 1.5 SE 12.3 7.3 • 2 SSE 2.2 3.4 4.6 1.8 21.5 1.9 . 2 5.6 4.8 3.5 1.0 . 9 1.0 5 S W 1.0 5.9 1.7 . 3 . 5 . 2 4.3 . 3 . ? • 2 WSW 5.1 . 6 . 3 • 6 - 1 . 9 . 2 4. 1 FNH 1 • 1 - 1 . 9 9.1 NE • 1 1.2 • 5 .2 . 2 3.1 6.1 10.2 ///// CALM 100.0 6 - 7

3.3

PERCENTAGE FREQUENCY OF OCCURRENCE UF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

All MENINER SCHULCEPING

STATION NUMBER	R: 724505	STATION			- 5				MONTH:		10 URS (LS1	-86 1: 0900-1	160
		•••••	• • • • • •	• • • • • • • • • • • • • • • • • • • •			IN KNOTS		• • • • • • •	•••••	• • • • • • • • •	•••••	
DIPECTION (DEGRees)	1	4-6	7-10	11-16	17~21	22-27			41-47	48-55	GE 56	TOTAL	MEAN WIND
N I	4	2.0	5.4	6.0	4	• • • • • • •	•••••	• • • • • • •	• • • • • • • •	••••••		14.3	10.3
i	l				• •							14.3	•
NNE 1	•2	1.2	1.6	1.7	- 1							4 • 8	9.4
NE]	• 3	1.0	1.9	. 4	-1							3.8	7.9
ENE	-4	1.1	1.0									2.5	5.8
ε	-5	1.7	. 9									1.8	5 • 1
FSE	.6	1.6	1.5	•1			. 1					4.0	6.5
S.E.	.4	1.5	1.5	.9	- 1		.1					4.5	8.3
.58	. 3	1.9	2.5	3 • 2	•2							8.2	9.6
S	1 • 1	3.1	6.7	8 . 2	3.9	1.5						24.4	12.1
SSW	.4	1.5	2.4	3.5	•6	-1						8.6	10.5
SW [• 3	• 8	. 6	.6	. 4							2.8	9.8
WSW	• 3	1.1	1.1	• 2								2.7	6.6
•	• 3	1.3	. 4	. 3	- 1							2.5	6.9
unu !	•5	• 9	.9		• 1							2.4	6.6
NW I	• 3	1 • 3	. 9	.6	• 3	- 1						3.5	9.0
NNW (.4	1 • 2	2.2	1.3	• 4	• 3						5.8	9,6
	• • • • • • • •		• • • • • •		• • • • • •							• • • • • • • • • •	
VARIAPLE 1													
CALM (111111111	/////////	//////	,,,,,,,,,,	///////	,,,,,,,	11111111	//////	,,,,,,,	,,,,,,,,	,,,,,,,	2.2	111111
TOTALS	7.1	23.1	31.3	27.2	6.9	2 • 0	• 2					100.0	9.5

GLUBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86

									MONTH:	0C T	HOURSILS	1): 1200-	1400
	1	•••••	• • • • • • •			D SPEED	IN KNOTS		•••••	•••••	•••••	• • • • • • • • •	•••••
DIRECTION (DEGREES)	l	4-6	7-10		17-21	-	28-33		41-47	48-55	GE 56	TOTAL	ME AN MINU
N	.9	1.6	4.6	6.1	•1	• • • • • • •	• • • • • • • •	• • • • • • •		••••••	•••••	13.3	10.2
NNE	.5	• 5	2.0	2 • 2	.5							5.8	10.6
NE	.2	1.0	1.6	.6	• 1							3.5	8.5
ENE	.4	• 5	. 5									1.5	5.1
ε	.2	1.6	.4									2.3	5 . 3
€SE	.4	• 5	.6									1.6	5.4
SE	•1	1.4	1.7	1.1	• 1							4.4	8.3
\$ 5 E	.4	1.5	3.0	2.5	.8	. 1						8.3	10.2
s	.9	2.0	7.0	8.7	3.9	1.4	. 1					24.0	12.7
SSH	. 4	1 • 3	2.3	3.2	1.8	.6	. 1					9.8	12.7
2.8	•2	. 3	1.7	1.2	. 8	- 1						4.3	11.7
WSW	!	•6	• 6	. 3								1.6	8.4
w	.4	• 8	. 9	. 3	- 1							2.5	7.9
NNW	.1	. 4	1.1	• 2								1.8	7.6
NW	.6	• 8	1.5	1.5	• 2	• 2						4.8	9.9
NNW	-3	1.7	2.5	2.6	• 5							7.6	9.7
VARIAPLE	' ••••••• I		• • • • • • •		•••••		· · · · · · · · ·	•••••	• • • • • • • •	•••••		• • • • • • • • •	
		,,,,,,,,	,,,,,,,,	,,,,,,,,,,	,,,,,,,,,	7111111		1111111		,,,,,,,,		2 0	
TOTALS	6.2	16.7	32.2	30.5	8.9	2.5					.,,,,,,,,	100.0	10.3
I	1							•				100.0	10.3
•••••	•••••	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •		• • • • • • • • •	•••••	• • • • • • • •	• • • • • • • •		• • • • • • • • •	

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LST): 1500-1700

WIND SPEED IN KNOTS

DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MIAA

(DEGREES) |N | 4.5 5.5 10.3 NNE . 9 2.4 9.3 . 2 NE . 4 1.6 3.4 6.6 ENE . 5 1.8 5.1 .6 •6 Ε . 9 1.1 . 2 2.2 4.1 . 9 ESE . 2 4.7 .8 . i 1.9 SE . 4 1.0 1.1 1.1 . 1 3.7 8.9 SSE 2.7 3.3 3.7 . 8 • 2 11.1 9.7 12.4 SSW 1.3 3.0 • 2 6.8 12.7 . l 9.3 SW 3.4 • 2 • 6 - 3

VARIABLE CALM 3.1 ///// TOTALS 29.9 3.2 100.0 9.7

- 1

. 4

1.9

3.1

2.2

3.7

6.1

6.3

6.3

10.9

9.2

TOTAL NUMBER OF OBSERVATIONS: 930

. 9

.6

.6

• 3

1.0

• 8

• 5

. 4

. 5

. 4

1.6

3.7

. 2

. 6

. 3

1.0

2.5

. 3

WSW

Utsu

NW

NNW.

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LST): 18UC-2UUU WIND SPEED IN KNOIS 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN DIFECTION ! 1 - 3 4-6 (DEGREES! ! **⊾**146 ı N 4.8 8.0 16.5 MNE 1.9 6.9 6.1 NE 1.1 1.7 . 9 . 3 4.0 5.3 ENE .6 . 6 5.0 1.8 Ε 1.8 . 1 . 1 3.9 4.0 1.5 ESE 1.2 . 6 . 1 3.4 4.8 SE 2.2 2.8 1.3 1.3 7.5 5 S E 2.4 5.2 15.3 S 1.9 1.0 ٧.1 ۱. ۹ .5 . I SN . 6 2.2 NSW - 1 - 1 . 5 . 1 • 2 9.2 • 3 . 3 • 3 ٠2 1.2 6.4 . 4 . 1 . 2 1.0 LNM . 2 8.2 NW . 3 • 6 • 3 **.** 1 - 1 1.5 6.7 NNW VARIABLE CALM 13-1 ///// 100.0

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SUPFACE WIND DIRECTION VERSUS WINU SFELD
FROM HOURLY OPSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-96
MONTH: OCT HOURSELSTI: 2100-230

									MONTH:	001	HOURSILS	11: 5100-	2360
ı							IN KNOT				•••••		•••••
DIPECTION 1 (DEGREES)	1 - 3	4-6	7-10	11-16		-	28-33		41-47	48-55	GE 56	TETAL	ME AN mit.u
N !	1.5	5.1	4.4	2.2	. 3	• ?	• • • • • • • •				••••••	13.7	7,7
NNE	1 • 2	1.9	1.2	1.5	.4							6 • 2	P • 1
NF .	1.3	1.0	1.0	•2								3.4	5.6
ENE	1 • 2	1 • 7	.5									3.4	4.2
ı ¦	2.6	1 • 7	1.0									5.5	4.2
£2£	1 • 1	1.5	. 9									3.4	4.7
SF	1 • 2	3 • g	2.0	1 - 1	• 1							A . 2	6.6
SSE	1.3	3 • g	4.2	3 . 3	. 8	• 1						13.4	H.6
s	2.3	5 • 3	4.0	5.5	1.6	. 4						19.0	9.4
SS₩ I	.6	• 8	1.0	.6	- 1	- 1						3.2	^μ • 1
SW	• ?	• 2										. 4	3.5
WSW I		. 1	. 1									• 2	5.5
- į	• 3	• 2		. 3								. 9	6. p
WAW	• 1	• 2	. 3	. 6	. 1							1.4	10.8
NH I	• 1	• 6		• 1								. 4	5.9
NNW	. 4	1.7	. 3	• 1	.3							2.9	6.8
VARIABLE	• • • • • • •	• • • • • • •	• • • • • • •	•••••	•••••	• • • • • • • •	••••••	• • • • • • • • • • • • • • • • • • • •	• • • • • • • •			• • • • • • • •	•••••
CALM /	,,,,,,,,	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	1111111	,,,,,,,	,,,,,,,	,,,,,,,	14.0	111111
TOTALS	15.4	29.6	20.9	15.6	3 - 8	. 9						100.0	6.5

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBE	R: 7245U5								MONTH:	0C 1	D: 77		ι
DIFECTION (DEGREES)		4-6	7-10	11-16	■IN 17-21	22-27	IN KNOTS 28-33	34-4C	41-47	48-55	GE 56	ICTAL 3	Mi Ari m 1 Pet
Ν.	1.6	3.1	4.1	4.0	•5			• • • • • •		• • • • • • • •	•••••	13.5	6.9
NNE		1.3	1.5	1 - 4	- 3							5.4	F . 5
NE	.8	1.4	1.1	. 3	•0							5.7	6.1
FRE	. A	1.0	.4	• 1								2.2	4.7
t	1.5	1.8	.5	• 0	.0							3.4	4.3
ESE	1.0	1.2	. 7	• 1			•0					7.1	5.0
SE	1 1 • 2	2.1	1.6	. 4	. 1	•0	• 0					6 • C	
SSE	1 1 - 2	3 - 3	3.7	2.9	.6	- 1						11.7	6.6
s	1.7	4.5	5.4	6.6	2 • 2	.9	•0					21.3	10.5
55#		1 - 1	1.3	1.6	.6	• 1	• 0					5.3	10.2
SW	.4	. 4	.6	. 4	•2	• 0						2.0	٠.3
WSW	. 3	. 4	. 3	• 1		•0						1.2	(.3
•	5	-6	. 4	. 3	. 1							1.8	6.8
Wha	.4	• 6	. 4	. 3	- 1							1.7	7.1
Pe Ma	.3	- 8	.8	.6	.2	.1						2.8	4.9
444	.6	1 - 8	1.8	1.2	• 2	. 1						5.6	6.3
VARIARLE	l	•••••	• • • • • • •	•••••	• • • • • • •		•••••	• • • • • • •	•••••	• • • • • • •	•••••	• • • • • • • •	•••••
LALM		///////	,,,,,,,	///////	,,,,,,,	///////	////////	//////	///////	,,,,,,,	,,,,,,,	9. G	111111
TOTALS	13.7	25+6	24.6	9.75	4.9	1 - 4	• 1					100.0	7.1

PERCENTAGE FREQUENCY OF OCCUPRENCE OF SURFACE WIND DIRECTION VERSUS WING SEEL FROM HOURLY GESTRVATIONS

.2 .1 .1 .1 .14. f. 4.4 1.0 1.4 ⊋.8 4 . 6 14.7 6.9 NNE 1.0 2.6 3.7 1.4 . 1 н. н 7. ٩ŧ • 2 1.0 . 4 . 4 . 2 3.3 F∧£ .6 1-1 . 8 . 1 2.0 Ĺ 1.3 4.0 . 9 . 4 3.3 FSE 1.0 4 . 4 1.3 1.1 . 2 4. ٠., 5.5 1 - 3 3 • p 1.9 5 S E 1.6 3.1 . 4 . 3 11-1 A . . 2.6 3 - 8 5.0 4.9 1.6 . ì 17.9 459 1.1 1.0 1.9 1.0 . 2 6.7 7.3 . 4 1.6 • 3 . 2 4.5 • 6 4 . 6 7.2 • 2 1.6 WINE • ? • 7 N = 1.1 1.2 . 5 . 1 1.0 7.7 . 2 . 1 8.94 1.4 . 6 . 7 1. . . : VARIABLE 11.9 ///// CALM 160.0 7.1 TOTALS 21.0 17.3 1.1 . 1

101AL NUMBER OF DESERVATIONS: 950

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

									MONTH:		HOURSILS	1): 0300-	0566
I ITECTION I OFUREEST 1	1-3	4 - 6	7-10	11-16	₩IX 17-21	D SPEED 22-27	IN KNOTS 28-33	34-40	41-47	48-55	GE 56	TCTAL 3	ME AI, b 1 N U
N	1.1	3.1	4.1	3.2	1.2	1.0	• • • • • • • •	• • • • • •	•••••	• • • • • • • •	••••••	13.8	10.3
tint	1 - 1	1.8	3.2	2.8	• 2	. 1	. 1					9.3	9.1
'4E	. 9	1.3	.6	• ?	• 2							1.2	6.0
FNF	1.0	1.0	. 3	- 1								7.4	4.8
ı İ	1 - 3	2.2	. 4									4.0	4.4
ESE	.9	1.8	. 4									3.0	5.0
SE I	1.6	1.1	. 6	•2								₹.4	4.8
SSE	1.2	3.3	1.8	7.1	. 4	. 3						4.2	F.5
5	2.8	4.6	4 • 2	5.1	. 8	• 2						17.7	н.я
SSW	٠,	1.4	1.1	.4		.2						4.1	7.3
SW	.4	1.0	• 2	. 3								2.0	, p
WSW	.6	• 8	.6									1.9	4.9
•	.6	1.0	• *									1.9	4.9
PNH	.7	. 4	. 4	.6								2.1	7.1
NW	-1	. 9	. 8	.2	.4	• ?						2.7	10.6
NNW	.7	1 • 3	1.2	2.4	.9	.7						6 • R	11.0
/ARIABLE	• • • • • • • • •	• • • • • • •	• • • • • • •	•••••	•••••		•••••	• • • • • •	•••••	••••••	• • • • • • •	• • • • • • • •	
CALM	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	11111111	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	12.4	111111
TOTALS	15.7	27.1	20.3	17.9	4.2	2.3	. 1					100.0	7.7

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: NOV HOURS(LS1): 06J0-0b0G STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

• • • • • • • • • • • • • • • • • • • •		• • • • • • • •	• • • • • • •	• • • • • • •		D SPEED	IN KNOTS	• • • • • •	• • • • • • • • • • • • • • • • • • • •		• • • • • • • • • • • • • • • • • • • •		•••••
DIRECTION (DEGREES)		4-6	7 - 1 G	11-16	17-21		28-33	34-40	41-47	48-55	GE 56	TCTAL	ME A14 h I 14 U
la .	1.3	2.9	4.2	4.8	1.7	.7	• 1	•••••			•••••	15.7	10.8
NNE	.9	2 • 7	2.6	2 • 1	• 2							8.4	6 • 3
۸E	1.0	. 9	.6	. 4								2.9	5.7
ENE	1 1 - 1	1.1	1.0									3.2	5 • 2
E	1.9	• 9	.9	•2								3.8	4.7
£ 2 E	.9	• 7	• 9									7.4	5.5
SE	.7	1.3	- 8	.6	• 1							3 . 4	6.7
SSE	1.1	4 - 4	2.3	1.3								9.2	6.8
\$	2.9	3.6	4.0	5.9	1.3	. 2						17.9	9.5
SSW	.9	1.2	. 8	• 2	• 2	• 1						3.4	7.2
Sw	.7	.9	. 4									2.0	4.6
WSW	.6	• 7	• 3	• 1								1.7	5.1
•	.6	1.0	• 3									1.9	4.4
WNW	.7	- 4	. 7	. 3								2.1	6.1
NW	. 3	1.0	• 6	. 7	. 4	. 3						3.3	10.7
NNW	.7	1.2	1.7	2.2	•6	• 3						6.7	10.5
VARIABLE	! ! !			•••••	•••••		••••••	• • • • • • •	• • • • • • • •	•••••	• • • • • • •	• • • • • • • • •	*
CALM	11111111	,,,,,,,	///////	,,,,,,,,	,,,,,,,	,,,,,,,	1111111	//////	///////	,,,,,,,	,,,,,,,	11.9	111111
TOTALS	16.1	24+8	22.0	16.9	4 - 6	1.7	.1				•••••	100.0	7.3

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC FROM HOURLY OBSERVATIONS.

STATION NUMBER: 724565 STATION NAME: MCCONNELL AFR KS PERIOD OF RECORD: DIFECTION ! 1 - 3 4-6 7-10 11-16 17-21 22-27 28-33 34-40 41-47 46-55 GE 56 TETAL PEAN IDEGREES) 1 24 1.1 2.1 3.8 7.3 2.6 •6 11.9 . 7 . 2 NNE 1.2 2.6 2.4 NE 1.0 • 3 1.4 t. . 4 ENE 1.9 5.8 ŧ . A - 6 3.8 7 . 2 1.0 ESE . 9 . 8 . 4 3.1 6.7 1.9 SE .6 . 9 - 6 SSE . 9 1.6 3.2 2.2 . 4 6.9 5 2.3 3.3 4.3 20.0 10.9 55 H ٠, 1.7 2.6 1.9 • 6 • 2 . 1 9.9 7.9 • 7 . 1 2.0 6.2 . 3 . 8 . 6 7.2 . 4 2.1 1.0 . 6 3.3 6.6 . 7 **ENB** . 4 - 1 7.1 1. . . 6 1.3 1.1 • 2 9.3 F18234 11.0 VARIABLE CALM 3.R ///// TOTALS 19.0 7.1 2.6 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

.....N . 9 2.0 17.2 12.0 3.2 . 2 6.7 10.9 PINE • 3 ΝE . 3 . 1 2.4 6.8 ENE **.** 1 .6 . 2 .6 1.4 6.5 . 9 Ł • 7 7.4 7.1 ESE . 8 . 6 2.0 1.3 . 4 SE .8 • 7 • l 3.3 7.3 . 7 'SE . 9 2.7 2.4 . 1 7.1 1 d - 4 . 1 20.1 12-4 1 - 3 2.3 1.9 11 - 3 . 8 . 9 - 1 5 . C SW 1.1 2.9 W 5 W . 3 . 6 7.0 . 9 6.4 . 8 . 6 . 8 3.0 100 • 2 • 6 1.3 - 1 . 3 2.6 8.5 NW . 4 1.0 1.0 .6 . 2 3.2 12.7 "IN a 2.3 . 9 . 8 11.4 VERSABLE ! CALM 1.9 ///// TOTALS 33.0 9.6 4.0 • 1 160.0 11.

HOPARS YOCHCIAMID TABGET OF SAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED.

AIR WEATHER SERVICE/MAC

PERIOD OF PECORD: 77-66
MONTH: NOV HOURS(LST): 15-0-1710

WIND SPEED IN KNOTS

DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-27 20-1710 I UFGREIST ! - 15c 1 11.3 2.3 7.4 .8 5.7 1.6 . 4 - 1 15.3 7.3 ٠. . DME -6 . 9 3.6 2.0 . 2 - I . 7 NE . 9 . 9 • 2 2.6 6 . : 2.0 INE 1.2 . 6 5.7 . 3 . 1 Ł . 3 f SE t . ti . 3 1.4 - 3 4.4 SE . 2 551 . 9 1.7 1.9 3.0 . 1 1.4 ς 2.7 5.0 7.4 3 . R . 9 21.2 11.0 3.2 H . 6 556 1.2 2.4 1.2 . 3 - 1 1-25 S . 7 1.0 . 9 . 2 . 1 3.4 4.4 . 9 1. 1.0 . 7 • 3 46 . B • 6 16.00 . 1 . 6 * 5.9 2.1 2+1 . 6 - 1 11.5 tooming and the termination of t 3.6 ///// 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED

STATION NUMBER: 724505 STATION NAME: MCCONNELL AF B KS

PERIOD OF RECORD: 77-86

MONTH: NOV HOURS (LST): 1800-2000

									HUNIH:	•••••	******	,,: 1850-	
FEREES)	1 - 3	4~6	7-10	11-16	WIN 17-21	10 SPEED 22-27	IN KNOTS 28-33	34-40	41-47	48-55	GE 56	TCTAL 3	ME AN WINU
N !	1.9	3.9	5.4	3.8	.9	.4	. 3			••••••	,	16.7	9.5
NNE !	.8	1.0	7.9	1.4	• 3							6.4	8.7
NE !	1.0	1.3	. 3	.1								2 . 8	4.8
ENE !	1-1	1.3	•2									2.7	4.0
E	. 9		1.0									3 . 8	5.4
ESE !	.8	1.9	.6	. 1								3 . 3	5.2
SE !	1.2	1.2	1.7	- 1								4.2	5.8
SSF	2.7	4.4	3.1	2.6	• 2							13.0	7.1
s	2.8	4.7	3.9	4.6	. 7	. 1	- 1					16.8	8.5
ssw	. 3	2.0	. 7	. 1	. 1							3.2	6.0
S W	• 2	.2	• 1	. 1								.7	6.3
WSW	•1	. 1	- 1		. 2							•6	11.4
•		1.1	- 3	. 3	- 1							1.9	7.7
WAW		• 3	• 3	. 1	• 1		. 1					1.0	11 • 3
NW	. 7	•8	1.0	.7								3.1	7.3
RNW	. 9	2.0	1.3	1.3	• 3	• 2						6.0	8.4
ARIAGLE 1	•••••		• • • • • • • •	•••••			*******	•••••	• • • • • • • • • • • • • • • • • • • •	•••••	••••••	• • • • • • • • •	• • • • • •
ALM /	1111111	,,,,,,,,	///////	////////	,,,,,,,	////////	,,,,,,,	//////	///////	,,,,,,,	,,,,,,,,	13.9	111111
OTALS	15.1	28.3	23.0	15.3	3.0	. 8	.6					100.0	6.6

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OLCURNENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED USAFETAC FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR MS

PERIOD OF RECORD: 17-86

					•				MONTH:	NOV	HOURS ILS	F1: 21UC~.	23L E
IPECTION DEGREES)	1-3	4-6	7-10	11-16	wI/ 17-21		IN KNOTS 28-33		41-47	48-55	GE 56	T (TAL	ME A N LINE
и [1.6	2.6	4.0	4.9	1.0	.1	. 3	• • • • • •	• • • • • • • •	•••••	.,	14.4	16,1
NNE !	. 9	2.1	2.6	1.2		- 1						6.8	7.9
NE I	1.3	1.1	1.2	• 3								4.0	6.0
FNE !	.9	1.0	. 8									2.7	5.1
E	1.0	2.9	• 2									4.1	4.4
ESE	.9	.9	. 6									2.3	4.4
SE !	1.0	2.0	1.6	. 3								4.9	6.0
SSE	1.4	4.1	3.9	1 - 7	•2	• 1						11.4	7.4
s	2.8	3.4	4.7	5.9	1.3	. 8						14.9	9.8
ssw	.7	1.0	. 8	. 8								3.2	6.9
SW J	.4	. 4	. 2									1.1	3.6
ws.	-1	. 3										. 4	4.0
	. 8	.6	. 3	• 1		• 1						1.5	'•9
PNH	. 4	. 7	. 3	• 1	. 3		• i					2.0	F.8
Nu j	. 3	1.4	2.1	. 9	-1							4,9	8.3
NNW	• ?	1.2	••	1.2	. 8							4.3	10.6
VARIABLE	•••••	• • • • • • • •					• • • • • • • • •	• • • • • •		• • • • • • •	• • • • • • • • •	•••••	• • • • • • •
CAL"	(1111111)	///////	mmi	///////	1111111	///////	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	//////	,,,,,,,,	///////	(1111111	12.6	111111
TOTALS	14.7	25.R	24.1	17.4	3 • 8	1.2	.4					100.0	7.1

PLACENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER	R: 724505	STATION	NAME:		-				PERIOD MONTH:	OF RECOR	D: 77- HOURS(LS)	-86 (): AL	L
DIPECTION (tofgreas)		4-6	7-10		WIF		IN KNOTS 28-33		41-47	48-55	GE 56	TCTAL	MEAN Winu
ti.	1.2	2.6	4.6	5.5	1.5	. 5	.1	•0	•••••	••••••	•••••	16.0	10.A
PINE	.8	1.6	2.8	2.1	.2	-1	• 0					7.6	8.9
1• E	.7	1.0	.7	.2	. 1							2.7	6.2
ENE	.7	. 9	.6	.1								2.4	5.2
Ł	1.0	1.5	.7	.2								3.4	5 • 2
FSE	.7	1.1	.7	.2								2.7	5.7
S.E.	l ! •9	1.2	1.2	. 3	.0							3.7	6.2
52E	l 1 - 3	3.0	2.7	2.2	. 4	- 1						9.7	0.2
s (l 1 2.4	3.6	4.4	6.0	1.9	.6	• D					18.8	10 - 2
SSW	 •8	1.7	1.6	1.2	. 3	• 2	•0					5.9	8.7
SW) } .5	• 7	.6	. 3	. 1		•0					2.2	6.9
#S#	! ! .3	• 7	.5	.2	•0							1.7	6.4
•	i 1 .7	1.0	. 5	. 3	•0	•0						2 • 4	5.9
969	1	•5	.6	. 3	. 1		•0					1.9	8.1
fe si	 . ;	.9	1.1	. 7	. 3	•1						3.3	9.5
NNW :) .6	1.3	1.5	2.0	. 7	.4						6.5	10.8
VARIABLE	 												
CALM	,,,,,,,,,	11111111	//////	,,,,,,,,,	///////	///////	,,,,,,,,,	1111111	///////	11111111	,,,,,,,	9.0	/////
TOTALS	13.3	23.4	24.8	21.7	5.6	2.0	• 2	• 0				100.0	B . 1
	, , , , , , , , , , , , , , , , , , ,						<i>.</i>						

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
HONTH: DEC HOURS(LST): 0000-0200

									nonth:	OE C	HOURS (ES		0200
DIRECTION (DEGREES)		4-6	7-10	11-16	WIN 17-21	0 SPEED 22-27	IN KNOTS 28-33	34-40	41-47	48-55	GE 56	TGTAL 1	ME AN WINU
N	1.6	3.0	3.9	6.5	1.7	• • • • • • •	• • • • • • • •	•••••	• • • • • • •	•••••	**	16.7	10.3
NNE		1.5	1.9	1.3	•5	- 1						5.9	9.4
NE	.4	1.0	1.6	. 3								3.3	6.9
ENE	.8	1.2	1.0	•2								3.1	5.6
Ε	1 -6	1.1	. 4	. 1								3 . 2	4.3
ESE	.5	1.3		. 1								1.9	4 • 1
SE	.5	1.5	.5	•2								2.8	5.5
SSE	.9	3.0	1.5	1.9	.5							7.8	8.4
s	2.8	4.2	3.8	4.7	1.9	. 5						19.0	9.5
SSW	1.3	2.4	1.9	1.1	• 2							6.9	7.0
sw	.5	1.4	. 8	-1								2.8	5.7
WSW	.2	1.0	• 2									1.4	5 • 1
w	. 3	.9	• 2	-1	. 3							1.8	7.6
HNW	.2	1.1	- 1			. 3						1.7	7.9
NW	-2	1.6	1.1	. 3	• 2							3.4	7.9
NNV	.5	1.4	1.4	3.0	1.0	. 3						7.6	11.4
VARIABLE	; ; • • • • • • • • • • • • • • • • • •						• • • • • • • •	• • • • • •			• • • • • • • •	• • • • • • • • •	
-	! } //////////											,, ,	
	1						.,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,,,		
TOTALS	l 13.0	27.4	20.3	20.0	6.5	1.3						100.0	7.5
• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • •		• • • • • • •		•••••		• • • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86 MONTH: DEC HOURS(LST): 0300-0500 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS WIND SPEED IN KNOTS DIFECTION | 7-10 11-16 17-21 22-27 28-33 34-40 41-47 48-55 GE 56 TCTAL MEAN 1-3 4-6 MIND ı IDEGREES! |N 10.9 3.0 7.8 2.8 19.2 3 • 2 2.2 1.2 1.8 . 9 . 3 5.3 7.8 NNE 1 • 1 1.7 NE • 3 1.0 1.8 . 6 3 - 8 . 9 5.9 FNF . 6 . 9 - 1 2.5 E 1.0 1.1 .6 . 1 2.8 5.1 ESE 1.6 . 5 3.0 4.8 SE .5 1.2 . 3 • 2 2.3 5.3 3 • 7 7.7 SSE . 8 3.7 s 1.2 2 - 3 1.3 SSW 1 - 3 5.5 . 3 1.1 • 3 SW . 8 1.0 . 3 1.7 5.2 **W5W** . 4 4.7 . 8 • 8 . 4 1.9 - 1 0.8 HNW • 1 • 5 • 2 - 1 1.1 2.0 . 5 7.7 • 3 NNW 2.2 10.6 VARIABLE I 8.6 ///// CALM 7. 100.0

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR MEATHER SERVICE/MAC

PERCENTAGE FPEQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
MONTH: DEC HOURS(LST): U600-0800

21% LOW MOUSE		3.4.100			B	•			MONTH:	DEC	HOURS (LS	r): 0600-	0800
		•••••	• • • • • • • •	•••••		ID SPEED	IN KNOTS	• • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
DIPECTION (DEGREES)		9 - 6	7-10	11-16	17-21		28-33		41-47	48-55	GE 56	1CTAL 2	ME AN W I N D
N	1 1.4	3.2	4 • C	10.4	2.2	. 4		•••••	• • • • • • • •	•••••	•••••	21.6	11.3
:NE	• 3	1.2	1.8	.9	• 2							4.4	8 • 9
NE	.2	. 9	1.3	.9		• 2						3.4	9.5
ENE	• 2	1.0	. 9	. 3								2.4	6 • 7
£	.9	1.3	. 3									2.5	4.3
F 5E	9.	- 8	. 6	•2								2.5	5 • 6
SE	1 • 2	1.9	1 - 1	• 1								4.3	5 • 2
SSE	1.4	3.0	3.3	1 - 1	. 3							9.1	7.4
5	2.4	3.2	4.0	3 • 3	1 • 2	. 3						14.4	8.9
5 S W	.4	2 • 6	1.5	1 - 3	. 3							6.1	8.1
Sw	.8	1.1	.5	- 1								2.5	5.3
454	.5	. 4	• 1									1.1	3.9
al .	1.0	1.0	. 9	.4								3.2	6.2
HNW	.6	• 5	. 5		. 1							1.8	5 • 8
NW	.8	1.2	1.4	.4	-1	• 2						4.1	8 - 1
NNW	1.5	- 8	1.9	2.0	.8	. ?						1.2	9.9
VARIABLE	, , , , , , , , , , , , , , , , , , , ,	•••••	• • • • • • •	• • • • • • • •	•••••	•••••		•••••	• • • • • • • •	• • • • • • •	• • • • • • • • •		
	///////////////////////////////////////	11111111	777777		1111111		,,,,,,,,,,	1111111	,,,,,,,,	,,,,,,,,	,,,,,,,,	9.4	111111
	ĺ							,,,,					
TOTALS	14.4 1	24.0	24.2	21.5	5 • 2	1.4						100.0	7.8
			• • • • • • •			• • • • • •	• • • • • • • •	• • • • • •		• • • • • • •	• • • • • • •		• • • • • • • • • • •

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

PEPIOD OF PECORD: 77-86

100.0 9.4

STATION NUMBER: 724505 STATION NAME: MCCONNELL AF B KS

			•						MONTH:	DEC	HOURSILS	7): 0900-	1160
• • • • • • • • • • • • • • • • • • • •	1	• • • • • • • •	• • • • • • • •	•••••	WIN	D SPEED	IN KNOTS	· · · · · · · · · · · · · · · · · · ·	• • • • • • • •	• • • • • • •	•••••	• • • • • • • •	• • • • • • • • • • • • • • • • • • • •
DIPECTION (DEGREES)		4-6	7-10	11-16		22-21			41-47	48-55	GE 56	TCTAL 2	ME AN D I N D
N	.6	3-1	5.6	8.6	2.3	.8	•••••	• • • • • • • •	• • • • • • •	•••••		21.0	11.6
NNE	.2	1 - 4	1.8	2 - 2	• 5	. 3						6.5	10.9
NE	.6	1.2	.9	1.1								3.8	7.3
FNE	.2	- 4	1.3	- 1								2.0	7.5
Ł	.5	1.6	. 8	• 2								3.1	5.8
ESE	.3	.9	. 8	.4								2.4	7.1
SE	.9	• 6	1.6	.5								3.7	6.9
SSE	.2	1-4	3.0	1.6	• 2	. 1						6.6	9.6
s	1.0	2.9	4.0	5.5	2.2	1.0						16.5	11.6
SSW	.8	1.2	1.7	1.4	. 8	. 3					-	6.1	10.2
SW	1.0	- 4	.6	•6	.1							2.8	6.7
WSW	.2	• 5	.8									1.5	6.5
4	.9	1 - 1	.4	• >	• 1							2.7	5.3
WNW	.5	1 - 0	.4	• \$. 1							2.6	7.7
NW	.6	• A	1.1	1.2	. 4							4.1	9.1
NNW	.9	1.2	1.9	3.5	1.5	• 2						9.2	11.4
VARIARLE	,		• • • • • • •		• • • • • • • •			•••••		• • • • • • • •			
	į												
CALM	1 <i>////////</i> 	,,,,,,,	,,,,,,,	////////	,,,,,,,	'''''	1111111	'''''	,,,,,,,	///////	///////	5.4	111111

8.2 2.7

PLRCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

	• • • • • • • •	•••••		• • • • • • • • •			IN KNOTS				•••••	• • • • • • • • •	
DIPECTION ODEGREES)	1 - 3	4-6	7-10	11-16			28-33		41-47	48-55	GE 56	TCTAL 3	ME AN WIND
N .	.4	2.7	5.2	8.8	3.4	.6	.1	• • • • • • •		••••••		21.3	17.6
NNE	• 3	1.3	1.3	2.4	.5	- 1						5.9	11.0
NE	• 3	1.0	1.0	.5	. 1							2.9	7.6
ENE		• 8	. 9	• 2								1.8	7.6
E	-8	.9	. 2									1.8	3 • 6
ESE	.4	• 3	. 3	• 2								1.3	6.3
SE	. 3	• 3	.6	. 4								1.7	8.1
. 322	.6	1.5	1 - 1	2.7	• 5	- 1						6.6	10-4
s !	.5	1.9	4.0	5.9	2.6	1.8	•2					17.0	13.2
SSW	• 3	2.0	3.0	2.0	1.5	. 3						9.2	10.9
Sw	1.4	1 - 1	. 9	1.6	•2							5.2	8.1
WSW !	.5	•5	.6	• 2	.1							2.9	6.7
. !	• 3	1.5	.9	. 1								2.8	6.0
VNW		.9	. 9	.6		• 1						2.5	9.6
Nu !	.9	.9	. 8	2.2	•6	. 2						5.5	10.6
ANN	. 3	1.2	1.2	4.3	1.5	• 3						8.8	12.6
VARIABLE	•••••	•••••	• • • • • • •	• • • • • • • •	•••••	•••••	•••••			•••••	•••••	• • • • • • • •	•••••
CALM .	,,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	///////	(//////	,,,,,,,,	,,,,,,	11111111	,,,,,,,	,,,,,,,	3.7	111111
TOTALS	7.5	18.7	22.7	32.3	11.2	3.7	. 3					100.0	10.6

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND STRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

#IND SPEED IN KNOTS

DIPECTION | 1-3 4-6 7-10 11-16 17-21 22-37 30 77 50 (DEGREES) | WIND N 6.0 8.7 2.5 . 5 2.8 20.8 11.5 NNE .6 1.4 1.9 2.5 1.0 7.4 10.3 NE . 5 1.1 • 5 • 3 2.6 8.0 . 3 FNE 4.1 . 8 2.0 £ 4.3 . 9 . 3 ESE . 3 . 1 1.6 6.0 SE . 8 1.2 . 6 . 3 2.9 5.9 SSE . 5 1.D 1.8 2.0 • 5 . 1 6.0 10.4 S 2.5 2.2 4.7 5.8 2.5 . 8 . 1 18.5 55 ¥ . 8 1.7 2.9 2.6 1.2 9.1 10.2 1.0 6.1 1.0 WSW . 5 2.5 7.5 . 2 . 8 . 3 2.5 • 2 6.7 . 4 MNE • 2 • 6 . 1 . 1 1.5 7.5 1.0 Na . 3 . 9 1.3 . 3 . 1 3.9 9.9 NNW 5.2 VARIABLE CALM 3.0 ///// TOTALS 30.9 . 1 100.0 1.8

DEBBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED STAFFLIAGE FROM HOURLY OBSERVATIONS

ATR WEATHER SERVICE/MAC

STATION NUMBER	R: 724505	MOTTATS	NAME:						MONTH:		40URS(LS	-86 T): 1800-	2000
OIFECTION (DEGRE(S)	1	4-6	7-10		⊯IN 17-21	D SPEED 22-27	IN KNOTS 28-33	34-40	41-47		GE 56	TCTAL %	MEAN WIND
N	1.5	3.8	4.9	5.5	1.4	.5		•••••	•••••	• • • • • • • •	•••••	17.6	10.1
NNE	1-1	2.6	2.5	1.9	.5							8.6	8.5
NE	.9	.6	. 8	.5								2.1	6 • 5
FNE	• 3	1.1	.4									1.8	5 • 5
Ĺ	1.4	1.4	. 3									3 • 1	4 • 2
ESE	.6	1.3	. 8	•2								2.9	5.7
SE	.3	1.9	1.3	• 3								3.9	6.3
32 <i>?</i>	1.9	2 • g	3.2	1.3		• 1						9.4	6.9
S	3.0	3 • 7	4.4	3.9	1.6	. 1						16.7	8.8
SSW	1.3	1.8	1-1	1 - 3	. 3							5.8	7.3
S W	• 3	- 8	.5									1.6	5 • 3
WSW	.6	• 2										.9	2.8
•	.5	. 3	• 3		• 1							1 • 3	6.0
WNW !	•2	.4	د .	•2								1.2	6.8
N¥ I	•2	1.4	. 9	• 1								2.6	6.2
thu	.6	2.0	2.0	3.7	.6							9.1	10.1
VARIABLE		•••••	• • • • • • •	• • • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •		• • • • • • • •	• • • • • • •	• • • • • • • •	•••••	
CALM	111111111	,,,,,,,	//////	,,,,,,,,,	,,,,,,,	///////	,,,,,,,,	1111111	,,,,,,,,	,,,,,,,	,,,,,,,	10.8	/////
TOTALS	14.9	26.7	23.7	19.0	4.6	. 8						100.0	7.2

PERCENTAGE FREJUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

TION NUMBER	: 724505	STATION	NAME:		•				MONTH:		HOURSILS	T1: 2100-	2310
 D1586110N	1-3	4-6	7-10		* I *	D SPEED	IN KNOTS 28-33	.		48-55	GE 56	TCTAL	ME AN
IDEGREES)										40 33	00 30	1	-INU
N [1.4	3.0	5 • 5	4.9	1.8	•••••		• • • • • • •	• • • • • • • •	*******	•••••	16.6	9.7
NNE I	.6	1.6	2.0	1.6	. 3							6.3	8.8
NE	.8	• 6	1.5	.8								3.7	7.4
ENE]	. 4	1.5	.5									2.5	5.1
٤	1 • 2	1.7	.5									3.5	4.7
ESE !	.8	1.0	.6	•2								2.6	5.7
SE !	•2	2.0	1.0	• 1								3.3	5.7
382	1 • 1	1.9	2.4	2.9	-1							8.4	8.7
s	2.8	4 • D	5.6	3.8	1.6	. 4						18.2	9.0
SSW 1	.9	1.8	2.0	1.2	. 3							6.3	7.7
2M]	.6	1.1	.5									2 . 3	4.9
W.S.W	• 3	• 6	. 3	•1								1.4	5.7
.	.4	.9		• 2								1.5	5.4
ENN	.4	•5	. 1	. 1								1.2	5.2
NW	•2	•6	1.0	• 2								2.0	7.2
NNE	.9	2.3	1.5	3.0	1.2							8.8	10 • 3
	•												
VARIABLE 1													
CALM I	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,,,,,,,	///////	////////	///////	//////	///////////////////////////////////////	1111111	///////	///////	,,,,,,,	11.4	111111
TOTALS	13.1	25.4	25.2	19.1	5 • 4	. 4						100.0	7.3

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY ORSERVATIONS

ATICN NUMPER	: 724565	STATION	NAME:						MONTH:		HOURS ILS	-86 T1: AL	L
DIFECTION	1-3	4-6	7-10		# I N	D SPEED	IN KNOTS 28-33			48-55		TCTAL	ME AN
IDFUREES)						•						1	LIND
N į	1.2	3.1	4.7	7.7	2.3	. 3	•0	• • • • • • •			•••••	19.3	11,1
NNE I	•6	1.5	1.9	1.7	.5	- 1						6,3	9.4
34	. 5	• 8	1.2	.7	.0	.0						3.3	7.6
LNE I	.4	.9	٩.	- 1								2.2	6.0
į į	1.0	1.3	. 4	- 1								2.8	4.6
ESE 1	.6	1.0	. 5	• 2	.0							2.3	5.6
SE 1	.6	1.3	. 9	. 3								3.1	6.0
32?	.9	2.3	2.3	1.8	. 4	- 1						7.8	6.5
s	2.3	3 • 3	4.4	4.6	1.9	. 7	•0					17.1	10 - 1
SSW	• •	2.0	1.9	1.5	.6	. 1	•6					7.0	8.8
Sw	.8	.9	.6	.5	.1	••						2.9	6.6
NSW I	.4	• 7	.4	•1									
Í					•0							1.6	5 . R
■ .	.6	• 9	• 5	• 2	- 1							2.2	6.0
ene j	. 3	• 7	. 4	• 2	•0	• 1						1.7	7.5
NW F	.4	1.2	1.1	.8	• 3	• 1						3 • b	8.6
ENG 1	. 7	1.4	1.8	3.5	1.1	•?						8.7	11.2
VAPIAČLE	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •		•••••		• • • • • • • •		• • • • • • • • • • • • • • • • • • • •		• • • • • • •
CALH	,,,,,,,,,	1111111	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,,	,,,,,,	,,,,,,,	,,,,,,,	,,,,,,,	A.0	111111
TOTALS	12.7	23.4	23.8	23.8	7.2	1.6	. 1					100.0	A _ 4

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WIND SFEED FROM HOURLY OBSERVATIONS

AIR MEATHER SERVICE/MAC

PERIOD OF RECORD: 77-86 MONTH: ALL HOURS(LST): STATION NUMBER: 724505 STATION NAME: MCCONNELL AFRIKS ALL WIND SPEED IN KNOTS 21 22-27 28-33 DIPECTION 1 - 3 4-6 34-40 41-47 48-55 GE 56 (DEGPERS) | • IND 3.3 3.7 1.0 •0 11.7 10.1 • 0 **.** A 1.6 1.0 1.2 • 2 • 0 • 0 5.0 e., NNE 1.5 4.0 6.5 NE . 8 1.1 .5 . 1 • C ENE 1.0 1.5 1.0 . 3 • 0 .0 3.8 5.8 5.7 1.4 5.6 € 1.6 2.3 . 3 • 0 .0 5.9 1.4 . 3 3.7 FSE 1.0 1.0 • 0 .0 • 0 SE 1.0 1.9 1.6 . 7 . 1 . 0 • 0 5.3 6.8 < 5 F 1.2 2.8 3.6 2.9 . 6 . I • C 11.1 P.9 5 1.7 3.4 5.2 6.7 2.1 .6 • 0 19.9 10.7 1.7 • 0 9.7 2.4 7.6 Su . 5 • 7 . 7 .5 . 1 • 0 • 0 6.4 ₩S.= . 4 • 6 . 4 • 2 • 0 • D . (1 1.6 1.9 6.4 . 5 . 4 • 2 - 7 • 0 • 0 .0 ¥ 1.5 . 5 . 4 8.0 la fa la . 2 . 1 • 0 • 0 .0 NH . 3 • 7 . 7 - 6 • 2 - 1 • 0 2.6 9.2 NNW .5 1.1 1.3 . 5 . 2 • 0 . 3 5.2 10-1 VARIABLE | CALP 7.9 ///// TOTALS 1.5 . 1 • 0 100.0 8.0

HORAL CEIMATOLOGY BRANCH GRAFETAC ATH REATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SURFACE WIND DIRECTION VERSUS WING SFEED FROM HOURLY ORSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86

MONTH: ALL

CEILINGS 200 TO 1400 FEET WITH VISIBILITIES 1/2 MILE OR MORE

AND/OR

CEILINGS 200 FEET OR MORE WITH VISIBILITIES 1/2 TO 2-1/2 MILES

•••••		• • • • • • •	• • • • • • • •		¥IN	0 SPEE0	IN KNOTS	• • • • • • •	• • • • • • •	· · · · · · · · ·	•••••	• • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
O I PECTION LOC GREESI		4 - t	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	GE 56	TCTAL	ME AN Wlni
N	.8	2.5	6.5	9.4	2.6	. A	. 1	• • • • • • •		•••••		22.8	11.9
NNE	.7	2.1	4.4	3 • 8	. A	- 1	•0					12.0	10.0
ΝE	-7	2.0	2.4	1.1	• 2	•0						5.4	7.9
f NE	. 7	1.8	1.7	. 8	. 1							5.1	7.2
Ĺ	1 • 3	2.7	1.9	. 9	. 1	• 1						6.4	€.7
ESE	.7	1 - 4	1.2	. 4	.0							3.7	6.5
st	.6	1.5	1.5	. 7	. 1		0.					4.2	7.5
€\$€	.5	2.0	2.4	2.2	- 4	- 1	• 0					7.6	9.3
\$. a	1.9	2.8	3.2	1.2	. 3	• C					10.2	10.7
55#	• *	. 7	. 9	. 7	- 4	. 1						3.1	9.6
5# [• 2	. 4	. 3	• 2	•0							1.2	7.0
W5W	- 1	. 3	. 3	. 1	•0							. 9	6 • 7
•	• 3	. 3	. 3	• 2	- 1							1.2	7.2
646	• 1	. 3	. 4	. 3	. 1	.0	• 0					1.3	9.7
Pa Sa	• ?	•5	. 6	. 6	.7	. 1						2.7	10.3
Political	•7	1.0	1.9	2.5	. 8	. 3	• (1					6.8	11.8
VARIABLE		• • • • • • •	• • • • • • • •		• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • •	• • • • • • • •	· · · · · · · ·	•••••		
CVF. 1	 //////////	1111111	///////	,,,,,,,,,	///////	,,,,,,,	////////	,,,,,,,	,,,,,,,,	,,,,,,,,	//////	/ 4.7	/////
ינומר. (ו	9.8	21.0	29.6	27.3	7.0	1.7	• ?					0.001	٠.3

STAL NUMBER OF GRSERVATIONS: SAZZ

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

PART D

CEILING VERSUS VISIBILITY

This summary is a bivariate percentage frequency distribution by classes of ceiling from zero to equal to or greater than 20,000 feet and as a separate class "no ceiling", versus visibility in 16 classes from zero to equal to or greater than 10 miles. Data are derived from hourly observations, and three sets of tables are presented as follows:

- 1. Annual all years and all hours combined
- 2. By month all years and all hours combined
- 3. By month by standard 5-hour groups

Due to the cumulative nature of this presentation, it is possible to determine the percentage frequency of occurrence for any given limit of ceiling or visibility separately, or in combination of ceiling and visibility. The totals progress to the right and downward. Ceiling may be determined independently by reference to totals in the extreme right hand column. Also, visibility may be determined independently by reference to the horizontal row of totals at the bottom of the page. The percentage frequency for which the station was meeting or exceeding any given set of minima may be determined from the figure at the intersection of the appropriate ceiling column and visibility row. Several examples in the use of these tables are shown on pages 2 and 3 below.

U. S. Weather Bureau and Navy stations did not report ceilings within the range 10,000 feet and higher prior to January 1949. Summaries prepared from data for these stations using the earlier period and data subsequent to January 1949 will be modified to limit ceilings to 10,000 feet. Short periods of record prior to 1949 for these stations will be eliminated from the summary. For Air Force stations, the "no ceiling" category includes clear and scattered conditions, and ceilings above 20,000 feet for period through June 1948. Reginning in July 1948 for Air Force stations and January 1949 for USWB and U. S. Navy stations the "no ceiling" category consists of observations with less than 6/10 total sky cover and those cases where total sky cover is 6/10 or more, but not more than 1/2 of the sky cover is opaque.

Beginning in January 1968, METAR stations report visibilities to 6 miles and then greater than 6 miles. Thus, for METAR stations, the category equal to or greater than 10 miles is not printed in the tables, unless the summary was for a period ending before January 1968.

Continued on Reverse Side

EXAMPLES FOR USE OF CEILING VERGUS VISIBILITY TABLES IN THIS TABULATION

CEILING							VIS	1911 IJY 151	AIUIE MI	LESJ						
(FEET)	≥ 10	•≥ 6	≥ 5	≥ 4	≥ 3	≥ 2 %	1	ı	1	21	≥ %	≥ %	≥ %	≥ 5/16	2 %	≥ 0
NO CEILING																
							<u> </u>									\sim
≥ 1800 ≥ 1500					_21.0											92,6
≥ 1200 ≥ 1000																
≥ 900 ≥ 800																
≥ 700 ≥ 600											~					
≥ 500 ≥ 400										97.4						98.1
≥ 300 ≥ 200																l
≥ 100 ≥ o					95.4		96,9			98,3						100,0

- EXAMPLE # 1 Read ceiling values independently of visibility under column at right headed ≥ 0 . For instance, from the table: Ceiling ≥ 1500 feet = 92.6%.

 Ceiling ≥ 500 feet = 98.1%.
- EXAMPLE # 2 Read visibilities independently of ceilings on bottom line opposite ≥ 0 . From the table: Visibility ≥ 3 miles = 95.4%. Visibility ≥ 2 miles = 96.9%. Visibility ≥ 1 mile = 98.3%.
- EXAMPLE # 3 To obtain combinations of ceiling with visibility, read figure at intersection of the two categories; i.e.: Ceiling \geq 1500 feet with visibility \geq 3 miles = 91.0%.

ADDITIONAL EXAMPLES

Values below minimum stated in the table may be obtained by subtracting the value given in the table from 100%.

Thus, to obtain the percentage of observations with ceiling < 1500 feet and/or visibility < 3 miles, subtract the value read from the table at the intersection, which is 91.0, from 100.0. The answer 9.0 is the percentage of observations with ceiling < 1500 feet and/or visibility < 3 miles.

Likewise, the percentage of observations with ceiling < 500 feet and/or visibility < 1 mile is 2.6, obtained by subtracting 97.4 from 100.0.

EXAMPLE # 5 To find the percentage of observations falling within the two categories given in example above, subtract the value read from the table for the first set of limits from the value in the table for the second set of limits. The difference will be the percentage of observations meeting the lower set of limits, but not meeting the higher set of limits.

The value 91.0 read from the table at the intersection of \geq 1500 feet with \geq 3 miles, subtracted from 97.4 read from the table at the intersection of \geq 500 feet with \geq 1 mile is equal to 6.4%. Thus; 6.4 percent of the observations meet the criteria: "ceiling \geq 500 feet with visibility \geq 1 mile, but < 3 miles; or ceiling \geq 500 feet, but < 1500 feet with visibility \geq 1 mile."

Since these tabulations are prepared in several ways including by month, by 3-hour groups it is possible to determine diurnal variations of ceiling and visibility limits as well as probabilities of various ceiling visibility combinations.

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

							NNELL A					PERIOD Month					CO
EILING		• • • • • •			• • • • • • •	• • • • • •	• • • • • •	VISI	BILITY	IN STATE	UTE MIL	ES.	• • • • • • •		• • • • • • •	• • • • • •	
IN		GE	GΕ	GΕ	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	CE
FEET	-	10		5			2 1/2		1 1/2		1 • • • • • •	3/4		1/2		1/4	Q
CEIL	ı	28.6	61.8	62.5	62.7	62.8	63.1	63.1	63,2	63.3	63.4	63.4	63.4	63.4	63.4	63.4	63.5
2000			65.7	66.8	67.1	67.4	67.7	67.8	68.0	68.1	68.2	68.2	68.2	68.2	68+2	68.2	68.3
1800			65.9	67.0	67.3	67.6	68.0	68.1	68.2	68.3	68.4	68.4	68 - 4	68.4	68.4	68.4	66.5
1600			66.D	67.1	67.4	67.7	68-1	68.2	68.3	68.4	68 • 5	68.5	68.5	68.5	68.5	68.5	68.6
1400			66.0	67.1	67.4	67.7	68.1	68.2	68.3	68.4	68.5	68.5	68 - 5	68.5	68.5	68.5	68.6
1200	0 1	30.4	66.2	67.3	67.6	68.0	68.3	68.4	68.5	68.6	68.7	68.7	68 • 7	68.7	68.7	68.7	66.8
1000			68.1	69.1	69.5	69.8	70.1	70.2	70.3	70.4	70.5	70.5	70.5	70.5	70.5	70.5	70.6
		31.8	68.4	69.5	69.8	70.1	70.4	70.5	70.6	70.8	70.9	70.9	70.9	70.9	70.9	70.9	71.0
		31.9	69.2	70.3	7 C - 6	71.0	71.3	71.4	71.5	71.6	71.9	71.9	71.9	71.9	71.9	71.9	72.U
700			69.7	70.8	71.1	71.4	71.7	71.8	71.9	72.0	72.4	12.4	72.4	72.4	72.4	72.4	72.5
600	01	32.6	70.6	71.9	72.3	72.6	72.9	73.0	73.1	73.2	73.5	73.5	73.5	73.5	73.5	73.5	73.7
500	0	33.0	72.2	73.7	74.0	74.3	74.6	74.7	74.8	74.9	75.3	75.3	75.3	75.3	75.3	75.3	75.4
		33.2	73.1	74.7	75.1	75.4	75 • 7	75 • 8	75.9	76.0	76.3	76.3	76.3	76.3	76.3	76.3	76.5
		33.3	73.9	75.5	75.8	76.1	76.5	76.6	76.7	76.8	77 - 1	77.1	77.1	77.1	77.1	77.1	77.2
		33.4	74.2	75.8	76.1	76.5	76.8	76.9	77.0	77.1	77.4	77.4	77.4	77.4	77.4	77.4	77.5
300	0 I	33.8	75.6	77.2	77.5	78.0	78.3	78.4	78.5	78.6	78.9	78.9	78.9	78.9	78.9	78.9	79•U
250	0.1	34.0	76.8	78.4	79.0	79.5	79.8	79.9	80.0	80.1	80.4	80.4	80.4	80.4	80.4	80.4	80.5
200	σį	34.3	77.4	79.1	80.3	80.8	81.1	81.3	81.4	81.6	81.9	81.9	81.9	81.9	91.9	81.9	82.0
180	01	34.3	77.8	79.6	8 C.9	61.3	81.6	81.8	81.9	82.2	82.5	82.5	B2.5	82.5	A2.5	82.5	82.6
		34.4	78.8	80.9	82.3	83.0	83.3	83.5	83.7	83.9	84.2	84.2	84.2	84.2	84.2	84.2	84.3
120	0 1	34.4	79.6	81.7	B 3 • 4	84.5	84.8	85.3	85.9	86.1	86.6	86.6	86.6	86.6	86.6	86.6	86.7
100	σI	34.4	80.6	82.8	84.7	85.9	86.5	87.0	87.7	88.1	88.6	88.6	88.6	88.6	88.6	88.6	88.7
		54.4	81.2	83.5	85.7	86.9	87.4	88.1	88.8	89.2	89 • B	89.8	89.8	89.8	89.8	80.8	69.9
		34.4	81.5	84.4	86.7	87.8	88.7	89.4	90.1	90.5	91.1	91.1	91.1	91.1	91.1	91.1	91.2
		34.4	91.6	84.7	87.0	88.3	89.1	89.8	90.6	91.1	91.6	91.6	91.6	91.6	91.6	91.6	91.7
. 6ú	D I	34.4	82.0	85.5	88.4	90.0	90.9	91.6	92.5	92.9	93.4	93.4	93.4	93.4	93.4	93.4	93.5
		34.4	82.0	85.7	89.0	91.0	91.9	92.8	93.7	94.1	94.7	94.7	94.7	94.7	94.7	94.7	94.8
		34.4	82.6	86.2	89.8	92.2	93.1	94.0	94.9	95.4	96.1	96.2	96 • 2	96.3	96.3	96.3	96.5
		34.4	82.6	86.3	89.9	92.3	93.3	94.3	95.4	96.0	97.3	97.5	97.5	97.6	97.6	97.6	97.7
		34.4	82.6	86.3	89.9	92.3	93.3	94.3	95.4	96.1	97.8	98.5	98.5	99.0	99.1	99.1	99.2
10	0 (34.4	82.6	86.3	89.9	92.3	93.3	94.3	95.4	96.1	98.1	98.7	98.7	99.4	99.5	99.8	100.0
-	0 1	34.4	82.6	86.3	89.9	92.3	93.3	94.3	95.4	96.1	98.1	98.7	98.7	99.4	99.5	99.8	inn•n

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

SIA	TION N	UMBER:	724505	STATIO	ON NAME:	мссо	NNELL A	FB KS				PERIOD	OF RECO		-86 (LST); (J300-05	ac
	LING	• • • • • •	• • • • • • •			• • • • •	• • • • • • •			IN STATE			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
	N I	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GĹ	GE	GE	GΕ	LΕ
	ËT İ	10	6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	Ü
																•	
NO	CEIL 1	28.7	59.9	60.3	6 C . 8	61.1	61.1	61.2	61.5	61.5	61.5	61.6	61.6	61.6	61.6	61.7	61.9
	200001		63.2	64.2	64.7	65.1	65.1	65.3	65.6	65.6	65.6	65.7	65.7	65.7	65.7	65.8	66.0
	180001		63.5	64.5	65.1	65.4	65.4	65.6	65.9	65.9	65.9	66.0	66 . U	66.0	66.0	66.1	66.3
	160001		63.7	64.6	65.2	65.5	65.5	65.7	66.0	66.0	66.0	66.1	66 • 1	66.1	66.1	66.2	66.5
	140001		63.9	64.8	65.4	65.7	65.7	65.9	66.2	66.2	66-2	66.3	66.3	66.3	66.3	66.5	66.7
ÜΕ	120001	29. H	64.D	64.9	65.5	65.8	65.8	66.0	66.3	66 • 3	66.3	66.5	66.5	66.5	66.5	66.6	66.8
		10.0									. 7 .						
	100001		64.9	66.6	66.6	66.9	66.9 66.9	67.1 67.1	67.4 67.4	67.4 67.4	67.4 67.4	67.5 67.5	67.5	67.5	67.5 67.5	67.6 67.6	67.8 67.8
υE -SE	90001		64 • 9 66 • 2	66.D 67.3	66.6 67.8	66.9 68.2	68.2	68.4	68.7	68.7	68.7	68.8	67.5 68.8	67.5 68.8	68.8	69.0	69.2
úΕ	ומפחו		66.7	67.7	68.5	68.8	68.8	69.0	69.4	69.4	69.4	69.5	69.5	69.5	69.5	69.7	64.9
GE	60001		67.5	68.6	69.5	69.8	69.9	70.1	70.4	70.4	70.4	70.5	70.5	70.5	70.5	70.8	71.0
υţ	01.001	30.7	01.5	00.0	4,43	0780	0,,,	74.1	10.4	70.4	10.4	10.3	70.5	10.5	,,,,	10.0	110
G.E	scool	21 1	68 • 8	70.0	70.9	71.2	71.3	71.6	71.9	71.9	71.9	72.0	72.0	72.0	72.0	72.3	72.5
GE	45001		69.9	71.1	72.2	72.5	72.7	73.0	73.3	73.3	73.3	73.4	73.4	73.4	73.4	73.7	73.9
5 E	40001		70.5	71.8	72.9	73.2	73.4	73.8	74.1	74.1	74.1	74.2	74.2	74.2	74.2	74.4	14.6
6 E	35001		71.0	72.6	73.7	74.0	74.2	74.5	74.8	74 - 8	74.8	74.9	74.9	74.9	74.9	75.2	75.4
5€	30001		72.8	74.4	75.5	76.0	76.2	76.6	76.9	76.9	76.9	77.0	11.0	77.0	77.0	77.2	77.4
											-						
G F	25001	33.3	73.5	75.4	76.9	77.7	78.0	78.4	78.8	78.8	78.8	78.9	78.9	78.9	78.9	79.1	79.4
ä€	ן סטיי ג		74.6	76.6	78.3	79.1	79.4	79.8	80.3	80.3	80.3	80.4	80.4	80.4	80.4	60.6	86.9
6 E	19001		74.8	76.8	78.5	79.4	79.6	80.0	80.5	86.5	80.5	80.6	80.6	80.6	80.6	80.9	81.1
GΕ	1500		76.0	78.5	8 L . 2	81.2	81.4	81.8	82.4	B2-4	82.4	82.5	82.5	82.5	82.5	82.7	82.9
6 €	12001	33.9	77.0	79.5	81.3	82.3	82.5	83.1	83.9	83.9	43.9	84.0	84.0	84.0	84.D	84.2	84.4
66	10001		78.5	81.2	83.3	84.5	84.8	85.9	86.7	86.7	86.8	87.0	87.0	87-1	87.1	87.3	87.5
GE GE		33.9	79.1	82.0	84.2	85.5	85 - 8	86.9	87.6	87.6	. 7 . 7	88.0	88.0	88.1	88.1	88.3	88.5
6£		33.9 33.9	79.5 79.6	82.5 82.7	85.3 85.7	86.6 87.0	86.9 87.3	88.D 88.4	88.8 89.4	88.9	7.D 89.6	89.2 89.8	89.2 89.8	89.4 89.9	89.4 89.9	89.6 90.1	89.8 90.3
GΕ		33.9	80.3	83.5	86.9	89.1	89.5	90.5	91.6	91.7	91.9	92.2	92.2	92.3	92.3	92.5	92.7
O.E.	6401	23.7	80.3	03.5	56.7	89.1	07.3	70.3	71.0	71.1	71.7	72.42	72.2	72.3	*2.3	72.5	42.1
1, 1	5001	33.9	80.6	84.6	87.4	90.0	98.4	91.8	92.9	93.0	93.3	93.5	93.5	93.7	93.7	93.9	94.1
νĒ		33.9	80.9	84.4	87.8	91.1	91.8	93.2	94.4	94.5	95.2	95.7	95.8	96.0	96.0	96.2	96.5
SE		33.9	80.9	84.5	86.0	91.2	92.0	93.7	94.8	95.1	96.3	97.8	97.1	97.3	97.3	97.5	96.0
ı F		33.9	80.9	84.5	88.0	91.2	92.0	93.7	94.8	95.2	96.7	97.3	97.4	98.1	98.1	98.3	96.7
4.€		33.9	80.9	84.5	88.D	91.2	92.0	93.7	94.8	95.3	96.8	97.5	97.6	98.4	98.4	98.9	99.6
	•																
ΒF	01	33.9	80.9	84.5	88.0	91.2	92.0	93.7	94.8	95.3	97.0	97.7	97.8	98.6	98.6	99.1	100.0
		• • • • • •		• • • • • •													• • • • • • • • • • • • • • • • • • • •

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

TAT	ION N	UMBER:	724505	ITATE			NNELL AI					MONTH		HOURS	(LST):		
	ING	•••••	• • • • • • • •	• • • • • • •	• • • • • • • •	•••••	• • • • • • •		BILITY				•••••	• • • • • • •	• • • • • • •	• • • • • • •	•••••
FEE	ı I		φ£ 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	G E 5 / 8	G€ 1/2	GE 5/16	G€ 1/4	6€ U
٠	••••	• • • • • •	•••••	• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • •		• • • • • • •	• • • • • • •	• • • • • •		• • • • • • •	• • • • • •	• • • • • •	• • • • • • •
0 0	ETL I	25.1	54.4	54.7	55.6	55.7	55 • 8	55.8	55.8	55.9	55.9	56.0	56.0	56.2	56.2	56.2	56.6
	aroo!		59.4	59.9	60.8	60.9	61.0	61.0	61.0	61.1	61 - 1	61.2	61.2	61.4	61.4	61.4	61.7
	80001		59.6	60.1	61.0	61-1	61.2	61.2	61.2	61.3	61.3	61.4	61 4	61.6	61.6	61.6	61.9
	Pubul		59.6	60.1	61.0	61.1	61.2	61.2	61.2	61.3	61.3	61.4	61.4	61.6	61.6	61.6	61.9
	4000 I		60.0	60.5	61.4	61.5	61.6	51.6	61.6	61.7	61.7	61.8	61.8	62.0	62.0	62.0	62.4
£ }	2000	27.1	60.3	60.9	61.7	61.8	61.9	61.9	61.9	62.0	62.0	62.2	62.2	62.4	62.4	62.4	62.7
F 1	00001	28.3	62.9	63.5	64.4	64.5	64.6	64.6	64.6	64.7	64.7	64.8	64 - 8	65.1	65.1	65.1	65.4
	90001		62.9	63.5	64.4	64.5	64.6	64.6	64.6	64.7	64.7	64.8	64.8	65.1	65.1	65.1	65.4
	80001		65.3	66.1	67.0	67.1	67.2	67.2	67.2	67.3	67.3	67.4	67.4	67.6	67.6	67.6	68.0
	7000		65.4	66.3	67.2	67.3	67.4	67.4	67.4	67.5	67.5	67.6	67.6	67.8	67.8	67.8	66.2
ŧ.	60001	29.9	66.3	67.4	68.3	68.4	68.5	68.5	68.5	68.6	68.6	68.7	68.7	68.9	68.9	68.9	69.2
F	50001	30.5	67.6	68.7	69.6	69.8	69.9	69.9	69.9	70.0	70.0	70.1	70.1	70.3	70.3	70.3	76.6
	4500	30.9	69.0	70.3	71.3	71.5	71.6	71.6	71.6	71.7	71.7	71.8	71.8	72.0	72.0	72.0	72.4
Ε	40001	31.2	69.8	71.1	72.0	72.3	72.4	72.4	72.4	72.5	72.5	72.6	72.6	72.8	72.8	72.8	73.1
Ŀ	35001	31.4	70.5	71.9	72.9	73.1	73.2	73.2	73.2	73.3	73.3	73.4	73.4	73.7	73.7	73.7	74.0
F	30001	31.6	71.7	73.3	74.4	74.6	74.7	74.7	74.7	74.8	74.8	74.9	74.9	75.2	75.2	75.2	75.5
E	2:001	32.4	73.2	75.1	76.1	76.5	76.7	76.8	76.9	77.1	77.1	77.2	77.2	77.4	77.4	77.4	77.7
	20001		74.6	76.5	77.5	78.0	78.2	78.3	78.4	78.7	78.7	78.8	78.8	79.0	79.0	79.0	79.4
F	10001	33.3	75.2	77.3	78.4	78.8	79.0	79.1	79.2	79.6	79.6	79.7	79.7	79.9	79.9	79.9	8C-2
ŗ	15001	33.4	76.0	78.4	79.6	80.1	80.3	80_4	80.6	81.1	81.2	81.3	81.3	81.5	81.5	81.5	81.8
ŧ	12001	33.5	76 • 8	19.2	8 G .6	81.2	81.5	81.8	82.2	82.6	82.7	82.8	82 - 8	83.0	83.0	83.0	83.3
E	iraci	33.7	77.5	80.1	81.7	82.3	82.6	82.9	83.2	83.7	84.1	89.2	84.2	84.4	84.4	84.4	84.7
Ε		33.7	78.0	80.6	82.4	82.9	83.2	83.7	84.0	84.4	84.8	84.9	84.9	85.2	85.2	o5.2	85.5
E	P001	33.7	78.5	81.5	83.3	83.9	84.2	84 . 6	84.9	85.4	85.9	86.0	86.0	86.2	86.2	86.2	86.6
F	700	53.7	79.0	82.7	8 4 . 8	86.0	86.3	86.8	87.1	87.5	88.1	88.2	88.2	88.4	8 Fa. 4	88.4	86.7
	6001	33.7	79.4	83.3	85.8	88.0	88.3	88.9	89.5	89.9	90.5	90.6	90.6	90.9	90.9	90.9	91.2
1	5001	33.7	79.4	83.4	86.2	88.6	89.0	90.D	90.6	91.3	92.0	92.3	92.3	92.5	92.5	92.5	92.8
Ē	4001	33.7	79.6	83.7	86.5	89.8	90.4	91.9	92.8	93.5	94.3	94.5	94.5	94.7	94.7	94.7	95.1
E.	*00 l	33.7	79.7	83.9	86.7	90.0	90.9	92.7	93.7	94.6	95.7	96.2	96.3	96.7	96.7	96.7	97.0
f	200	33.7	79.7	83.9	86.7	90.0	90.9	92.9	94.0	95.3	96.6	97.2	97.3	97.7	97.7	97.8	98.3
F	1001	33 • 7	79.7	83.9	86.7	90.0	90.9	92.9	94.0	95.3	96.8	97.5	97.7	98.2	98.4	98.6	99.5
E	n i	33.7	79.7	83.9	86.7	90.0	90.9	92.9	94.0	95.3	96.8	97.5	97.7	98.2	98.4	98.6	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

					ON NAME:							PERIOD MONTH					
	L ING	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	•••••			BILITY				• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
	in I	GE	GE	GE	GE	GE	GE	GE	GE	GE	GΕ	GE	GE	G E	GΕ	GE	GE
	ĒT İ		6	5	ŭ.,		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	υ
	-		-												•••••	-	
										•••							
NO	CEIL	25.9	54.3	55.2	55.4	55.6	55.6	56.0	56.0	56.0	56.0	56.1	56.1	56.1	56 - 1	56 • 2	56.5
GΕ	200001	28.1	60.3	61.2	61.4	61.6	61.6	62.0	62.0	62.0	62 • D	62.2	62.2	62.3	62.3	62.4	64.7
	180001		60.4	61.3	61.5	61.7	61.7	62.2	62.2	62.2	62.2	62.3	62.3	62.4	62.4	62.5	62.8
	160001		60.5	61.4	61.0	61.8	61.8	62.3	62.3	62.3	62.3	62.4	62.4	62.5	62.5	62.6	62.9
GE	140001	28.6	61.1	61.9	62.2	62.4	62.4	62.8	62.8	62.8	62.8	62.9	62.9	63.0	63.0	63.1	63.4
GE	12000	28.8	61-6	62.5	62.7	62.9	62.9	63.3	63.3	63.3	63.3	63	63.4	63.5	63.5	63.7	64.0
GE	100001	30.2	63.8	64.6	64.8	65.1	65.1	65.5	65.5	65.5	65.5	65.6	65.6	65.7	65.7	65.8	66.1
Ģ€	90001	30.2	63.8	64.6	64.8	65 • Î	65.1	65.5	65.5	65.5	65.5	65.6	65.6	65.7	65.7	65.8	66.1
GE	80001	31.2	65.8	66.9	67.1	67.3	67.3	67.7	67.7	67.7	67.7	67.8	67.8	68.0	68.0	68.1	66.4
GE	1001	31.7	66.5	67.5	67.7	68.0	68.D	68.4	68.4	68.4	68.4	68.5	68.5	68.6	68.6	68.7	69.0
GE	60001	32.2	67.3	68.5	69.0	69.2	69.2	69.7	69.8	69.8	69.8	70.D	70.0	70.1	70.1	70.2	70.5
GF	Scool		69.0	70.5	71.1	71.3	71.3	71.7	71.8	71.8	71.8	72.0	72.0	72.2	72.2	72.3	12.6
υE	4500		69.0	70.5	71.1	71.3	71.3	71.7	71.8	71.8	71.8	72.0	72.0	72.2	72.2	12.3	72.6
G€	4000		70.2	71.8	72.5	72.7	72.7	73.1	73.2	73.2	73.2	73.4	73.4	73.5	73.5	73.7	74.0
GE	3500		70.9	72.6	73.2	73.5	73.5	74.0	74.1	74.1	74.1	74.3	74.3	74.4	74.4	74.5	74.8
GE	30001	33.3	71.2	73.1	74.0	74.4	74.4	74.8	74.9	74.9	75.1	75.3	75.3	75.4	75.4	75.5	75.8
										_	_		_				
υE	2500		72.3	74.2	75.1	75.5	75.5	75.9	76.3	76.3	76.5	76.7	76.7	76 - 8	76.8	76.9	77.2 76.5
GE	1800		73.1 73.7	75.2 75.8	76.0 76.7	76.5 77.1	76.5 77.1	77.1 77.7	77.6 78.4	77.6 78.4	77.7 78.5	78.0 78.7	78.0 78.7	78.1 78.8	78 - 1 78 - 8	78.2 78.9	19.2
6 E	15001		74.2	76.7	78.3	78.7	78.7	79.4	80.2	80.3	80.5	80.9	80.9	81.0	81.0	81.1	81.4
GE	12001		75.3	77.7	79.5	80.1	80.1	81.1	82.2	82.3	82.5	82.8	82.8	82.9	82.9	63.0	83.3
υť	17001	34.1	13.3	,,,,	17.5	90.1	80.1	01.1	02.4	02.5	02.5	02.00	02.0	95.7	02.07	03.0	6363
GΕ	10001	34.7	75.5	78 - 3	86.4	81.3	81.3	82.3	83.4	63.7	84.3	84.7	84.7	84.8	84.8	84.9	85.3
GE		34 - 7	75.8	78.8	81.0	82.3	82.4	83.5	84.8	85.1	85.7	86.1	86.3	86.5	86.5	86.6	86.9
GE	RGO	34.7	76 - 1	79.6	82.0	83.4	83.5	84.7	86.3	86.7	87.5	88.0	88.2	88.3	88.3	88.4	86.7
GE	7001	34.7	76.5	80.3	82.9	84.9	85.3	86.6	88.4	88.8	89.8	90.2	90.4	90.5	90.5	90.6	91.0
GE	1009	34.7	76.6	80.9	83.8	85.9	86.5	87.7	89.6	90.1	91.2	91.6	91.8	91.9	91.9	92.0	92.4
GĒ		34.7	76 - 6	80.9	83.8	86.1	86.8	88.4	90.4	91.0	92.0	92.6	92.8	92.9	92.9	93.0	93.4
GE		34.7	76.8	81.1	84.1	86.9	87.5	89.5	92.0	92.8	93.9	94.4	94.6	94.7	94.7	94.8	95.3
GE		34.7	76.8	81.1	84.2	87.1	87.7	89.8	92.5	93.4	95 • 2	95.9	96.1	96.5	96.5	96.6	97.0
GE		34.7	76.8	81.1	84.2	87.1	87.7	89.8	92.6	93.8	95.7	96.8	97.0	97.8	98.0	98.1	98.6
G€	1001	34.7	76.8	81.1	84.2	87.1	87.7	89.8	92.6	93.8	95.7	96 • B	97.0	98.1	98.2	98.5	99.4
											05 -					0.0	100.0
GE	01	34.7	76 • 8	81.1	84.2	87.1	87.7	89.8	92.6	93.8	95.7	96.8	97.0	98.1	98.3	78.6	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

5.7	ATION N	IUMALR:	724505	STATI	ON NAME:	MCCO	NNELL A	Fg KS				DE PIOD Honth		ORD: 77 HOURS	-86 (LST):	1200-14	00
	IL ING	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •			IN STATE			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	•••••
		GΕ	GE	GE	GE	GΕ	GE	GE	GE	GE	6E	GE	G£	GE	GE	GE	6E
	ET I		6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	0
• •	• • • • • •	• • • • • •	• • • • • • • •	••••	• • • • • • • •		• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •		•••••
N 0	CETL 1	25.6	54.0	54.5	54.5	54.6	54.6	54.7	54.8	54.8	54 • 8	54.8	54.8	54.8	54.8	54.8	54.8
ΰE	200001	28.6	61.8	62.6	62.7	62.9	62.9	63.1	63.2	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
68	180001	28.7	62.0	62 - 8	62.9	63.1	63.1	63.3	63.4	63.5	63.5	63.5	63.5	63.5	63.5	63.5	63.5
	10000		62.3	63.D	62.1	63.3	63.3	63.5	63.7	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
	140001		63.0	63.8	63.9	64.1	64.1	64.3	64.4	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5
3 €	120001	29.5	63.8	64.5	64.6	64.8	64.8	65.1	65.2	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3
۵E	100001	30.9	66.2	67.0	67.1	67.3	67.3	67.5	67.6	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7
	90001		66.6	67.3	67.4	67-6	67.6	67.8	68.U	68.1	68.1	69.1	68.1	68.1	68.1	68.1	66.1
GE	aruol		68.1	68.8	68.9	69.5	69.5	69.7	69.8	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9
υE	70001		68.7	69.5	69.6	70.1	70.1	70.3	70.4	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5
G.E	euna l	32.7	69.6	70.3	7 C .4	71.0	11.0	71.2	71.3	71.4	71.5	11.5	71.5	71.5	71.5	71.5	71.5
٥E	50001	32.8	70.5	71.5	71.6	72.2	72.2	72.4	72.5	12.6	72.7	72.7	72.7	72.7	72.7	12.7	72.7
C E	4500		71.0	72.D	72.2	72.7	72.7	72.9	73.0	73.1	73.2	73.2	73.2	73.2	73.2	73.2	73.2
ĢΕ	4000		71.8	73.7	73.9	74.4	74.4	74.6	74.8	74.9	75.1	75.1	75 - 1	75.2	75.2	75.2	75.2
GΕ	3500		72.3	74 - 1	74.3	74.8	74.8	75.1	75.3	75.4	75.5	75.5	75.5	75.6	75.6	75.6	75.6
ĿΕ	3000	34.0	73.0	75 - 1	75.5	76.2	76.2	76.5	76.7	76.8	76.9	76.9	76.9	77.0	77.0	77.0	77.0
GE	25001	34.7	74.6	76.9	77.3	78.3	78.3	78.5	78.7	78.8	78.9	78.9	78.9	79.1	79.1	79.1	79.1
GΕ	2000		75.7	78 • 3	78.8	79.8	79.8	80 - 1	80.4	80.5	80.6	80.6	80.6	80.9	80.9	80.9	86.9
GΕ	1800		76 - 1	78.8	79.4	80.3	80.3	80.6	81.0	81.1	81.2	81.2	81.2	81.4	01.4	81.4	81.4
G.E	15001		77.4	80.1	81.1	82.0	82.0	82.5	83.0	83.1	83.2	83.4	83.4	83.7	A3.7	83.7	83.7
ĢΕ	12001	35.6	78.4	81.4	B 3 • 2	84.3	84.3	85.1	85.7	85.9	86.1	86.3	86.5	86.6	86.6	86.6	66.6
G E	10001		79.9	83.0	85.1	86.5	86.5	87.7	88.4	88.6	88.9	89.6	89.6	89.8	89.8	8 • • 6	84.8
6 E		35.6	80.4	83.5	85.8	87.4	87.4	80.8	89.5	69.7	90.0	90.6	90.6	90.9	90.9	¥().9	96.9
GE		35.6	80.6	84.1	96.6	88.3	88.3	89.8	90.8	91.0	91.3	91.9	91.9	92.2	92.2	92.2	92.2
ĢΕ		35.6	80.8	84.4	87.2	89.4	89.4	91.1	92.0	92.4	92.9	93.5	93.5	93.8	93.8	93.g	93.8
υ€	6001	35.6	81.0	84.8	86.0	90.3	90.3	92.2	93.1	93.8	94.4	95.2	95.2	95.4	95.4	95.4	95.5
GΕ		35.6	81.1	84.9	86.2	91.0	91.0	93.0	94.2	95.2	96.0	96.8	96.8	97.0	97.0	97.0	97.1
6.5		35.6	81.1	84.9	88.3	91.2	91.2	93.3	94.6	95.6	96.5	97.2	97.2	97.4	97.4	97.4	97.5
UE		35.6	81.1	84.9	88.3	91.2	91.2	93.8	95.3	96.3	97.4	98.3	98.3	98.6	98.6	98.6	98.7
UΕ		35.6	81.1	84.9	98.3	91.2	91.2	93.8	95.3	96.3	97.5	98.5	98.6	99.5	99.5	99.5	99.7
G F	1001	35.6	81.1	84.9	88.3	91.2	91.2	93.8	95.3	96.3	97.5	98.5	98.6	99.6	99.6	99.7	95.9
C.E	01	35.6	81.1	84.9	88.3	91.2	91.2	93.8	95.3	96.3	97.5	98.5	98.6	99.6	99.6	99.7	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
HONTH: JAN HOURS(LST): 1500-1700 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS ILING VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 G£ GE GE 1/4 5/8 1/2 5/16 56.9 57.1 57.3 57.4 57.5 57.5 57.5 57.5 57.5 57.5 57.5 57.5 57.5 57.5 CE 200001 31.2 66.0 67.0 67.0 67.0 67.7 67.0 67.0 67.0 18000| 31.2 16000| 31.2 66.5 66.7 66.8 67.0 67.4 67.5 67.7 67.7 67.7 67.7 67.7 67.7 67.7 67.7 67.0 67.2 67.6 68.0 68.0 68.0 68.0 68.0 68.0 68.0 68.0 68.0 GE 14C001 31.2 67.0 67.3 67.5 68.0 68.1 68.3 68.3 68.3 68.3 68.3 68.3 68.3 68.3 68.3 66.3 12000| 31.4 68.5 68.7 68.7 68.7 GE 10000| 33.1 72.4 72.6 74.0 70.3 71.1 71.5 71.9 72.0 72.3 72.3 72.3 72.4 72.4 72.4 72.4 9000| 33.1 8000| 33.7 70.4 71.8 71.2 71.6 72.2 73.5 72.4 73.8 72.4 72.5 73.9 72.5 73.9 72.6 74.0 72.6 74.0 72.6 74.0 72.6 72.6 74.0 72.0 73.4 GE 70001 33.8 74.5 74.5 74.5 74.5 74.5 74.5 74.8 60001 33.9 72.7 73.7 74.1 74.5 74.6 74.8 74.9 74.9 75.1 75.1 75.1 75.1 75.1 75.1 5000| 34.3 4500| 34.6 4000| 34.7 75.5 75.8 76.7 75.6 75.9 76.8 76.0 76.3 77.3 76.0 76.3 77.3 76.0 76.3 77.3 76.0 76.3 77.3 76.0 76.3 71.3 73.7 74.0 74.6 74.9 75.1 75.4 75.8 75.8 75.9 76.0 76.2 76.3 77.3 76.1 77.0 76.1 77.1 76.2 77.2 GE 74.3 GE 75.7 76.2 78.D 78.1 3500 | 34.8 74.8 76.3 77.4 77.5 77.7 77.8 78.1 78.1 78.1 78.1 GE 76.9 78.0 76.1 81.0 83.0 83.8 81.0 83.0 83.8 85.7 25001 35.7 80.4 82.2 82.9 80.6 82.5 80.8 62.7 83.4 80.9 83.0 83.8 GE 80.3 80.9 81.0 20001 35.9 18001 36.2 78.6 79.2 81.0 82.8 83.5 82.9 83.7 83.0 83.8 GE 80.4 82.0 83.0 83.2 GΕ 81.1 82.7 83.8 GE 15001 36.3 80.8 82.8 83.3 85.3 65.4 85.5 85.7 85.8 85.8 85.8 85.8 87.7 87.8 GE 12001 36.3 81.3 84.1 84.6 86.1 86.8 87.0 87.2 87.5 87.8 90.2 91.1 91.7 90.8 91.7 92.6 10001 36.3 85.8 86.0 88.4 68.9 89.5 90.0 90.0 90.9 GE 82.5 86.8 86.6 89.1 90.5 90.8 90.9 90.9 90.9 90.9 ĞĒ 82.6 91.4 91.7 91.8 91.6 91.8 91.8 6 E ADD 1 36.3 82.6 82.6 86.0 87.3 89.2 89.5 90.3 91.3 87.6 93.9 93.9 700 | 36.3 90.0 90.2 91.3 GE 86.1 95.1 GE 6001 36.3 82.6 8 7 .B 90.2 90.4 91.6 92.9 93.5 94.3 94.7 95.1 95.1 95.1 500| 36.3 400| 36.3 88.2 89.0 89.0 91.0 92.0 96.0 97.8 96.6 98.4 98.5 96.6 98.4 96.9 98.7 96.9 82.6 82.7 86.7 92.3 93.3 95.2 95.3 96 • 8 96 • 9 98.7 98.7 98.7 6 E 91.8 300 | 36.3 82.7 86.7 91.8 92.0 98.0 98.5 99.0 99.0 99.0 99.0 GE 200 | 36.3 82.7 86.7 89.0 91.8 92.0 93.3 95.3 97.0 98.2 98.8 98.8 99.4 99.7 99.7 99.7 82.7 86.7 92.0 99.7 99.8 100.0 GF 01 36.3 82.7 86.7 89.0 91.8 93.3 05.3 97.0 98.2 98.8 98.8 99.4

TOTAL NUMPER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER	724505	STATI								PERIOD Month	OF REC		(LST):		
CEILING	•••••	•••••		• • • • • • •	• • • • • • •			IN STAT	 Lite Mil	 FS	• • • • • • •		• • • • • • •	• • • • • •	••••••
IN GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GĘ	G E	GE	GE	ĢĒ
FEET 10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	O
	•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •		• • • • • • • • • • • • • • • • • • • •
40 CEIL 27.0	58.8	59.4	59.4	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	54.5
6E 20F001 30.3	65.3	65.8	65.8	66.0	66.0	66.1	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2
PE 18000 30.3	65.6	66.1	66.1	66.3	66.3	66.5	66.6	66.6	66.6	66.6	66 • 6	66.6	66.6	66.6	66.6
GE 160001 30.3	66.0	66.6	66.6	66.8	66.8	66.9	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0
GE 14000[30.6	66.6	67-1	67.1	67.3	67.3	67.4	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5
68 120001 30.9	67.4	68.0	68.0	68.2	68.2	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
GF 100001 32.8	70.8	71.4	71.4	71.6	71.6	71.7	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8
DE 90001 32.8	70.8	71.4	71.6	71.8	71.8	71.9	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0
GE 80001 32.9	71-8	72.5	72.7	72.9	72.9	73.0	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1
GE 7000 32.9	71.8	72.5	72.7	72.9	72.9	73.0	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1
ng ecool 35.4	71.8	72.6	72.8	73.0	73.0	73.1	73.2	73.2	73.2	73.2	73.2	73.2	73.2	73.2	73.2
of 50001 32.9	72.5	73.2	73.4	73.7	73.7	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
GE 4500 33.0	72.8	73.5	73.8	74.0	74.0	74.1	74.2	74.2	74.2	74.2	74.2	74.2	74.2	14.2	74.2
GC 40001 33.4	73.5	74.3	74.6	74.8	74.8	74.9	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1
SE 35001 33.5	74.5	75.3	75.7	75.9	75.9	76.0	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1
of 30001 33.9	75.8	76.6	77.0	17.2	77.2	77.3	77.4	77.4	77.4	77.5	77.5	77.5	77.5	77.5	77.5
SE 20001 34.1	77.6	78.L	79.1	79.6	79.6	79.7	79.8	79.8	79.8	79.9	79.9	19.9	79.9	79.9	79.9
GE 20001 34.7	79.2	80.9	81.5	81.9	81.9	82.0	82.3	82.3	92.3	82.4	82.4	82.4	82.4	82.4	82.4
UE 1800 34.8	79.6	81.2	81.8	82.3	82.3	82.4	82.6	82.6	82.6	82.7	82.7	82.7	82.7	82.7	82.7
CE 1º001 34.8	81.9	83.7	84.8	85.4	85.4	85.5	85.9	86.0	86.2	86.3	86.3	86.3	86.3	86.3	86.3
GF 1200 34.8	83.0	84.7	86.0	86.9	87.1	87.2	87.6	87.7	88.0	88.1	88.1	88.1	88.1	88.1	86.1
OF 10001 34.8	84.1	86 • 5	88.2	89.2	89.5	89.9	90.5	90.6	90.9	91.0	91.0	91.0	91.0	91.0	91.0
UE 900 34.8	84.3	86.7	88,5	89.6	90.0	90.4	91.4	91.5	91.7	91.8	91.8	91.8	91.8	91.8	91.8
UE 800 34.8	84.7	87.2	89.2	90.3	90.8	91.3	92.3	92.5	92.8	92.9	92.9	92.9	92.9	92.9	92.9
6E 700 34.8	84.7	87.2	89.5	90.6	91.2	92.2	93.1	93.3	93.7	93.8	93.8	93.8	93.8	93.8	93.8
GE 6001 34.8	85.1	87.8	90.2	91.7	92.5	93.4	94.4	94.6	95.3	95.4	95.4	95.5	95.5	95.5	95.5
GF "001 34.A	A5.2	88.2	90.8	92.5	93.2	94.4	95.6	95.9	96.6	96.7	96.7	96.9	96.8	96.8	96.8
JE 4001 34.8	85.2	88.4	91.2	93.2	94.1	95.5	96.7	97.1	97.8	9 A . D	98.0	98.1	98.1	98.1	98.1
UE 3001 34.5	85.2	88.4	91.2	43.2	94.1	95.5	96.8	97.3	98.1	98.2	98.2	98.4	98.4	98.4	96.4
uE 200 34.8	85.2	88.4	91.2	93.2	94.1	95.5	96.8	97.3	98.2	98.6	98.6	98.8	99.0	99.1	99.1
OF 1601 34.8	85.2	88.4	91.2	93.2	94.1	95.5	96.8	97.3	98.4	98.8	99.0	99.2	99.6	99.7	100.0
GE 01 34.8	85.2	88.4	91.2	93.2	94.1	95.5	96.8	97.3	98.4	98.8	99.0	99.2	99.6	99.7	100.0
• • • • • • • • • • • • • • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •		• • • • • •			• • • • • • •	• • • • • •	• • • • • • •		• • • • • • • •			

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIPILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86 MONTH: JAN HOURS(LST): 2100-2300 VISIBILITY IN STATUTE MILES CEILING IN 1 GE GE GE GE 6 5 4 GE GE GE GE GE GE GE GE 2 1 1/2 1 1/4 1 GF GF GE 6E IN I GE FEET | 10 1/4 3 2 1/2 3/4 5/8 1/2 U 5/16 62.0 62.2 62.2 62.2 62.2 62.2 62.2 62.2 NO CEIL 1 27.1 60.5 61.3 61.7 62.2 62.2 62.2 62.2 67.4 67.7 67.7 67.4 67.7 67.7 GE 200001 29.1 65.7 66.6 67.0 67.3 67.4 67.7 67.7 67.4 67.4 67.4 67.4 67.7 67.7 67.4 67.4 67.7 67.7 67.4 67.4 GE 18000 29.1 GE 16000 29.1 GE 14000 29.1 GE 12000 29.6 67.3 67.6 67.7 67.7 67.7 67.7 67.7 67.7 66.0 66.9 66.9 66.0 67.7 67.7 66.8 67.6 68.1 68.4 68.5 68.5 68.5 68.5 68.5 68.5 68.5 68.5 68.5 68.5 60.5 64.9 70.3 70.4 71.7 70.3 70.4 GE 100001 30.9 69.5 70.2 70.3 70.3 70.3 70.3 70.3 70.3 70.3 70.3 69.6 70.4 70.4 70.4 71.7 90001 31.0 70.4 71.7 ijΈ 68.7 70.0 70.3 70.4 70.4 70.4 70.4 70.4 71.7 70.0 71.3 71.6 71.7 71.7 71.7 71.7 71.7 71.7 71.7 70.8 72.4 72.5 72.5 72.5 72.5 72.5 72.5 GE 70001 31.7 71.6 72.0 72.5 77.5 72.5 72.5 72.5 50001 31.8 73.8 74.5 75.4 ь£ 73.3 73.8 73.8 73.8 73.8 73.8 74.5 ÚΕ 45001 32.4 72.5 73.1 73.7 74.1 74.9 74.4 74.5 75.4 74.5 75.4 74.5 74.5 74.5 75.4 74.5 74.5 74.5 74.5 74.4 75.4 75.4 75.4 75.4 75.4 75.4 75.4 40001 32.6 35001 33.1 75.4 ũΕ ĞE 74 - 1 76.0 76.5 76.5 76.5 76.5 30001 33.3 77.3 74.9 76.2 76.9 77.3 77.3 80.1 82.3 82.9 25001 33.5 20001 34.2 80.0 82.2 80.1 82.3 6 F 77.0 7 R . R 79.5 79.9 80.0 80.0 80.0 80.0 80.1 40.1 A0.1 80.1 78.6 80.5 82.0 82.2 82.2 82.2 82.7 82.3 82.3 82.9 82.3 81.6 82.2 81.0 82.7 82.9 82.9 GE 18001 34.2 79.0 82.2 82.6 82.7 82.7 82.7 82.9 85.9 15001 34.2 81.3 85.2 85.6 85.7 85.9 85.9 45.9 85.9 GE 84.6 85.5 85.6 85.6 GF 12001 34.2 82.2 84.5 85.8 86.3 86.9 87.0 87.3 87.5 87.5 A7.5 87.5 87.5 87.5 1000| 34.3 90.3 91.3 90.3 91.3 88.6 90.1 89.6 90.5 90.3 91.3 90.3 91.3 90.3 91.3 83.2 83.5 85.8 87.6 88.3 69.8 90.8 90.3 91.1 ĿΕ 90.8 92.0 92.3 GE PUD | 34.3 84.0 87.D 89.0 90.2 91.0 91.5 91.7 91.7 92.3 92.3 92.4 91.7 93.4 91.9 92.6 92.6 7001 34.3 84.1 87.1 89.2 90.4 91,2 91.9 92.3 92.5 92.5 92.5 92.5 91.7 92.8 96.2 GE 88.0 5001 34.3 4001 34.3 3001 34.3 95.1 96.6 97.8 95.1 96.7 98.0 93.0 93.8 95.1 GE 90.3 91.9 94.1 94.5 94.5 94.8 95.1 95.2 95.3 84.4 88.1 90.4 92.7 96.0 96 • D 97 • D 96.3 96.6 97.8 96.7 96.8 L E 84.4 88.3 90.6 92.9 94.0 96.6 98.2 98.2 96.6 88.3 96.7 98.6 98.6 99.O GE GE 1001 34-3 88.3 90.6 92.9 94.0 95.7 96.7 97.1 98.6 98.7 98.9 98.9 99.5 99.9 0 (34.3 92.9 94.D 95.7 96.7 97.1 97.5 98.6 98.7 98.9 98.9 99.5 100.0 88.3 90.6

TOTAL NUMBER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PEPIOD OF RECORD: 77-86
MONTH: JAN HOURS(LST): VISIBILITY IN STATUTE MILES GE GE GE GE 2 1 1/2 1 1/4 I CEILING IN | GE FEET | In GE GE 6 5 GE GE GE G.F GE ٥E GE 4 FEET | 10 3 2 1/2 3 3/4 5/8 1/2 5/16 1/4 58.7 58.8 58.9 58.9 58.9 59.0 59.1 NO CEIL | 26.8 57.5 58.1 58.4 58.6 58.8 58.8 58.9 58.9 64.7 65.0 65.2 GE 200001 29-2 64-1 64-4 64.5 64.8 65.1 65.0 65.3 65.4 65.8 65.4 65.5 65.9 65.1 65.1 65.1 65.5 65.2 65.2 65.2 65.3 63.4 65.1 65.5 65.4 65.6 65.9 64.8 65.5 65.5 65.5 18000| 29.3 63.7 65.4 65.6 GE 16000| 29.3 GE 14000| 29.5 65.3 63.8 64.5 65.6 65.6 65.6 66.0 65.8 66.0 66.0 66.1 of 120001 29.7 64.7 65.4 65.8 66.0 66.1 66.3 66.4 66.4 66.4 66.5 66.5 66.5 66.5 66.5 66.6 GE 10c00| 31.0 GE 9000| 31.1 66.9 67.8 68.4 68.5 68.8 68.8 69.0 70.6 68.9 69.0 68.9 68.8 68.9 70.5 68.3 68.6 68.8 68.9 69.Ü 70.6 69.0 69.2 69.4 8000 | 31.6 68.5 70.1 70.2 70.4 70.4 70.5 70.6 70.6 70.7 70.8 71.5 (, F 70001 31-8 69.0 70.3 70.6 70.7 70.8 70.9 71.0 71.0 71.1 71.1 71.1 71.1 71.2 71.4 6 E 50001 32.4 70.6 71.9 72.4 72.7 72.8 73.0 73.1 73.1 73.2 73.2 73.2 73.3 73.3 73.5 74.5 75.3 4500] 32.7 4000] 33.0 71.4 72.6 73.5 73.1 74.1 73.4 74.4 73.7 73.8 73.9 74.9 13.9 74.9 74.0 75.0 74.0 75.0 74 • D 75 • 1 74.0 75.1 74 • 1 75 • 1 74.2 65 75.2 35001 33.2 74.2 75.2 75.5 75.7 75.7 75.9 77.2 30001 33.5 75.4 77.0 77.0 77.2 υE 73.8 76.1 76.6 76.8 76.9 79.2 81.0 81.6 1.97 79.1 80.9 G.F 25001 34.0 75.3 77.0 77.A 78.4 78.5 78.7 78.9 79.0 79.0 79.2 19.2 79.4 80.4 81.0 81.0 81.6 83.9 81.0 2000 | 34.4 1800 | 34.5 76.5 76.9 79.4 80.0 80.1 80.7 80.8 80.8 81.2 78.4 78.9 GE 81.2 81.3 81.5 81.5 81.6 81.7 84.0 80.6 80.7 81.4 83.6 82.5 82.7 83.9 15001 34.6 78.3 80.6 81.8 83.0 12001 34.7 79.2 81.6 83.1 83.9 84.1 85.2 85.3 85 • 6 85.7 85.7 85.8 85.8 85.8 86.0 1000| 34.7 89.3 88.3 89.3 88.4 88.4 49.4 90.7 88.5 80.6 80.9 83.4 84.0 85.4 86.2 86.6 87.5 87.7 88.7 89.4 úΕ 86.9 88.5 89.0 P00 | 34.7 87.8 88.7 90.2 90.5 90.5 90.6 90.6 90.8

90.6

93.2

94.6 95.0

95.1

95.1

90.9

92.5

93.8

95.2 95.8

96.0

96.0

96.0

01.4

94.4

96.D

96.9

97.3

97.4

97.4

91.7

94.8

96.4

94.2

98.2

91.7

94.8

96.4 97.5

98.3

98.3

91.8

93.6

94.9

96.6

98.9

98.9

91.8

93.6

94.9

96.6

98.7

99.0

99.1

91.9

95.0 96.6 97.8

99.3

92.0

96.0

99.8

99.3 100.0

89.7

91.2

92.1

93.3

93.6

93.6

84.8

96.1

90.8

91.7

91.9

91.9

A A . 3

90.2

91.1

91.2

91.2

TOTAL NUMBER OF OBSERVATIONS: 7440

81.1

81.6

81.7

81.7

84.4

85.2 85.4 85.5

85.5

86.7

88.0

88.4

88.5

88.5

700 1 34.7

6001 34.7

5001 34.7

400 | 34.7 300 | 34.7

2001 34.7

1001 34.7

01 34.7

(, F

G€

ı,€ G€

ı, Ç

U.€

Ŀ۴

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): 0000-0200 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES CEILING E GE GE GE 5 4 3 2 1/2 GE GE GE 2 1 1/2 1 1/4 IN | 5E FEET | 10 GE GE 1 3/4 GE GE 6 5/6 1/2 5/16 1/4 O NO CEIL | 29.4 54.5 55.7 57.2 57.3 57.3 57.3 57.3 57.3 57.4 57.4 56.4 56.6 56.7 57.8 56.6 GF 200001 30.5 58.9 59.6 59.9 60.5 60.5 6n.8 60.8 60.8 60.9 60.9 61.2 57.6 50 . A 60.4 62.1 GE 18000| 30.9 GE 16000| 30.9 59.2 59.9 60.2 60.9 60.9 61.1 61.2 60.8 61.1 61.1 61.2 61.6 64.4 60.3 57.9 60.2 60.8 60.9 61.1 61.1 61.2 61.6 62.4 14000| 30.9 60.2 60.4 60.5 61.0 61.3 58.5 UE 120001 31.0 59.8 60.5 60.8 60.9 61.3 61.5 61.5 61.7 61.7 61.8 61.8 62.2 63.0 GE 130001 31.7 61.1 62.4 63.1 63.4 63.9 64.1 64.3 64.3 64.3 64.4 64.4 64.8 65.6 62.9 63.8 63.6 64.5 63.9 64.5 65.5 64.5 64.8 64.9 65.2 90001 31.7 61.6 63.8 64.4 64.8 64.8 64.9 66.1 80001 32.0 62.5 64.9 65.4 65.7 65.7 65.7 65.8 66.2 67.0 6 E 70001 32.5 63.1 64.4 65.1 65.4 65.5 66 . N 66.1 66.1 66.3 66.3 66.3 66.4 66.4 66.8 67.6 60001 32.6 63.5 64.8 65.6 66.5 66.9 65 - 8 66.0 66.4 66.5 5000| 33.7 4500| 33.8 4000| 33.8 3500| 34.5 68.4 68.7 69.7 65.1 65.4 66.4 67.3 67.5 67.5 67.7 68.1 68.3 68.2 68.4 67.6 68.4 68.4 68.6 68.6 68.9 69.7 68.7 69.7 71.5 67.8 68.4 68 • 7 69 • 7 68.8 69.1 ŭ€ 66.4 67.7 68.6 68.8 68.9 69.4 69.5 69.9 6⁹ • 9 71 • 6 70.2 71.0 67.6 69.3 70.1 70.6 70.7 71.2 71.3 71.5 72.0 υE 30001 34.6 68.7 70.4 71.3 71.9 72.0 72.5 72.6 72.6 72.8 72 - B 72.8 72.9 72.9 73.3 74.1 2500| 35.2 2000| 35.9 1800| 35.9 74.9 77.2 77.7 75.2 77.4 77.9 70.3 72.1 73.9 75.8 15.2 77.4 75.3 77.5 75.3 77.5 15.1 11.9 74 . C 75.1 75.4 76.0 76.5 76.6 17.1 77.2 77.1 77.4 11.9 76.7 72.5 74.3 11.9 78.0 78.0 7R.4 74.5 78.8 80.5 60.5 UE 15001 36.8 76.8 78.0 79.1 19.7 80.3 60.3 80.5 80.6 80.6 81.0 81.8 80.5 82.2 10001 37.1 79.6 94.9 84.9 84.9 85.0 A5.0 d5.3 80.2 81.2 83.1 83.9 84.5 76.6 82.9 84.6 900 | 37.1 800 | 37.1 77.U 80.1 81.9 84.2 85.0 85.9 86.2 87.1 86.2 87.1 86 · 2 87 · 1 86.3 87.2 86.3 87.2 86.6 87.6 6 E 63.9 85.1 85.8 87.5 86.4 G € 84.8 86.1 86.8 700 | 37.1 77.4 81.0 83.0 87.9 87.9 87.9 88.1 98.1 88.4 89.2 88.9 89.1 89.0 89.1 89.5 υE 6001 37.2 77.9 81.4 A 4.5 85.9 86.3 87.5 88.2 88.3 88.9 96.3 84.3 84.3 84.5 87.2 87.4 87.7 5001 37.2 78.0 81.9 86.8 88.4 89.1 89.6 90.4 89.7 90.8 90.9 91.0 91.1 91.1 91.5 94.3 G.E 92.6 94.0 4001 37.2 3001 37.2 91.8 92.2 92.3 +2.9 93.7 81.9 90.5 91.7 92.6 78.0 86.8 89.7 ωĚ 78.0 82.0 87.1 91.4 94.0 74.6 95.4 2001 37.2 94.1 94.6 94.6 95.2 G.F 78.0 89.7 84.5 87.7 92.2 82.0 87.1 91.6 1001 37.2 94.2 95.2 95.5 95.6 97.2 99.4 92.3 95.6 01 37.2 78.0 82.0 84.5 87.1 87.7 89.8 91.7 92.3 94.2 94.7 95.2 95.5 97.2 100.0 G.E

TOTAL NUMBER OF OBSERVATIONS:

546

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

511	ATION N	IUMBER:	724505	STATI	ON NAME	: MCC0	NNELL A	FB KS				PE PI OU MONTH	OF PEC	0RD: 77 HOURS	-86 (LST):	0300-05	60
LE	L 156					• • • • • • • •		v 1 S I	BILITY	IN STAT	ulf mil	• • • • • • • • • • • • • • • • • • •	• • • • • • •		• • • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •
FE	IN I	6£ 10	e e	6£	L F 4		GE 2 1/2	G E	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GΕ 5/16	GE 1/4	ίΕ U
• • •	• • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • •	
N O	CEIL I	29.0	52.0	52.7	53.9	54.6	55.2	55.8	55.9	55.9	55.9	55.9	55.9	56.0	56.0	56.1	57.4
⇒E	200001	30.5	56.5	57.2	58.4	59.1	59.7	60.3	60.4	60.4	60.4	60.4	60.4	60.5	60.5	60.6	61.9
	100381		56 . 6	57.3	58.5	59.2	59.8	60.4	60.5	60.5	60.5	60.5	60.5	60.6	60.6	bn.8	64.1
G.E	160001	3C.6	56.6	57.3	58.6	59.3	59.9	60.5	60.6	60.6	60.6	60.6	60.6	60.8	60.8	60.9	62.2
	140001		57.0	57.7	59.1	59.8	60.4	61.0	61-1	61.1	61.1	61.1	61.1	61.2	61.2	61.3	62.6
٥E	120001	30.6	57.2	57.9	59.3	60.0	60.6	61.2	61.3	61.3	61.3	61 - 3	61.3	61.5	61.5	61.6	62.9
, ,	100001		59.1	59.8	61.2	61.9	62.5	63.1			(7 . 5						
SF	40001		59.5	60.2	61.6	62.3	62.9	63.5	63.2 63.6	63.2 63.6	63.2 63.6	63.2 63.6	63.2 63.6	63.4	63.4	63.5	64.8
G.E	80001		60.9	61.6	63.0	63.7	64.3	64.9	65.0	65.0	65.U	65.0	65.0	63.7 65.1	63.7 65.1	63.8 65.2	65.1 66.5
ti E	70001		61.3	62.1	63.5	64.2	64.8	65.4	65.5	65.5	65.5	65.5	65.5	65.6	65.6	65.7	67.0
la E	1007a		61.9	62.6	64.1	64.8	65.4	66.0	66.1	66.1	66.1	66.1	66.1	66.2	66.2	66.3	67.6
.,			•••	02.0			03.1	00.0	00.1	00.1	00.1	00.1	00 • 1	00 . 2	00 • 2	00.3	6.1.0
ં !	50001		63.0	63.7	65.1	65.8	66.4	67.0	67.1	67.1	67.1	67.1	67.1	67.3	67.3	67.4	68.7
6.5	45001		63.6	64.3	65.7	66.4	67.0	67.6	67.7	67.7	67.7	67.7	67.7	67.8	67.8	68.D	69.3
υ.€	40001		64.3	65 • C	66.4	67.1	67.7	68.3	68.4	68.4	68.4	68.4	68.4	68.6	68.6	68.7	76.0
, f	3,001		64.8	65.5	66.9	67.6	68 • Z	68.8	68.9	68.9	68.9	68.9	68.9	69.0	69.0	69.1	76.4
υ£	30001	34.0	66.3	67.3	68.7	69.6	70.2	70.8	70.9	70.9	70.9	70.9	70.9	71.0	71.0	71.2	72.5
υ.Ε	24601	44.0	67.4	68.6	7 0 . 1	71.0	71.6	72.2	72.3	72.3	72.3	77.3					
ű.E	20001		68.3	69.5	71.0	72.1	72.7	73.3	73.4	73.4	73.4	73.4	72.3 73.4	72.5	72.5	72.6	73.9
υE	18001		69.1	70.3	71.9	73.3	73.9	74.5	74.6	74.6	74.6	74.6	74.6	73.5 74.7	73.5 74.7	73.6 74.8	74.9 76.1
	1:001		70.7	71.9	73.4	75.1	75.8	76.4	76.5	76.5	76.5	76.5	76.5	76.6	76.6	76.7	78.0
SE	12001		72.5	73.9	75.5	77.8	78.5	79.2	79.3	79.3	79.4	79.4	79.4	79.6	79.6	79.7	81.0
								_								• .	- 1.0
-9€	10001		74.1	76.1	77.9	80.4	81.1	81.9	82.2	82.2	92.3	82.3	82.3	82.4	92.4	82.5	63.8
, f		35.5	74 - 2	76.4	78.5	81.6	82.3	83.1	83.3	63.3	83.6	83.6	83.6	83.7	83.7	63.8	85.1
•		35.5	75.4	77.9	80.3	83.6	84.3	85.1	85.3	65.3	P5.6	85.6	85.6	85.7	85.7	8 . 5 ه	97.1
2.€		35.5	76.C	78.6	81.0	84.6	85.5	86.4	87.1	87.1	87.6	87.6	87.6	87.7	87.7	8.76	84.1
υŧ	eaut	35.5	76.0	18.6	81.2	85.2	86.2	87.2	87.9	87.9	88.5	88.5	88.5	88.7	88.7	88.8	96.1
í, E	rael	35.5	76.1	78.7	81.6	85.7	87.0	88.2	89.1	89.1	90.0	90.0	90 • 1	90.2	90.2	90.3	91.6
-i-E		35.5	76.2	78.8	81.6	85.9	87.5	88.9	90.2	90.2	91.1	91.1	91.3	91.4	91.4	91.5	91.6
1.8		35.5	76.2	79.0	81.9	86.2	97.6	89.8	91.6	91.8	93.4	93.5	93.6	93.7	93.7	93.9	95.2
.,r	2601	35.5	76.2	79.0	81.0	86.2	87.8	89.8	91.6	92.1	93.7	94.0	94.1	94.6	94.8	95.3	97.0
, ŧ	1001	35.5	76.2	79 . U	81.9	86.2	87.8	89.g	91.6	92.1	94.0	94.6	94.9	95.7	96.0	96.9	99.6
	01	35.5	76.2	79.0	81.9	86.2	87.8	89.8	91.6	92.1	94.0	94.6	94.9	95.7	96.0	97.0	106.6

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

							NNELL A										
	LING	•••••	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	•••••			IN STATE			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
		GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GΕ	GE	٥E
	Er i	_	6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	۵
	• • • • • •				.						. .		• • • • • •				
• • • •	••••	•••••							• • • • • • • •							• • • • • • •	
N O	CEIL	24.7	47.6	48.5	49.2	49.4	49.9	50.6	50.1	50.7	51.1	51.3	51.3	51.4	51.4	51.5	52.4
6 F	200001	26.6	52.4	53.3	54.1	54.8	55.3	56.0	56.1	56.1	56.5	56.7	56.7	56.9	56.9	57.0	57.8
	180001		52.5	53.4	54.3	55.0	55.4	56.1	56.3	56.3	56.6	56.9	56.9	57.0	57.0	57.1	57.9
GF	160001	26.6	52.6	53.5	54.4	55.1	55.6	56.3	56.4	56.4	56.7	57.0	57.0	57.1	57.1	57.2	56.0
GE	140001	26.8	53.1	54.0	54.8	55.6	56.0	56.7	56.9	56.9	57.2	57.4	57.4	57.6	57.6	57.7	58.5
68	120001	27.1	54.0	55.0	55.9	56.6	57.1	57.8	57.9	57.9	58.3	58.5	58.5	58.6	58.6	58.7	59.6
GE	100001	27.7	55.8	56.9	57.0	58.5	59.G	59.7	59.8	59.8	60.2	60.4	60.4	60.5	60.5	60.6	61.5
GΕ	90001	27.7	56.0	57.1	58.O	58.7	59.2	59.9	60.0	60.0	60.4	60.6	60.6	60.8	60.8	60.9	61.7
ĢΕ	80001	27.8	57.3	58.4	59.3	60.0	60.5	61.2	61.3	61.3	61.7	61.9	61.9	62.1	62.1	62.2	63.0
GE	70001	27.9	57.7	58.7	59.7	60.4	60.9	61.6	61.7	61.7	62.1	62.3	62.3	62.4	62.4	62.5	63.4
6 E	60001	28.0	57.9	59.0	59.9	60.6	61.1	61.8	61.9	61.9	62.3	62.5	62.5	62.6	62.6	62.8	63.6
υ£	50001	28.5	59.6	60.6	61.6	62.3	62.8	63.5	63.6	63.6	63.9	64.2	64.2	64.3	64.3	64.4	65.2
GΕ	4500	28.6	60.0	61.1	62.1	62.8	63.2	63.9	64.1	64.1	64.4	64.7	64.7	64.8	64.8	64.9	65.7
GΕ	40001	28.6	60.5	61.6	62.5	63.2	63.8	64.5	64.7	64.7	65.0	65.2	65.2	65.4	65.4	65.5	66.3
ijΕ	3500	28.8	61.3	62.4	63.4	64.1	64.7	65.4	65.5	65.5	65.8	66.1	66.1	66.2	66.2	66.3	67.1
GE	3000	29.3	62.2	63.2	64.2	65.0	65.6	66.3	66.4	66.4	66.8	67.0	67.G	67.1	67.1	67.3	68.1
6 E	25001	29.7	63.7	65.1	66.1	67.1	67.7	68.6	68.7	68.7	69.1	69.4	69.4	69.5	69.5	69.6	76.4
٥E	50001	29.8	65 - 1	66.5	67.5	68.6	69.1	70.1	70.2	70.2	70.7	70.9	70.9	71.0	71.0	71.2	72.0
GE	18001	29.8	65.2	66.9	67.8	68.9	69.5	70.4	70.6	70.6	71.2	71.4	71.4	71.5	71.5	71.6	72.5
GΕ	15001	30.3	67.1	69.3	76.2	71.5	72.2	73.4	73.6	73.6	74.3	74.6	74 . 6	74.7	74.7	74.8	75.7
GΕ	12001	31.1	69.5	71.7	72.8	74.5	75.2	76.5	76.7	76.7	77.5	77.8	77.8	77.9	77.9	78.0	78.8
GΕ	1001	31.3	71.3	73.8	75.2	76.8	77.5	79.1	79.4	79.4	80.3	80.5	80.5	80.7	80.7	80.9	81.7
68		31.3	72.2	74.7	76.4	78.3	79.0	80.6	81.1	81.1	A2.0	87.4	82.4	82.6	82.6	82.7	83.6
GΕ		31.3	72.9	75.5	77.7	79.7	80.4	82.2	82.7	82.7	83 · 8	84.2	84.2	84.4	84.4	84.5	85.3
GE		31.3	73.8	76.5	79.0	81.1	82.2	83.9	84.6	84.9	P5.9	86.3	86.3	86.5	86.5	86.6	87.5
ĿΕ	6001	31.3	73.8	76.5	79.0	81.2	82.6	84.6	85.5	85.8	87.2	87.6	87.6	87.8	87.8	87.9	88 • 8
GE	5001	31.3	73.9	76.6	79.2	81.6	83.0	85.0	85.9	86.3	88.1	88.4	88.4	88.8	88.8	89.0	89.8
GE		31.3	74.2	77.0	79.7	82.5	84.2	86.2	87.2	87.9	89.8	90.3	90.3	90.7	90.7	90.9	91.7
ij€		31.3	74.2	77.0	79.7	82.5	84.3	86.5	87.9	88.7	91.3	92.0	92.0	92.6	92.6	92.8	93.6
GΕ	2001	31.3	74.2	77.U	79.7	82.6	84.4	86.8	88.2	68.9	91.6	92.8	92.8	93.4	93.4	94.1	95.2
ĿΕ	1001	31.3	74.2	77.0	79.7	82.6	84.4	86.8	88.3	89.1	92.1	93.4	93.5	94.3	94.4	95.7	99.2
Ŀξ	01	31.3	74.2	77.0	79.7	82.6	84.4	86.8	88.3	69 · 1	92.1	93.4	93.5	94.4	94.6	96.1	100.0
• • •	• • • • •	• • • • •	• • • • • •	• • • • • •			• • • • • •		• • • • • •	• • • • • • •		• • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • • • • • • •

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 7										MONTH	_	HOURS	KŠTI: (
	• • • • • • •	• • • • • • •	•••••	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •
CE IL 1 133	GE	GE	GE	GE	GE	GF A 1 2 1 6	66	IN STATE	0E 115 mili	LS GE	GE	GE	Gf	G E	ĿΕ
IN GE FEET 10	6	5	4		2 1/2			1 1/4	1	3/4	5/8		5/16	1/4	C.
											•	1/2			
	• • • • • •						• • • • • •	•••••	• • • • • •	• • • • • • •	• • • • • •		• • • • • •	• • • • • •	
40 CEIL 25.1	45.7	46.6	48.0	48.3	46.5	48.6	48.6	48.6	48.9	49.1	49.1	49.1	49.2	49.2	44.3
GF 200001 27.1	51.4	52.6	54.4	54.8	55.1	55.3	55.3	55.3	55.7	55.8	55.0	55.8	55.9	55.9	50.0
6E 18000 27.1	51.7	52.8	54.6	55.1	55.3	55.6	55.6	55.7	56.0	56.1	56.1	56.1	56.3	56.3	56.4
GE 160001 27.1	51.7	52.8	54.6	55.1	55.3	55.6	55.6	55.7	56.0	56.1	56.1	56.1	56.3	56.3	56.4
UE 140001 27.2	51.9	53.1	54.8	55.3	55 • 6	55.8	55.8	55.9	56.3	56.4	56.4	56.4	56.5	56.5	56.6
GE 12cool 27.8	53.5	54.7	56.5	57.0	57.2	57.4	57.4	57.6	57.9	59.0	58.0	58.0	58 • 2	58.2	58.3
GE 100001 28.7	56.0	57.3	59.2	60.0	60.3	60.5	60.5	60.6	61.0	61.1	61.1	61.1	61.2	61.2	61.3
JE 90001 28.7	56 • U	57.3	59.2	60.0	60.3	60.5	60.5	60.6	61.0	61.1	61.1	61.1	61.2	b1 • 2	61.3
UE 60001 29.4	57.4	58.7	60.8	61.6	61.8	62.1	62.1	62.2	62.6	67.8	62.8	62.8	62.9	62.9	63.0
GE 7000 29.8	58.2	59.5	61.5	62.5	62.8	63.0	63.0	63.1	63.6	63.7	63.7	63.7	63.8	63.8	63.9
OE 90001 30.1	58.7	60.0	62.1	63.1	63.4	63.6	63.6	63,7	64.2	64.3	64.3	64.3	64.4	64.4	64.5
SE 50001 30.3	59.3	60.6	62.6	63.7	63.9	64.2	64.2	64.3	64.8	64.9	64.9	64.9	65.0	65.0	65.1
GF 45001 30.6	59.8	61.1	63.1	64.2	64.4	64.7	64.7	64.8	65.2	65.4	65.4	65.4	65.5	65.5	65.6
GE 4000 30.7	60.5	62.1	64.1	65.2	65.6	66.0	66.0	66.1	66.5	66.7	66.7	66.7	66.8	06.8	66.9
GE 35001 31.0	61.3	62.9	64.9	66.2	66.5	66.9	66.9	67.0	67.5	67.6	67.6	67.6	67.7	67.7	67.8
GE 3000 31.6	63.0	64.7	66.8	68.1	68.6	69.0	69.0	69.1	69.6	69.7	69.7	69.7	69.9	69.9	16.0
									.						•
SE 2500 31.9	64.8	66.5	68.7	70.1	70.7	71.3	71.3	71.4	71.9	72.0	72.0	72.0	72 • 1 73 • 8	72.1 73.8	72.2
	65.7	67.5	69.6	71.0	71.6 71.9	72.6	72.7	72.8 73.0	73.5 73.8	73.6 73.9	73.6 73.9	73.6 73.9	74.0	74.0	73.9 74.1
		67.7	69.9	71.3		72.8	72.9	74.9	75.9	76.0	76.U	76.1	76.2	76.2	76.4
SE 1500 32.4 GE 1200 32.5	67.5	69.4 70.4	71.5 72.0	73.2	73.8 74.9	74.7 76.1	74.8		77.7	77.8	77.8	77.9	78.0	18.0	78.1
or 17901 32.5	00.4	10.4	12.0	74.3	14.9	70.1	76.4	76.7	11.1	,,.,	11.0	11.4	70.U	,,,,	70.1
⊍€ 1000 33.0	70.9	73. 3	75.4	77.8	78.4	80.0	80.5	81.0	81.9	82.0	82.0	82.2	82.3	82.3	82.4
5E 9001 33.1	71.7	74.5	76.7	79.1	79.7	81.4	82.5	83.1	84.3	84.4	84 - 4	84.5	84.6	4.6	84.9
JE 800 33.1	72.0	74.9	77.3	79.8	80.4	82.2	83.0	83.8	95.1	85.2	85.2	85.3	85.5	05.5	85.9
SE 700 33.1	72.2	75.3	77.8	80.4	81.0	82.9	83.9	84.9	86.2	86.3	86.3	46.4	R6.5	86.5	P7.U
GE 6001 33.1	72.5	75 • 7	78.1	81.1	82.0	84.0	85.6	86.9	88.3	88.5	88.5	88.7	88.8	68.8	89.2
GE 500 1 33.1	72.7	75.9	78.5	81.6	82.9	85.0	86.8	88.4	90.2	90.5	90.5	90.7	90.8	90.8	91.3
SE 4001 33.1	72.7	76.0	78.8	81.9	83.5	85.8	88.1	90.0	91.8	92.3	92.3	92.4	92.6	92.7	93.1
aF 300 33.1	72.7	76.G	76.8	82.2	83.7	86.1	88.7	91.0	93.6	94.2	94.2	94.4	94.6	74.8	95.3
√E 200 33• I	72.8	76.1	79.0	82.3	83.8	86.3	88.9	91.3	94.1	94.8	94.8	95.9	96.1	97.3	96.0
GE 1001 33.1	72.8	76.1	79.0	82.3	83.8	86.3	88.9	91.3	94.1	95.0	95.C	96.2	96.6	98.2	94.5
/ C	72 0	7.	70.0			0.4	00.0			01.0	0.5 (0/ 3	04.4	a 9 3	100 0
CE 01 33.1	72.8	76.1	79.0	82.3	83.8	86.3	88.9	91.3	94.1	95.0	95.0	96.2	96.6	98.2	100.0

SEDHAL CLIMATOLOGY BRANCH DARFETAC AIR MEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

514	TICN N	HIMPLR:	724505	STATI	ON NAME:	MCCO	INNELL AF	FB KS				DESTOD	OF REC	ORD: 77	-86		
												MONTH	: FEB	HOURS	(LST):	1200-14	υO
		• • • • •			• • • • • • • •	• • • • •							• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • •
	LING									IN STAT							
		CE	G E	GE	GE	GE	GE.	GE	6€	GE	GΕ	GE	ĢĒ	GE	GE	GE	GE
	E T		ь	5	4		2 1/2		1 1/2		1	3/4	5/6	1/2	5/16	1/4	G
		•••••	• • • • • • •		• • • • • • • •	• • • • • •		• • • • • •		• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
							_										
N 0	CEIL	27.4	50.4	51.5	51.9	52.4	52.4	52.4	52.5	52.5	52 • \$	52.5	52.5	52.5	52.5	52.5	52.5
					•••												
	200001		57.9	59.5	59.9	60.5	60.6	60.6	60.9	60.9	60.9	60.9 60.9	60.9 60.9	60.9 60.9	60.9 60.9	60.9	60.9 60.9
	18100		57.9 57.9	59.5 59.5	59.9 59.9	60.5	60.6 60.6	60.6	60.9	60.9 60.9	60.9 60.9	60.9	60.9	60.9	60.9	60.9	66.9
	16000		58.5	60.C	6 U • 5	61.1	61.2	61.2	60.9 61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5
	14000		60.3	61.8	62.3	62.9	63.0	63.0	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2
υc	12000	31.0	60.3	01.0	02.03	02.7	63.0	03.0	03.2	63.2	03.2	63.2	63.2	63.2	0342	03.2	03.2
	100001	71 4	62.1	63.6	64.2	64.8	64.9	64.9	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1
6 £		31.4	62.2	63.7	64.3	64.9	65.0	65.0	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
υŧ		32.2	63.5	65.1	65.6	66.4	66.5	66.5	66.8	66.8	66.8	66.B	66.8	66.8	66.8	66.8	66.8
5.5		32.3	63.8	65.5	66.2	66.8	66.9	66.9	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
o F		32.7	64.4	66.2	66.9	67.5	67.6	67.6	67.8	67.8	67.6	67.8	67.8	67.8	67.8	67.8	67.8
.,.	00001	32.,	01.1	00.2	00.7	0	47.0	01.0	00	00	01.0	0	01.0	00	0.40	0	0170
, E	£ 0110 1	33.1	64.9	66.7	67.4	68.n	68.1	68.1	68.3	68.3	68.3	69.3	68.3	68.3	68.3	68.3	68.3
LΕ		33.7	65.2	67.0	67.7	68.3	68.4	68.4	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7
G.E		33.7	66.2	68.0	68.7	69.4	69.6	69.6	69.9	69.9	69.9	69.9	69.9	69.9	69,9	69.9	64.9
υE		33.9	66.5	68.3	69.0	69.7	70.0	70.0	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2
υĒ		34.8	68.0	69.7	70.7	71.5	72.0	72.0	12.2	72.2	12.2	72.2	72.2	72.2	72.2	72.2	72.2
	'									•		•					
i, F	25001	35.8	70.6	12.3	73.3	74.2	74.7	74.7	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9
, f		35.9	71.5	73.3	74.2	75.2	75.8	75.8	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1
ωĹ	1966	35.9	71.9	73.6	74.6	75.5	76 - 1	76.1	76.5	76.5	76.5	76.5	76.5	76.5	76.5	76.5	76.5
ŧ	15001	36.4	73.5	75.5	76.6	77.8	78.6	78.6	79.1	79.1	79.1	79.1	79.1	79.2	79.2	19.2	79.2
5,5	ומטרו	36.4	75.4	77.9	79.0	83.5	81.6	81.6	82.3	62.3	82.3	82.3	82.3	82.4	82.4	82.4	82.4
× f		36.4	77.0	79.6	8 C • 7	83.1	84.2	84.5	85.5	85.5	85.5	85.5	85.5	85.7	95.7	85.7	85.7
G (36.4	77.3	80.4	81.9	84.6	85.8	86.4	87.4	87.4	A7.6	87.6	87.6	87.9	87.9	88.1	88.1
6 F		36.4	77.7	80.7	82.5	85.6	97.0	87 • 7	88.9	88.9	89.2	89.2	89.2	89.7	39.7	89.8	89.6
O.E.		26.4	77.7	80.9	82.6	85.7	87.4	88.5	89.8	89.8	90 • 3	90.3	90.3	90.9	90.9	91.1	91.4
60	6001	36.4	77.7	81.0	82.7	85.9	87.6	88.9	90.8	91.1	91.7	92.0	92.0	92.6	92.6	92.8	93.0
																05.5	
, '		36.4	77.8	81.2	8 3 • 2	86.5	88.3	90.4	92.4	93.3	94.0	94.4	94.4 95.6	95 • 2 96 • 3	95.2 96.3	95.5 96.8	95.7 97.0
		36.4	77.8 77.8	81.2	83.2	86.6	88.5	91.1 91.1	93.4	94.3	95 • 2 95 • 6	95.6 96.5	96.5	97.3	97.3	96.8 98.0	96.2
·		36.4		81.2	83.2	86.6	88.5		93.5	94.7		96.9	96.9	98.0	98.0	98.8	99.2
		36.4	77.6	81.2	83.2	86.6	88.5	91.1 91.1	93.5 93.5	94.7 94.7	95 • 7 95 • 7	96.9	96.9	98.0	98.1	99.1	99.8
•	1601	30.4	77 - 8	81.2	43.2	86.6	88.5	71.1	47.0	74.1	73.1	70.7	70.7	70.0	70.1	77.1	79.8
, ,	n I	36.4	77.8	61.2	A 3 . 2	86.6	86.5	91.1	93.5	94.7	95.7	96.9	96.9	98.0	98.1	00.1	100.0
		30.4	//.0	31.2	n 3 . Z	00.0	78.5	41.1	43.2	74.1	7301	70.7	70.7	77.00	70.1	7701	
																 • •	

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC PEPIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): 1500-17G0 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES CEILING GE GΕ GE GE GE 2 1 1/2 1 1/4 GE GE G.F GE GF FEET 1 10 4 3 2 1/2 5 3/4 5/8 1/2 5/16 1/4 1 0 6 52.7 NO CEIL | 28.0 51.7 52.4 52.7 52.7 50.9 52.7 52.7 59.1 59.7 59.7 60.4 60.4 60.2 60.4 60.4 60.4 60.4 60.4 GE 200001 30.7 59.8 60.0 60.4 60.4 58.4 60.4 GE 16000| 30.7 GE 16000| 30.7 59.0 60.4 60.4 60.8 61.U 61.0 61.0 61.0 61.0 61.0 61.0 61.0 60.6 61.0 61.0 60.6 61.0 61.0 6E 12COOL 31.2 60.6 61.5 62.2 62.5 62.8 62.8 62.8 62.8 62.8 62.8 62.8 10000| 32.3 9000| 32.3 8000| 33.6 64.5 65.0 67.0 64.8 65.2 67.3 65.1 65.6 67.6 65.1 65.6 67.6 65.1 65.6 67.6 65.6 67.6 65.6 67.6 64.9 65.4 65.1 65.6 65.1 65.6 65.1 65.6 G E G E 62.9 63.8 65.l 65.1 65.6 63.4 64.3 65.6 67.6 67.4 67.6 GE 65.2 66.3 67.6 67.6 68.2 6E 70001 33-6 65 . 8 66.9 67.6 67.8 68.U 68.2 68.2 68.2 68.2 68.2 68.2 68.2 66.2 68.6 68 • 8 69.1 5rool 34.4 68.6 69.3 69.6 71.5 69.6 70.0 71.9 69.9 70.2 72.2 69.9 70.2 72.2 69.9 70.2 72.2 69.9 69.9 70.2 69.9 70.2 69.9 69.9 71.7 GF 4500 | 34.5 67.8 70.2 70.2 70.2 40001 35.0 69.6 70.7 72.2 12.2 72.2 72.2 72.2 72.2 G٤ GE 35001 35.0 70.1 71.2 72.0 72.2 72.3 72.7 72.7 72.7 72.7 72.7 72.7 72.7 72.7 72.7 75.8 6 E 3FUD1 35.6 75.2 75.3 75.7 75.8 GE GE 25001 36.2 76.4 71.7 77.3 77.3 78.7 77.4 79.0 77.4 77.4 77.4 77.4 77.4 74.1 75.4 76.7 76.8 77.2 77.4 2000| 36.5 78.3 79.6 78.6 79.0 80.4 79.0 80.4 75.4 76.7 78.1 78.7 79.0 79.0 79.0 79.0 80.4 GΕ 76.1 77.8 77.8 79.7 78.8 79.4 80.0 83.0 80.0 80.4 80.4 80.4 80.4 15001 36.8 82.2 81.4 85.6 1000| 36.8 900| 36.8 800| 36.8 700| 36.8 81.7 83.5 87.2 88.7 87.2 88.7 87.6 89.0 87.6 89.0 87.6 89.0 87.6 89.0 87.6 87.6 89.1 GE 79.4 85.2 85.7 86.8 79.9 36.9 88.1 € E 86.2 79.9 85.1 85.2 GE 82.5 87.4 88.1 89.5 90.2 90.2 90.5 90.5 90.5 90.5 90.5 90.7 96.7 91.4 91.5 91.6 87.6 91.4 91.4 91.7 91.8 GE 82.6 88.3 89.8 91.0 91.0 93.6 95.2 93.7 95.6 96.7 500| 36.8 400| 36.8 300| 36.8 93.4 93.6 95.2 82.9 82.9 83.0 92.8 93.5 93.9 85.7 85.7 85.9 94.2 96.1 97.4 94.4 96.3 97.6 GE GE 80.0 88.1 68.2 88.8 91.3 80.0 94.0 94.4 92.1 94.0 95.7 96.1 96.1 96.8 GE 89.2 88.5 7001 36.8 1001 36.8 83.0 85.9 89.2 92.1 94.1 94.1 96.2 97.0 97.0 97.2 98.0 98.2 98.9 99.3 98 • 1 98.5 80.0 83.0 85.9 88.5 92.1

98.1

98.5

97.2

99.2 100.0

TOTAL NUMBER OF OBSERVATIONS:

80.0

83.0

DI 36.8

GE

846

88.5

89.2

92.1

94.1

94.6

96.2

97.0

85.9

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

5.7	AT.	ION I	NUMBER:	724505	STATI	ON NAME:	MCCO	NNELL AF	BKS				PERIOD MONTH	OF REC		-86 (LST):	1800-20	60
		I NG	• • • • • •	• • • • • • • •	•••••	• • • • • • • •	· · · · · ·	• • • • • • •	 IZIV	BILITY	IN STATE	UTF MILI	• • • • • • • • • • • • • • • • • • •	• • • • • • •	• • • • • • •	• • • • • •		
	IN		l GE	GE	GE	GE	GE	GE	GE	GΕ	GE	GE	GE	GE	GE	GE	GE	GE
	EE.		10	6	5	4		2 1/2	2		1 1/4	1	3/4	5/8	1/2	5/16	1/4	 U
									· · · · · · ·									
N O	CI	EIL	28.6	53.4	53.9	54.0	54.4	54.7	54.7	55.0	55.0	55 a D	55.0	55.0	55.0	55.0	55.0	55.0
			30.3	58.0	59.1	59.5	59.9	60.3	60.3	60.5	60.5	60.5	611.5	60.5	60.5	60.5	60.5	6C.5
			30.3	58.4	59.5	59.8	60.3	60.6	60.6	60.9	00.9	60.9	60.9	60.9	6ე.9	60.9	60.9	66.9
			30.3	58.4	59.5	59.8	60.3	6C•6	60.6	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	6U•9
			30.4	58.7	59.8	60.3	60.8	61.1	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
GE	1.	2000	31.1	59.9	61.0	61.5	61.9	62.3	62.3	62.5	62.5	62.5	67.5	62.5	62.5	62.5	62.5	62.5
					_													
			32.6	62.2	63.4	63.8	64.4	64.8	64 • 8	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.D
6E			32.6	62.9	64.1	64.5	65.1	65.5	65.5	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
G€			33.6	64.2	65.4	65.8	66.4	66.8	66.8	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0
GE			33.7	64.9	66.1	66.5	67.1	67.5	67.5	67.7	67.7	67.7	67.7	61.1	67.7	67.7	67.7	67.7
GE	•	יטטייפ	34.2	65.5	66.7	67.1	67.7	68.1	68.1	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	66.3
GE		Saaa.	34.6	66.8	68.1	68.6	69.1	69.5	69.5	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
65			35.0	68.0	69.3	69.7	70.3	70.7	70.7	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9
6 E			35.2	68.6	69.9	70.3	70.9	71.3	71.3	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9
ÚΕ			35.2	69.3	70.6	71.0	71.6	72.0	72.0	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	7;.6
GE			35.6	71.0	72.3	72.8	73.5	73.9	73.9	74.5	74.6	74.7	74.7	74.7	74.7	74.7	74.7	74.7
GE		25001	36.2	72.9	74.2	74.7	75.5	75.9	75.9	76.5	76.6	76.7	76.7	76.7	76.7	76.7	76.7	76.7
GΕ	i	2000	36.4	74.9	76.5	77.0	77.9	78.4	78.5	79.1	79.2	79.3	79.3	79.3	79.3	79.3	19.3	79.3
GE	1	I AUD I	36.6	75.5	77.1	77.5	78.8	79.3	79.4	80.0	80.1	80.3	80.3	80.3	80.3	80.3	80.3	8 6. 3
GF	1	1500	37.2	77.3	79.2	80.0	81.4	82.0	82.5	83.1	b3.2	83.3	83.3	83.3	83.3	83.3	83.3	83.3
GE	1	12001	37.4	78.4	80.5	81.6	83.1	83.8	84.6	85.2	65.3	85.5	85.5	85.5	85.5	P5.5	85.5	85.5
GE			37.4	79.4	81.7	82.9	84.8	85.7	87.1	87.7	67.9	88.3	88.4	88.4	88 - 4	88.4	88.4	88.4
ĿΕ			37.4	79.6	82.0	83.3	85.5	86.4	87.8	88.5	89.C	89.4	89.5	89.5	89.5	89.5	89.5	89.5
GE			37.4	79.8	82.5	A 3.9	86.2	87.1	88.5	89.2	89.7	90.1	90.2	90.2	90.2	90.2	90.2	90.2
GE			37.4	79.8	82.5	84.2	86.4	87.5	88.9	89.7	90.3	90 • 7	90.8	90.8	90.9	90.9	90.9	90.9
GE		600	37.4	74.8	82.6	84.5	87.0	88.2	90.0	90.8	91.4	91.7	91.8	91.8	92.0	92.0	92.0	92.0
GΕ		500	37.4	79.8	82.7	84.8	87.4	88.5	90.4	91.7	92.4	93.0	93.3	93.3	93.4	93.4	93.4	93.4
GE			37.4	79.8	82.9	84.9	87.5	88.9	90.9	92.3	93.3	94.4	94.9	94.9	95.0	95.0	95.0	95.0
GE			37.4	79.8	82.9	84.9	87.7	89.1	91.1	93.0	94.1	95.6	96.5	96.5	96.7	96.7	96.7	96.7
GE			37.4	79.8	82.9	84.9	87.7	89.1	91.1	93.6	94.9	97.0	97.9	97.9	98.2	98.3	98.3	98.3
GE			37.4	79.8	82.9	84.9	87.7	89.1	91.1	93.6	94.9	97.4	98.2	98.3	98 • 8	99.2	99.2	99.3
O.L		400	, ,,,,,	1,40	3,	0 117	5	U/ • 1	,,,,	, , , , ,	, , , ,	, , , ,	*****	,0.3	40.0	* * * 2	,,	
GE		0	37.4	79.8	82.9	84.9	87.7	89.1	91.1	93.6	94.9	97.4	98.2	98.3	98.8	99.2	99.2	106.0
• •	• • •	• • • • •	• • • • • •	• • • • • • •		• • • • • • •	• • • • •	• • • • • • •	• • • • • •	• • • • • •		• • • • • •	• • • • • •	• • • • • •	• • • • • •			• • • • • • • • • • • •

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PEPIOD OF RECORD: 77-86
MONTH: FEB HOURS(LST): 2100-23CO ***************** VISIBILITY IN STATUTE MILES GE GE 3 2 1/2 6**ε** 10 6E 4 GE GE 1 3/4 IN | FEET | E GE GE 2 1 1/2 1 1/4 GΕ 5/8 1/2 5/16 1/4 NO CEIL 1 28.5 54.0 55.0 55.3 56.9 56.9 57.0 57.1 57.1 57.1 57.1 57.1 57.1 57.1 57.1 57.2 GE 200001 30.1 57.4 57.7 58.5 59.2 60.9 60.9 61.1 61.1 61.1 61.1 61.1 59.5 59.5 59.5 GE 180001 30.1 GE 160001 30.1 58 • 7 58 • 7 61.1 61.1 61.2 61.3 61.3 61.3 61.5 57.7 61.1 61.2 61.3 61.3 61.3 61.3 61.3 61.3 57.7 61.3 GE 14cm01 30.1 58.7 61.1 61.1 61.3 61.3 61.3 61.3 61.3 61.3 01.3 61.5 60.2 60.4 61.1 63.0 GE 10000 | 31.9 GE 9000 | 31.9 GE 8000 | 32.7 62.2 63.8 63.8 63.9 64.1 64.8 66.7 64.1 64.8 06.7 64.2 61.5 64.1 64-1 64.1 64.1 64 - 1 64.1 6 E 62. 62.9 64.5 64.5 64.8 64.8 64.8 64.8 64.8 64.8 66.5 66.8 7000 | 33.1 60001 33.1 64.2 65.2 66.0 67.6 67.7 67.8 67.8 67.8 67.8 67.8 67.8 68.0 69.4 70.7 69.4 70.7 69.4 70.7 69.4 70.7 69.4 6€ 50001 33.7 65.4 66.5 67.4 69.1 69.1 69.3 69.4 69.4 69.4 69.5 4500| 34.2 4000| 34.2 70.7 67.8 68.6 69.5 68.7 69.4 70.3 70.6 71.3 66.7 70.4 71.2 72.1 70.4 71.2 70.7 71.4 GΕ 70.7 70.8 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.5 GE 35001 34.3 68.2 72.2 72.1 72.3 72.3 74.5 72.3 72.5 30001 34.6 69.7 25001 34.8 76.4 77.7 2000| 34.8 1800| 34.9 1500| 35.7 72.7 73.3 75.1 76.3 79.8 83.0 6F 77.7 78 · 3 79 · 8 74.1 75.2 78.0 78.4 78.4 78.4 78.4 78.4 78.4 76.5 74.9 76.2 79.2 82.3 79.6 79.9 83.1 79.9 79.9 79.9 79.9 80.0 79.9 83.1 82.2 83.0 83.1 83.1 83.1 83.1 83.2 85.0 85.5 85.5 85.6 10001 35.8 9001 35.8 8001 35.8 85.8 87.2 87.9 GE GE 77.4 77.8 86.5 87.2 88.9 87.2 88.9 87.2 88.9 87.2 .8.9 87.4 89.0 79.9 85.6 80.5 82.9 78.1 80.9 87.5 89.1 89.1 89.7 89.6 90.2 89.6 90.2 89.6 89.6 90.2 90.2 69.6 GΕ 88.7 89.7 GE 700 | 35.9 78.3 83.7 90.2 6 € 6001 35.9 88.8 89.4 90.2 90.9 90.9 91.4 91.4 91.4 91.4 91.4 5001 35.9 4001 35.9 84.6 85.0 85.1 93.1 94.0 78.5 78.5 93.1 94.0 95.6 93.1 93.3 92.6 93.1 93.1 90.3 91.6 92.8 94.D 95.6 95.6 ĠΕ 2001 35.9 2001 35.9 78 - 5 82.4 90.0 92.2 94.0 94.3 95.6 95.6 95.9 96.1 97.6 78.5 85.2 85.2 90 · 1 96.6 96.6 96.7 96.6 96.8 96.8 GΕ 82.4 90.8 92.3 94.6 94.9 96.3 96.6 100 | 35.9 90.8

91.0

97.0

97.4 100.0

TOTAL NUMBER OF ORSERVATIONS:

78.5

82.4

90.1

90.8

92.3

94.6

94.9

96.5

96 . 7

96.7

85.2

01 35.9

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION	NUMBER:	724505	STATE	ON NAME:	MCC 0	NNELL AF	B KS				PEPIOD MONTH	OF REC		-86 (LST1:	ALL	
		• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •							• • • • • •	• • • • • •	• • • • • •	• • • • • • • • • •
CEILING									IN STATE							_
IN	QE.	GE	GE	GΕ	GE	GE	GE	GE	GE	GE	GE	GΕ	GE	GE	GE	€ E
FEET	1 10	6	5	4		2 1/2	2	1 1/2		1	3/4	5/8	1/2	5/16	1/4	0
• • • • • • •		• • • • • • • •	• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •
NO CEIL	1 27.6	51.1	52.0	52.6	53.1	53.3	53.6	53.7	53.7	53.8	53.9	53.9	53.9	53.9	54.0	54.4
						••••			••••							•
GE 2000	29.5	56.2	57.3	58.1	58.7	59.0	59.3	59.4	59.4	59.5	59.6	59.6	59.6	59.6	59.7	60.1
GE 18000	29.6	56.5	57.5	50.4	59.0	59.2	59.5	59.7	59.7	59.8	59.8	59 • 8	59.9	59.9	60.0	6U.4
CE 16000	29.6	56.5	57.5	58.4	59.0	59.3	59.6	59.7	59.7	59.8	59.9	59.9	59.9	59.9	60.0	60.4
GE 14000	0 29.7	56.8	57.9	5 გ • 8	59.4	59.7	60.0	60.1	60.1	60.2	68.3	60.3	60 • 3	60.3	60.4	60.8
GE 12000	0.00	57.8	58.9	59.8	60.4	60.7	61.0	61.1	61.1	61.2	61.3	61.3	61.3	61.3	61.4	61.8
GF 1000	1 1 1 0	59.9	61.1	62.0	62.7	63.0	63.3	63.4	63.4	63.5	63.5	63.5	63.6	63.6	63.7	64.1
0E 9000		60.3	61.5	62.4	63.1	63.3	63.6	63.8	63.8	63.9	63.9	63.9	64.0	64.0	64.1	64.5
	31.6	61.8	62.9	63.9	64.6	64.8	65.1	65.2	65.3	65.4	65.4	65.4	65.5	65.5	65.6	66.0
	31.8	62.4	63.5	64.5	65.2	65.5	65.8	65.9	65.9	66.0	66.1	66.1	66.1	66.1	66.2	66.6
	32.1	62.9	64.1	65.0	65.8	66.0	66.3	66.4	66.4	66.6	66.6	66.6	66.7	66.7	66.7	67.1
0L 01101	,, ,,,,	02.07		0.5.0	03.0	00.0	00.5	00.4	00.4	00.0	00.0	00.0				
GE 5000	32.6	63.9	65.2	66.1	66.9	67.1	67.4	67.6	67.6	67.7	67.7	67.7	67.8	67.8	67.9	68.3
6E 450	32.9	64.6	65.8	66.8	67.5	67.8	68.1	68.2	68.2	68.3	68.4	68.4	68.4	68.4	68.5	68.9
GE 4FO	33.1	65.4	66.7	67.7	68.5	68.8	69.1	69.2	69.3	69.4	69.4	69.4	69.5	69.5	69.6	70.0
GE 3500	33.3	66.1	67.4	68.5	69.3	69.6	69.9	70.1	70.1	70.2	70.2	70.2	70.3	70.3	70.4	70.8
GE 3000	33.8	67.7	69.1	70.2	71.1	71.5	71.8	72.0	72.0	72.2	72.2	12.2	72.3	72.3	72.4	72.8
GE 2*00	34.2	69.4	70.9	72.0	73.1	73.5	73.9	74.1	74 - 1	74.3	74.4	74.4	74.4	74.4	74.5	74.9
GE 2000	34.4	70.7	72.3	73.4	74.5	74.9	75.4	75.7	75.7	76.0	76.0	76.0	76.1	76.1	76.2	76 • t
GE 1800	34.5	71.2	72.B	74.0	75.3	75.7	76.2	76.5	76.5	76.8	76.8	76.8	76.9	76.9	17.0	77.4
SE 1500	35.0	72.9	74.9	76.3	77.8	78.3	78.8	79.2	79.2	79.5	79.6	79.6	79.6	79.6	79.7	86-1
GE 1700	31 35.3	74.4	76.6	78.1	79.8	80.4	81.1	81.5	81.6	82.0	82.0	B2.D	82.1	82.1	95.5	82.6
GE 1000	35.4	75.8	78.2	79.8	82.1	82.7	83.7	84.2	64.3	84.7	84.8	84.8	84.9	84.9	85.0	85.4
	35.4	76.2	78.9	86.7	83.2	83.9	85.1	85.7	65.9	86.4	86.4	86.4	86.6	86.6	86.7	87.1
	35.4	76.7	79.5	81.6	84.3	85.0	86.2	86.9	67.1	87.6	87.7	87.7	87.8	87.9	88.0	80.4
	35.4	76.9	79.8	82.0	84.9	85.7	87.0	87.9	68.2	88.8	88.8	88.8	89.0	89.1	89.2	89.7
	35.4	77.0	80.0	82.3	85.3	86.3	87.8	88.9	69.2	90.0	90.1	90.1	90.3	90.3	90.4	90.9
0. (.0.									0.00	, , , ,	,,,,	,,,,	,,,	, 000	,,,,	
	35.4	77.1	80.3	82.7	85.9	87.0	88.8	90.1	90.6	91.6	91.8	91.8	92.0	92.1	92.2	92.7
	35.4	77.2	80.4	82.9	86.1	87,4	89.4	91.0	91.6	92.9	93.2	93.2	93.5	93.5	93.7	94.2
	35.4	77.2	80.4	83.0	86.3	87.6	89.8	91.8	92.6	94.3	94.7	94.8	95.1	95.2	95.5	96.0
	35.4	77.2	80.4	83.0	86.4	87.7	89.9	92.0	92.9	94.9	95.6	95.6	96.2	96.3	96.9	97.8
GE 100	35.4	77.2	80.4	83.0	86.4	87.7	89.9	92.0	93.0	95 • U	95.8	96.0	96.7	96.9	97.8	99.4
GE (1 35.4	77.2	80.4	83.0	86.4	87.7	89.9	92.0	93.0	95.0	95.8	96.0	96.7	96.9	97.0	106.0
			*****		• • • • •	*****	0717	72.04			,,,,,	*****				
					-		• •	. , • •								

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 729505 STATION NAME: MCCONNELL AFR KS

ST	ATION N	IUMBER:	724505	STATI	ON NAME:	MCCO	NNELL A	FBKS					OF REC				
												HONTH			(LST):		
	ILING	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • •	• • • • • •			IN STAT			• • • • • • •	• • • • • • •	•••••	• • • • • •	• • • • • • • • • • • • • • • • • • • •
		Gξ	GE	GE	6 E	GE	GE	GE	GE	GE	GE GE	GE.	G£	GΕ	GE	GE	GE
	EET I		6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	Ü
		-	_				-	_			_						_
													• • • • • • • • • • • • • • • • • • • •				
NO	CEIL	31.1	55.9	56.8	57.2	57.5	57.5	57.5	57.5	57.5	57.6	57.6	57.6	57.6	57.6	57.6	57.7
														•			
	200001		60.0	60.9	61.3	61.6	61.6	61.6	61.6	61.6	61.7	61.7	61.7	61.7	61.7	61.7	61.8
	18000		60.2	61.1	61.5	61.8	61.8	61.8	61.8	61.8	61.9	61.9	61.9	61.9	61.9	61.9	62.0
	160001		60.2	61.1	61.5	61.8	61.8	61.8	61.8	61.8	61.9	61.9	61.9	61.9	61.9	61.9	62.D
	14000		60.3	61.2	61.6	61.9	61.9	61.9	61.9	61.9	62.0	62.0	62.D	62.0	62.D	62.0	62.2
GE	150001	33.5	61 - 3	62.2	62.6	62.9	62.9	62.9	62.9	62.9	63.0	63.0	63.0	63.0	63.0	63.D	63.1
	100001	77 7	62.3	63.1	63.5	63.9	63.9	63.9	63.9	63.9	64.0	64.0	64.0	64.0	64.0	64.0	64.1
	9000		62.3	63.1	63.5	63.9	63.9	63.9	63.9	63.9	64.0	64.0	64.0	64.0	64.0	64.0	64.1
	80001		64.8	65.7	66.2	66.6	66.6	66.6	66.6	66.6	66.7	66.7	66 • 7	66.7	66.7	66.7	66.8
	7000 (66.1	67.0	67.5	67.8	67.8	67.8	67.8	67.8	68.0	68.0	68.0	68.0	68.D	0.84	68.1
	60001		66.6	67.4	68.0	68.3	68.3	68.3	68.3	68.3	68.4	69.4	68.4	68.4	68.4	68.4	68.5
GE	Scool	35.B	68.3	69.1	69.7	70.0	70.0	70.0	70.0	70.0	70.2	70.2	70.2	70.2	70.2	70.2	70.3
ĿΕ	45001	36.3	70.1	71.0	71.5	71.8	71.8	71.8	71.8	71.8	72.0	72.0	72.0	72.0	72.0	72.0	72.2
GΕ		36.7	71.5	72.5	73.0	73.3	73.3	73.3	73.3	73.3	73.5	73.5	73.5	73.5	73.5	73.5	73.7
GΕ		37.0	73.2	74.3	74.8	75.3	75.3	75.3	75.3	75.3	75.5	75.5	75.5	75.5	75.5	75.5	75.6
GΕ	30001	37.1	74.9	76.2	76.9	77.3	77.3	77.4	77.4	77.4	77.6	77.6	77.6	77.6	77.6	77.6	77.7
	25001	17 2	74 3		78.2	70 (70 4	78.7	70 7	70 -	•••	** *	78.9	78.9	78.9	78.9	79.0
UΕ			76.2 77.5	77.5 78.9	79.6	78.6 80.1	78.6 80.1	80.4	78.7 80.4	78.7 80.4	78 • 9 80 • 6	78.9 80.6	80.6	80.6	80.6	40.6	80.8
GE			78.5	80.G	86.6	81.2	81.2	81.5	81.5	81.5	81.7	81.7	81.7	81.7	81.7	81.7	81.8
GE		38.9	80.0	81.6	82.4	83.1	83.1	83.4	83.4	83.4	B3.7	83.7	83.7	83.7	83.7	83.7	83.8
ű.E		38.9	81.5	83.7	84.5	85.3	85.3	85 . 7	85.7	85.7	85.9	85.9	85.9	85.9	85.9	85.9	86.0
	•																
6 F	10001	39.1	84 - (1	86.1	87.4	88.3	88.3	88.7	88.8	66.8	89.0	89.0	89.0	89.0	89.0	89.0	89.1
ωË		39.1	84.4	87.0	88.6	89.5	89.7	90.4	90.5	90.5	90.8	90.8	90.8	90.8	90.8) J • B	90.9
GΕ		39.1	85.5	88.3	9 U • 4	91.4	91.6	92.6	92.6	92.8	93.0	93.1	93.1	93.1	93.1	93.1	93.2
G E		39.1	85.6	88.4	96.8	92.0	92.3	93.3	93.7	93.7	93.9	94.0	94.0	94.0	94.0	94.0	94.1
GE	eua l	39.1	85.7	88.6	91.3	92.7	92.9	94.3	94.6	94.6	94.8	94.9	94.9	94.9	94.9	94.9	95.1
6 E	5001	39.1	86.0	89.4	92.6	94.3	94.5	96.2	96.6	96.6	96.9	97.0	97.0	97.0	97.0	97.0	97.2
G E		39.1	86.0	89.5	92.8	95.4	95.6	97.4	98.2	98.2	98.5	98.6	98.6	98.6	98.6	98.6	98.8
GE		39.1	86.0	89.6	92.9	95.7	96.0	98.1	98.9	98.9	99.2	99.4	99.4	99.4	99.4	99.4	99.6
GE		39.1	86.0	89.6	92.9	95.9	96.2	98.3	99.1	99.1	99.6	99.7	99.7	99.8	99.8	99.8	100.0
6 €		39.1	86.0	89.6	92.9	95.9	96.2	98.3	99.1	99.1	99.6	99.7	99.7	99.8	99.8	99.8	100.0
-	•		-								_			-	-		
GΕ	JI	39.1	P6.U	89.6	92.9	95.9	96.2	98.3	99.1	99.1	99.6	99.7	99.7	99.8	99.8	99.8	100.0

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86 MONTH: MAR HOURS (LST): 0300-0500 ******************************** VISIBILITY IN STATUTE HILES CEILING GE GE 3 2 1/2 IN | GE FEET | 10 GE 5 GE GE GE 2 1 1/2 1 1/4 GE 1 GE GE GE 5/8 1/2 5/16 Ü 57.1 56.0 57.1 57.2 57.2 57.3 57.5 57.5 57.5 57.5 57.5 57.5 NO CEIL | 28.2 55.1 56.6 GE 200001 30.2 GE 180001 30.2 GE 160001 30.2 60.6 60.9 58.5 58.5 59.5 59.5 60.3 60.3 61.0 61.0 61.1 61.2 61.3 61.3 61.3 61.3 60.9 61.3 61.0 61.3 61.3 GE 140001 30.2 58.6 59.6 60.4 61.0 61.0 61.1 61.1 61.2 61.3 61.4 61.4 61.4 61.4 61.4 61.4 59.8 GE 120001 30.3 58.8 60.6 61.2 61.2 61.3 61.3 61.5 61.6 61.6 10000| 31.5 9000| 31.5 8000| 32.6 62.3 62.3 63.8 63.1 63.1 64.6 63.8 63.8 64.1 63.7 63.7 63.8 64.0 64.1 64.1 64 - 1 64.1 63.7 63.9 64.0 64.1 64.1 64.1 64.1 63.7 GE 62.8 65.2 65.3 65.3 65.6 65.6 70001 33.0 64.8 GE 66.6 67.2 PC001 33.3 65.4 66.2 67.0 67.2 67.2 67.2 67.2 50001 68.6 70.8 72.6 GE 33.5 67.6 68.2 70.3 72.2 68.2 70.3 68.3 68.3 68.4 68.5 68.6 70.8 68.6 68.6 68.6 GE 4500| 34.1 4000| 34.4 67.4 68.7 70.4 72.3 70.4 10.5 70.6 70.8 72.6 70.8 70.8 70.8 69.0 70.5 71.4 72.2 72.4 72.5 72.6 72.6 72.6 72.6 35001 34.4 71.7 73.4 73.4 73.8 73.9 73.9 73.9 73.9 73.9 6 F 70.0 72.6 73.5 73. . 73.9 3000 | 34.7 76.5 75.5 76.3 77.8 GE 2500| 35.1 2000| 35.3 1800| 36.2 72.3 73.6 74.5 74.3 75.2 76.7 76 • 7 77 • 6 79 • 2 76.9 77.8 79.5 76.9 77.8 79.6 77.0 77.1 77.2 77.2 78.8 79.7 81.6 78.2 79.9 81.8 78.1 79.8 78 · 2 79 · 9 78.2 79.9 78.2 79.9 78.2 79.9 76.2 79.9 79.2 GE 15001 36.7 78.4 79.8 81.2 81.8 81.8 81.8 GΕ 12001 36.9 78.3 80.6 82.3 83.7 83.7 83.9 84.0 84.1 84.3 84.3 64.3 84.3 86.0 87.8 89.1 86.9 89.1 90.4 1000| 37.3 80.3 81.5 82.8 84.4 86.9 89.1 86.9 89.1 86.1 88.1 86.3 88.5 86.5 86.8 89.0 86.9 89.1 86.9 84.1 88.8 89.1 90.4 91.3 G£ 86.2 85.6 GF POD | 37.6 82.3 89.4 89.8 89.9 90.1 90.3 90.4 90.4 90.4 96.4 7301 37.7 90.0 90.2 90.6 90.8 91.0 91.2 91.3 91.3 91.3 91.3 91.3 82.5 88.2 GΕ 500 | 37.8 400 | 37.8 300 | 37.8 93.4 94.9 96.2 94.5 96.7 98.1 90.1 92.7 93.7 94.7 93.7 95.6 96.9 93.9 95.8 97.1 94.2 96.3 97.7 94.3 96.5 97.8 94.4 GE 83.4 87.2 92.9 94.3 94.4 94.4 83.5 87.3 87.5 90.4 93.9 95.1 96 • 5 97 • 8 96.6 98.0 96.6 98.0 96.6 98.0 GE 2001 37.8 83.8 87.5 90.9 94.8 95.2 96.5 97.3 97.5 98.6 98.7 98.7 98.9 98.9 98.9 99.0 97.3 97.6 99.2 99.2 100.0 GE 1001 37.8 83.8 87.5 90.9 94.8 95.2 96.5 98.7 98.9 98.9 99.2

TOTAL NUMBER OF OBSERVATIONS:

83.8

87.5

D1 37-8

GΕ

930

94.8

95.2

96.5

97.3

97.6

98.7

98.9

0A.9

99.2

99.2

99.2 100.0

96.9

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: MAR HOURS(LST): 0600-0800 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS CEILING VISIBILITY IN STATUTE MILES I GE GE GE GE GE GE GΕ G€ GE GE GE 2 1 1/2 1 1/4 GE GE FEET | 10 3 2 1/2 3/4 5/16 NO CEIL | 25.3 49.0 50.0 51.6 52.3 52.5 52.6 55.1 55.3 55.3 56.9 57.1 57.6 57.8 57.7 58.0 58.3 58.5 58.5 58.3 58.5 58.5 54 • 1 54 • 3 57.7 58.0 58.2 58.2 58.4 58 • 2 58 • 4 58.3 58.5 200001 28.4 GE 58.0 58.5 180001 28.5 58.6 58.6 58.6 58.7 160001 28.5 54.3 57.1 57.8 58.0 58 • D 58.5 58.5 58.6 GE 140001 28.5 54.4 55.4 57.2 58.0 58.1 58.1 58.3 58.5 58.5 58.6 58.6 58.6 58.6 58.7 55.1 GE 120001 28.8 56.D 58.6 58.7 58 - 9 59.1 100001 0000| 29.8 9000| 29.8 8000| 31.3 57.0 57.2 59.1 59.9 60.1 62.0 60.6 60.9 62.8 60.9 61.1 63.0 60.9 61.1 63.0 61.1 61.3 63.2 61.3 61.5 63.4 61.3 61.5 63.4 61.4 61.6 63.5 61.4 61.6 63.5 58.1 58.3 61.4 61.6 63.5 61.4 61.6 63.5 61.5 61.7 63.7 61.5 6 F 60.2 63.7 32.5 7000 GE 60001 32.6 61.2 64.9 65.2 65.2 65.4 65•6 65.6 65.7 65.7 65.7 65.7 65.8 GE GE 5000 | 32.7 4500 | 32.9 63.5 65.6 66.3 67.6 69.0 66.7 68.0 66.7 68.1 69.6 66.9 68.3 69.8 67.1 68.5 70.1 67.2 68.6 70.2 67.2 68.6 70.2 67.2 68.6 63.8 64.9 65.7 68.6 70.2 71.0 68.5 70.1 68.7 70.3 68 · 1 68.3 69.5 70.2 GΕ 40001 33.2 66.0 70.2 70.9 70.5 71.0 GE 35001 33.2 69.0 69.8 70.3 70.9 71.0 71.0 71.1 66.8 71.1 GE 25001 33.7 69.1 72.5 72.9 73.0 73.2 73.5 73.5 73.7 73.7 73.8 GE 2000| 33.8 1800| 34.3 69.0 70.4 71.3 73.9 73.8 74.6 74.2 75.1 74.3 75.2 74.5 75.4 74.8 74.8 75.7 74.9 75.8 74.9 75.8 74.9 75.8 74.9 75.8 75.1 75.9 75.1 1500 | 34.7 72.2 73.8 77.2 77.6 78.0 78.5 78 - 6 78.6 78.6 78.6 78.7 G E 12001 34.9 78.5 80.0 80.3 80.5 80.9 80.9 81.0 81.0 81.0 81.0 81.1 81.1 GE GE 1000| 35.5 75.7 78.0 81.1 82.4 83.7 82.9 84.3 83.2 84.8 83.5 85.2 84.0 84.0 85.6 84.1 85.7 84.1 85.7 84 • 1 85 • 7 84.1 84.2 ~5.8 84.2 85.8 76.6 85.6 8001 35.5 7001 35.6 83.2 84.3 84.8 85.6 87.2 86.1 87.7 86.9 88.7 87.1 87.2 GE 77.0 80.0 86.5 86.9 87.1 87.1 87.1 87.2 GE 80.8 88.3 88.9 G E 77.6 81.4 87.6 89.8 90.4 90.9 90.9 91.3 91.3 6001 35.6 5001 35.6 4001 35.6 82.0 82.7 85.9 86.7 90.0 91.1 91.8 91 • 2 92 • 8 94 • 1 92.2 93.8 95.1 92.6 94.3 95.9 92.7 93.1 94.8 93.2 93.2 95.1 93.2 95.1 93.3 95.2 88.8 6 E 78.0 95.2 700 | 35.6 78.0 82.8 87.1 90.5 96.B 96.6 96.7 96.8 96.8 96.9 GE 2001 35.6 78.0 82.8 87.1 90.5 91.8 94.3 95.5 96.3 96.7 97.3 97.4 97.5 97.5 98.1 98.2 1001 35.6 87.1 99.4 78.0 82.8 90.5 98.5

97.7

96.9

97.8

98.4

98.6

99.5

100.0

91.8

94.3

95.5

96.3

90.5

TOTAL NUMBER OF OBSERVATIONS:

78.0

87.1

82.8

01 35.6

GE

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VFRSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86 MONTH: MAR HOURS(LST): 0900-1100 VISIBILITY IN STATUTE MILES CEILING GE GE 3 2 1/2 GE 5 GE 4 GE GE GE 2 1 1/2 1 1/4 G ξ 5 / 8 GE 5/16 GE 1/4 GE G.E GE O IN CE 1 3/4 1/2 6 49.7 50.6 51.2 51.2 NO CEIL | 26.0 51.0 51.2 51.2 51.2 51.2 51.2 51.2 51.2 51.2 51.2 51.3 57.3 57.5 57.6 57.3 57.5 57.3 57.5 57.6 57.3 57.3 57.3 GE 2000ml 29.4 55.5 56.8 57.5 57.3 GE 180001 29.4 GE 160001 29.4 55.7 55.8 57.0 57.1 57.3 57.5 57.6 57.5 57.6 57.5 57.6 57.5 57.6 57.5 57.5 57.6 57.5 57.6 57.6 57.7 57.4 57.6 57.6 57.6 58.1 140001 29.7 56.2 57.7 57.5 57.8 58.1 58.1 58.1 58.1 58.1 58.1 58.1 58.1 59.6 GE 120001 30.5 59.0 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.7 GE 10000| 31.7 GE 9000| 31.8 GE 8000| 32.2 GE 7000| 32.7 61.5 61.5 61.8 63.3 61.5 61.8 61.8 61.5 61.8 61.5 59.6 60.9 61.5 61.5 61.5 61.5 61.5 61.1 61.8 61.8 59.8 61.5 61.8 61.8 61.9 61.8 63.0 63.3 63.3 61.1 63.2 63.3 63.3 63.3 63.3 63.4 63.2 61.8 63.9 64.1 64.2 64.2 64.2 64.2 64.2 64.2 64.2 64.2 64.2 64.3 64.2 5000| 33.4 4500| 33.4 4000| 33.8 66.3 65.8 66.1 66.3 66.3 67.0 68.6 GE 63.5 66.3 66.3 66.3 66.3 66.5 66.3 GE 64.2 65.8 66.5 66.8 67.0 68.6 67.0 67.0 68.6 67.0 68.6 67.0 67.1 68.7 68.4 68.6 68.6 68.6 66.6 6 E 35001 34.0 67.8 69.0 69.2 69.5 69.5 69.5 69.5 69.5 69.5 69.5 69.5 69.5 69.6 70.2 30001 34.1 67.2 70.4 70.6 70.6 70.6 70.6 68.9 70.6 70.6 70.6 70.6 70.6 70.8 70.0 72.9 73.9 71.3 74.4 75.4 79.9 2500| 34.4 2000| 35.2 1900| 35.5 25001 68.3 70.8 74.9 73.9 71.7 71.9 71.9 75.1 71.9 71.9 75.1 71.9 75.1 71.9 75.1 71.9 75.1 72.0 75.2 74.8 75.9 76.1 76.1 76.1 GE 71.7 74.8 76.1 76.1 76.1 76.1 76.1 76.1 76.2 79.1 80.4 15001 36.0 80.6 80.6 80.6 77.4 80.6 8D.6 80.6 80.6 GE 80.6 80.6 80.8 12001 36.7 77.8 80.6 82.6 83.4 84.1 troot 78.9 86.5 87.7 86.5 87.7 86.5 86.5 87.7 86.5 86.5 87.7 86.5 87.7 86.5 87.7 86.5 87.7 86.6 86.2 9001 36.7 79.2 82.7 87.1 ĿΕ 84.7 A001 36.7 79.8 83.4 86.0 89.4 90.1 90.1 90.1 90.1 90.1 90.1 90.1 90.1 90.1 90.2 90.6 91.5 93.8 91.7 GΕ 700 | 36.8 80.4 84.3 87.1 89.4 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.8 6001 36.8 94.5 *00| 36.8 400| 36.8 300| 36.8 91.8 92.8 93.2 95.3 96.8 97.6 Gε 80.9 85.5 88.7 89.4 93.3 94.3 94.5 95.2 95.2 95.3 95.3 96.8 95.5 97.1 95.5 95.6 97.2 95.7 GE 80.9 86.0 95.5 96.2 96.3 96.7 97.5 97.1 97.3 94.7 98.1 98.1 98.3 86.0 89.4 96.8 97.6 96.4 υE 80.9 2001 36.8 86.0 98.6 98.6 99.5 1001 36.8 80.9 98.6

96.8

98.2

TOTAL NUMPER OF OBSERVATIONS: 930

86.C

93.2

94.7

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

-	-				ON NAME:											1200-14	00
	LING	• • • • • •		• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •			IN STATI			• • • • • • •		• • • • • • •	• • • • • • •	• • • • • • • • • • • •
		GE	GE	GE	GE	GE	GE	GE	GF	6£	GE	GE	GΕ	GE	GE	GE	6E
	ËT İ		6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	G
-																	
											• • • • • • •	•					
NO	CEIL I	28.7	49.9	50.2	50.2	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50 • 3	54.3
GE	200001	32.5	59.1	59.6	59.6	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
	180001		59.7	60.1	66.1	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60 • 2	60.2	60.2	60.2	6C.2
	160001		60 • C	60.4	611.4	60.5	60.5	60.5	60.5	6n.5	60 - 5	60.5	60.5	60.5	60.5	60.5	64.5
GE	140001	33.2	60.4	60.9	66.9	61.0	61.0	61.0	61.0	61.0	61.0	61.0	61.0	61.0	61.0	61.0	61.0
GE	12000 [33.7	61.1	61.5	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
																-	_
БE	100001	34.3	62.3	62.7	62.7	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.6
	3L001		62.9	63.3	63.3	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
G€	80001		64.1	64.5	64.5	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
G.E.	7 npo		65.3	65.7	65.7	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65 • 6
GΕ	60001	36.2	66.2	66.7	66.7	66 • 8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	60.8
																	4.3. 1
GE	5000 l 4500 l		67.4 68.1	68.G 68.6	68.0 68.6	68.1	58.1 68.7	68.1	68.1 68.7	68.1 68.7	68.1 68.7	68 • 1 68 • 7	68 • 1 68 • 7	68.1 68.7	68.1 68.7	68.1 68.7	68.1 68.7
G E	40001		69.5	70.1	70.1	70.2	70.3	68.7 70.3	70.3	70.3	70.3	70.3	70.3	70.3	70 - 3	70.3	70.3
GE	35001		71.4	72.0	72.0	72.2	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3
GE	30001		73.0	73.7	73.7	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
0	31.001	30.0	,,,,,	, , , ,		,,,,	, 3.,	13.4	13.7	, , ,	1347	1 3 4 7			13.7		
G.E	25001	38.5	74.4	75.3	75.3	75.4	75.5	15.5	75.5	75.5	75 • 5	75.5	75.5	75.5	75.5	75.5	75.5
űĚ	2000		78.9	80.8	80.9	81.2	81.3	81.3	81.3	81.3	81.3	81.3	81.3	61.3	61.3	81.3	81.3
GE	18601		79.9	81.9	82.0	82.4	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	62.5	82.5
GE	15001		82.7	85.5	86.1	86.6	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	66.9	80.9
GE	12001	40.8	84.6	87.8	88.6	89.1	89.6	89.8	89.8	8 • 9 8	89.8	89.8	89.8	89.8	89.8	69.8	89.8
GΕ	10001		85.1	88.3	89.2	90.2	96.8	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91-1	91.1
GE		40.9	85-6	88.8	89.9	91.0	91.5	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	•1 • 8	91.8
GE		4C.9	86.2	89.6	90.9	92.3	93.D	93.3	93.3	93.4	93.4	93.4	93.4	93.4	93.4	+3.4	93.4
GE		40.9	87.0	90.4	91.8	93.7	94.8	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE	6001	40.9	87.2	91.0	92.4	95.3	96.7	97.2	97.2	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE	5001	40.9	87.3	91.2	92.6	95.8	97.2	97.8	97.8	98.1	98.1	98.1	98.1	98.1	98.1	98.1	96.1
GE		40.9	87.3	91.5	92.9	96.2	97.7	98.4	98.6	99.1	99.4	99.4	99.4	99.4	99.4	99.4	94.4
GE		40.9	87.3	91.5	92.9	96.2	97.7	98.4	98.6	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE		40.9	87.4	91.6	93.0	96.3	97.8	98.5	98.7	99.4	99.7	99.9	99.9	100.0	100.0	100.0	100.0
GΕ		40.9	87.4	91.6	93.0	96.3	97.8	98.5	98.7	99.4	99.7	99.9	99.9	100.0	100.0	100.0	100.0
GF	r i	40.9	87.4	91.6	93.0	96.3	97.8	98.5	98.7	0 U (00 7	90 0	00 0	100 0	100.0	100.0	*00.0
0.2		70.7	01.4	41.0	73.0	70.3				77.4			77.7	100.0	400.0	100.0	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

, T A 1	ION	-	R: 724505					-				MONTH		HOURS	(F21):	1530+17	CO
LEIL			• • • • • • • • •	• • • • • • •	•••••	• • • • • •	• • • • • • •	v 1 S 1	BILITY	IN STAT	UTF MI	15	• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • • • •
IA FEE	ŧ	GE	GE 6	G E 5	٥٤ 4	G E 3	GE 2 1/2	GE	6F 1 1/2	GE	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 5/16	GE 1/4	UE D
	• • • •	• • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •
٧0 C	EIL	1 27.	46.2	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9
ı E	0000	1 33.	57.7	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58 • 4	58.4	58.4	58.4	58.4	58.4	58.4
ξĺ	8000	1 33.	58.4	59 · D	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	54.0
E 1	6000	1 33.	58.8	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
5F 1	4000	1 23.	7 59.4	60.1	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2
∍€ 1	2000	34.	60.3	61.1	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
.£ 1	ucga	1 35.	63.1	64.0	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1
эE	9000	35.	63.8	64.6	64.7	64 • 7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7
ΣE	8,000	1 35.	65.5	66.3	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5
٦٠	7000	36.	66.9	67.7	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	ь7.8	67.8
3 €	6000	1 37.	67.5	68.4	68.5	68.5	68.5	68.5	68.5	68.5	68.5	69.5	68.5	68.5	68.5	68.5	68.5
S E	5000	37.	68.1	68.9	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.U	69.0	69.0
G E	4500	1 37.	68.7	69.6	69.7	69.7	69 • 7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
JE	4000	38.	70.5	71.7	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.6	71.8	71.5	71.8	71.8
ıξ	3500	1 39.	72.3	73.4	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
5 E	3000	1 39.	74.6	75.8	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0
ιE	2500	1 41.4	79.2	80.9	81.2	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3
, E	2000	41.	82.5	84.5	85.4	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7
υF	1800	41.	83.1	85.2	86.0	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
٠E		41.		87.6	88.9	89.5	89.5	89.5	89.6	89.6	89.7	89.7	89.7	89.7	89.7	89.7	84.7
ı E	1200	41.	, A6.7	89.4	96.9	91.6	91.6	91.6	91.7	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8
5 E	1000	41.	87.1	89.9	91-6	92.8	92.9	93.2	93.5	93.3	93.5	93.5	93.5	93.5	93.5	93.5	93.5
ĿΕ		1 41.		90.4	92.4	93.7	93.9	94.3	94.4	94.4	94.6	94.6	94.6	94.6	94.6	94.6	94.6
٦٠	800	41.	7 88.4	91.6	94.0	95.4	95.7	96.1	96.2	96.2	96.5	96.5	96.5	96.5	96.5	96.5	96.5
ΣE		41.		91.8	94.2	95.B	96.1	96.8	97.0	97.0	97.4	97.4	97.4	97.4	97.4	97.4	97.4
5 f.	€00	41.	88.5	91.9	94.3	96.1	96.6	97.4	97.6	98.0	98.4	98.4	98.4	78.4	98.4	98.4	90.4
, F	500	1 41.	88.5	91.9	94.3	96.2	96.9	97.7	98.5	98.9	99.4	99.4	99.4	99.4	99.4	99.4	99.4
∫ f		1 41.		91.9	94.3	96.3	97.0	97.8	98.7	99.2	99.7	99.7	99.7	99.7	99.7	99.7	99.7
, E		41.		91.9	94.3	96.3	97.0	98.0	98.8	99.5	99.9	99.9	99.9	99.9	99.9	99.9	94.9
, E		41.		91.9	94.3	96.3	97.0	98.0	98.8	99.5	100.0	100.0	100.0	100.0	100.0	190.0	100.0
, E	100	41.	88.5	91.9	94.3	96.3	97.0	98.0	98.8	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0
ı E	0	J 41.	88.5	91.9	94.3	96.3	97.0	98.0	98.8	99.5	100.0	100.0	100.0	100.0	100.0	100.0	10ս.ը

TOTAL NUMPER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86

MONTH: MAR HOURS(LST): 1800-2000 ILING VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 GE GE 1/2 5/16 σ 5/8 1/4 6 NO CETE 1 28.6 49.5 49.9 49.9 GF 200001 32.9 59.7 66.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 611.3 60.0 60.3 UE 18000 33.0 UE 16000 33.0 61.0 59.9 60.2 6 C • 5 60.5 60.5 60.5 60.5 60.5 60.5 60.5 60,5 60.5 60.5 60.5 60.3 61.0 61.0 61.0 61.2 60.6 61.0 61.0 61.0 61.0 61.0 61.0 61.0 61.0 140001 33.1 60.5 61.2 61.2 120001 34.0 62.7 63.1 63.1 63.1 63.1 63.1 63.1 63.1 63.1 63.1 65.9 65.9 100001 34.4 65.9 65.9 65.9 65.9 ĢΕ 9000 | 34.4 8000 | 35.1 65.9 69.0 65.9 t. F 65.2 65.5 65.9 65.9 65.9 65.9 65.9 65.9 65.9 65.9 65.9 65.9 65.9 68.3 68.6 69.1 69.1 69.1 69.1 69.1 69.1 69.1 69.1 69.1 70.4 G E 70001 35.8 69.5 69.8 70.3 70.4 70.4 70.4 70.4 70.4 70.4 70.4 70.4 70.4 70.4 70.4 60001 36.0 70.8 70.8 70 . 8 70.8 70.8 Ų.₽ 50001 36.3 45001 36.6 40001 37.4 71.6 72.6 75.4 70.6 71.0 71.5 71.6 71.6 71.6 71.6 71.6 71.6 71.6 71.6 71.6 71.6 72.6 72.6 71.6 74.4 74.7 75.3 75.4 75.4 75.4 75.4 75.4 75.4 75.4 úΕ 75.4 75.4 75.4 3 00 | 37.8 76.8 76.8 S E 30001 38.4 78.2 78.5 79.0 79.2 79.4 79 - 4 79.4 79.4 79.4 79.4 79.4 79.4 74.4 25001 39.4 84.6 84.6 84.6 87.5 83.9 84.5 84.6 84.6 84.6 84.0 84-6 87.5 87.5 87.5 87.5 87.5 87.5 υE 20001 39.8 84.1 84.7 85.2 86.3 87.2 87.5 1001 40.0 85.8 87.0 88.2 88.2 88.2 89.9 88.2 88.2 88.2 88.2 88.2 89.9 88.2 89.9 88.2 84.9 85.9 89.9 89.9 ьE 15001 40.0 87.1 88.7 89.6 89.9 10001 40.2 92.7 93.8 95.3 93.4 93.4 93.5 93.5 93.5 43.5 93.5 88.0 93.0 93.4 93.5 GE 89.4 91.3 900 | 40.3 800 | 40.3 84.3 90.6 92.0 94.1 94 • 7 94.7 95.1 96.8 94.8 95.1 95.1 95.1 95.1 95.1 95.1 96 8 96.6 96.8 96.8 96.8 96.8 96 - 8 t, E 7001 40.3 90.9 93.3 96.2 96.7 97.5 98.0 98.4 49.4 98.4 98.4 99.0 99.0 99.0 6 E 6001 40.3 88.3 90.9 93.3 96.3 97.D 98.2 98.6 98.8 99.0 99.0 99.0 99.0 97.1 97.2 97.2 97.2 99.0 99.1 99.2 100 | 40.3 90.9 93.3 96.3 96.5 98.3 98.4 99.4 99.7 99.7 99.7 99.7 99.7 99.7 59.7 93.3 99.5 99.9 99.9 400 | 40.3 99.9 88.3 88.3 90.9 6 E 90.9 96.5 98.4 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 98.4 100.0 90.9 93.3 96.5 99.2 99.6 100.0 100.0 6E 2001 40.3 88.3 100.0 100.0 100.0 100.0 1001 40.3 97.2 99.2 100.0 100.0 100.0 100.0 130.0 100.0 100.0 93.3 96.5 98.4 99.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 01 40.3 88.5 93.9 6 E

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VFRSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: MAR HOURS(LST): 2100-2300 CEILING VISIBILITY IN STATUTE MILES SE UE GE GE GE UE GE 5 4 3 2 1/2 2 1 1/2 1 1/4 IN | GE FEET | 10 GE. GΕ GE GΕ GE GE GE 1/2 5/16 O. NO CETE | 31.9 54.2 54.3 54.3 54.4 54.4 54.4 54.4 54.4 54.4 54.4 GE 20000 | 33.4 GE 18000 | 33.4 GE 16000 | 33.4 GE 14000 | 33.4 60.4 60 • 4 60 • 4 60.2 60.3 60.3 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.2 60.3 60.4 60.4 60.4 60.6 60.4 60.4 60.3 60.4 60.4 60.4 60.4 60.4 60.4 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 66.6 60.5 60.6 60.4 60.5 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 66.6 GE 12000 34.2 61.7 61.7 63.9 63.9 65.8 GE 10000| 34.8 GE 9000| 34.8 GE 8000| 35.4 63.7 63.9 63.9 63.9 63.9 65.8 63.9 63.9 63.9 63.8 63.8 63.9 63.9 63.9 63.9 63.9 63.9 63.9 63.9 63.9 65.5 65.6 65.8 65.8 65.8 65.8 65.6 65.6 65.8 65.8 65.8 GE 7000 35.5 66.3 66.5 66.5 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 GE 60001 35.6 66.7 66.7 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 5000 | 36.6 4500 | 37.0 68.9 70.1 72.7 69.D 70.2 72.8 69.0 69.2 70.4 73.0 69.2 70.4 69.2 70.4 69.2 70.4 69.2 70.4 73.0 69.2 70.4 69 • 2 70 • 4 69.2 70.4 69.2 70.4 69.2 70.4 69.2 70.4 69.2 70.4 4000| 37.8 3500| 37.8 73.0 74.5 GF 72.8 73.0 73.0 73.0 73.0 73.0 73.0 73.0 73.0 73.0 GE 74.5 74.1 74.3 74.5 74.5 74.5 74.5 30001 38.0 77.1 2500| 38.6 2000| 39.6 1900| 39.8 81.5 84.8 85.5 81.5 84.9 85.6 81.5 84.9 85.6 79.8 82.5 82.9 81.2 84.4 85.1 81.5 84.9 85.6 81.5 84.9 85.6 6 E G E G E 80.6 83.4 84.1 81.5 81.5 81.5 81.5 84.9 91.5 81.5 84.9 85.6 81.5 84.9 85.6 84.8 85.5 84.9 85.6 84.9 85.6 84.9 85.6 85.6 88.0 GE 15001 40.2 84.5 85.8 87.0 87.7 87.7 88.0 88.0 88.0 BB.D 88.0 88.0 88.0 66.D 68.D ĿΕ 12001 40.3 88.1 86.8 89.4 91.3 92.5 94.0 91.9 93.4 95.2 92.2 93.7 95.5 92.2 93.7 95.5 10001 40.5 87.5 89.0 90.4 91.3 92.2 92.2 92.2 92.2 92.2 92.2 92.2 900| 40.6 P00| 40.6 88.1 88.7 89.9 93.7 93.7 93.7 93.7 95.5 93.7 G E 92.7 94.0 95.5 95.5 95.5 700 | 40.6 91.1 97.0 97.0 97.0 97.0 97.0 97.0 97.0 ÚΕ 6001 40.6 91.6 94.0 95.8 95.8 97.4 98.3 98.3 98.3 98.3 98.3 98.3 91.6 91.6 91.6 96.2 96.2 96.5 99.1 99.2 99.7 5001 40.6 89.6 96.2 98.3 98.3 99.1 99.2 99.7 99.7 99.2 99.7 94.3 99.2 99.7 99.2 99.7 99.2 99.2 99.7 99.2 99.2 4001 40.6 G.F ₹001 40.6 89.8 96.5 98.5 96.5 98.5 7031 48.6 89.8 91.6 94.3 96.5 99.7 99.8 100.0 100.0 100.0 100.0 100.0 100.0 100 . D 01 40.6 98.5 99.7 89.8 91.6 24.3 96.5 96.5 99.7 99.8 100.0 100.6 100.0 100.0 100.0 100.0

TA NEMBER OF ORSERVATIONS: 950

PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

	-		724505					_				PEPIOD Month				ALL	
	LING	• • • • • •	•••••		• • • • • • •	• • • • •	• • • • • •			IN STATE			• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
F E	N E7		GE 6	GE 5	GE 4		GE 2 1/2	GE	GE 1 1/2	GE	GE 1	GE 3/4	ն է 5 / 8	GE 1/2	GE 5/16	GE 1/4	GE O
	CEIL I		51 • 2	51.8	52.2	52.4	52.4	52.5	52.5	52.5	52.5	57.6	52.6	52.6	52.6	52.6	52.6
υ <u>ε</u> σε σε	200001 180001 160001 140001	31.7 31.7 31.9	58 • 1 58 • 4 58 • 5 58 • 8	58.8 59.1 59.3 59.5	59.2 59.5 59.7 60.0	59.5 59.8 60.0 60.2	59.5 59.8 60.0 60.3	59.5 59.8 60.0 60.3	59.6 59.8 60.0 60.3	59.6 59.9 60.1 60.3	59.6 59.9 60.1 60.4	59.7 59.9 60.1 60.4	59.7 59.9 60.1 60.4	59.7 59.9 60.1 60.4	59.7 59.9 60.1 60.4	59.7 59.9 60.1	54.7 60.0 60.2 60.4 61.4
G E	120001 100001 90001	33.2	59.8 61.8 62.0	60.5	63.0	63.3	63.3	63.3	63.4	63.4	63.4	63.5	63.5	63.5	63.5	63.5	63.5
6 E 6 E 6 E	90001 90001		63.9 65.0 55.6	64.6 65.8 66.4	65.2 66.4 66.9	65.5 66.7 67.2	65.5 66.7 67.3	65.5 66.7 67.3	65.6 66.7 67.3	65.6 66.8 67.4	65.6 66.8 67.4	65.6 66.8 67.4	65.6 66.8 67.4	65.6 66.8 67.4	65.6 66.8 67.4	65.7 66.8 67.4	65.7 66.9 67.5
GE GE GE	5000 4500 4000 3500	35•6 36•1 36•4	66.9 68.0 69.7 71.1	67.7 68.8 70.7 72.0	66.3 69.4 71.3 72.7	68.6 69.7 71.6 73.1	68.6 69.8 71.7 73.2	68.7 69.8 71.8 73.2	68.7 69.9 71.8 73.3	69.7 69.9 71.9 73.3	68.8 69.9 71.9 73.3	68.8 70.0 71.9 73.4	68,8 70.0 71.9 73.4	68.8 70.3 71.9 73.4	68.8 70.0 71.9 73.4	68.8 70.0 71.9 73.4	68.8 70.0 72.6 73.4
GE GE	3000 2500 2000	37.2	72.9 75.0 77.3	74.0 76.3 78.9	74.8 77.2 80.0	75.2 77.7 80.6	75.3 77.8 80.8	75.4 77.9 80.9	75.4 78.0 80.9	75.4 78.0 81.0	75.5 78.1 81.0	75.5 78.1 81.0	75.5 78.1 81.0	75.5 78.1 81.0	75.5 78.1 81.0	75.5 78.1 81.0	75.6 75.1 81.1
G E G E G E	1800 1500 1200	38.2 38.5	78.2 80.2 81.9	79.9 82.2 84.1	86.9 83.5 85.7	81.6 84.3 66.6	81 • 7 84 • 5 86 • 8	81.9 84.7 87.1	81.9 84.8 87.2	81.9 64.8 67.2	82.0 84.9 87.3	82.0 84.9 87.3	82.0 84.9 87.3	82.0 84.9 87.3	82.0 84.9 87.3	62.0 84.9 87.3	82.1 84.9 87.3
6 E 6 E 6 E	1003	39.0 39.1 39.1 39.1	83.3 83.9 84.5 84.9	85.7 86.6 87.5 87.9	87.4 88.5 89.7 96.4	88.6 89.8 91.3 92.3	88.9 90.1 91.8 92.9	89.3 90.7 92.4 93.7	89.4 90.8 92.6 94.0	89.5 90.9 92.7 94.1	89.6 91.0 92.8 94.2	89.6 91.1 92.9 94.3	89.6 91.1 92.9 94.3	89.6 91.1 92.9 94.3	89.6 91.1 92.9 94.3	89.6 91.1 92.9 94.3	69.6 91.1 92.9 94.3
GE GE	500 [39.1 39.1 39.1	85.1 85.3 85.3	88.4 88.7 88.9	91.0 91.5 91.8	93.3 94.0 94.6	93.9 94.8 95.4	95.9 95.7	95.3 96.5 97.4	95.5 96.7 97.7	95.7 96.9 98.0	95.8 97.0 98.1	95.8 97.0 98.1	95.8 97.0 98.2	95•8 97•0 98•2	95.8 97.1 98.2	95.8 97.1 96.3
ς Ε G Ε	200 l	39.1 39.1 39.1	85.3 85.3 85.3	89.0 89.0 89.0	91.9 91.9 91.9	95.0 95.0 95.0	95.8 95.8 95.8	97.2 97.3 97.3	98.1 98.1 98.1	98.4 98.5 98.5	98 - 7 99 - 1 99 - 1	99.8 99.3 99.4	98.8 99.3 99.4	98.9 99.4 99.6	98.9 99.5 99.6	98.9 99.6 99.8	99.0 99.6 100.0
G E	01	39.1	85.3	89.0	91.9	95.0	95.8	97.3	98.1	98.5	99.1	99.4	99.4	99.6	99.7	99.6	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STA	N NOIT	UMRER:	724505	STATE	ON NAME:	HCCO	NNELL AF	BKS				PERIOD MONTH	OF REC			0000-02	00
		• • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • •	• • • • • •		071 172	IN STATE		• • • • • • •		• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • • •
	LING N I	G£	G€	GE	G.E	GE	GE	GE	GE	GE	95 30	E S GE	GE	GE	GE	GE	ŭ€.
	N I		6	UL 5	U		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	0
-		-	_								_			_			
• • •		• • • • • •	• • • • • • •	•••••	• • • • • • •		•••••		• • • • • • •	•••••		• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • •
N O	CEIL I	36.3	61.5	62.3	62.7	62.8	62.0	62.8	62.8	62.8	62.8	62.8	62.6	62.8	62.8	62.8	62.8
GΕ	200001	38.2	66.7	67.2	61.0	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7
	180001		66.9	67.4	67.8	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9
GΕ	160001	38.4	66.9	67.4	67.8	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9
ÜE	140001	38.4	66.9	67.4	67.8	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9	67.9
GE	120001	38.8	67.7	68.2	68.6	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	66 • 7
GE	100001	39.0	69.6	70.1	70.4	70.6	70.6	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	76.7
GE	90001	39.1	69.7	70.2	76.6	70.7	70.7	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8
	80001		71 - 6	72.3	72.7	72.8	72.8	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9
GE	70001	40.2	72.8	73.3	73.7	73.8	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
GΕ	6000]	40.6	73.7	74.2	74.6	74.7	74.7	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
	Conni		75.1	76.0	7	. .	•	7, 7	, .		7. 7	7. 7	76.7	76.7	76.7	76.7	76.7
GE GE	50001 45001		76.4	77.3	76.4 77.8	76.6 78.0	76.6 75.U	76.7 78.1	76•7 78•1	76•7 78•3	76.7 78.1	76.7 78.1	78.1	78.1	78 - 1	78.1	76.1
GE	4000		78.8	79.7	80.2	80.4	80.4	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
GE	35001		80.1	81.0	81.6	81.8	81.8	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9
GE	30001		81.8	82.9	83.6	83.9	83.9	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0
• •	J. 30,		0		03.0		0,00	0	• • • • • • • • • • • • • • • • • • • •								
GE	25001	42.9	82.6	83.7	84.3	84.9	84.9	85.0	85.0	85.D	95.D	85.O	85.0	85.0	85.0	85.n	85.0
ĞÊ	20001		84 . 8	86.1	86.8	87.3	87.3	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
GE	10001	43.3	85.6	86.9	87.6	88.1	88.1	68.2	88.2	68.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2
GΕ	1500	43.4	86.8	88.1	86.9	89.4	89.4	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7
6 E	12001	43.9	87.9	89.3	96.3	90.9	90.9	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE	10001	7	89.8	91.7	92.8	93.3	93.3	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6
68		44.6	90.6	92.8	94.0	94.9	94.9	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE		44.7	90.9	93.6	94.8	95.7	95.7	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
üΕ		44.7	91.2	94.1	95.3	96.3	96.3	96.7	96 - 7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE		44.8	92.1	95.6	96.3	97.3	97.3	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
•-																	
GE	4001	44.8	92.1	95.0	96.4	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98 • 2
GE	400 (44.8	92.3	95.2	96.8	98.1	98.3	99.0	99.0	99.0	99.D	99.0	99.D	99.0	99.0	99.D	99.0
GE	3001	44.8	92.3	95.2	97.0	98.4	98.7	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE		44.8	92.3	95.2	97.0	98.4	98.7	99.3	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE	100	44.8	92.3	95.2	97.0	98.4	98.7	99.3	99.4	99.4	99.6	99.6	99.6	99.7	99.7	100.0	100.0
GE	0 (44.8	92.3	95.2	97.0	98.4	98.7	99.3	99.4	99.4	99.6	99.6	99.6	99.7	99.7	100.0	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PEPIOD OF RECORD: 77-86
MONTH: APR HOURS(LS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES

GE GE GE GE GE GE

3 2 1/2 2 1 1/2 HOURS(LST): 0300-0500 CEILING IN | GE FEET | 1 G E 6 GE 5 GE 6 F GE 10 3/4 5/8 1/2 5/16 1/4 NO CEIL | 32.8 56.2 56.4 57.1 57.7 57.8 57.9 58.9 58.1 58.1 58.4 58.6 58.6 58.8 58.8 58.9 60.9 63.2 63.7 63.7 62.6 63.0 63.0 62.8 63.2 63.2 63.2 63.7 63.7 GE 200001 34.4 62.4 62.8 63.1 63.4 63.9 63.9 63.4 63.9 63.9 63.6 63.6 GE 18C00| 34.9 GE 16C00| 34.9 61.3 61.6 62.2 62.8 62.8 62.9 63.2 63.6 64.0 64.0 64.0 64.0 62.2 63.2 61.6 62.8 62.9 63.0 63.9 63.9 64.0 64.0 GE 140001 63.2 GE 12COD1 35.2 62.4 62.7 63.3 63.9 64.0 64.1 64.3 64.7 64.8 64.8 65.0 65.0 65.1 65.1 66.0 66.1 66.6 66.7 69.8 67.4 67.6 70.7 67.7 67.8 70.9 67.8 67.9 71.0 65 • 1 65 • 2 68 • 3 65.3 65.4 66.7 66.8 67.0 67.1 67.0 67.1 67.4 67.6 67.8 67.8 70.9 68.6 ĢΕ 80001 37.4 69.2 69.9 70.0 70.2 70.2 70.6 70.7 71.0 7000| 37.4 68.6 69.4 70.0 70.1 70.2 70.9 71.1 71.1 71.2 70.4 70.4 70 . R 70.9 71.2 71.7 GE GE 74.0 75.9 76.6 50001 38.6 71 • 6 73 • 2 73.7 74.1 74.4 76.3 77.0 71.8 73.4 72.6 73.6 74.1 74.3 76.0 76.7 76.2 76.9 74.2 74.9 75.6 75.0 75.7 75.2 75.9 75.4 76.1 75.6 76.2 76.0 76.7 76.2 76.9 45001 39.3 40001 39.7 73.9 74.1 GE GE 76.3 79.0 76.7 79.3 77.3 35001 40.2 74.7 74.9 75.7 76.4 77.0 77.4 77.7 77.7 77.A 77.8 30001 40.4 77.3 79.1 78.3 79.6 79.7 80.0 80.1 80.3 80.3 80.4 80.4 2500| 40.8 2000| 40.9 1800| 40.9 80.4 82.2 82.2 81.9 83.7 83.7 82.0 83.8 83.8 83.0 84.8 84.8 83.2 85.0 85.0 83.2 85.0 95.0 83.3 85.1 85.1 83.3 85.1 85.1 G E G E 81.2 83.0 82 • 2 84 • 0 82.4 84.2 8*2* • 6 84 • 3 82.9 84.7 83.0 84.8 79.7 GE 81.3 83.0 84.0 84.2 64.3 84.7 84.8 87.2 1500| 41.3 84.3 86.1 87.2 87.4 87.4 87.6 86.2 86.4 86.7 86.8 87.1 89.7 1200 41.4 86 • 2 87.3 88.2 88.3 88.6 89.2 89.3 89.3 89.6 89.7 GE GE 1000| 41.6 86 • 4 86 • 8 88.1 89.0 89.2 90.1 90.1 91.0 90.2 91.1 91.2 92.1 91.6 9D.4 91.3 90.7 91.6 90.8 91.7 91.1 91.2 91.4 91.4 92.3 91.6 92.4 GE 800 | 41.6 87.3 90.1 91.2 92.1 92.2 92.7 93.0 93.3 93.7 93.8 93.4 93.9 95.2 G.F 7001 41-6 97.4 91.2 92.9 94.0 94.4 94.7 94.8 95.1 95.2 95.4 95.4 95.6 95.6 91.9 90.3 5001 41.6 94.2 94.8 95.0 97.0 98.2 99.0 97.1 98.3 99.1 GE 87.9 95.2 95.3 95.9 96.1 97.1 96•3 97•4 96.7 96.8 96.8 97.0 97.1 92.7 95.9 G E 400| 41.6 300| 41.6 88.2 96.U 96.7 97.1 98.0 98.8 98.0 98.8 98.2 96.3 88.2 96.4 97.8 98.7 98.2 99.0 200 41.6 96.3 96.4 97.2 99.0 99.6 GE 1001 41.6 88.2 92.7 95.0 96.3 96.4 97.2 97.9 98.3 96.8 99.0 99.0 99.3 99.3 99.8 100.0 99.3 0 | 41.6 88.2 92.7 95.0 96.3 96.4 97.2 97.9 98.3 99.0 99.0 99.3 99.8 98 • 8

TOTAL NUMBER OF OBSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB K

ST	ATION	NUMBER	: 724505	STATI	ON NAME:	MCCO	NNELL A	FB KS				PERIOD	OF REC		-86 (LST): (8n-0040	ព្
																_	••••••
	ILING									IN STAT							
		35	GE	GE	GE	GΕ	GE	GE	GE	GE	GE	GΕ	GE	GΕ	GE	GE	6E
		1 10		5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	u ••••••
•••	• • • • • •	•••••			• • • • • • • • • • • • • • • • • • • •											••••	
N O	CEIL	27.6	51.6	52.1	52,2	52.7	52 • 7	52.7	53.0	53.0	53.0	53.0	53.0	53.1	53.1	53.1	53.6
GE	20000	30.2	56.8	57.4	57.6	58.0	58.0	58.0	58.4	58.4	58.4	58.4	58.4	58.6	58.6	58.6	59.0
GE	18000	30.6	57.2	57.9	58.0	58.4	58.4	58.4	58.9	58.9	58.9	58.9	58 • 9	59.0	59.0	59.B	59.4
GE	16000	1 30 - 7	57.3	58.0	58.1	58.6	58.6	58.6	59.0	59.0	59.0	59.0	59.0	59.1	59.1	59.1	59.6
		8.02	58 - 1	58.8	58.9	59.3	59.3	59.3	59.8	59.8	59.8	59.8	59.8	59.9	59.9	59.9	60.3
GE	15000	31.6	59.1	59.8	59.9	60.3	60.3	60.3	60.8	60.8	60.8	60.8	60.8	60.9	60.9	60.9	61.3
GE	10000	1 32.1	60.7	61.3	61.4	61.9	61.9	61.9	62.3	62.3	62.3	62.3	62.3	62.4	62.4	62.4	62.9
GE	9000	32.1	60.7	61.3	61.4	62.0	62.0	62.0	62.4	62.4	62.4	62.4	62.4	62.6	62.6	62.6	63.0
GE	8000	33.3	64.7	65.3	65.6	66 - 1	66.1	66.1	66.6	66.6	66.6	66.6	66.6	66.7	66.7	66.7	67.1
GE	7000	33.8	66.2	66.9	67.2	67.9	67.9	68.0	68.4	68.4	68 • 4	68.4	68.4	68.6	68.6	68.6	69.0
GE	6000	1 34.6	67.3	68.1	68.4	69.1	69-1	69.2	69.7	09.7	69.7	69.7	69.7	69.8	69.8	69.8	76.2
GE	5000	1 35.7	69.8	70.6	70.9	71.7	71.7	71.8	72.2	72.2	72.2	72.2	72.2	72.3	72.3	72.3	72.8
ũΕ		35.7	70 • 2	71.0	71.6	72.4	72.4	72.6	73.0	73.0	73.0	73.0	73.0	73.1	73.1	73.1	73.6
GE		1 36.3	71.7	72.8	73.4	74 - 7	74.8	75.0	75.4	75.4	75.4	75.4	75.4	75.6	75.6	75.6	76.6
GE	3500	36.6	72.1	73.2	74.0	75.2	75.3	75.6	76.0	76.0	76 • D	76.0	76.0	76 - 1	76.1	76.1	76.6
ĢE	3000	36.7	73.8	75.0	75.8	77.0	77.1	77.3	77.8	77.8	77.8	77.8	77.8	77.9	77.9	77.9	78.3
GE	2500	1 37.3	75 - 8	77.1	78.0	79.2	79.3	79.7	80.1	80.1	80.1	80.1	80.1	80.2	80 - 2	80.2	80.7
GE		1 37.6	77.0	78.8	79.9	81.1	81.3	81.9	82.3	82.3	82.3	82.3	82.3	82 • 4	82.4	82.4	82.9
G£		37.6	77.3	79.1	8 C . 2	81.4	81.8	82.3	82.8	82.8	82.8	82.8	82.8	82.9	82.9	82.9	83.3
٥E		37.7	78.9	80.8	82.0	83.2	83.7	84.6	85.1	85.1	85.1	85.1	85.1	85.2	85.2	85.2	85.7
GE	1200	37.7	80.2	82.2	83.4	84.7	85.2	86.2	86.8	86.8	86.8	86.8	86.8	86.9	86.9	86.9	87.3
GE		1 37.7	81.1	83.4	84.8	86.1	86.7	87.7	88.2	88.2	88.2	88.2	88.2	88.3	28.3	88.3	8.89
GE		37.7	81.6	84.4	86.0	87.3	87.9	88.9	89.7	89.7	89.7	89.7	89.7	89.8	89.8	89.8	9i.2
GE		37.8	82.3	85.7	87.2	88.9	84.4	90.6	91.3	91.3	91.3	91.3	91.3	91.6	91.6	91.6	92.0
6 E		37.8	82.8	86.4	88.4	90.1	90.7	91.8	92.6	92.6	92.6	92.6	92.6	92 • 8	92.8	92.8	93.2
6 E	600	37.8	82.9	86.8	88.9	90.7	91.3	92.4	93.2	93.3	93.3	93.3	93.3	93.6	93.6	93.6	94.0
GΕ		37.8	83.1	87.2	89.8	91.9	92.6	93.7	94.4	94.7	94.7	94.7	94.7	94.9	94.9	94.9	95.3
GE		37.8	83.3	87.6	9 Li • 2	92.8	93.4	95.1	95.9	96.1	96.2	96.4	96.4	96.7	96.7	96.7	97.1
(E		37.8	83.3	87.6	9 ü •2	93.0	93.7	95.4	96.4	97.0	97.4	97.8	97.8	98.1	98.1	98.2	96.8
GE		37.8	83.3	87.6	96.2	93.0	93.7	95.4	96.4	97.1	97.6	98.0	98.0	98.4	98.4	98.6	99.2
GE	100	37.8	83.3	87.6	90.2	93.0	93.7	95.4	96.4	97.1	97.6	98.2	98.2	98.7	98.7	98.9	99.8
GΕ	0	1 37.8	83.3	87.6	90.2	93.0	93.7	95.4	96.4	97.1	97.6	98.2	98.2	98.7	98.7	98.9	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: APR HOURS(LS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HOURS(LST): 0900-1100 VISIBILITY IN STATUTE MILES
GE GE GE GE GE GE
3 2 1/2 2 1 1/2 1 1/4 1 3/4 IN | GE FEET | 10 3 G E GE GE 5 4 GE GE GE 5/8 1/2 5/16 1/4 52.1 58.1 58 • 2 GE 200001 32.2 58.0 58.1 58.1 58.1 58.1 58.1 58.1 58 • 1 58 • 2 58.2 58.2 58.2 58.3 GE 18000| 32.3 GE 16000| 32.3 GE 14000| 32.7 58.1 58.2 58.2 58.2 58.2 58.2 58 • 2 58 • 2 58.2 58.3 58.3 58 • 3 58 • 3 58.3 58.3 58.3 58.3 58.4 58.3 58.1 58.2 58.2 58.2 58.2 58.2 58.3 58.7 58.8 58.6 59.3 58 • 8 59 • 3 58.8 58.8 58.8 58.8 58.8 58.9 58.9 58.9 58.9 58.9 59.0 59.6 GE 120001 32.9 59.3 GE 10000| 33.6 GE 9000| 33.6 61.7 61.7 61.7 61.7 61.8 61.9 61.8 61.9 65.0 61.7 61.7 61.7 61.7 61.8 61.8 61.8 61.9 61.8 61.8 61.9 61.8 61.9 62.0 8000| 35.0 7000| 36.3 65.0 65.1 67.1 64.9 64.9 64.9 65.0 GE 64.8 64.9 64.9 64.9 65.0 66.9 67.0 66.9 66.9 66.9 66.9 66.9 66 . 9 6mgol 37.1 68.0 68.0 68.0 68.0 68.0 68.0 68.0 68.1 68.1 68.1 68.1 66.2 5000| 38.3 4500| 38.4 70.4 70.9 72.9 70.6 71.0 73.0 70.6 71.0 73.0 70.2 70.4 70.9 70.4 70.9 70.4 70.9 70.4 70.9 70.4 70.4 70.9 70.4 70.9 70.6 71.0 70.6 71.0 70.6 71.0 71.1 70.7 GE 40001 39.0 35001 39.2 72.8 73.1 72.6 72.9 72.9 72.9 72.9 72.9 73.0 73.0 73.0 73.1 73.2 73.3 73.3 73.3 73.4 GE 72.9 73.2 73.2 73.2 73.2 73.2 73.2 73.3 73.3 75.0 GE 25001 40.7 76.6 76 • 6 79 • 1 79 • 9 76.6 79.1 79.9 ĜΕ 75.7 76.0 76.2 76.3 76.4 76.4 76.4 76.4 76.4 76.6 76.6 76.7 79.0 79.8 83.9 2000| 40.8 78.2 79.0 78.6 78.9 79.7 79.0 79.8 79.0 79.8 79.0 79.8 79.0 79.8 79.1 79.9 79.1 79.9 79.1 79.9 79.2 8U.0 77.7 78.4 GE 15001 41.4 82.7 84.C 84.1 84.1 84.1 84.2 GE 12801 41.6 84.0 85.6 86.4 87.3 87.6 87.7 1000| 41.7 84.8 85.9 68 • 3 90 • 1 88.8 89.1 91.1 89.1 91.1 GE 86 • 7 88 • 2 87.6 88.7 88.8 88.8 88.9 89.1 89.1 89.1 89.2 90.7 90.8 90.8 90.9 91.1 91.1 91.1 91.2 GE 89.2 GΕ 2001 41.8 86.9 89.8 90.8 91.9 92.6 92.7 92.7 92.7 92.8 93.0 93.0 93.D 93.1 7001 41.8 87.6 93.2 94.2 94.4 94.4 94.4 94.6 GE 90.6 91.7 94.1 94.1 94.4 600 | 41.8 500| 41.8 400| 41.8 300| 41.8 91.9 92.0 92.2 95.1 95.6 95.9 96.8 98.6 96.8 98.6 88.3 93.6 96.6 97.0 97.6 98.1 98.0 GΕ 97.9 98.1 98.4 98.4 98.6 96.7 98.4 98.8 98 • 9 99.2 99.2 99.4 99.4 99.4 99.6 GΕ ĞĒ 2001 41.8 88.3 92.2 9 3 . 6 96.0 97.1 98.2 98.6 99.0 99.1 99.6 99.6 99.8 99.9 99.8 99.8 99.9 1001 41.8 92.2 93.8 98.6 98.2

98.6 99.0

99.2

99.7

99.9

99.7

99.9

99.9 100.0

TOTAL NUMBER OF OBSERVATIONS:

88.3

01 41.8

GE

900

96.0

97.1

92.2 93.8

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: APR HOURS(LST): 1200-1400

												MONTH	APR	HOURS	(LST):	1200-14	00
CEI	LING		• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	•••••		BILITY	IN STAT	UTE MIL	ES.	• • • • • •	•••••	•••••	•••••	
	N I	G£	GΕ	GE	GΕ	GΕ	30	33	GE	GF	GE	GE	GE	GΕ	GE	GE	4E
	ET		6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	U
										• • •					_		
NO	CEIL	29.9	51.9	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2
	200001		59.1	59.4	59.4	59.4	\$9.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
	18000		59.1	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
	160001		59.1	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
	140001		59.4	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59 - 8	59.8	54.8
GE	120001	33.9	60.6	60.9	6 C . 9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
GE	100001	34.7	63.4	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
θE	90001	34.8	63.7	64.0	64.0	64.0	64.0	64.D	64.0	64.0	64.0	64.D	64.0	64.0	64.0	64.0	64.0
GE	8000		66.8	67.1	67.2	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67 • 3	67.3	67.3	67.3	67.3
GΕ	7000		68.1	68.4	68.6	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	66.7
GE	6naa1	37.9	68.9	69.2	69.3	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4
GE	50001	38.8	70.6	70.9	71.0	71-1	71.1	71.1	71.1	71.1	71.1	71.1	71 - 1	71.1	71.1	71.1	71.1
GΕ	45001	39.0	71.8	72.1	72.2	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	12.3	72.3
GE	4000		73.8	74 - 1	74.2	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3
ΘE	35001		75.0	75.4	75.6	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	15.1
GE	3000 (40.7	76.9	77.3	77.6	77.8	77.8	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	17.9	77.9
GE	2500 [42.0	80.7	81.4	81.8	82.1	82.1	82.2	82.2	82.2	82.2	82.2	82 • 2	82.2	A2.2	82.2	82.2
۵Ē	2000	42.3	83.7	84.4	84.9	85.2	85.2	85.3	85.3	85.3	85.3	85.3	85.3	85 • 3	R5.3	85.3	M5.3
GE	10091	42.4	84.4	85.2	85.7	86.0	86.0	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	66.1
GΕ	1500		87.3	88.2	88.8	89.1	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE	12001	43.2	90.0	91.4	92.3	92.7	92.8	93.0	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
GE	10001	43.2	91.2	92.8	93.9	94.3	94.4	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE	900	43.2	91.9	93.4	94.8	95.3	95.4	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	45.9	95.9
GE	1008	43.2	92.3	93.9	95.6	96.1	96.2	96.8	97.0	97. ₀	97.0	97.0	97.0	97.0	97.0	97.0	97.6
6E	700 l	43.2	92.4	94.0	95.8	96.4	96.7	97.2	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE	6001	43.2	92.7	94.3	96.1	97.0	97.2	97.8	98.3	98.4	98.4	98.4	98.4	98.4	98.4	98.4	96.4
GE	5001	43.2	92.8	94.4	96.2	97.2	97.4	98.1	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.9	96.9
GE	4001	43.2	92.8	94.4	96.2	97.2	97.6	98.4	99.4	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.6
Ŀ٤		43.2	92.8	94.4	96.2	97.2	97.6	98.4	99.4	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9
ĿĘ.		43.2	92.8	94.4	96.2	97.2	97.6	98.4	99.4	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.6
GE	100 [43.2	92.8	94.4	96.2	97.2	97.6	98.4	99.4	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0
Gξ	ارم	43.2	92.8	94	96.2	97.2	97.6	98.4	99.4	99.7	99.8	99.8	99.8	100.0	100.0	100.0	106.0

TOTAL NUMBER OF OBSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER:	724505	STATI	ON NAME:	MCCO	NNELL AF	FB KS				PERIOD MONTH		ORD: 77 HOURS		1500-17	00
	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • •	• • • • • • •			IN STAT			• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • •
CEILING IN GE	GE	GĘ	GE	GE	GE	GE AT2T	GE	GE STAT	6E	C S GE	GE	GE	GE	GΕ	GE
FEET 10	6	5	4		2 1/2			1 1/4	1	3/4	5/8	1/2	5/16	1/4	0
	_									• • • • • • •	• • • • • •	• • • • • • •			
NO CEIL 31.1	52.4	52.6	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
GE 20000 35.6	62.0	62.1	62.2	65.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62 • 2	62.2	62.2
GE 18000 35.8	62 • 3	62.4	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
GE 160001 35.8	62.3	62.4	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
GE 140001 36.1	62.7	62.8	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9
DE 120001 36.9	64.0	64.1	64.2	64.2	64.2	64.2	64.2	64.2	64.2	64 • 2	64.2	64.2	64.2	64.2	64.2
GE 10000 37.7	66 • 2	66.3	66.4	66.4	66.4	66.4	66.4	66.4	66.4	66.4	66 . 4	66.4	66.4	66.4	66 - 4
GE 90001 37.8	66 - 4	66.6	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7
GE 8CUO 39.1	69.4	69.6	69.7	69.7	69.7	69.7	69 • 7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
GE 7C00 39.8	70.6	70.7	70.8	70.8	70.8	70.8	70.8	7g.8	70.8	70.8	70.8	70.8	70.8 71.6	70.8 71.6	7u.8 71.6
GE 60001 40.2	71.3	71.4	71.6	11.0	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	/1.0	/1.6	11.0
GE 50001 41.6	74.3	74.4	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6
GE 4500 41.8	75.4	75.6	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7	75.7
GE 40001 43.0	78.4	78.7	78.8	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	76.9
GE 35001 43.7	79.4	79.7	79.8	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9
GE 30001 44.2	91-8	82.0	82.6	82.7	82.7	82.7	82.8	82.8	82.8	82.8	82.8	82.8	82.8	82 · A	82.8
02 00001 1112	,,,,,,											•-•	- 2	0	•
GE 25001 45.3	84.8	85.1	85.9	86.2	86.4	86.4	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6
GE 20001 45.8	87.1	87.7	88.4	88.8	89.D	89.0	89.1	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE 18001 46.1	88.6	89.1	89.9	90.2	90.4	90.4	90.6	90.6	90.7	90.7	90.7	90.7	90.7	90.7	90.7
GE 1:001 46.2	91.4	92.3	93.2	93.6	93.8	93.8	93.9	93.9	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 1200 46.3	92.1	93.1	94.1	94.4	94.8	94.8	94.9	94.9	95.0	95.0	95.0	95.0	95.0	95.0	95.0
GE 1000 46.4	92.7	93.8	94.9	95.2	95.6	95.6	95.7	95.7	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 9001 46.4	93.0	94.8	96.2	96.6	96.9	96.9	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 8001 46.4	93.6	95.6	97.3	97.8	98.1	98.1	98.3	98.3	98.4	98.4	98.4	98.4	98 • 4	98.4	98.4
GE 700 46.4	93.6	95.6	97.4	97.9	98 • 3	98.3	98.6	98.6	98.7	98.7	98.7	98.7	98.7	98.7	96.7
UE 600 46.4	93.6	95.6	97.4	97.9	98.3	98.3	98.7	98.7	98.8	98.8	98.8	98.8	96.8	98.8	96.8
											99.3		99.3	99.3	99.3
GE 400 46.4	93.6 93.6	95.7 95.7	97.6 97.6	98.0	98.6	98.6	99.ü	99.0 99.2	99•2 99.4	99.3 99.6	99.5	99.3 99.7	99.7	99.7	99.3
GE 2001 46.4	93.6	95.7	97.6	98.0 98.0	98.6 98.6	98.7 98.7	99.2	99.2	99.6	99.7	99.7	99.1	99.8	90.8	99.8
GE 2001 46.4	93.6	95.7	97.6	98.0	98.6	98.7	99.2	99.3	99.6	99.7	99.7	99.8	99.8	99.8	99.8
GE 100 46.4	93.6	95.7	91.6	98.0	98.6	98 • 8	99.4	99.6	99.8	99.9	99.9	100.0	100.0	100.0	100.0
Or 1001 4044	73.0	73.1	7 1 • 0	70.U	70.0	78 • 8	7747	77.0	,,,,	,,,,	,,,,	.00.5		.00.0	
GE 01 46.4	93.6	95.7	97.6	98.0	98.6	98.8	99.4	99.6	99.8	99.9	99.9	100.0	100.0	100.0	100.0
					******						• • • • • •				

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION	NUMPER:	724505	STATI	ON NAME:	MCCO	NNELL AF	BKS					OF REC			1800-2 <u>0</u>	co
CEILING	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • •	• • • • • •	• • • • • • •			IN STATE			•••••	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •
IN	I GE	GE	GE	G.F	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GΕ
FEET	1 10	6	5	4	3	2 1/2			1 1/4	1	3/4	5/8	1/2	5/16	1/4	0
			3	•	,	2 1/2	2	1 1/2	1 1/4		3/4	3/6	1/2	21.10	1/4	U
• • • • • •	• • • • • • • •	•••••	• • • • • •	• • • • • • •	• • • • • •	•••••	• • • • • •	•••••	• • • • • • • •	• • • • • • •	• • • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • • •
NO CEIL	33.3	57.9	58.0	58.0	58.1	58.1	58.2	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
GE 2000	0 37.8	67.8	68.0	68.0	68.1	68.1	68.2	68.3	68.3	68.3	69.3	68.3	68.3	68.3	68.3	68.3
GE 1800	01 37.8	67.8	68.0	68.0	68.1	68.1	68.2	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3
GE 1600	D 37.9	67.9	68.1	68.1	68.2	68.2	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
	01 38.3	68.4	68.7	68.7	68.8	68 • 8	68.9	69.0	69.0	69.0	69.n	69.0	69.0	69.0	69.0	69.0
	01 39.2	70.3	70.6	76.6	70.7	70.7	70.8	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9	74.9
02 12.0	0, 3, 12					,,,,,			,					•		
6E 1000	01 40.0	72.0	72.2	72.2	72.3	72.3	72.4	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
GE 900	01 40.0	72.0	72.2	72.2	72.3	72.3	72.4	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
	01 40.2	73.1	73.3	73.3	73.4	73.4	73.6	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
GE 700	01 40.9	75.0	75.2	75.2	75.3	75.3	75.4	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6
	0 41.4	76.0	76.2	76.2	76.3	76.3	76.4	76.6	76.6	76 • 6	76.6	76.6	76.6	76.6	76.6	76.6
02 000						,,,,		,,,,,	,	.0.0						
GE 500	01 42.3	77.8	78.3	78.3	78.4	78.4	78.6	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
	0 43.1	79.4	80.0	0.08	80.1	80.1	80.2	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.3
GE 400	0 43.4	81.3	82.2	82.3	82.4	82.4	82.6	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7
GE 350	0 43.9	82.4	83.6	83.7	83.8	83.8	83.9	84.1	84.1	84 - 1	84.1	84.1	84.1	84.1	84.1	84.1
	0 44.1	83.4	84.7	84.8	84.9	84.9	85.0	*85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
01 000	-,					. .	03.00	03-1		•••						
GE 250	01 45.0	85.7	86.9	87.0	87.1	87.1	87.2	87.4	87.4	87.4	87.4	87.4	87.4	87.4	67.4	87.4
	0 45.1	88 • i	89.4	89.6	89.7	89.7	89.9	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
	01 45.1	89.4	90.8	96.9	91.0	91.0	91.2	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4
	0 45.1	90.6	91.9	92.1	92.3	92.3	92.7	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
	0 45.1	91.3	92.7	93.0	93.2	93.2	93.6	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
	-	-	_													
GE 100	0 45.1	92.0	93.6	93.9	94.2	94.2	94.9	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
GE 90	0 45.1	92.4	94.7	95.0	95.3	95.6	96.2	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE BU	0 45.1	92.7	95.6	95.6	96.0	96.4	97.1	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 70	01 45.1	92.7	95.1	95.9	96.8	97.2	97.9	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	96.3
GE 60	01 45.1	92.7	95.3	96.1	97.1	97.6	98.3	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
	0 45.1	92.7	95.4	96.4	97.6	98.D	98.8	99.2		99.3	99.3	99.3	99.3	99.3	99.3	99.3
	0 45.1	92.7	95.4	96.4	97.6	98.1	98.9	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7
	0 45.1	92.7	95.4	96.4	97.6	98.1	98.9	99.7		99.9	99.9	100.0	100.0	100.0	100.0	100.0
	0 45.1	92.7	95.4	96.4	97.6	98.1	98.9	99.7	99.8	99.9	99.9	100.0	100.0	100 · D	100.0	100.0
GE 10	0 45.1	92.7	95.4	96.4	97.6	98.1	98.9	99.7	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0
						••				20.5				100 0	1.00 -	100 0
	0 45.1	92.7	95.4	96.4	97.6	98.1	98.9	99.7	99.8	99.9		100.0	-	100.0	100.0	100.0
							· · · · · ·									

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

			724505	-	-			-				MONTH		HOURS	(LST):	2100-23	٥٥
	ILING	•••••	• • • • • • • • •			•••••				IN STATE				• • • • • • •	•••••		• • • • • • • • • • •
F	IN I		GE 6	6E 5	GE 4		6E 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	6E 1	GE 3/4	Gε 5/8	GE 1/2	GE 5/16	GE 1/4	6E U
N O	CETL I	36.8	63.2	63.7	63.7	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
GF GE	20000 18000 16000 14000 12000	38.9 38.9 38.9	68.6 68.7 68.7 69.9	69.2 69.3 69.3 69.3	69.3 69.4 69.4 69.4 70.7	69.4 69.6 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 69.6 70.8	69.4 69.6 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 69.6 70.8	69.4 69.6 69.6 70.8	69.4 69.6 69.6 69.6 70.8
GE GE	7000	40.3 40.8 41.2	71.6 71.8 73.6 74.7 75.9	72.2 72.4 74.2 75.4 76.7	72.3 72.6 74.3 75.6 76.8	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 71.0	72.4 72.7 74.6 75.8 77.0	72 • 4 72 • 7 74 • 6 75 • 8 77 • C	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 71.0	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 77.0	72.4 72.7 74.6 75.8 77.0
GE GE GE GE	4500 4000 3500	42.8 43.1	77.1 78.1 79.9 81.4 82.4	78.2 79.2 81.1 82.7 84.0	7 8 . 4 7 9 . 6 8 1 . 4 8 3 . 0 8 4 . 3	78.7 80.0 81.9 83.4 84.8	78.7 80.0 81.9 83.4 84.8	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 63.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9	78.7 80.0 81.9 83.4 84.9
GE GE GE	2000 1800 1500	44.6	83.7 85.8 86.2 86.8 88.1	85.4 87.7 88.1 89.0 90.6	85.8 88.0 88.4 89.6 91.1	86.3 88.6 89.0 90.2 91.8	86.3 88.6 89.0 90.2 91.8	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 90.3	86.4 88.7 89.1 90.3 92.0	86.4 88.7 89.1 96.3 92.0
6 E 6 E 6 E 6 E	900 800 700	45.0 45.0 45.0 45.0	89.8 90.6 91.1 91.8 92.3	92.2 93.3 93.9 94.9 95.7	92.8 94.1 94.8 95.8 96.7	93.6 95.0 95.7 97.0 98.3	93.6 95.2 95.9 97.2 98.6	93.8 95.4 96.1 97.4 98.8	93.8 95=6 96.2 97.6 98.9	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0	93.9 95.7 96.3 97.7 99.0
6E 6E 6E 6E	400 l 300 l 200 l	45.1 45.1 45.1 45.1 45.1	92.4 92.4 92.4 92.4 92.4	95.8 95.8 95.8 95.8 95.8	96.8 96.8 96.9 96.9 96.9	98.6 98.6 98.7 98.7 98.7	98.8 98.8 98.9 98.9	99.0 99.2 99.3 99.3	99.1 99.3 99.8 99.8	99.2 99.4 99.9 99.9	99.2 99.4 99.9 99.9	99.2 99.4 100.0 100.0	99.2 99.4 100.0 100.0	99.2 99.4 100.0 100.0	99.2 99.4 100.0 100.0	99.2 99.4 100.0 100.0	99.2 99.4 100.0 100.0

45.1 92.4 95.8 96.9 98.7 98.9 99.3 99.8 99.9 99.9 100.0 100.0 100.0 100.0 1₀₀.0 1₀₀.0

TOTAL NUMBER OF OBSERVATIONS:

900

01 45.1

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: APR HOURS(LST): STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES
GE GE GE GE
2 1 1/2 1 1/4 1 CEILING GE GE GE 4 3 2 1/2 GE GE 6 5 GE GE 1 3/4 GE GE 1/2 5/16 I GE GĘ IN | GE FEET | 10 5/8 1/4 0 56.7 NO CEIL | 32.1 55.9 56.2 56.3 56.5 56.5 56.5 56.6 56.6 56.7 56.7 56.7 56.7 56.8 56.6 62.5 62.7 62.7 62.8 63.0 63.1 63.2 63.4 63.4 63.2 63.4 63.4 63.3 63.5 63.5 63.4 63.6 63.6 63.4 63.6 63.7 63.5 63.7 63.7 GE 20000| 35.0 GE 18000| 35.2 63.0 63.2 63.2 63.4 63.3 63.3 63.6 63.4 63.4 63.4 GE 160001 35.3 GE 140001 35.4 63.2 63.4 63.5 63.6 63.6 63.7 63.7 63.7 63.8 63.9 63.9 63.4 63.6 64.9 GE 120001 36.0 64.2 64.5 64.8 65.0 65.0 65.0 65.1 65.1 65.1 65.1 65.1 65.2 GE 10000| 36.7 GE 9000| 36.7 GE 8000| 37.8 67.0 67.1 67.1 67.3 70.0 67.2 67.2 67.3 70.0 67.2 67.4 67.2 67.4 67.2 66.9 67.1 67.3 70.0 67.4 66.4 66.8 67.2 67.4 69.8 70.0 70.0 70.1 70.1 70.1 GE 70001 38.4 70.3 70.7 70.9 71.1 72.1 71.2 71.2 71.3 71.3 72.3 71.3 71.4 71.4 71.4 71.4 71.4 71.5 60001 38.9 72.1 72.2 72.3 5000| 39.9 4500| 40.2 4000| 40.8 74.5 75.8 77.9 74.6 75.8 77.9 74.6 75.8 77.9 74.6 75.8 74.6 75.9 78.0 ĢΕ 73.8 74.4 74.6 75.8 73.3 74.1 74.3 74.3 74.5 74.5 74.7 75.5 77.6 78.7 75.7 71.9 74.4 74.9 76.9 75.2 77.3 75.6 77.8 75.7 77.8 GE 75.6 75•9 78•1 78.0 78.0 6E 77.7 78.9 79.0 79.0 79.0 79.0 GE 30001 41.6 79.0 80.6 80.6 80.8 80.9 80.9 80.9 81.0 81.0 81.0 81.0 81.D 81.1 83.5 85.9 86.7 83.4 85.8 83.4 85.9 83.5 85.9 GE GE 2500| 42.3 2000| 42.5 81.1 83.2 82.0 84.3 82.5 84.9 83.0 85.4 83.1 85.5 83.2 85.7 83.3 83.4 85.9 83.5 85.9 83.5 86.0 85.8 18001 42.6 85.6 87.9 GE 83.9 85.1 86.l 86.2 86.4 86.5 86-5 86.6 86.6 86.6 86.7 86.7 86.8 89.1 89.1 89.1 15001 42.8 85.9 89.0 89.0 89.1 89.1 89.2 GE 87.2 88.5 88.6 8.86 89.0 17001 43.0 90.4 90.8 91.0 92.8 94.2 95.4 92 • 8 94 • 2 95 • 4 92.8 94.2 GE 10001 43.1 88.5 89.1 89.6 90.3 91.3 92.2 91.2 92.4 93.4 91.9 93.2 94.3 92.1 93.5 92.4 93.8 95.0 92.6 94.1 95.3 92.7 92.7 92.6 92.7 92.9 900 | 43.2 800 | 43.2 94.0 94.1 95.3 94.2 GE 68 95.4 95.4 95.4 95.5 94.6 89.9 92.7 95.5 96.3 96.3 96.4 96.4 96.4 96.5 96.5 97.3 GE 6001 43.2 90.3 93.3 94.7 95.9 96.3 96.8 97.1 97.1 97.2 97.3 97.3 97.3 97.3 97.4 96.8 97.2 97.4 500| 43.2 400| 43.2 300| 43.2 93.5 93.6 93.6 95.1 95.3 95.4 96.4 96.7 96.9 97.8 98.5 99.0 98.0 99.9 99.5 98.0 99.0 99.6 GE 90.4 97.3 97.9 97.7 97.8 97.9 97.9 98.8 98.0 98.0 98.7 98.8 98.9 98.4 98.9 ĿΕ 99.3 99.5 GΕ 90.5 98.2 98.6 200 | 43.2 100 | 43.2 99.1 99.4 99.6 90.5 96.9 97.4 99.3 99.4 99•6 99.6 93.6 95.4 98.2 98.8 GE 99.5 99.7 99.8 100.0 99.5 99.5 99.7 01 43.2 90.5 93.6 96.9 97.4 98 • 2 98.8 99.8 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PEPIOD OF PECORD: 77-86
MONTH: MAY HOURS(LST1: BGUD-D2DD STATION NUMBER: 7245US STATION NAME: MCCONNELL AFB KS MONTH

VISIBILITY IN STATUTE MILES

IN 1 GE GE GE GE GE GE GE GE GE GE
FEET { 10 6 5 4 3 2 1/2 2 1 1/2 1 1/4 1 3/4

NO CEIL 1 26-6 50 7 7 7 ******************************** G.f. GE 1/2 5/16 174 il 5/8 NO CEIL 1 26.6 59.2 59.4 59.4 59.4 59.4 GE 200001 29.1 GE 180001 29.2 GE 160001 29.2 64.4 64.6 64.7 64.8 65.1 65.2 64.8 65.1 65.2 64.9 65.2 65.3 64.9 65.2 65.3 65.1 65.3 65.4 63.7 64.7 64.9 64.9 64.9 65.1 65.3 64.9 65.2 65.2 63.9 64.0 64.3 65.2 65.3 65.4 65.4 65.4 GE 140001 29.4 65.4 65.6 65.7 65.7 65.7 65.1 65.5 65.6 65.6 65.6 65.6 65 - 7 GE 120001 29.6 64.9 66.1 66.2 66.2 66.5 66.5 66.5 69.6 69.7 73.2 69.7 69.8 73.3 GE 100001 31.3 GE 90001 31.3 68.3 69.7 69.7 69.9 70.0 69.9 69.8 69.8 69.8 69.8 09.9 73.4 69.4 69.9 73.4 69-9 73.4 69.9 73.4 69.9 70.0 73.5 70.0 76.0 8000 | 32.6 71.9 12.9 73.3 73.3 73.4 73.5 73.5 70001 32.8 60001 33.3 73.0 74.0 74.3 74.4 74.4 74.4 74.5 14.5 74.5 74.5 74.5 74.6 74.6 74.6 74.6 75.2 75.8 75.6 75.8 75.9 75.5 75.7 75.8 75.8 75.8 75.9 76.7 77.2 80.0 78.6 79.1 82.5 78.7 79.4 82.7 78.7 79.4 82.7 78.9 79.6 82.9 78.3 78.8 81.9 78.8 79.5 82.8 78.9 79.6 82.9 18.9 19.6 82.9 78.9 79.6 82.9 79.0 79.7 6 F 5mnn1 34.2 79.₀ 79.0 79.0 78.9 GE GE 45001 34.4 40001 35.2 79.6 82.9 79.7 83.0 83.0 85.1 g3.0 83.0 3:001 35.7 84.5 84.9 84.9 85.1 ĢE 30001 35.8 84.0 86.3 87.0 87.2 87.2 87.3 87.4 87.4 87.4 87.4 87.4 87.5 87.5 87.5 87.5 89.2 90.9 91.1 92.5 G E 89.2 90.9 89.2 90.9 89.2 89.4 91.0 25001 35.9 85.5 88.1 86.8 89.0 89.0 89.1 89.2 89.4 89.4 89.4 20001 36.2 90.4 90.8 90.9 91.0 91.0 86.6 90.0 90.2 90.3 91.0 89.2 GE 18001 36.2 86.8 89.5 90.5 90.6 91.0 91.1 91.1 91.1 91.1 91.2 91.2 91.2 92.6 1.001 36.5 91.5 92.5 GE 88.0 90.8 91.8 91.9 92.4 92.5 92.5 92.6 92.6 95.6 95.6 96.1 97.3 10001 36.5 90.2 94.8 95.5 95.6 95.7 96.2 97.4 95.7 95.6 95.7 95.7 GF 900 | 36.5 800 | 36.5 90.3 93.8 94.8 95.4 95.5 96.0 97.2 96.1 96.1 96.1 97.3 96.1 97.3 96.2 97.4 96 • 2 97 • 4 96.2 GΕ 94.8 95.9 96.5 96.6 97.8 98.0 G E 7001 36-5 95.2 96.2 97.1 98.0 98.0 98.0 98.0 98.1 98.1 98.1 6001 36.5 91.3 97.5 95.4 96.6 97.3 98.3 98.4 98.4 98.4 98.4 98.4 98.5 98.5 98.5 96.5 5001 36.5 4001 36.5 95.6 95.7 96.8 96.9 97.5 97.6 97.7 97.8 98.5 98.6 98.6 98.7 98.6 98.7 98.6 98.7 99.4 98.6 98.7 91.5 98.7 98.8 98.7 91.5 91.5 GΕ 3001 36.5 99.5 95.7 49.4 GΕ 97.2 98.3 98.5 99.2 99.4 99.4 99.4 99.5 99.5 99.6 99.9 2001 36.5 91.5 98.5 99.2 99.4 99.4 99.6 99.6 99.6 99.9 99.9 104.0 95.7 97.2 98.3 99.6 1001 36.5 98.3 98.5 99.6 99.9 99.9 99.9 104.0 DI 36.5 99.6 99.9 100.0


PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: MAY HOURS(LST): 0300-0500 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE HILES CEILING IN | GE FEET | 10 1/2 5/16 5/8 1/4 υ NO CEIL | 21.8 50 . D 51.1 52.3 52.9 53.0 53.5 53.7 53.7 53.7 53.7 53.7 53.8 53.8 53.8 53.9 SE 20000 | 24.3 GE 18000 | 24.3 GE 16000 | 24.3 61.5 61.8 61.9 61.6 61.9 62.0 58.9 60.8 61.1 61.5 61.6 61.6 57.5 60.1 60.9 61.4 61.5 61.5 61.5 61.7 61.2 61.8 6..2 59.2 60.4 61.7 61.8 61.8 61.8 61.9 61.2 61.9 58.0 59.4 60.5 61.8 62.0 62.0 61.9 61.9 61.9 140001 24.3 58.0 64.5 61.2 61.3 61.9 61.9 62.0 62.0 61.8 62.0 GE 120001 24.6 58.9 61.6 63.0 63.0 GE 100001 25.5 GE 90001 25.7 65.5 66.1 66.1 66.2 66.2 66.0 66.2 66.3 62.3 64.0 65.2 65.8 66.5 66.6 66.6 66.6 66.6 66.6 66.7 66.7 66.8 GΕ 80001 27.0 67.0 68.7 69.9 70.5 70.6 71.2 71.3 71.3 71.3 71.3 71.3 71.4 71.4 71.4 71.5 70001 27.5 68.3 70.1 71.3 72.0 72.0 72.2 72.7 72.8 72.8 72.8 72.8 72.8 72.9 72.9 72.9 73.0 72.9 60001 27.8 73.5 68 . 9 70.9 72.8 73.5 73.5 73.5 73.7 73.7 73.7 73.8 73.3 74.1 75.8 76.6 77.3 76.1 78.1 78.8 78 • 2 78 • 9 78.7 79.5 78.8 79.6 78.8 79.6 78.8 79.6 78.8 79.6 78.9 79.7 78.9 79.7 78.9 79.7 79.U 79.8 GF 50001 30.1 45001 30.2 40001 31.3 76.1 8U.4 81.3 81.3 81.8 81.9 82.0 82.9 82.0 82.9 GΕ 78.7 81.2 81.9 91.9 61.9 81.9 €2.2 79.6 76.7 35001 31.3 82.0 82.8 82.8 82.8 82.8 82.9 83.0 82.8 6E 3 can l 31.7 81.3 83-0 83.9 84.6 84.7 84.7 84.8 84.8 25001 32.3 20001 32.4 85.1 85.9 87.2 86.8 98.1 86.9 88.2 66.9 88.2 86.7 86.1 87.4 86.8 81.3 GE 84.4 88.1 88.1 88.1 88.2 88.3 18001 32.4 81.5 84.6 86.6 87.4 87.6 88.2 88.3 A8.3 88.3 88.3 88.5 i.E 15001 32.6 82.6 86.0 86.1 88.9 89.2 90.1 90.2 90.2 90.2 90.2 90.2 90.3 90.4 90.3 41 - 4 91.4 91.5 91.5 83.8 89.2 90.1 90.4 91.3 91.4 91.0 GΕ 10001 32.9 85.3 89.1 91.5 92.5 92.8 93.7 93.7 93.8 93.8 93.8 93.8 93.9 93.9 91.9 94.0 93.8 G.E 900| 32.9 800| 32.9 85.9 89.9 92.4 93.3 94.5 94.6 94.6 95.5 94.6 94.6 94.7 94.7 94.7 94.8 90.5 94.4 GΕ 86.6 94.1 76.5 47.1 6001 32.9 87.2 97.0 G E 94.2 95.4 95.7 96.6 97.0 97.U 97.0 97.0 97.1 97.1 47.2 97.8 98.6 98.8 GE 5nol 32.9 87.4 87.4 91.6 91.7 94.7 95.9 96.2 97.2 97.7 97.8 97.8 97.B 97.8 98.0 98.7 98.0 98.7 98.0 98.7 96.8 97.5 98.6 98.8 98.7 4001 32.9 98.6 96.2 96.8 98.6 87.4 87.4 6E 3001 32.9 96.9 48.9 91.8 95.1 96.3 97.8 98.8 98.8 98.9 98.4 94.0 98.9 99.0 99.4 99.4 99.4 99.5 99.5 .9.5 91.8 96.6 98.1 95.2 106.0 GE 1001 32.9 99.0 99.4 99.4 99.5 99.5 1.6.3 99.0 01 32.9 91.8 95.2 97.1 98.1 98.9 99.5 99.5 100.5 ú£ 87.4 96.6 97.4 99.4 99.5

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF PECORD: 77-86
HONTH: MAY HOURS(LST): D600-08CC STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS, CEILING VISIBILITY IN STATUTE MILES IN | GE FEET | 10 GE GE GE 1/2 5/16 5/8 1/4 0 NO CEIL | 18.3 46.3 47.0 47.0 47.1 47.2 47.3 47.3 44.3 45.8 47.0 47.0 54.1 54.6 54.8 54.2 54.7 54.9 GE 200001 21.1 50.5 52.4 53.3 54.1 54.1 54.1 54.4 54.4 54.4 54.5 54.6 54.3 54.4 GE 18000 21.1 GE 16000 21.2 52.9 53.9 54.6 54.6 54.6 54.8 54.9 54.9 55.2 54.9 54.9 55.1 55.3 51.1 55.2 55.4 55.7 51.3 54.4 140001 21.3 55.2 51.5 GE 12cool 22.3 55.5 56.0 57.4 57 4 57.6 58.0 59.4 59.6 60.4 60.6 61.7 GE 100001 23.1 61.4 61.4 61.4 61.4 61.5 61.6 61.7 61.7 61.7 61.8 61.9 61.9 90001 23.2 80001 24.3 61.6 67.0 61.7 61.9 62.0 G F 57.5 61.6 61.6 61.6 61.5 61.9 62.7 64.8 65.9 67.1 67.1 67.1 67.3 67.4 67.4 67.4 67.4 67.5 67.0 5 F 70001 24.8 63.9 66.2 67.3 68.5 68.6 70.2 68.6 68.7 68.8 68.9 68.9 68.9 68.9 69.0 64.1 60001 25.3 76.8 73.5 74.2 77.1 73.9 74.5 77.4 73.9 74.5 77.4 68.5 68.9 71.5 73.9 73.9 74.5 77.4 74.0 74.6 77.5 G E 50001 26.1 4'001 26.2 73.4 73.9 73.7 73.8 71.1 72.3 73.5 73.5 71.5 74.2 74.3 77.2 74.5 77.4 4000| 26.9 3500| 26.9 77.3 77.6 GE 75.6 76.8 77.6 76•9 77•7 78.0 78.4 30001 27.3 76.8 79.8 80.1 80.2 80.3 80.4 80.5 80.5 80.5 80.5 60.6 25001 28.0 78.0 79.6 81.5 81.6 81.8 82.0 82.2 87.3 82.3 84.2 82.3 7.1.4 , , . , , , , 2001 28.4 19001 28.5 76.3 84.0 84.2 (E 81.4 83.8 84.1 84.4 80.3 84-1 84.7 84.8 84.9 84.9 84.9 84.9 5.5 ± 1 86.5 21. 6.5 15401 29.0 78.5 81.8 8 1.7 85.6 85.7 86.0 66.2 86 - 3 86.5 86.5 96.5 80.5 88.5 88.8 84.6 - . . ં, દ્ 86.6 1000 L 29.7 81.7 85.9 87.8 89.8 90.6 90.1 20.4 90.6 90.8 90.9 90.9 90.9 Ģ. . . υE 89.9 . . . 9001 29.7 9001 29.8 7001 29.8 88.7 82.3 82.7 86.7 90.9 91.1 91.6 91.7 91.8 91.8 91.9 91.5 ı.E 91.8 91.6 92.2 92.4 94.0 92.5 92.6 92.6 92.6 91.4 ¥. . . 94. 95.3 o f 600 | 30.0 A 5 . 3 88.1 93.1 93.5 93.9 95.1 95.2 93.9 94.3 94.3 94.4 97.2 47.5 1001 30.0 88.4 95.3 96.3 96.7 97.1 97.2 96.4 97.4 97.7 98.3 ι£ 4001 30.1 83.7 88.6 91.4 96.1 96.6 SE 7001 30.1 83.7 88.6 91.4 95.1 95.1 98.2 98.6 99.1 99.2 ٠.. ٠٠.. ٠٠. 99.1 99. 94.3 98.2 6 2001 30.1 83.7 88.6 91.4 96.6 98.6 99.1 A3.7 91.4 95.1 96.6 98.2 6 E 01 30-1 88.6 98.6

AD-A179 196 3/4 UNCLASSIFIED NL



MICROCOPY RESOLUTION (FEST CHAR NATIONAL PROFITE OF TAN ART

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY USAFETAC FROM HOURLY OBSERVATIONS AIR WEATHER SERVICE/MAC

							NNELL A						: MAY	HOURS	(LŠT):	0930-11	
	LING	• • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • • •		BILITY				• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	••••
I		GE	GE	GΕ	GΕ	GE	GE	GE	GE	GE	GE	GE		GE	GE	GŁ	6
_	-	10	6	5	4		2 1/2		1 1/2		1	3/4		1/2	5/16	1/4	
	CEIL 1		47.5	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	46
						-											
	200001		54.5	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55
	180001		55.4	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56 • 2	56.2	56.2	56.2	56.2	56.2	56
	160001		55.5	56.3	56.3	56.3	56.3	56 • 3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56
	140001		56.1	57.0	51.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	5.7
e E	120001	26.3	57.8	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	56
E	100001	27.2	61.1	62.0	62.0	62.2	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62
	90001		61.1	62.0	62.0	62.2	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62
βĒ	10008	28.6	63.9	64.8	64.8	65.1	65.1	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65
Œ	70001	29.4	64.9	66.0	66.0	66.3	66.3	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66
E	60001	29.7	66.0	67.1	67.1	67.4	67.4	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67
E	50001	30.2	67.3	68 - 8	66.9	69.4	69.4	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69
ÞΕ	4500	30.2	67.8	69.4	69.5	69.9	69.9	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70
ēΕ	40001	30.5	70.6	72.3	72.4	72,8	72.9	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73
·Ε	35001	30.6	71.2	72.9	73.0	73.4	73.5	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.
Ε	3000	31.5	73.9	75.7	75.8	76.3	76.5	76.7	76.7	76.7	76.7	76.7	76 • 7	76.7	76.7	76.7	76
E	25001	32.4	75.3	77.3	77.4	78.0	78.1	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	7 b
	20001		78.8	81.2	81.4	82.0	82.2	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	5.
·Ε	18001	33.7	79.6	81.9	82.2	82.8	82.9	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83
ξ.	15001	34.5	83.1	85.7	96.0	86.7	86.8	87.0	87.U	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.
E	1500	35.3	86.0	88.8	89.4	90.1	90.2	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.
Ε	10001	35.6	88.5	91.5	92.0	92.9	93.1	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.
E	900	35.9	88.9	92.2	92.8	93.8	94.0	94.3	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.
·Ε		36.1	89.7	93-1	93.8	94.8	95.3	95.7	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.D	96
E	7001	36.2	90.2	93.9	94.5	95.7	96.1	96.6	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96
E	6001	36.2	90.5	94.3	94.9	96.2	96.7	97.3	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97
E		36.2	90.6	94.8	95.5	96.8	97.2	97.8	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	96
E		36.2	90.9	95.2	96.0	97.4	97.8	98.8	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99
E		36.2	90.9	95.2	96.0	97.4	97.8	98.8	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99
Æ		36.2	90.9	95.2	96.0	97.4	97.8	98.8	99.7	99.8	99.8	99.9	99.9	99.9	100.0	100.0	100
Ε	1001	36.2	90.9	95.2	96.0	97.4	97.8	98.8	99.7	99.8	99.8	99.9	99.9	99.9	100.0	130.0	100
E	n i	36.2	90.9	95.2	96.0	97.4	97.8	98.8	99.7	99.8	99.8	99.9	99.9	00.0	100.0	1.10.0	100

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VFRSUS VISIBILITY FROM HOURLY OBSERVATIONS

PEPIOD OF RECORD: 77-86 MONTH: MAY HOURS(LST): 1200-1400 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES CEILING GE 4 GE GE GE 2 1 1/2 1 1/4 GE 5/16 IN | GE FEET | 10 GΕ GΕ GE GE GE GE 3 2 1/2 5/8 1/4 ь 1/2 49.8 49.8 NO CEIL | 24.0 59.1 59.1 59.1 59.1 59.1 59.1 GE 200001 28.8 59.1 59.1 59.1 59.1 59.1 58.5 59.1 59.1 58.5 58.5 59.5 59.1 59.1 59.1 59.1 59.1 GE 18000| 28.8 GE 16000| 28.8 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 59.1 GF 14P001 29.2 60.1 66.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 6C.1 GE 120nnl 30.0 60.9 61.5 61.5 61.5 61.5 61.5 61.5 10000| 31.5 9000| 31.5 8000| 32.8 64.8 64.8 67.2 67.7 64.8 64.8 67.2 67.7 64.8 64.8 67.3 67.8 64.8 64.8 67.3 64.8 64.8 67.3 64.8 67.3 64.8 64.8 67.3 64.8 64.6 67.3 64.8 64.8 64.8 64.8 67.3 63.9 64.8 64.8 64.8 64.8 63.9 64.8 64.8 64.8 64.8 GE GE 33.0 67.6 66.8 60001 33.3 68.3 68.4 68.4 68.4 68.4 68.4 68.4 68.4 68.4 68.4 68.4 68.4 69.7 71.1 74.8 76.7 70.9 72.3 70.9 72.3 76.2 78.1 70.9 72.3 76.2 70.9 72.3 76.2 78.1 70.9 72.3 70.9 70.9 70.9 72.3 70.9 72.3 70.9 72.3 76.9 72.3 76.2 78.1 50001 34.7 45001 35.1 72.2 76.1 72.2 72.3 76.2 72.3 76.2 78.1 72.3 76.2 78.1 76.2 78.1 76.2 78.1 76.2 78.1 40001 36.1 76.2 78.1 35001 36.6 78.0 78.1 GE 78.0 78.1 78 - 1 86.3 89.7 89.9 25001 39.2 86.3 86.3 86.3 86.3 GE 86.3 86.3 86.3 86.3 86.3 86.3 84.4 86.1 86.1 86.3 89.7 89.9 93.4 GE 2000 | 40.2 1800 | 40.2 87.6 87.8 89.5 89.5 89.7 89.9 89.7 89.9 89.7 89.9 89.7 89.7 89.9 89.7 89.9 89.7 89.9 89.7 89.9 89.7 89.9 89.7 15001 41.0 91.1 93.1 93.1 93.4 93.4 93.4 93.4 93.5 93.5 93.5 93.5 93.5 93.5 93.5 96.1 96.2 96.2 GE 12001 41.3 96.1 96.2 96.2 96.2 96.8 97.2 98.0 GE GE 10001 41.5 93.9 94.0 96.1 96.3 96.2 96.6 97.0 97.7 96.8 97.1 97.6 98.5 96.9 97.3 96.9 97.3 97.0 97.4 97.0 97.4 97.0 97.4 97.0 97.4 97.0 97.4 97.0 97.4 97.0 97.4 6 E PG0| 41.5 700| 41.5 96.8 97.5 97.7 98.1 98.9 98.1 98.9 98.2 98.2 99.0 98.2 98.2 98.2 94.4 98.2 98.2 94.9 98.6 99.0 99.0 99.0 99.0 GE 6001 41.5 97.7 98.7 98.8 99.0 99.5 99.5 99.5 99.5 99.5 99.5 99.5 5001 41.5 4001 41.5 3001 41.5 99.2 99.2 99.4 99.6 99.6 99.7 99.7 99.7 99.7 99.7 99.7 99.7 95.2 95.2 97.8 98.8 98.8 98.1 98.9 99.6 99.8 99.7 99.7 GE 99.7 99.7 97.8 98.9 99.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 97.8 99.4 6 E 2001 41.5 95.2 98.1 98.9 99.0 99.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100 | 41.5 100.0 100.0 100.0 GE 95.2 98.9 100.0 100.0 98.1 G.F DI 41.5 95.2 97.A 98.1 98.9 99.0 99.4 99.7 99.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0

FOTAL NUMBER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIPILITY FROM HOURLY OBSERVATIONS

STA	ITION N	UMBER:	724505	STATI	ON NAME:	MCCO	NNELL A	FB KS				PERIOD		ORD: 77		1500-17	100
::		• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • •	• • • • • •	• • • • • •						• • • • • •				
	LING N I	GE	GE	GE	GE	c r				IN STAT			. .				_
		10	6	υ <u>ι</u> 5	4	GE	GE	GE	GE	GE	GE .	GE			GE	GE	٥E
_				-			2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	D
٠.	• • • • •	• • • • • • •	• • • • • •	•••••	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •
0	CEIL I	27.0	52.0	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6
Ę	200001	32.9	64.6	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3
Ε	180001	33.2	64.9	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
ε	160001	33.2	64.9	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
E	140001	33.7	66.0	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66 . 7	66.7	66.7	66.7	66.7
E	150001	34.2	66.7	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.5
	100001		69.1	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	76.0
	9000		69.9	70.8	7G.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	7ú.8
	8 000 1		72.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
	7000		73.7	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6
E	6 L N O	37.6	74.0	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9
	5000 ļ		75 - 8	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	17.0	77.0	77.0	77.0
	4.00 [76.2	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4
	4000		81.1	82.8	82.9	83.0	83.0	83.0	83.0	83.0	83.0	83.0	63.U	83.0	83.0	83.0	83.0
E			83.1	84.8	84.9	85.1	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
E	30001	41.1	85.7	87.6	88.0	88.2	88.3	88.3	88.3	88.3	88.3	88.3	88 - 3	88.3	A8.3	86.3	86.3
Ε	25001	42.4	89.1	91.4	91.7	91.9	92.0	92.0	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2
E	2 roo (42.4	90.5	92.8	93.1	93.3	93.4	93.5	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
E	1800	42.4	90.8	93.0	93.3	93.5	93.7	93.8	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
Ε	15001	42.5	92.9	95.4	95.7	96.0	96.1	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
E	1 200 1	42.6	94.4	97.0	97.4	97.7	98.0	98.2	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	96.4
E	1000 (94.8	97.5	98.0	98.3	98.5	98.7	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
E		42.6	94.8	97.5	98.0	98.3	98.5	98.7	99.0	99.0	99.U	99.0	99.0	99.0	99.0	99.0	99.0
E		42.6	94.9	97.6	98.1	98.4	98 • 6	98.8	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
£		42.6	94.9	97.6	98.1	98.4	98.6	98.8	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
E	600 l	42.6	94.9	97.6	96.1	98.5	98.7	98.9	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
Ε		42.6	94.9	97.6	96.1	98.5	98.7	98.9	99.4	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.5
E		42.6	94.9	97.6	98.1	98.5	98.7	98.9	99.4	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.5
£		42.6	94.9	97.6	98.1	98.5	98.7	98.9	99.7	99.7	99.7	99.7	99.6	100.0	100.0	100.0	100.0
E		42.6	94.9	97.6	98.1	98.5	98.7	98.9	99.7	99.7	99.7	99.7	99.8	100.0	100.0	100.0	106.0
Ε	100	42.6	94.9	97.6	98-1	98.5	98.7	98.9	99.7	99.7	99.7	99.7	99.8	100.0	100.0	100.0	100.0
Ε	าเ	42.6	94.9	97.6	98.1	98.5	98.7	98.9	99.7	99.7	99.7	99.7	00 0	100.0	10n n	100.0	100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 71-86
MONTH: MAY HOURS(LS HOURS (LST): 1800-2000 VISIBILITY IN STATUTE MILES CE IL ING IN | GE FEET | 1 GE GE 3 2 1/2 GE GE 1 GE 6 5 GE GE GE 2 1 1/4 GF GF G.f GF 10 1/2 5/16 NO CETE 1 28.2 56.0 56.0 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.1 GE 200001 34.1 GE 180001 34.4 GE 160001 34.6 70.1 76.4 70.9 70.2 70.5 71.0 71.6 70.3 70.6 71.1 71.7 70.0 70.3 70.6 20.3 70.3 70-3 70.3 7 (7 . 3 7 (7 . 6 70.3 70.3 70.6 71.1 70.6 70.6 70.6 70.6 71.1 70.6 71.1 70.6 71.1 70.6 71.1 70.8 71.1 71.1 71.7 71.1 71.1 71.1 GE 140001 34.8 71.7 71.4 71.7 71.7 71.7 71.7 71 - 7 71.7 73.0 73.1 GE 120001 35.4 73.3 GE 10000| 36.9 GE 9000| 36.9 GE 8000| 37.6 77.1 77.3 83.1 76.7 76.9 16.9 77.1 77.1 77.3 77.0 77.1 77.1 77.1 71.3 77.1 77.3 80.1 77.1 77.1 77.5 77.1 77.1 77.1 77.3 60.1 77.2 77.3 79.6 79.9 80.0 1.08 AD.1 80.1 80.1 90.1 80.1 80.1 1.118 80.1 00.5 80.9 70001 18-0 81.0 81.1 81.1 81.1 81.1 61.1 A1 - 1 81.1 81.1 81.1 01.1 F1 - 1 81.5 82.2 62.2 81.8 81.9 82.2 82.2 82.2 H2 . 2 82.2 8...2 50001 39.5 45001 39.6 83.4 84.3 87.5 84.4 85.4 88.7 84.3 84.8 85.8 89.4 64.8 84.8 89.4 84.8 85.8 89.4 GE 84.7 85.7 84.8 85.8 64.8 65.8 89.4 84.8 85.8 84.8 84.8 85.8 84.8 85.7 89.2 95.8 85.8 40001 40.5 35001 40.9 30001 41.6 88.6 89.4 90.8 89.2 89.4 89.4 99.4 49.4 R 4 . 4 (, F 88.7 89.9 90.1 90.6 90.6 90.8 90.8 90.8 90.8 90.8 90.8 96.8 90.6 92.0 92.3 92.8 92.8 92.9 92.9 92.9 92.9 92.9 92.9 92.9 92.9 92.9 2500| 41.8 2000| 41.9 1800| 41.9 91.6 92.3 92.5 93.3 94.4 94.7 95.9 94.1 95.4 95.7 94.0 95.2 95.5 94.1 95.4 95.7 97.4 94.1 95.4 95.7 94 • 1 95 • 4 94.1 95.4 95.7 97.5 94.1 95.4 95.7 94.1 95.4 95.7 94 • 1 95 • 4 95 • 7 94.1 95.4 95.4 94.2 GE 95.5 95.1 95.7 15001 41.9 93.5 95.4 97.0 97.0 97.5 97.5 97.5 97.5 97.5 97.5 97.5 67.5 GF 12001 41.9 90.5 1000| 41.9 900| 41.9 800| 41.9 94.5 94.5 94.5 97.2 97.2 97.2 G E 98.3 98.3 98.4 98.9 99.0 98.9 98.7 98.7 98.9 99.0 98.9 94.9 99.9 99.0 96.7 99.0 99.0 99.0 99.0 98.3 99.0 6E 96.7 98.4 98.8 99.1 99.1 90.1 99.1 7001 41.9 94.6 97.3 99.0 99.0 99.5 99.5 GE 96.8 98.6 98.6 99.5 99.5 99.5 99.5 99.5 49.5 GE 6001 41.9 98.6 99.5 99.5 99.5 99.5 500| 41.9 400| 41.9 300| 41.9 96.6 98.7 99.7 99.7 100.0 99.7 99.7 190.0 98.8 99.7 99.2 99.7 99.7 99.7 99.7 GE 94.6 96.8 97.3 98.7 98.8 99.2 99.7 99.7 99.7 99.7 99.7 99.7 99.7 100.0 100.0 99.7 GF 2001 41.9 96.8 97.3 99.7 99.7 100.0 100.0 100.0 100.0 1001 41.9 96.8 97.3 98.7 98.8 99.2 99.7 99.7 97.7 99.7 100.0 100.0 130.0 106.0 99.7 100.0 01 41.9 96.8 97.3 98.7 98.8 99.2 99.7 99.7 99.7 99.7 100.0 130.0 100.0

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/HAC PERIOD OF RECORD: 77-86

MONTH: MAY HOURS(LST): 2100-2300 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS VISIBILITY IN STATUTE MILES CEILING GE GE 3 2 1/2 IN | GE FEET | 10 G E 6 GE 4 GE GE 5 GE GE GE 2 1 1/2 1 1/4 GE GE GE 1/2 GE 1/4 6**E** 1 3/4 5/8 5/16 60.9 68.9 60.9 60.9 60.9 60.9 60.9 66.9 NO CEIL | 30.6 60.6 60.9 60.9 60.9 60.9 60.9 60.9 70.4 70.8 70.9 70.6 70.6 70.6 70.6 70.6 70.6 71.0 71.1 GE 200001 34.6 GE 180001 34.8 70.6 70.6 70.6 70.6 70.6 70.6 70.6 70.6 71.0 71.0 71.1 71.0 71.0 71.1 71.0 71.0 71.0 71.0 71.0 71.0 71.0 71.0 71.1 71.1 71.1 71.1 GE 160001 34.9 71.1 71.1 71.1 71.1 GE 14000 35.1 71.3 71.5 71.5 GE 120001 35.5 72.9 73.1 73.1 73.1 73.1 73.1 73.1 73.1 73.1 73.1 73.1 73.1 73.1 75.4 75.5 77.6 75.4 75.5 77.6 75.4 75.5 77.6 75.4 75.5 77.6 75.2 75.3 77.1 75.4 75.5 75.4 75.5 75.4 75.5 75.4 75.5 75.4 75.5 77.6 75.4 75.5 77.6 75.4 75.5 GE 10000 35.8 GE 9000 35.8 75.5 77.5 75.5 77.6 GE 75.5 8000 36.3 77.6 77.6 77.6 77.5 77.6 70001 37.0 78.1 78.5 78.6 78.6 78.6 78.6 78.6 78.6 78 - 6 78.6 78.6 78.6 78.6 78.6 76.6 60G01 37.4 81.9 83.4 86.9 82.0 82.0 92.D 82.0 83.5 87.3 50001 38.3 81.9 82.0 82.0 82.0 82.0 ЬE 81.9 81.9 83.3 4500| 38.6 4000| 39.5 82.6 85.7 83.4 87.2 83.4 87.2 83.4 87.2 83.5 63.5 87.3 83.5 87.3 83.5 87.3 83.5 87.3 83.5 87.3 83.5 87.3 GE 83.5 87.3 GE 86.7 35001 39.7 87.5 87.7 88.2 88.4 89.4 88.4 88.4 88.4 88.4 RA . 4 G E 30001 40.2 88.6 89.9 96.2 90.8 90.8 90.8 91.0 91.0 91.0 91.0 91.0 91.0 91.0 91.0 91.0 89.5 90.5 91.1 91.8 93.0 93.8 G E G E 90.9 92.0 91.2 92.4 91.8 93.0 92.0 93.2 92.0 93.2 92.U 93.2 92.0 93.2 92.0 93.2 92.0 93.2 92.0 93.2 92.0 93.2 25001 40.2 91.8 93.0 92.6 2000 | 40.3 1800| 40.3 93.8 92.7 93.0 93.0 94.0 GΕ 93.8 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 15001 40.3 94.1 94.4 91.3 94.1 GΕ 1200 | 40.3 96.2 96.2 96.2 96.2 96.2 97.1 97.4 98.4 95.9 96.7 97.0 98.0 10001 40.3 93.5 9001 40.3 8001 40.3 96.2 97.6 97.6 GF 95.7 97.0 97.6 97.6 97.6 97.6 97.6 97.6 97.6 98.6 98.6 98.6 98.6 98.6 96.6 96.2 96.0 GE 7001 40.3 96.5 97.3 98.2 98.2 98.8 99.0 99.0 99.0 99.0 99.0 99 . R 99.0 99.0 99.0 99.0 99.0 99.0 99.D 99.0 99.0 99.0 99.0 GE 6001 40.3 93.9 96.5 97.3 98.2 98.2 98.8 99.0 93.9 93.9 93.9 97.5 97.7 97.7 99.1 99.5 99.5 99.4 99.7 99.8 99.4 99.7 99.8 99.4 99.7 99.8 99.4 99.7 99.8 f. F 5001 40.3 96.€ 99.4 98.5 99.4 99.4 99.4 99.4 99.4 4001 40.3 98.8 99.7 99.7 99.7 99.7 99.7 96.8 98.7 98.7 6 F 96.8 2001 40.3 93.9 97.7 99.7 98.8 99.5 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 96.8 1001 40.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0

99.9

100.0 100.0

100.0 100.0 100.0 100.0 100.0 100.0

TOTAL NUMBER OF OBSERVATIONS: 940

93.9

96.8

01 40.3

GE

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

CTATION NUMBER - 320505 - 5747100 - 5465 - 400000011 - 458 MC

STATION	NUMRE	R: 724505	STATI	ON NAME:	4000	NNELL A	FB KS				PERIOD Month		ORD: 77 HOURS	-86 (LST):	ALL	
CEILING	• • • • • •	••••••	• • • • • • •	• • • • • • • •	• • • • • •	• • • • • • •						• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	•••••
IN	, 1 CE	GE	GE	GE	G£	GE	G F	GE	IN STATE	of Oic ⊨ir	66	·		G.E.		
FEET	1 1		O.C.	4		2 1/2		1 1/2		0 t	5/4	Θ <u>ε</u> 5./8	1/2 5£	5/16	6€ 1/4	LF C
										-		-		2/10	1/4	
•••••	••••							•••••		• • • • • • •	• • • • • • •	• • • • • • • •	•••••	• • • • • •		
NO CEIL	1 24.	7 52.2	52.9	53.2	53.3	53.3	53.4	53.4	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
GE 2000	O 28.	7 61.2	62.U	62.4	62.6	62.6	62.6	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.8
6E 1800	101 75.	9 61.6	62.4	62.7	62.9	62.9	63.0	63.0	63.0	63.1	6 7 . 1	63.1	63.1	63.1	63.1	63.1
UE 16F0			62.5	62.8	63.1	63.1	63.1	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.3
UE 1400			63.1	63.4	63.6	63.6	63.7	63.7	63.7	63.7	63.8	63.8	63.8	63.8	63.8	63.8
6F 1200	101 29.	7 63.6	64.4	64.8	65.0	65.Q	65.1	65.1	65.1	65.1	65.1	65 - 1	65.2	65.2	65.2	65.2
GF 1000	01 30.	9 66.7	67.7	66.0	68.2	66.3	68.3	68.4	68.4	68.4	68.4	68 - 4	68.4	68.4	68.4	68.5
UE 900	O (31.	0 66.9	67.9	68.2	6°.5	68.5	68.6	68.6	68.6	68.6	64.6	68.6	68.7	68 . 7	68.7	60.7
	0 32.		71.2	71.6	71.9	71.9	72.0	72 • U	72.0	72.0	72.0	72.0	72.1	72.1	72.1	7 1
	01 35.		12.3	72.6	72.9	73.0	73.0	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.2
ce end	101 32.	8 72.1	73.2	73.6	73.9	73.9	74.0	74.0	74.1	74 - 1	74.1	74 - 1	74 - 1	74.1	74.1	74.2
uf 500	01 31.	9 74.5	16.0	76.4	76.8	76.8	76.9	76.9	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.1
	.nl 34+		76.8	77.2	77.6	77.6	77.8	77.8	77.8	77.8	77.8	77.6	77.9	77.9	77.9	77.9
	ID] 34.		80.2	8 U • 7	81.1	81.2	81.3	81.4	61.4	B1.4	81.4	81.4	81.4	81.4	81.5	P1.5
	0 35.		81.4	82.O	b2.5	82.5	82.7	82 - 7	82.8	82.8	82.8	82.8	82.8	82.8	8.28	F H
GF 300	01 36.	0 82.0	84.1	84.7	85.2	85.3	85.5	85.5	45.5	85.6	85.6	85.6	85.6	85.6	85.6	85.6
⊍E 2*Β	01 36.	5 83.8	86.0	A 6 . 7	87.3	97.4	87.5	87.6	87.6	87.6	87.6	87.6	87.7	87.7	87.7	87.7
	0 36.		87.8	88.6	89.3	89.3	89.5	89.6	89.7	R9.7	89.7	89.7	89.7	89.7	89.7	89.7
	0 36.		88.2	85.0	89.7	89.8	$a \cdot a_{e}$	90.1	90-1	90 • 1	90.1	90.1	90.1	90.1	90.1	90.2
	0 37.		90.1	91.9	91.7	91.8	92.1	92.2	92.2	92.3	92.3	92.3	92.3	92.3	92.3	92.3
6F 120	0 1 37.	5 89.2	92.0	92.9	93.7	93.8	94.1	94.5	44.3	94.3	94.3	94.3	94.4	94.4	94.4	94.4
	01 37.		93.2	94.1	95.0	95.1	95.5	95.7	95.7	95.7	95.7	95.7	95 . R	95.8	95.8	95.8
	01 37.		93.6	94.6	95.5	95.6	96 • B	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3
	01 37.		94.1	95.2	96.1	96.3	96 • 7	97.U	47.0	97.1	97-1	97.1	97.1	97.1	97.1	97.1
	37.		94.5	95.6	96.7	96.9	97.4	91.7	47.7	97.8	97.B	97.8	97.8	97.8	97.8	97.8
LE 60	01 37.	7 91.4	94.7	95.9	97.0	97.2	47.7	98.1	98.2	98.2	98.2	98.2	48.2	98.2	98.3	96.3
6E 50	0 37.	7 91.5	94.9	96.1	97.3	97.6	98.2	98.7	98.7	98.6	98.8	98.8	98.A	98.5	48.8	96.9
	01 57.		95.0	96.3	97.5	97.8	98.5	99.1	99.1	99.2	99.2	99.2	99.3	99.3	99.3	94.3
	01 37.		95.C	90.4	97.6	98+0	98.7	99.3	99.4	99.5	99.5	99.6	99.7	99.7	99.7	94.7
	01 37.		95.U	90.4	97.7	98.0	98.7	99.4	99.5	99.7	99.7	99.7	99.8	99.8	99.9	100.0
GE 1U	ol 37.	A 91.5	95.0	96.4	97.1	96.0	98.7	99.4	99.5	99.7	99.7	99.7	99.8	99.9	99.9	100.0
6E	0 37.		95.6	96.4	97.7	98-0	98•7	99.4	99.5	99.7	99.7	99.7	99.8	99,9	99.9	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

		-					NNELL A					MONTH		HOURS	(LST):		00
	LING		• • • • • • •	• • • • • • •	• • • • • • •				BILITY					• • • • • • •	• • • • • • •	• • • • • •	• • • • • •
		GE	GE	GE	GE	GΕ	GE	GΕ	GE	GE	GE	GE	G€	GE	GE	GE	GE
	ET 1		6		4	3	2 1/2	2	1 1/2			3/4	5/6	1/2	5/16	1/4	
O	CE IL I	77.8	63.3	63.4	63.7	63.8	63.8	64.0	64.0	64.0	64.0	64.0	64.6	64.0	64.0	64.D	64.1
	200001		74.0	74.1	74.3	74.4	74.4	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.8
	180001		74.1	74.2	74.4	74.6	74.6	74 - 8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.9
	100001		74.1	74.2	74.4	74.6	74.6	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.9
	140001		74.1	74.2	74.4	74.6	74.6	74.8	74.8	74.8	74.8	74.8	74.8	74 • B	74.8	74.8	74.9
Ē	12000	37.3	74.8	74.9	75.2	75.3	75.3	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.7
E	100001	37.9	78.0	78.1	76.4	78.6	78.6	78.8	78.8	78.8	78.8	79.8	78.8	78.8	78.8	78.8	76.9
E	900ni	37.9	78.0	78.1	78.4	78.6	78.6	78.8	78.8	78 - 8	78.8	79.8	78.8	79.8	78.8	78.8	76.9
Ε	8000	39.1	81.2	81.3	81.7	81.8	81.8	82.0	82.0	82.0	82.0	87.0	82.0	82.0	82.0	82.0	P. 1
E	70001	39.2	82.8	82.9	83.2	83.3	83.3	83.6	83.0	63.6	#3.6	83.6	83.6	83.6	83.6	83.6	A3.7
Ε	60001	39.4	83.4	83.E	83.9	84.0	84.C	84 • 2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.3
Ē	5 can (39.7	85.7	85.8	86.1	86.4	86.4	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.8
E	45001	40.0	86.2	86.3	86.7	87.0	87.C	87.2	87.2	87.2	P7.2	87.2	87.2	87.2	87.2	87.2	87.3
Ε	4000	40.4	89.7	89.8	96.1	90.4	90.4	90.7	94.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.8
Ε	35001	41.0	90.7	90.9	91.2	91.6	91.6	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	92.0	92.1
E	30001	41.1	92.0	92.4	92.9	93.2	93.2	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.8	93.9
Ε	25no1	41.1	92.8	93.2	93.7	94.0	94.0	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.6	94.7
E	20001	41.3	93.6	94.0	94.4	94.9	94.9	95.3	95.3	95.3	95.3	95.4	95.4	95.4	95.4	95.7	95.8
Ε	18001	41.3	93.8	94.2	94.7	95.1	95.1	95.6	95.6	95.6	95.6	95.7	95.7	95.7	95.7	95.9	96.0
E.	15001	41.4	94.8	95.4	95.9	96.3	96.3	96.8	96.8	96.8	96.8	96.9	96.9	96.9	96.9	97.1	97.2
Ε	12001	41.4	94.9	95.7	96.2	96.7	96.7	97.2	97.2	97.2	97.2	97.3	97.3	97.3	97.3	97.6	97.7
Ε	10001	41.8	95.2	96.U	96.6	97.0	97.4	97.6	97.6	97.6	97.6	97.7	97.7	97.7	97.7	97.9	96.0
Ε		42.0	95.6	96.3	96.9	97.3	97.3	97.9	97.9	97.9	97.9	9 A . D	98.0	98.0	98.0	98.2	98.3
E		42.0	95.6	96.3	96.9	97.3	97.3	97.9	97.9	91.9	97.9	98.0	98.0	98.0	98.0	98 • 2	96.3
Ε		42.0	95 - 8	96.6	97.1	97.6	97.6	98.1	98.1	98.1	98.1	98.2	98.2	98.2	98.2	98.4	98.6
Ξ	6001	42.0	95.8	96.6	97.1	97.6	97.6	98.2	98.2	98.2	98.2	98.3	98.3	98.3	98.3	48.6	96.1
Ξ	5001	42.0	96 • 2	97.D	97.6	98.1	98.1	98.8	98.8	98.8	98.8	90.9	98.9	98.9	98.9	99.1	99.2
Ε	4001	42.0	96.2	97.1	97.9	98.7	96.7	99.5	99.3	99.3	99.3	90.4	99.4	99.4	99.4	99.7	99.8
E		42.0	96 • 2	97.1	98.0	98.9	96.9	99.6	99.6	49.6	99.6	99.7	99.7	99.7	99.7	99.9	100.0
E		42.0	96.2	97.1	98.0	98.9	98.9	99.6	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.9	100.0
£	1001	42.0	96 • 2	97.1	98.0	98.9	98.9	99.6	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.9	106.0
		42.0	96.2	97.1	98.0	98.9	98.9	99.6	99.6	49.6	99.6	99.7	99.7	99.7	99.7		100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

ATION	NUMBER:	724505	STATE	UN NAME:	мссо	NHELL AI	. B K?				PERIOD MONTH	OF REC		-86 {LST1:	5300-05	00
IL I !! G		• • • • • • •	••••	• • • • • • • •	• • • • •	• • • • • • •			IN STATE			• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •
IN	30 [30	GE	٥E	G£	G£	GE	GE	GE	GE	GΕ	GΕ	5 Ł	ĢΕ	D.E.	LE
EET	1 10	ь	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	٤
	•••••		•••••	• • • • • • • •		• • • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •		
CEIL	1 29+0	59.7	60.6	61.2	61.3	61.4	61.6	61.0	61.6	61.6	61.6	61.6	61.6	61.6	61.8	61.9
20000	11 30.4	68.7	69.6	70.2	70.3	70.4	70.6	70.6	70.6	70.6	70.6	70.6	70.6	73.6	70.8	76.9
	30.9	68 - 8	69.7	76.3	70.4	70.6	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.9	71.1
16000	30.9	68.8	69.7	70.3	70.4	70.6	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.9	71.
14000	1 31.0	69.2	70.1	74.8	70.9	71.0	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.3	71.
12000	31.7	70.3	71.2	71.9	72.0	72.1	72.2	72.2	12.2	72.2	72.2	72.2	72.2	72.2	72.4	72.
1000	1 32 a	74.2	75.1	75.8	75.9	76.G	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76 • 3	76.
	32.8	74.2	75.1	75.8	75.9	76.0	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.3	76.
8000	33.9	78.1	79.0	79.7	79.8	79.9	80.0	80.0	60.0	80.0	80.0	80.0	80.0	80.0	ø0.2	80.
	11 34.6	80.7	81.6	82.2	82.3	82.4	82.6	82.6	82.6	82.6	82.6	82.6	82.6	R2.6	82.8	8
6000	34.7	80.9	81.8	82.4	87.6	82.7	82.8	82.8	87.8	82.8	82.8	82.8	82.8	R2.8	0.80	83.
5000	35.0	82.1	83.0	8 3 • 7	83.8	A3.9	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.C	64.2	84.
4 = 00	1 35.0	82.6	83.4	84.1	84.2	84 - 3	34.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.7	84.
4000	36.0	85.8	86.8	87.4	87.7	87.8	87.9	87.9	67.9	87.9	87.9	87.9	87.9	87.9	68.1	8 b •
3500	1 36.4	86.8	87.9	88.7	88.9	89.1	89.3	89.3	89.3	89.4	89.4	89.4	89.4	89.4	69.7	84.
3000	1 36.8	P8 • 4	89.8	90.7	90.9	91.2	91.4	91.4	91.4	91.7	91.7	91.7	91.7	91.7	91.9	92.
2500	1 36.8	89.1	90.4	91.3	91.6	91.9	92.4	92.4	92.4	92.7	92.7	92.7	92.7	92.7	92.9	93.
2000	11 37.0	89.7	91.0	91.9	92.1	92.6	93.1	93.1	93.1	93.3	93.3	93.3	93.3	93.3	93.6	93.
1 P G C	11 37.C	89.9	91.3	92.2	92.4	92.9	93.4	93.4	93.4	93.7	93.7	93.7	93.7	93.7	93.9	94.
	11 37.2	90.6	92.2	93.6	93.8	94.2	94.8	94.8	94.8	95.C	95.0	95.0	95.0	95.0	95.2	95.
1200	37.4	90.9	92.7	94.0	94.2	94.7	95.2	95.2	95.2	95.4	95.4	95.4	95.4	95.4	95.7	95.
1000	11 37.7	91.1	92.9	94.2	94.4	94.9	95.4	95.4	95.4	95.7	95.7	95.7	95.7	95.7	95.9	96.
	11 37.7	91.1	92.9	94.2	94.4	94.9	95.4	95.4	95.4	95 • 7	95.7	95.7	95.7	95.7	95.9	96.
	37.8	91.4	93.2	94.6	94.8	95.2	95.8	95.8	95.8	96.0	96.0	96.0	96 • C	96.0	46.2	96.
	1 37.A	91.9	93.7	95.1	95.3	95.8	96.4	96.4	46.4	96.7	96.7	96.7	96.7	96.7	86.8	97.
ზიმ	1 57.A	91.9	43.7	95.1	95.3	95.8	96.4	96.4	96.4	96.7	96.7	96.7	96.7	96.7	96.9	97.
	1 37.8	92.3	94.4	95.9	96.1	96.6	97.2	97.2	97.2	97.4	97.4	97.4	97.4	97.4	97.7	97.
	11 37.8	92.3	94.4	96.0	96.3	96.8	47.6	91.7	97.7	97.9	97.9	97.9	97.9	97.9	98.1	96.
	1 37.B	92.5	94.8	96.6	97.0	97.4	48.2	98.6	¥8.7	98.9	98.9	98.9	98.9	96.9	99.1	99.
	11 37.P	92.3	94.8	96.6	97.2	97.7	98.6	98.9	99.0	99.2	99.3	99.3	99.3	99.3	99.6	99.
100	37.8	92.3	94. #	96.6	97.7	97.7	99.6	98.9	99.0	99.3	99.6	99.6	99.6	99.6	99.9	100.0
r	11 37.8	92.3	94.8	94.6	97.2	97.7	98.6	98.4	99.0	99.3	99.6	99.6	99.6	99.6	99.9	100-0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

STATION	NUMBER:	724505	STATIO	ON NAME:	HCCO	NNELL AF	вкѕ				PERIOD MONTH	OF RECO			u 6⊔0- <u>n</u> 8	ւն
CEILING	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •			IN STATE			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	
IN	1 68	GE	GE	G.F	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
FEET	1 10	6	5	4	3	2 1/2	2		1 1/4	1	3/4	5/8	1/2	5/16	1/4	ū
NO CETL	1 24.1	48.9	50.7	51.4	51.9	51.9	51.9	51.9	51.9	52.0	52.1	52.1	52.1	52 • 1	52.1	52.1
GF 20000		60.1	62.1	63.0	63.7	63.7	63.7	63.7	63.7	63.8	63.9	63.9	63.9	63.9	64 • C	64.4
5E 18€0€ 6E 16€0€		60.3	62.3	63.2	63.9	64.0	64.0	64.0	64.0	64.1	64.2	64.2	64 • 2	64.2	64.3	64.3
		60 • 3 60 • 4	62.3 62.4	63.3	64.0	64.1	64.1	64-1	64.1	64.2	64.3	64.3	64.3	64 • 3	54.4	64.4
- 6€ 14000 - 6€ 12000		61.8	63.8	64.8	64.1	64 • 2 65 • 6	64.2 65.6	64.2	64.2	64.3	64.4	64.4	64.4 65.8	64.4	65.9	64.6 65.9
36 14 (6)	11 24.1	01.6	03.0	04.0	03.4	63.6	00.0	65.6	65.6	65.7	65.8	65.8	63.6	03.0	02.4	63.4
6F 1000	30.0	66.3	68.3	69.3	70.1	70.2	70.2	70.2	70.2	70.3	70.4	70.4	70.4	70.4	70.6	70.6
	30.3	67.1	69.1	76.1	70.9	71.0	71.0	71.0	71.0	71.1	71.2	71.2	71.2	71.2	71.3	71.5
	31.3	71.1	73.1	74.1	74.9	75.0	75.0	75.U	75.0	75.1	75.2	75.2	75.2	75.2	75.3	75.3
GE 7000	31.7	73.1	75.2	76.3	77.1	77.2	77.2	77.2	77.2	77.3	77.4	77.4	77.4	77.4	77.6	77.6
UE 6000	31.9	74.1	76.2	77.3	78.1	78.2	78.2	78.2	78.2	78 • 3	78.4	78.4	79.4	78.4	78.6	70.6
	32-1	75 • 1	77.2	78.6	79.3	79.4	79.4	79.4	79.4	79.6	79.7	79.7	79.7	79.7	79.8	79.8
	1 32.4	75.9	78.0	79.3	80.1	80.2	80.2	83.2	80.2	AC . 3	80.4	80.4	80.4	PG.4	80.6	P6.6
	32.6	77.4	79.6	81.6	82.3	82.4	82.6	82.6	82.6	R2.7	82.8	82.8	82.8	8.59	62.9	82.9
	32.7	78.2	80.7	82.4	83.3	83.4	83.6	83.6	a 3 . 6	83.7	83.6	83.8	83.8	93.8	63.9	63.9
oE 3000	33.1	79.6	82.0	84.0	84.9	85.0	85.2	85.2	85.2	A5.3	85.4	85.4	85.4	85.4	85.6	85.6
CF 2505		0.61						• • •			07.0	0.7 0	0.7 0	47		
	33.7	80.9 82.0	83.4 84.9	85.6 87.0	86.4	86.6 88.1	86.8 88.4	86.8 88.4	66.8 88.4	96.9 88.6	87.0 69.7	87.0 88.7	97.0 88.7	97.0 88.7	87.1 88.8	67.1 80.8
	33.4	82.3	85.4	87.6	88.4	88.7	89.0	89.0	89.0	89.1	89.2	89.2	89.2	89.2	89.3	89.3
	33.8	92.8	85.9	88.0	88.9	89.1	89.6	89.6	89.6	P9.7	89.8	89.8	89.8	89.8	69.9	89.9
	34.1	83.9	87.3	89.4	90.3	90.7	91.1	91.1	91.1	91.2	91.3	91.3	91.3	91.3	91.4	91.4
	, , , , , ,				, , , ,	, , ,			,							
6E 1000	1 34.3	84.9	88.7	90.8	91.7	92.0	92.4	92.4	92.4	92.6	92.7	92.7	92.7	92.7	92.8	92.8
	34.6	85.8	89.7	91.9	92.8	93.1	93.6	93.6	93.6	93.7	93.8	93.8	93.8	93.8	93.9	93.9
GE BUO	1 34.6	86.4	90.4	92.7	93.6	93.9	94.3	94.3	94.4	94.6	94.7	94.7	94.7	94.7	94.8	94.8
UE 700	34.6	86.9	91.1	93.4	94.4	94.8	95.2	95.2	95.3	95.4	95.6	95.6	95.6	95.6	45.7	95.7
GE 600	11 34.6	86.9	91.4	94.2	95.2	95.7	96.1	96.1	96.2	96.3	96.4	96.4	96.4	96.4	96.6	96.6
GE 500	11 34.6	87.1	91.8	95.0	96.4	96.9	97.3	97.4	97.6	97.7	97.8	97.8	97.8	97.8	97.9	97.9
	34.6	87.3	92.1	95.3	96.9	97.3	98.0	98.1	98.2	98.3	98.6	98.6	98.5	4.80	98.7	48.7
	34.6	A7.4	92.3	95.6	97.2	97.8	98 • 6	98.8	98.9	99.1	99.3	99.3	99.3	99.3	99.4	99.4
	34.6	87.4	92.3	95.6	97.2	97.8	98.6	98.9	99.1	99.4	99.7	99.7	99.3	99.9	100.0	100.0
GE 100	34.6	87.4	92.3	95.6	97.2	97.8	98.6	98.9	99.1	79.4	99.7	99.7	99.8	99.9	100.0	106.0
GE C	1 34.6	87.4	92.3	95.6	97.2	97.8		00.0	99.1	99.4	99.7	99.7	99.8	00.0	100.0	100 5
UE	-			73.0	71.2	71.8	98 • 6	98.9	-						100.0	100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION N	JMEER:	724505	PINITON	NAME:	MCCONN	ELL AF	B KS				PFEIOD	OF REC	OPU: 77	-86		
											MONTH	: JUN	HOURS	(LST):	6930-116	.0
• • • • • • • •			• • • • • • •	• • • • • •		• • • • • •					• • • • • • •		• • • • • • •	• • • • • • •		
CEILIMG							VISIB	ILITY 1	IN STATI	BTE MILE	. \$					
IN [GE	GE	GE	G E	GE	GE	GĘ	GE	GŁ	GE	6£	GE	G£	Ŀ€	GE	U

													. 504			0420.11	CC
• •		• • • • • •		• • • • • • •	• • • • • • •		• • • • • • •						• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • •
CE	IL I 46							VISI	BILITY	IN STAT	BIE MIL	.E.S					
	IN [GE	GE	GE	G E	GE	GE	GE	GE	GE	GE	6£	GE	G£	Ŭ€	GE	u E
	EET I	10	6	5	4		2 1/2		1 1/2		1	3/4	5/6	1/2	116	1/4	ل
		-									_				, , , ,	1/4	U
• •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • • • • • •
NO	CEIL	27.3	54.6	55.7	55.8	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
													•				
	200001	20 11	63.1	64.3	64.4	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
	180001		63.3	64.6	64.9	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.6	65.0	65.4	65.0	65.0
	100001		64.1	65.6	65.7	65.8	65.8	65.8	65.8	65.8	65•€	65.8	65.8	65 • 8	65.8	u 5 • 8	65.6
ũΕ	140001	30.9	64.2	65.7	65.8	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9
GE	120001	31.6	65 • 4	66.9	67.0	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67-1
- •	00.	••••	0.3						•	•		• • • •				• • •	0,
					. .												
	100001		70.0	71.4	71.6	71.7	71 - 7	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7
ĿΕ	90001		73.8	72.2	72.3	72.4	72.4	72.4	72.4	72.4	72.4	77.4	72.4	72.4	72.4	72.4	72.4
GΕ	60001	34.9	74.3	75.6	75.9	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76 • U	76.0	76.U	76.0	76.J
GΕ	7000	35.1	75.4	77.0	77.1	77.2	77.2	77.2	77.2	77.2	77.2	77.2	11.2	17.2	77.2	77.2	77.2
GE			76.1	77.8	78.0	78.1	78.1	78.1	78.1	78.1	78.1	70.1	78.1	78.1	78.1	78.1	78.1
O L	0.001	J 7. 1	,0.1					,,,,	,,,,				10 1	, , , ,	, , ,		.0.1
GΕ	5000	35.8	77.9	79.6	79.8	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	19.9	74.4
5 E	4 5 0 0 1	35.9	78.3	80.0	80.2	80.3	80.3	80.3	80.3	60-3	80.3	80.3	80.3	80.3	80.3	8D.3	F6.3
υE	40001	36.1	80.6	82.6	83.0	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	1 - ذ ع
GΕ	35001	36.3	81.3	83.9	84.1	84.2	84.2	84.2	84.2	64.2	84.2	84.2	84.2	84.2	94.2	84.2	P4 . Z
ĿΕ			82.3	84.9	85.3	85.4	85.4	85.4			85.4	85.4			A5.4	85.4	85.4
G E	3,001	30.4	52.3	04.7	00.5	05.4	H 2 + 4	03.4	85.4	05.4	4.00	07.4	85.4	85.4	73.4	00.4	63.7
Ŀ€	25001	36.6	82.9	85.4	85.9	86.4	86.4	86.6	86.6	86.6	86.6	86.6	86.6	86.6	96.6	86.6	86.6
G E	20001	36.8	85.3	88.2	88.7	89.3	89.3	89.4	89.4	69.4	89_4	89.4	89.4	89.4	89.4	69.4	84.4
GΕ	10001	36 × 8	85.3	88.2	88.7	89.3	89.3	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	84.4
G F	1500		86.1	89.2	89.3	90.6	90.6	90 - 7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
G.F	12001		88.9	92.2	92.9	93.7	93.7	93.8	93.8	93.8	93.8	97.8	93.8	93.8	93.8	93.8	93.8
υĽ	12001	31.0	88.9	92.2	72.7	93.1	43.1	93.B	42.8	A 2 * U	93.0	7: . 6	43.8	93.0	93.6	A 2 • B	43.5
GΕ	10001	37.7	90.3	94.0	94.9	95.7	95.7	95.8	95.8	95.8	95.8	95 · B	95.8	95.8	95 • 8	95.8	95.0
GΕ	9001	37.B	90.8	94.6	95.6	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	46.4
GE	FU01	37 8	91.8	95.9	97.0	97.8	97.6	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
υE	7001		91.8	96.0	97.2	98.0	96.0	98.1	98.3	98.3	98.3	98.3	98.3	98.3	98.3	ÿ8 . 3	90.3
GE									_								
UT.	6001	37.8	91.9	96.1	91.7	98.4	96.4	98.6	98 • 8	98 • 8	98.8	98.8	98.8	98.8	98.8	98.8	98.6
υE	5001	37.8	92.4	96.8	98.4	99.3	99.3	99.6	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	44.8
6 E	4001		92.4	96.8	96.4	99.3	99.4	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE	7901		92.4	96.8	98.4	99.3	99.4	99.7	100.0	100.0	100.0	100.0	100.0	100.0	170.0	100.0	100.6
6.5	2001		_														
			92.4	96.8	98.4	99.3	99.4	99.7	100.0	100.0	100.6	100.0	100.0	100.0	100.0	130.0	160.0
υ£	1001	37.8	92.4	96.8	90.4	99.3	94.4	99.7	100.0	160.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GΕ	ρI	37.8	92.4	96.8	9 8 . 4	99.3	99.4	99.7	100.0	140.0	. 00 - 0	100-0	100 0	100.0	100.0	1.00.0	106.0
		2110	72 4 4		, ,, • •					100.0		10000	,00,0	100.0	10010	100.0	

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PEPIOD OF RECORD: 11-86
MONTH: JUN HOURS(ES MONTH: JUN HOURS(LST): 1200-1400 CEILING VISIBILITY IN STATUTE MILLS GE IN | CL FEET | 10 GE CE GE GE 3 2 1/2 GE GE GE GE 2 1 1/2 1 1/4 1 GE G.F GF GE GF FEET | 10 6 5 4 3 2 1/2 3/4 5/8 1/2 5/16 1/4 NO CEIL | 31.2 57.2 58.3 58.6 58.6 58.6 58.6 58.6 58.6 58.6 58.6 58.6 58.6 58 . 6 58.6 68.7 GE 200001 35.0 68.4 68.7 68.7 68.7 68.7 69.0 69.3 69.7 GE 160001 35.1 GE 160001 35.1 67.3 69.8 69.3 69.0 69.3 69.0 69.3 69.0 69.3 69.3 69.0 69.3 69.3 69.3 69.0 69.3 49.0 64.0 69.3 69.7 GE 140001 35.1 68.0 69.4 69.7 69.7 69.7 69.7 69.7 69.7 69.7 69.7 69.7 69.7 64.7 69.9 70.1 70.1 70.1 70.1 70.1 70.1 UE 120001 35.6 70.1 70.1 70.1 68.4 76.1 70.1 GE 100001 36.4 GE 90001 36.7 74.4 74.4 74.4 74.2 74.4 74.4 74 - 4 74.4 74.4 74.4 74.4 74.9 77.8 78.2 75.2 75.2 75.2 75.2 75.2 75.2 75.2 75.2 75.2 75.2 78.1 78.1 78.1 78.6 78.1 78.1 78.6 78.1 78.6 78.1 GΕ 8rppl 37.8 76.3 76.1 78.1 78.1 78.1 78.1 78.1 70001 38.0 78.6 78.6 78.6 78.6 79.6 60001 38-1 79.6 19.6 79.6 79.6 79.6 79.6 79.6 74.6 50001 38.4 45001 38.4 80.8 80.8 8 C . B 80.8 80.8 80.8 80.8 80.8 80.8 84.1 87.3 GE 78.9 8:1.3 86.8 80.8 84.1 80.8 8 · O a 80.8 80.8 80.6 80.8 80.6 80.B 80.8 84.1 40001 38.9 83.7 84.1 84.1 84.1 84.1 84.1 84.1 84.1 84.1 84.1 87.3 6.6 35.101 40-1 84 . A 86.9 R 7 - 3 87.3 87.3 87.3 87.3 £7.3 87.3 30001 40.6 88.3 90.4 91.1 91.1 2500| 41.9 2000| 41.9 1800| 41.9 91.0 92.4 92.7 93.1 94.6 94.8 93.8 95.2 95.4 93.9 95.3 95.6 93.9 95.3 95.6 93.9 95.3 95.6 93.9 95.3 95.6 93.9 95.3 95.6 93.9 95.3 95.6 96.3 93.9 91.9 93.9 93.9 95.3 93.9 43.5 95.3 95.6 95.3 95.6 95.3 95.3 95.3 95.6 GΕ 96.3 96.3 ъE 12001 41.9 94 - 7 97.0 97.9 97.9 97.9 97.9 97.9 97.9 97.9 98.0 98.0 98.0 96.0 1000| 41.9 98.6 98.9 98.6 98.9 98.6 58 64 95.2 95.4 97.7 97.9 98.6 98.9 98.6 98.9 98.6 98.9 98.6 98.9 98.6 94.7 98.7 98.7 95.7 9001 41.9 FOOT 47.1 98.9 98.9 99.0 99.0 99.0 99.2 98.8 99.3 99.6 99.6 1,5 95.8 98.2 99.4 99.4 99.4 99.4 99.4 99.4 99.4 99.4 99.6 99.6 7001 42.1 95.8 99.4 99.4 99.4 99.4 99.4 99.4 99.4 99.6 49.6 99.6 98.2 99.3 99.4 6 E 99.8 99.8 6401 42.1 99.7 99.7 99.7 5001 42.1 99.8 99.9 100.0 100.0 100.0 96.6 98.4 99.6 99.7 99.7 99.7 99.8 99.8 99.9 160.0 4001 42.1 3001 42.1 2001 2.1 GE GE 96 • D 98.4 98.4 99.6 99.7 99.7 99.7 99.1 99.1 99.8 99.8 99.8 99.8 99.8 99.9 99.9 99.9 100.0 188.3 100.0 100.0 100.0 100.0 100.0 96.0 98.4 95.6 99.7 99.7 99.7 99.R 99.8 99.8 99.9 99.9 130.0 100.0 100.0 100.0 99.8 1001 42.1 99.9 99.9 100.0 GE 96 . L 98.4 99.6 99.7 99.7 99.7 99.8 99.8 100.0 106.0 196.0 01 42.1 96.0 98.4 94.6 99.7 99.7 99.7 99.8 99.8 99.8 99.9 100.0 100.0 100.0 100.0

TOTAL NUMBER OF OBSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCUPRENCE OF CELLING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNECL AFB KS PEPIOD OF RECOPD: 77-8; MONTH: JUN HOURS(LST): 1500-17(0 CEILING IN | GE FEET | 10 VISIBILITY IN STATUTE MILES GE GF GE GE GE 2 1 1/2 1 1/4 1 3/4 1/2 5/8 1/16 NO CETE 1 32.1 60.6 60.8 8.04 64.8 60.8 72.6 12.8 12.9 72.6 72.8 72.8 72.6 12.8 JE 200001 36.8 72.6 72.8 72.6 72.6 7... 72.3 72.6 12.6 72.6 72.6 72.8 72.8 GE 180001 36.8 GE 160001 36.8 72.6 72.6 72.8 72.8 72.8 72.8 72.8 72.8 72.8 72.8 72.8 72.6 12.8 12.8 12.8 12.8 12.6 72.8 72.8 13.0 72.8 72.8 73.0 140001 37.0 72.8 73.0 73.0 13.0 73.0 73.0 73.0 73.0 73.0 73.0 73.0 73.0 73.6 6f 1200G1 37.3 74.0 74.2 74.2 74.2 74.2 74.2 6E 10000| 34.7 of 9000| 34.8 6E 8000| 40.8 GE 7000| 41.0 77.9 78.1 82.0 82.7 78 · 1 78 · 3 82 · 2 78.1 78.3 82.2 78.1 78.3 82.2 82.9 78.1 78.3 82.2 78.1 79.3 82.2 78.1 78.3 78.1 78.1 78.3 78.1 78.3 78.1 78.3 78.1 78.3 78.1 78.1 76.1 76.3 P2.2 P2.9 78.3 7e.3 78.3 82 • 2 82 • 9 82.2 82.2 82.2 82.2 82.9 62.9 82.9 82.9 82.9 82.9 60001 41.3 83.7 83.7 83.7 83.7 83.7 R 5 . 7 83.7 83.7 83.7 83.7 03.7 63.7 5000| 41.6 4500| 41.7 4000| 42.3 84.8 84.9 87.0 85.0 85.1 87.7 91.1 45.0 85.1 87.7 85.0 85.1 87.7 71.1 85.0 85.1 85.0 85.1 85.0 85.1 85. 85.1 F. . 1 8 7 . 7 85.1 87.7 65.1 85 · 1 97 · 3 85.1 85.1 i, F 85.1 87.6 91.0 87.7 87.7 87.7 87.7 91.1 91.1 91.1 91.1 91.1 91.1 6 E 35001 43.7 90.1 90.4 94.9 91.6 91.1 91.1 95.2 45.2 30001 44.3 93.7 94.4 94.9 95.0 95.1 95.2 95.2 ., € 25.01 44.6 25.00| 44.6 18.01| 44.6 96.6 91.3 97.4 96.7 91.4 97.6 96.7 97.4 97.6 95.1 95.8 95.9 96.6 96.3 96.7 96.1 96.7 96.7 97.2 97.4 97.6 97.9 97.4 97.6 97.4 97.4 97.4 97.4 97.4 97.4 47.6 υŧ 95.9 96.7 97.1 97.6 97.9 97.8 47.9 97.4 97.9 97.9 97.4 97.9 47.9 47.9 96.1 44.6 98.5 90.6 10001 44.6 96.8 97.1 98.3 96.4 98.6 98.6 98.6 76.6 98.6 98.6 48.6 97.9 97.9 98.4 98.6 97.3 97.6 99.9 98.3 98.6 98.6 98.9 98.9 98.9 98.9 98.9 900 | 44.6 950 | 44.7 700 | 44.8 98 • 7 99 • 7 100 · 0 99 · 9 98.9 96.9 98.9 98.9 93.9 48.9 90.9 i. 5 98.9 99.4 99.9 99.9 99.9 97.6 99.2 99.9 99.9 99.9 99.9 94.4 100.0 100.0 100.0 120.0 100.0 91.7 99.8 100.0 ١, ٤ 99.3 (50) 44.8 100.0 100.0 190.0 100.0 ion.a 100.0 170.0 100.0 100.0 97.7 91.7 91.7 98.6 98.6 94,3 100.0 FB01 44.8 100.0 99.6 99.8 140.0 100.0 100.0 100.0 100.0 5 f 100.0 1:10.0 150.0 100.0 ₹001 44.8 98.6 99.3 99.6 79.8 100.0 100.0 100.0 100.0 103.3 100.0 100.0 100.0 ٠, ۴ 100.0 2001 44.8 97.7 98.6 99.3 99.6 99.6 LOO.C 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 1001 44.8 99.6 140.0 100.0 97.7 98.6 99.3 100.0 100.0 99.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 01 44.8 97.7 98.6 99.5 99.6

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VFRSUS VISIBILITY FROM HOURLY OBSERVATIONS

STA	TION N	UMRER:	724505	STATIO	ON NAME:	мссо	NNELL A	FB KS					OF REC			1800-20	G C
								• • • • • •									
CEI	LING									IN STAT							
1	N	GŁ	GE	GE	GE	GE	GE	GΕ	ĢĒ	GE	G€	66	GŁ	G€	GE	G£	₽£
FE	ET I	10	Ł	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	L
• • •	• • • • •	• • • • • •	• • • • • • •	• • • • • •		• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • •
NO	CEIL (31.3	62.4	62.4	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
			-					.	.		•	• • •	-	-		• • •	
	1 00002		74.2	74.2	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4 74.7	74.4	74.4 74.7	74.4 74.7	74.4 74.7	74.4 74.7
	180001		74.4	74.4	74.7	74.7	74.7	74 • 7	74.7	74.7	74.7		74.7				74.7
	16000		74.4	74.4	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74 - 7	74.7	74.7	
	140001		74.7	74 • 7	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9
GE	120001	37.1	75.9	75.9	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76-1	76.1
	i crup l	70 6	79.7	79.7	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9
	90001		79.8	79.8	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.D	80.0	80 • n	80.0	80.0	86.0
GE	80001		82.4	82.4	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7
	70001		84.0	84.0	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	F4.2
ÚΕ	1001		84.9	84.9	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	A5.1	85.1	85.1
υę	61.001	40.0	74.7	04.7	83.1	03.1	92.7	03.1	03.1	0.2 • 1	03.1	0 7 • 1	83.1	03.1	03.1	65.1	63.1
GE	sraal	41.6	86.9	86.9	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
űĒ	4.00		87.6	87.6	87.8	67.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	67.8	87.8	87.8	87.6
υE	40001		90.0	90.0	96.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	96.4
üΕ	35001		91.6	91.9	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
úΕ	30001		94.2	94.9	95.7	95.9	95.9	96.0	96 • D	96 • D	96.0	96.0	96.0	96.0	96.0	96.0	96.0
					. 3	,											
GE	25001	44.2	95.1	96.0	96.9	97.2	97.2	97.3	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
ŪĚ	20001		95.6	96.4	97.3	97.7	97.7	97.8	97.8	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
ЬĒ	1000	44.2	95.9	96.8	97.7	98.0	98.0	98.1	98.1	98.2	98.2	98.2	98.2	98.2	98.2	98.2	96.2
GΕ	15001	44.4	96.2	97.1	98.0	98.3	98.3	98.4	98.4	98.6	98.6	98.6	98.6	98.6	98.6	48.6	96.6
υE	1200	44.4	96.8	97.7	98.6	98.9	98.9	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GΕ	1000		96.8	97.7	98.6	98.9	98.9	99.0	99.1	99.2	99.2	99.2	99.2	99.2	99.2	49.2	99.2
CE		44.4	96.9	97.8	98.7	99.0	99.0	99.1	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GΕ		44.6	97.0	97.9	98.8	99.1	99.1	99.2	99.3	99.6	99.6	99.6	99.6	99.6	99.6	49.6	96.6
υE	7001	44.6	97.C	97.9	98.8	99.2	99.2	99.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
66	6001	44.6	97 . U	97.9	98.8	99.2	99.2	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
6 E	rnn i	44.6	97.U	97.9	96.8	99.2	99.2	99.6	99.7	99.9	99.9	90.9	99.9	99.9	99.9	99.9	99.9
6 E		44.6	97.0	98.0	98.9	99.3	99.2	99.6	99.8	100.C	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Úξ		44.6	97.1	98.0	98.9	99.3	99.3	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
30		44.6	97.1	98.0	90.9	99.3	99.3	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
	•																
ĿΕ	1001	44.6	97.1	98.U	98.9	99.3	99.3	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	1.0.0	100.0
GE	0	44.6	97.1	98.0	98.9	99.3	99.3	99.7	99.8	100.0	100.0	100.0	100.0	130.0	100.0	100.0	100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

												אטע ::	-		2100-23	
EILING	• • • • • •	• • • • • • •		• • • • • • •	•••••	•••••	v 1 5 1	BILITY	IN STAT	UTE MIL	LS	•••••	• • • • • • •	• • • • • • •	• • • • • • •	•••••
	GE	G€	G£	úĒ	G£	٥ŧ	ĞE	GE	GE	GE	GE	GE	GΕ	GΕ	GE	68
FEET	10	6	- 5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	ů
							• • • • • •		• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •		• • • • • •	• • • • • •
O CEIL	37.8	64.0	64.2	64.2	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
E 200001	14 N	75.2	75.4	75.4	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.0
E 18000		75.6	75 - 8	75.6	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9
E 160001		75.6	75.8	75.8	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.4
E 140001		75.8	16.0	70.0	76.1	76.1	76.1	76 - 1	76 - 1	76.1	76.1	76.1	76 - 1	76.1	76.1	76.1
E 120001		77.0	77.2	77.2	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3
C 121.001	30.4	71.0	11.6	11.2	11.3	11.5	11.5	77.5	11.5	11.3	77.3	11.3	77.63	,	,	,
E lpgggl	18. n	80.3	80.6	80.6	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	90.7	40.7	8L.7
£ 90001		90.3	80.6	80.6	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80 • 7	80.7	80.7	AL. 7
E 80001		83.0	83.2	83.2	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	63.3	83.3
E 70001		85.2	85.4	85.4	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	65.6
E 60001		86.2	86.4	86.4	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	A
- •-•-•											• • • •			-		
E SPOOL	40.4	88.1	88.3	88.3	88.4	86.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	40.4
E 45001	41.1	8.89	89.0	85.0	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	59.1	89.1
E 40001		91.3	91.6	91.6	91.8	91.8	91.8	91.6	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.0
E 3500 l	42.3	92.2	92.6	92.6	92.8	92.8	92.8	92 • B	92.8	92.8	97.8	92.8	92.8	92.8	92.8	48
E 3000 (42.4	93.8	94.6	94.4	95.3	95.3	95.4	95.4	45.4	95.4	95.4	95.4	95.4	95.4	45.4	95.4
											5.					
E 25001		94.8	95.8	95.9	96.3	96.3	96 • 4	96.4	96.4	96.4 97.2	96.4	96.4 97.2	96.4	96.4	96.4	96.4
E 2000		95.6 95.8	96.6	96.7	97.1	97.1	97.2 97.4	97.2	97.2	97.4	97.2	97.4	97.2 97.4	97.4	97.2	97.4
E 18001			96.8	96.9	47.3	97.3	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
E 1200		96.2	97.2	91.3	97.8 97.9	97.8	98.0	98.0	98.0	98.0	98.0	97.9 98.G	98.0	98.0	y8.0	96.0
£ 17001	43.6	96.3	97.3	91.4	91.9	97.9	70.U	70.0	70.0	70.0	75.0	70.0	70.0	70.0	70.0	76.0
E leant	43.6	96.9	97.9	98.4	98.6	98.6	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	90.7
F 9501		97.0	98.0	96.1	98.7	96.7	98.8	98.8	98.8	98 • 6	98.8	98.8	98.8	98.8	98.8	96.8
1003	43.6	97.0	98.U	98.1	98.9	98.9	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
E 700 l	43.6	97.1	98.1	98.2	99.1	99.1	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	94.2
E 6001	43.6	97.4	98.4	96.6	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	49.6	99.6
E Sunl		97.7	98.7	98.9	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
E 4001		97.1	98.7	98.9	99.8	99.8	49.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
£ 300 [97.7	98.7	99.0	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	130 • 0	100.0	100.0	100.0
1 200		97.7	98.7	99.0	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	106-0
1001	43.6	91.1	98.7	99.0	99.9	45.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
E 01	43.6	97.7	98.7	99.0	0.5		100 0	100	140.0		100 0			100 0	14.0	1

PERCENTAGE FREGUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

5 T A	IIION !	NUMBE					-	NNELL AI						: JUN		(LŠT):	ALL	
CFI	LING	• • • • •	• • • • • •	• • • •	• • • • • • •	• • • • • •		• • • • • • •			IN STATE			• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • • • •
		I GE	C	E	G E	uF	GE	GE	G£	υE	GE	GE	GŁ	Gę	GΕ	٥E	GF	GE.
f t	£ T	i i	U	ь	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	0
			• • • • • •	• • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • •
										40.0						40.0	60.0	
40	CF IF	¥ 36.	2 58	. 8	59.5	59.8	59.9	59.9	60.0	60.0	63.0	60.U	60.0	60.0	60.0	60.0	60.0	60.0
r.F	23660	1 33.	9 69	. 3	70.1	76.4	70.5	76.5	70.6	70.6	70.6	70.6	70.6	70.6	70.6	70.6	70.7	76.7
	18000				70.3	70.6	70.8	76.8	70.8	70.8	70.8	70.9	70.9	70.9	70.9	70.9	70.9	76.9
υ£	160001	34.	0 69	. 1	70.5	70.0	70.9	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.1	71.1
üΕ	14000	34.	1 69	. 9	70.7	71.0	71.1	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.3	71.3
(F	12000	34.	6 71	.0	71.8	72.1	72.2	72.2	72 . 3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.4
							_											
	10000				75.7	76.0	76.2	76.2	76.2	76.2	76.2	76.3	76.3	76.3	76.3	76.3	76.3	76.3
5 E	acad (76.U	76.3	76.5	76.5	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.7
GΕ	8 PU 0	37.			79.4	79.7	79.8	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	0.00	86.6
u t	7000.	57.	4 80	٠ ١	80.9	81.3	81.4	81.4	81.5	81.5	81.5	91.5	81.5	81.5	81.5	81.5	61.5	61.6
Ե {	6 CCO (37.	7 80	. 9	81.7	82.1	82.2	82.2	82.3	82.3	82.3	A2.3	62.3	82.3	82.3	82.3	82.3	82.4
٠,٤	shun.	. 38.	1 82	. 4	83.3	83.7	83.8	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	84.0	84.0
u I	4500				83.7	84.1	84.3	84.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.5
L.E	41601				86.5	87.0	87.2	87.2	87.3	87.3	67.3	87.3	87.3	87.3	87.3	87.3	67.3	87.4
14.5	3160				88.1	88.7	88.9	89.0	89-1	89-1	89.1	89.1	89.1	89.1	89.1	89.1	89.2	89.2
6,6	3000				90.5	91.2	91.5	91.5	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.8	91.8
																_		
u f	2:00				91.7	92.4	92.8	92.9	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.2	93.2
t, E	2000				92.8	93.5	93.9	94.0	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.4	94.4
G.E.	1800				93.C	93.8	94.2	94.3	94.5	94.5	94.5	94.6	94.6	94.6	94.6	94.6	94.7	94.7
ıı E	1500				93.7	94.5	95.0	95.1	95.3	95.3	95.3	95.3	95.4	95.4	95.4	95.4	95.4	95.5
i, E	1700	40.	6 92	• 9	94.7	95.6	96.0	96.1	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4	96.5	96.5
G.E	iruni	1 40.	7 93	. 4	95.3	96.2	96.7	96.8	97.0	97.1	97.1	97.1	97.1	97.1	97.2	97.2	97.2	97.3
υŧ	900	40.	A 93	. 7	95.6	90.6	97.0	97.1	97.4	97.4	97.4	97.4	97.5	97.5	97.5	97.5	97.6	97.6
6 E	PLO	40.	9 94	. 1	96.1	97.1	97.5	97.7	97.9	97.9	48.C	98.0	98.1	98.1	98.1	98.1	98.1	98.2
6.6	160	40.	9 94	• 2	96.3	97.3	97.8	98.0	98.2	98.3	98.3	98.4	99.4	98.4	98.4	98.4	98.5	98.5
G É	600	40.	? 94	. 3	96.4	97.5	98.1	98.2	98.5	98.6	98.6	98.6	98.7	98.7	98.7	98-7	98.8	96.8
υE	E (O)	1 40.	9 94		96.7	97.9	99.5	96.7	99.0	99.1	99.1	99.2	99.2	99.2	99.2	99.2	99.3	99.3
G E		1 40. 1 40.			96.8	96.0	49.7	98.8	99.2	99.3	99.4	99.4	99.5	99.5	99.5	99.5	99.5	99.6
υE		40			96.8	98.2	98.9	95.0	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.8	99.8
ij€		40			76.H	90.2	98.9	99.1	99.5	99.6	49.7	99.8	97.A	99.6	99.8	99.9	99.9	106.0
υE		40.			96.8	96.2	98.9	94.1	99.5	99.6	99.7	99.8	99.8	99.8	99.9	99.9	100.0	100.0
	- 50			-				· · · •									•	
ω£	(r	40.	9 94	• t	96.8	98.2	99.4	99.1	99.5	99.6	99.7	9.00	99.8	99.8	99.9	99.9	100.0	106.0
•••	• • • • •	• • • • •		• • • •	*****	76.4		79.1		*****	*****	• • • • • • •		• • • • • • •	• • • • • • •			******

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY USAFETAC FROM HOURLY OBSERVATIONS AIR WEATHER SERVICE/MAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: JUL HOURS(LST): 0000-0256

													: JUL	HOURS	(LST):	0000-02	C.C	
CE	ILIPG	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •			IN STAT			•••••	• • • • • • •	•••••	• • • • • • •	• • • • • • • •	• • •
1	IN I	GΕ	GE	GE	GE	GE	GE	30	GE	GŁ	GE	G E	GE	GE	GE	GE	LE	
FE	ET I	10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	u	
• • •	• • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• •
N O	CEIL I	73.0	75.4	76.8	76.9	76.9	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	
NO		33.0	13.4	10.0	16.7	10.7	11.1	,,,,	,,,,	* * * * *	****	,,,,	****	,,,,	//•1	77.1	,,,,	
	200001		81,5	83.0	83.1	83.2	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	
GE	180001	35.6	81.6	83.1	83.2	83,3	83.5	83.5	83.5	83,5	R3.5	83.5	83.5	83.5	83.5	83.5	63.5	
	160001		81.7	83.2	83.3	83.4	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	e3.7	63.7	83.7	
	140001		82.3	83.8	83.9	84.0	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	
GE	120001	36.9	83.7	85.2	85.3	85.4	85.6	85.6	85.6	65.6	85.6	85.6	85.6	85.6	85.6	85.6	65.6	
6 F	100001	38.0	86.8	88.4	88.5	88.6	88.8	88.8	88.8	8.8	58.8	68.8	88.8	88.8	68.8	88.8	86.8	
GE	90001		87.3	88.9	89.0	89.1	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	
C.E	80001		88.7	90.4	90.5	90.6	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	96.4	
GE	70001		89.0	90.8	94.9	91.0	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	
GE	60001		90.4	92.3	92.4	92.5	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	
	•				,												•	
GE	50001	39.8	91.8	93.7	93.8	94.1	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	
GE	4500	39.8	92.3	94.1	94.2	94.5	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	
GE	40001	40.1	93.7	95.5	95.8	96.1	96.3	96.3	96.3	96.3	96.3	96.3	96 • 3	96.3	96.3	96.3	96.3	
GΕ	35001	40.3	94.3	96.1	96.5	96.8	97.0	97.0	97.0	97.0	97.0	97.0	97.D	97.0	97.0	97.0	97.0	
GE	3 C O O	40.3	95.1	97.2	97.5	97.8	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	96.1	
	350-1	40.1	05 #							0 - 4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	
GE		40.3	95.4 95.5	97.5 97.6	97.8 98.0	98.2 98.3	98.4 98.5	98.4 98.5	98.4 98.5	98.4 98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	
6.5	16001		95.6	97.7			98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	
	15001		95.7	97.8	98.1 98.2	98.4	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	
G E	12001		96.1	98.3	98.6	98.5 98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	
UE	12001	40.5	40.1	40.3	98.0	70.7	99.1	99.1	99.1	77.1	77.1	77.1	97.1	77.1	77.1	77.1	77.1	
٥E	10001	40.5	96 . 1	98.3	98.6	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	94.1	
GE	9001	40.5	96 - 1	98.3	98.6	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	
GΕ	1008	40.5	96.1	98.3	98.6	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	
GE	700	40.5	96.1	98.3	98.6	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	
G۴	6001	40.5	96 • 2	98.4	96.7	99.0	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	
ĿΕ	6004	40.5	96.2	98.6	98.9	99.2	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	
GE		40.5	96.2	98.7	99.1	99.5	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE		40.5	96.2	98.7	99.1	99.5	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE		40.5	96.2	98.7	99.1	99.5	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE		40.5	96.2	98.7	99.1	99.5	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	0.001	106.0	
J.	1001	707	70.2	70.1	7701	77.5	77.0	,,,,		*00*0	100+0	10010	100.0	100.0	100.0	10010	• 00•0	
υ£	0	40.5	96.2	98.7	99.1	99.5	79.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
																		• •

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

						NNELL A	=				MONTH		HOURS	(LST): (0300-05	CO
EILING	• • • • • • •	• • • • • • •		• • • • • • •	• • • • • •			BILITY				• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	•••••
	I GE	GE	GE	G E	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	ĿΕ
	10	6	5	4		2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	U
							• • • • • •	• • • • • •	• • • • • • •			• • • • • • •				
O CEIL	28.5	70.0	70.9	71.3	71.9	72.6	72.3	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4
E 20000	1 31.4	76.0	77.0	77.5	78.2	78.3	78.5	78.6	78.6	78.6	79.6	78.6	78.6	78.6	78.6	78.6
E 18000		76.3	77.3	77.8	78.5	76.6	78.8	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	76.9
E 16000		76.6	77.5	78.1	78.7	78.8	79.0	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1
E 14000	1 31.5	76.8	77.7	76.3	78.9	79.G	79.2	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4
E 12000	32.6	78.7	79.7	8 0 . 2	80.9	81.0	81.2	81.3	81.3	81.3	81.3	g1.3	81.3	81.3	81.3	81.3
		0.2		01			05.7	05 "		ar 4		05.4	05 4	95 "		
£ 10000		82 • 8	83.8	84.3	84.9	85 - 1	85.3	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4
	34.6	83.7	84.6	85.2	85 • 8	85.9	86.1	86.2	86.2	86 • 2	86.2	86.2	86.2	86.2	86.2	86.2
	35.7	85.6	86.6	87.1	87.7	87.8	88.1	88-2	88.2	88.2	88.2	88.2	88.2	R8.2	88.2	86.2
	35.9	86.0	87.1	87.6	88.3	88.4	88.6	88.7	88.7	88 • 7	84.7	88.7	88.7	88.7	68.7	88.7
E 6000	1 36.6	88.0	89.0	89.6	90.2	90.3	90.5	90.6	96.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
5000	37.0	88.7	90.1	90.6	91.4	91.5	91.7	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
E 4500	1 37.0	89.2	90.6	91.2	91.9	92.0	92.3	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
€ 4r00	J 37.0	90.5	91.9	92.5	93.2	93.3	93.5	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
E 3500	37.2	91.3	92.7	93.2	94.0	94.1	94.3	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
E 3000	1 37.3	92.7	94.1	94.7	95.5	95.6	95.9	96.1	96.1	96 - 1	96 • Ĭ	96.1	96.1	96.1	96.1	96.1
E 2*00	1 37.3	92.7	94.1	94.7	95.5	95.6	95.9	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
	37.3	92.8	94.2	94.8	95.6	95.7	96.0	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
	37.5	93.0	94.4	95.1	95.8	95.9	96.2	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
	37.7	93.5	94.9	95.6	96.3	96.5	96.8	97.0	97.0	97.4	97.0	97.0	97.0	97.0	97.0	97.0
	38.0	94.2	95.6	96.2	97.0	97.1	97.4	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
		a								_				••		
	38.0	94.5	95.9	96.6	97.3	97.4	97.7	98.0	98.0	98 • C	98.0	98.0	98.0	98.0	98.0	98.0
	1 38.0	94.6	96.1	96.0	97.5	97.6	98.0	98.2	98.2	98 • 2	98.2	98.2	98.2	98.2	98.2	96.2
	38.0	94.8	96.3	97.0	97.7	97.8	98.2	98.4	98.4	98.4	98.4	98 • 4	98 • 4	98.4	98.4	98.4
	1 38.0	94.8	96 • 5	97.1	97.8	98.0	98.3	98.5	98.5	98.5	98.5	98.5	98.5	96.5	98.5	98.5
	1 38.0	94.8	96.6	97.2	98.0	78 - 1	98.4	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
	1 38.n	94.8	96.6	97.4	98.2	98.3	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	96.8
400	1 38.0	94.8	96.7	97.6	98.5	98.6	98.9	99.1	99.1	99.1	99.1	99.1	99 • I	99.1	99.1	99.1
E 300	1 38.0	94.8	96.7	97.7	98.7	98.8	99.1	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
E 200	38.0	94.8	96.7	97.7	98.7	98.8	99.1	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
E 100	38.0	94.8	96.7	97.7	98.7	98.8	99.1	99.5	99.6	99.6	99.6	99.6	99.7	99.7	99.7	106.0
				97.7	98.7	98.6	99.1	99.5	99.6	99.6						

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VEHSUS VISIBILITY FROM HOURLY OBSERVATIONS

ILI		• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	INNELL A		BILITY			<i></i> .	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •
114		6 £	GE	GE	68	GE	GE.	GE	GE	DE THE	GE GE	CE GE	GE	GE	GE	GE	6E
FEET		10	6	5			2 1/2		1 1/2				5/8	1/2	5/16	1/4	ວະ
			. 							•••••	• • • • • • • • • • • • • • • • • • •		• • • • • • •				_
0 CE	in I	26.6	60.8	62.0	62.8	63.9	64.3	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
20	10001	29.4	68.1	69.7	711.5	71.6	72.0	72.3	72.3	72.3	72.4	72.4	72.4	72.4	72.4	12.4	74
	000		66.1	69.7	70.5	71.6	72.0	72.3	72.3	72.3	72.4	77.4	72.4	72.4	72.4	72.4	72.4
	1000		68.3	69.9	74.8	71.8	72.3	72.5	72.5	72.5	72.6	72.6	72.6	72.6	72.6	72.6	72.6
	10001		68.7	70.3	71.2	72.3	72.7	72.9	72.9	72.9	73.0	73.g	73.0	73.0	73.0	73.0	73.0
	1 0002		71.2	72.9	73.8	74.8	75.3	75.5	75.5	75.5	75.6	75.6	75.6	75.6	75.6	75.6	75.6
. 10	10001	17 6	75.9	78.2	79.0	80.2	80.9	81.1	81-1	81.1	⁹ 1.2	81.7	R1.2	81.2	P1.2	81.2	81.2
	000		76.3	78.6	79.5	80.6	81.3	81.5	81.5	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.6
	1007		80.2	82.5	83.5	84.8	85.7	85.9	85.9	85.9	86.0	86.0	86.0	86.0	86.0	86.D	86.0
	reagl		81.6	83.9	84.9	86.3	87.2	87.4	87.4	87.4	A7.5	87.5	87.5	87.5	A7.5	67.5	A7.5
	0001		82.6	85.1		87.6						88.8	88.8	88.8	A8.8	88.8	
. 0	o t-uu j	37.7	02.0	0 2 • 1	86.2	87.6	88.5	88,7	88.7	88.7	88.8	00.0	80.0	00.0	na.8	80.0	86.8
	snoo j		84.2	87.0	88.2	89.6	90.5	90.8	90.8	90.6	90.9	90.9	90.9	90.3	90.9	90.9	96.9
	1500 j		84.5	87.3	88.6	90.0	91.0	91.3	91.3	91.3	91.4	91.4	91.4	91.4	91.4	91.4	91.4
. 4	10001	36.3	85.4	88.2	89.5	90.9	91.6	92.2	92.2	92.2	92.3	92.3	92.3	92.3	92.3	92.3	96.3
E 3	35001	36.5	86.1	88.9	90.2	91.6	92.6	92.9	92.9	92.9	93.0	93.0	93.0	93.0	93.0	93.0	93.0
3	1000	36.5	86.3	89.1	90.4	91.8	92.8	93.1	93.1	93.1	93.2	93.2	93.2	93.2	93.2	93.2	93.2
: 2	2 00 1	36.7	86.7	89.5	96.8	92.2	93.1	93.5	93.5	93.5	93.7	93.7	93.7	93.7	93.7	93.7	93.7
Ξ 2	1007	36.7	86.8	89.6	91.0	92.4	93.3	93.8	93.8	93.8	93.9	93.9	93.9	93.9	93.9	93.9	91.9
. 1	10081	36.8	86.9	89.8	91.2	92.6	93.5	94.0	94.0	94.0	94.1	94.1	94.1	94.1	94.1	94.1	94.1
	500 [87.7	90.6	92.2	93.5	94.5	94.9	95.1	95.1	95.3	95.3	95.3	95.3	95.3	95.3	95.3
	1000		88.5	91.4	92.9	94.4	95.4	95.8	95.9	95.9	96.1	96.1	96 • 1	96.1	96.1	96.1	96.1
1	10001	37.5	89.4	92.3	9 3 • 8	95.3	96.2	96.7	96.8	96.9	97.1	97.1	97.1	97.1	97.1	97.1	97.1
	900		89.5	92.4	93.9	95.6	96.6	97.1	97.2	97.3	97.5	97.5	97.5	97.5	97.5	97.5	97.5
-	Pug I		89.7	92.7	94.2	96.0	97.0	97.6	97.7	97.8	98 • 1	98.1	98 • 1	98.1	98.1	98.1	96.1
	7001		89.9	93.0	94.5	96.3	97.3	98.0	98.1	98.2	98.4	98.4	98.4	99.4	98.4	48.4	98.4
	£001		89.9	93.1	94.6	96.5	97.4	98.1	98.2	98.3	98.5	98.5	98.5	98.5	98.5	98.5	90.5
	5001	87.6	89.9	93.2	94.7	96.6	97.5	98.3	98.4	98.5	98.7	98.7	98.7	98.7	98.7	98.7	96.7
	4001		89.9	93.2	94.7	96.6	97.5	98.5	98.7	98.8	99.0	99.0	99.0	99.0	99.0	99.0	99
	3001		90.0	93.3	94.8	96.7	97.6	98.7	98.9	99.0	99.4	99.4	99.4	99.4	99.4	99.4	99.4
	1002		90.0	93.3		96.7	97.6									99.7	99.7
					94.6			98.7	99.0	99.1	99.6	99.6	99.6	99.7	99.7		
	1001	3/.6	90.0	93.3	94.8	96.7	97.6	98.7	99.0	99.1	99.6	99.6	99.6	99.8	99.8	99.8	100.0
	0.1	37.6	90.0	93.3	94.8	96.7	97.6	98.7	99 . U	99.1	99.6	99.6	99.6	99.8	99.8	99.8	100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

												MUNIH					
	LING							VISI	BILITY	IN STAT	UTE MIL	٤s					
1	N I	GE	G E	GE	GE		GĒ		ĢΕ			GE				G€	٥ŧ
Έ	ET I	10	ь	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	ن
٠	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •
	CEIL I	12.1	69.4	70.6	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5
u	CEIL	32.3	07.4	10.6	/ 1 • 5	/1+3	/1.5	/1.5	11.5	11.5	71.5	11.5	/1.5	11.5	/1.5	11.5	71.5
E	100105	35.1	76.3	78.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1
Ε	180001	35.3	76.6	78.3	79.4	79.4	79 - 4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	74.4
Ε	10001	35.3	76.9	78.6	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7
ŧ	140001	35.5	77.3	79.0	84.1	8 g • 1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	RO . 1	80.1	FU.1
F.	150001	36.1	78.8	80 • 5	A 1 .6	81.6	81.6	81.6	81.6	81.6	91.6	81.6	81.6	81.6	81.6	81.6	81.6
	100001	37.5	82.2	84.1	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	45.2	u5.2	85.2
	90001		82.5	84.4	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5
	80001		85.1	87.1	88.4	88.4	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	P8.5	88.5	80.5
	70001		85.6	87.6	86.9	88.9	85.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	69.0	89.0
	60001		85.7	87.7	89.0	89.0	89.1	89-1	89-1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	A9.1
	5rool		86.3	88.4	89.7	89.7	89.8	89.8	89.8	69.8	8 . 68	89.8	89.8	89.8	89.B	69.8	64.8
	4500		86.7	88.8	96.1	90.1	90.2	90 • 2	90.2	90.2	90 • 2	90.2	90.2	90.2	90.2	40.2	96.2
£	40001		87.4	89.6	90.9	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.C	91.0
	3500		88.3	90.4	91.7	91.7	91.8	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
Ε	3 C D D	39.8	88.9	91.3	92.6	92.7	92.8	93.0	93.6	93.0	93.0	93.0	93.6	93.0	95.0	93.0	93.0
F	25001	40.1	89.8	92.2	93.4	93.5	93.7	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	9.69
	2000		90.3	92.8	94.1	94.2	94.3	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
Ε	10001	40.2	90.4	92.9	94.2	94.3	94.4	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
Ε	15001	41.1	91.9	94.5	95.8	95.9	96.0	96.2	96.6	96.6	96.6	96.6	96.6	96.6	96.6	46.6	96.0
E	1200	41.6	92.8	95.6	96.9	97.1	97.2	97.4	97.7	97.7	97.7	97.7	97.7	97.7	97.1	97.7	97.1
Ē	10001	41.6	92.9	96.6	97.3	97.6	97.7	98.0	98.3	98.3	98 - 3	99.3	98.3	98.3	98.3	98.3	96.3
		41.7	93.3	96.8	98.1	98.4	98.5	98.7	99.0	99.1	99.2	99.2	99.2	99.2	99.2	99.2	99.2
Ē		41.7	93.3	96.4	98.2	98.5	98.6	98.8	99.1	99.7	99.4	99.4	99.4	99.4	49.4	99.4	99.4
Ē		41.7	93.3	96.9	98.2	98.5	98 • 8	99.1	99.5	99.6	99.7	99.7	99.1	99.7	95.7	94.7	99.7
E		41.7	93.3	96.9	96.2	98.5	98.8	99.1	99.5	99.6	99.7	99.7	99.7	99.7	99.7	49.7	99.7
-	5.00	41.8	93.5	97.1	98.4	98.7	99.0	99.4	99.7	99.9	100.0	100.0	100.0	100.0	100.0	1.00	106.6
Ē		41.8	93.5	97.1	98.4	98.7	99.0	99.4	99.7	99.9	100.0	100.0	100.0	100.0	100.0		106.6
Ę		41.8	93.5	97.1	96.4	98.7	99.0	99.4	99.7	99.9	100.0	100.0	100.0	100.0	170.0		100.0
t E		41.8	93.5	97.1	96.4	98.7	99.0	99.4	99.7	99.9	100.0	100.0	100 • C		100.0	100.0	100.0
r F		41.8	93.5	97.1	98.4	98.7	99.0	99.4	99.7	99.9	100.0	100.0			100.0		
L	1001	41.0	73.3	71.1	70.7	70 . 1	77.0	77.4	7761	77.7	* 17 O * U	100.0	100.0	.00.0	.00.0	. 30.0	100.0
	n i	41.8	93.5	97.1	98.4	98.7	99.0	99.4	00 7	600	100.0	100.0	100 6		100.0	100 0	100 0

AIR WEATHER SERVICE/HAC

GLOBAL CLIMATOLOGY BRANCH PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY USAFFTAC FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS PEPIOD OF RECORD: 77-86 MONTH: JUL HOURS (LST): 1200-1400 VISIBILITY IN STATUTE MILES CEILING CEILING VISIBILITY IN STATUTE MILES
IN 1 GE GE GE GE GE GE GE GE GE FEET 1 10 6 5 4 3 2 1/2 2 1 1/2 1 1/4 1 3/4 GE GŁ 5/8 1/2 5/16 1/4 6 NO CETE | 34.4 72.6 81.2 GE 200001 37.7 79.8 80.6 81.1 81.2 81.2 81.2 81.2 81.2 81.2 81.2 GE 18000| 38.1 GE 16000| 39.2 80.1 80.5 81.0 81.4 81.5 81.5 gl.9 81.5 81.5 81.5 P1.5 81.9 81.5 81.5 81.9 81.5 81.9 61.5 61.9 51.5 81.9 81.5 81.9 GE 14000 38.4 80.8 81.6 82.0 82.2 82.2 82.2 82.2 82.2 92.2 62.2 82.2 82.2 82.2 82.2 82.2 GE 120001 39.9 83.0 83.9 84.3 84.4 GE 10000 41.3 GE 9000 41.3 GE 8000 41.9 88.1 88.4 91.0 88.1 88.4 91.0 88.1 88.4 91.0 88.4 91.0 80.4 91.0 87.5 87.8 88.1 88.4 88.1 88.4 98.0 88.1 88.1 88.1 88.1 88.1 88.4 91.0 88.4 90.4 90.9 90.9 91.0 91.0 91.0 91.0 41.0 91.0 89.6 42.4 91.3 91.4 91.4 91.4 91.4 91.4 70001 90.0 91.4 GΕ 60001 42.7 91.7 92.3 92.3 92.3 92.3 42.3 92.1 92.3 92.3 92.3 92.3 92.3 92.3 5000| 42.8 4500| 42.8 4000| 42.9 3500| 43.1 92.6 92.7 93.5 92.6 92.7 93.5 92.6 92.7 93.5 92.6 92.6 92.7 92.6 92.7 ű E G E 91.2 91.3 92.0 92.5 92.6 92.6 92.7 92.6 9..6 92.7 93.4 93.0 93.5 93.5 93.5 93.5 93.5 93.5 93.5 93.5 93.5 94.4 94.4 94.4 GF 93.0 93.9 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 30001 43.2 96.8 96.8 98.0 99.0 96.B 96.8 90.8 96+8 98+6 98+0 96.A 96.8 96.8 96.8 GΕ 25001 43.4 95.3 96.2 96.7 96.8 96.8 20001 44.0 19001 44.0 17001 44.3 98.0 98.0 98.5 96.3 97.4 97.8 98.0 98.0 98.U 98.0 98.0 98.0 98.0 98.0 98.0 YR.O 90.0 98.0 98.0 ĿΕ 96.8 97.8 98.5 98.5 98.5 98.5 98.5 98.5 98.5 98.5 98.5 ye.5 46.5 98.8 98.8 98.8 98.6 98.8 98.8 GE 12001 44.3 97.1 98.2 98.8 98.8 98.8 98.8 Ve.F 10001 44.3 9001 44.3 8001 44.3 98.7 98.8 99.6 99.7 99.7 99.6 99.7 99.8 99.9 99.9 99.8 99.9 99.9 94.8 97.6 99.1 99.8 99.8 99.8 99.8 99.8 49.A 99.9 99.9 99.9 100.0 99.2 99.9 99.9 6 E 98.8 98.8 99.2 99.8 99.9 9.40 99.9 94.4 97.7 99.7 99.9 44.3 97.7 99.8 94.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 7001 99.8 100.0 99.9 100.0 100.0 107.0 100.0 100.0 100.0 130.0 COO! 44.3 400! 44.3 700! 44.3 99.9 100.0 100.0 97.7 97.7 99.8 99.8 100.0 100.0 100.0 98.8 98.8 99.2 99.8 99.8 100.0 100.0 100.0 100.0 100.0 100.0 1 ... 97.7 99.9 100.0 100.0 100.0 100.0 170.0 1.03.0 100.0 100.0 6 F 2001 44.3 97.7 98.8 99.2 49.8 99.8 99.9 100.0 1.00.0 100.0 100.0 100.0 Lun. C I Ches 94.2 99.8 1001 90.8 100.0 G€ 99.8 99.8 99.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 D1 44.3 97.7 98.8 99.2

TOTAL NUMBER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS PERIOD OF RECORD: 77-86
MONTH: JUL HOURS(LST): 1500-1700 VISIBILITY IN STATUTE MILES CEILING GE 73.7 73.7 NO CEIL | 33.8 72.8 73.4 73.4 73.7 73.7 73.7 73.7 73.7 73.7 73.7 73.7 73.7 6F 20000| 39.2 6F 19000| 38.3 6F 16000| 38.4 83.7 93.9 84.0 82.6 83.4 83.4 83.7 83.7 83.7 83.7 83.7 83.9 84.0 83.7 83.7 83.7 83.7 63.7 83.7 82.8 82.9 83.7 83.9 83.9 84.0 83.9 84.0 83.7 83.9 83.9 83.9 83.9 83.9 84.0 84.0 84.0 04.0 84.0 83.0 64.0 64.0 GE 140001 39.4 GE 120unl 39.5 84 - 7 85.6 85.8 85.8 85.A 85.8 AS.B 85.8 85.8 GE 10000 39.8 GE 9000 39.9 GE 8000 41.1 88.6 91.3 88.1 66.3 88.3 88.6 58.3 68.6 88.3 8A.6 VI.3 VI.6 87.5 88.4 86.4 88.6 86.6 88.6 88.6 88.6 88.6 88.6 86.6 91.3 89.9 91.0 91.0 91.3 91.3 91.3 91.3 91.3 91.3 91.3 91.3 91.3 91.6 91.6 91.6 91.6 91.6 70001 41.1 90.1 91.3 91.6 úΕ 91.3 91.6 91.6 91.6 91.6 60001 41.1 90.6 92.2 GF. 93.7 94.1 95.5 93.7 94.1 95.5 50001 41.7 91.9 92.2 93.0 93.7 93.7 93.7 93.7 93.2 93.5 93.5 93.5 93.7 93.7 93.7 94.1 93.3 93.7 94.0 94.0 94.0 94.1 95.5 94.1 95.5 94.1 95.5 94.1 95.5 95.5 i.F 4000 41.8 97.6 34001 43.0 95.1 96.6 97.0 97.5 97.5 97.5 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 98.0 ω£ 30001 43.1 96.0 97.5 98.5 98.5 98.5 98.6 98.6 98.6 98.6 98.6 98.6 98.6 98.6 96.6 2500| 43.2 2000| 43.5 1800| 43.5 98.6 99.1 98.6 96.1 97.6 98.1 99.6 99.1 98.7 98.7 98.7 98.7 98.7 94.7 94.7 99.2 99.2 99.2 99.2 99.2 99.2 99.2 99.1 99.2 Δî 96.8 98.3 96.7 99.2 99.2 99.2 99.4 99.4 99.4 15001 43.5 96.8 98.3 96.7 99.2 99.2 99.2 99.4 99.4 U.F 99.4 99.4 99.4 99.4 00.4 00.4 99.4 09.4 10..0 6 f 10001 43.5 99.9 99.9 99.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 100.0 9501 43.5 9601 43.5 97.4 98.9 99.4 99.9 99.9 100.0 100.0 100.0 100.0 af id 99.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 αŧ 7601 43.5 97-4 98.4 99.4 99.9 99.9 99.9 100.0 100.0 100.0 100.0 100.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 97.4 98.9 99.9 79.9 100.0 100.0 100.0 fanl 43.5 4601 43.5 7601 43.5 98.9 98.9 98.9 99.4 99.4 99.4 99.4 99.9 99.9 99.9 99.9 99.9 99.9 100.0 100.0 100.0 97.4 99.9 99.9 100.0 160.0 100-0 100.0 100.0 100.0 1.10.0 100.0 97.4 100.0 100.0 100.0 100.0 100.0 1,1 99.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 υF 1001 43.5 97.4 ... 99.4 40.9 99.9 99.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 1.00.0 100.0 01-47.5 100.0 100.0 100.0 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF KLCORD: 77-86
MONTH: JUL HOURS(LST): 1800-2000 CEILING VISIBILITY IN STATUTE HILES
IN 1 GE GE GE GE GE GE GE GE GE GE FEET 1 10 6 5 4 3 2 1/2 2 1 1/2 1 1/4 1 3/4 GE GΕ 1/2 5/16 5/8 1/4 U NO CEIL 1 35.3 75.9 76.0 76.0 76.0 76.0 76.0 74.9 76.0 76.0 76.0 76 . C 76.0 76.0 76.D 76.0 86.8 86.8 86.9 Gr 200001 40.0 85.3 86.5 86.8 86.8 86.8 86.8 86.8 86.8 86.9 86.8 86.9 86.8 86.8 86.8 86.8 86.8 8.48 GE 180001 40.0 GE 160001 40.1 85.3 85.4 86.8 86.8 86.8 86.8 86.8 86.8 86.8 86.8 86.5 86.8 86.6 86.9 GE 140001 40.1 85.6 86.8 87.1 67.1 87-1 87.1 87.1 87.1 87.1 88.3 GE 120001 40.8 86.8 88.C 88.3 88.3 88.3 88. 1 88. T AA . 3 88.3 88. I AB . 3 88.3 90.5 90.5 92.5 GE 100001 41.7 GE 90001 41.7 88.9 88.9 90.1 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.1 90.5 90.5 96.5 80001 42.6 90.9 92.0 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 93.2 93.2 93.2 93.2 93.2 93.2 GF 70001 42.9 91.6 92.8 93.2 93.2 93.2 93.2 93.2 93.2 93.2 60001 43.1 93.9 94.3 94.3 94.3 94.3 ĢĒ 94.3 94.3 94.3 94.3 95.5 95.6 97.1 95.5 95.6 97.1 5000| 43.3 4500| 43.3 4000| 43.4 94.9 95.1 96.5 95.5 95.6 97.0 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 95.5 95.6 97.1 GF 93.5 93.7 95.5 95.6 GE 95.1 97.1 35001 43.5 95.6 97.0 97.7 97.7 97.7 97.7 97.7 91.7 97.7 97.7 97.7 (s F 30001 43.8 96.5 97.h 98.5 98.6 98.6 98.6 98.6 48.6 98.6 94.7 98.7 98.7 98.7 48.7 96.7 98.9 99.2 99.2 2500| 43.8 2000| 43.8 96.7 96.9 98 · 1 98 · 3 98.7 6.5 98 • 8 99 • 0 98.8 99.0 98.8 98.8 98.8 98.9 98.9 98.9 98.9 96.9 ĞĒ 99.0 99.1 99.1 99.1 99.2 99.2 99.2 99.2 99.2 1800 | 43.8 GĘ 96.9 98.3 98.9 99.0 99.6 99.0 99.1 99.1 99.1 99.2 99.2 99.2 99.2 99.2 1 - 00 | 43.8 96.9 99.2 99.5 99.5 99.5 98.5 99.1 99.2 υE 99.6 99.5 1200 | 43.8 98.5 99.5 99.5 99.7 99.7 99.7 10001 43.8 99.5 99.6 97.0 97.2 98.6 98.8 99.5 99.7 99.5 99.6 99.8 99.6 99.6 GE 9001 43.8 99.4 99.7 99.7 99.7 99.7 99.7 99.7 FOO! 43.8 99.6 99.9 99.9 99,9 99.9 94.4 GE GE 7001 43.8 98.6 99.7 99.8 99.8 99.8 99.9 99.9 99.9 100.0 100.0 100.0 100.0 100.0 104.40 6001 43.8 GĒ 99.8 100.0 100.0 100.0 98.8 99.8 99.8 100.0 100.0 100.0 5001 43.8 4001 43.8 3001 43.8 97.2 97.2 97.2 98.8 98.8 98.8 99.7 99.7 99.7 99.8 99.8 99.8 99.8 99.8 99.8 99.8 99.8 99.8 99.9 99.9 99.9 99.9 99.9 99.9 100.0 99.9 99.9 100.0 100.0 100.0 ÚΕ 99.9 100.0 100.0 100.0 100.0 100.0 2001 43.8 97.2 99.9 100.0 98.8 99.7 99.8 100.0 100.0 100.0 1.00.0 166.0 100 | 43.8 G E 97.2 98.8 99.8 99.8 99.9 99.9 99.9 100.0 100.0 100.0 100.0 100.0 106.0 01 43.8 97.2 99.8 99.9 99-9 100-0 100-0 100-0 100-0

TOTAL NUMBER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

5.1	A T	100	NUI	MPER:	724505	STATIO	ON NAME:	мсс о	NNELL AF	ВК					OF REC		-86 (LST):	2100-23	UC 20
		 I NG		• • • • •	• • • • • • •	••••	••••••	• • • • •	• • • • • • •			IN STAT			• • • • • • •				
	18		1	GE	GE	GE	6 E	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	G E
	ΕE			10	6	- 5	4		2 1/2			1 1/4	1	3/4	5/8	1/2	5/16	1/4	J
NO	C	ŁIL	1 .	34.1	77.2	78.4	7 d • 4	78.4	78.4	78 • 4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	76.4
, ,	,	anao	1	37.1	84.2	85.6	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.6
		8000			84.3	85.7	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	95.9	85.9	85.9
		6760			84.4	85.8	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.n	86.0	86.0
		4600			84.7	86.1	80.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
G E	ì	2000	Ĺ.	37.7	86.0	87.4	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	°7.6	87.6	A7.6	87.6	87.6
G E		9000 9000			88 • 5	89.8 90.0	90.0 96.2	90.0	90.0 90.2	90.0	90.U 90.2	90.0	90 • B 90 • 2	90.0 90.2	90.0 90.2	90.0 90.2	90.0	90.0 90.2	90.8 90.2
GE		8000			90.6	92.3	92.5	92.5	92.5	90 • 2 92 • 5	92.5	90.2 92.5	92.5	92.5	92.5	92.5	90.2	92.5	90.2
GE		7000			91.5	93.0	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
6.E		6000			92.0	93.5	93.8	93.8	93.8	93.8	93.8	93.8	93.a	93.8	93.8	93.8	93.8	93.8	93.0
GL		50.50	'	40.0	72.0	,,,,	, , , ,	73.0	73.0	73.0	73.0	73.6	73.8	43.6	73.0	73.0	73.6	73.0	73.6
ЬE		5000	1.	40.5	93.2	94.7	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.0	94.9	94.9
GE		4500	1 4	40.5	94.0	95.5	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95. <i>1</i>	95.7	95.7
GE		4000	1 (41.1	95.5	97.0	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
υE		3 5 G G		-	96.0	97.5	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	A6.0	98.0
G E		3000	1 4	41.5	96 • 5	98.0	98.4	98.7	98.7	98.7	98.7	98.7	98.8	98.8	98.8	98.8	98.8	96.8	96.0
G.E		2500		4 . 5	96.6	98 - 1	98.5	98.8	98.8	98.8	98.8	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.7
ĞĒ		2000			96.6	98.1	96.5	98.8	98.0	98.8	98.8	98.8	98.9	98.9	98.9	98.9	98.9	94.9	96.9
6 E		1800			96.7	98.2	98.6	98.9	98.9	98.9	98.9	98.9	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE		1500	1 4	41.5	96.8	98.3	98.7	99.0	99.0	99.0	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	94.1
6 F		1200	1 4	41.5	96.8	98.4	96.9	99.2	99.2	99.2	99.2	99.2	99.4	99.4	99.4	99.4	99.4	49.4	94.4
6 E		1000		. 1 5	96.8	98.4	96.9	99.4	99.4	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.5	49.5	44.5
GE				41.5	96.9	98.5	99.0	99.5	99.5	99.5	99.5	99.5	99.6	97.6	99.6	99.6	99.6	y9.6	94.6
6 E				41.5	96.9	98.5	99.1	99.6	99.6	99.6	99.6	99.6	99.1	99.7	99.7	99.7	99.7	99.7	99.7
GΕ				41.5	96.9	98.5	99.1	99.6	99.6	99.6	99.6	99.6	59.7	99.7	99.7	99.7	99.7	99.7	44.7
ĢΕ				41.5	96.9	98.6	99.2	99.7	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.5	99.8	94.0
		·																	
GE GE				41.5 41.5	96.9 96.9	98.7 98.7	99.5 99.5	99.9	99.9 99.9	99.9 99.9	99.9	99.9 99.9	100.0	100.0	100.0	100.0	100.0 100.0	190.0 190.n	100.0 100.0
υE				41.5	96.9	99.7	99.5	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	103.0	100.0	150.0	106.6
6 E			•	41.5	96.9	98.7	99.5	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.3	100.0	100.0	130.0	100.0
GE				41.5	96.9	98.7	99.5	99.9	99.9	99.9	99.4	99.9	100.0	100.0	100.0	100.0	100.0	100.0	106.0
														-					
GΕ		n	1 4	41.5	96.9	98.7	99.5	99.9	99.9	99.9	99.9	99.9	100.0		100.0		-		100.0

PERCENTAGE FREQUENCY OF OCCUPRENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

-		: 724505									MONTH	: JUL		(LŠTI:	ALL	
EILING		••••••	• • • • • • •	• • • • • • •	• • • • • •	•••••			IN STATE	UTF MIL		• • • • • • •	• • • • • •	• • • • • • •		• • • • • • •
IN	1 GE	GE	GE	GE	GΕ	GE	GE	GE	GE	GE	GΕ	GE	GÈ	ĜE	3 C	υE
FLET	1 10	6	5	4	3	2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	J
• • • • • •	• • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	•••••	• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • •		
CEIL	1 32.2	71.5	72.6	72.9	73.1	73.2	73.2	73.3	73.3	73.3	73.3	73.3	73.3	73.3	13.3	73.3
20000	35.6	79.2	80.5	86.9	81.2	81.3	81.3	81.4	81.4	A1.4	81.4	81.4	81.4	P1.4	81.4	H1.4
18000	35.6	79.4	80.6	81.1	81.4	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	A1.5	81.5	61.5
16000	1 35.7	79.6	80.6	91.3	81.6	81.7	81.7	81.7	81.7	81.7	81.7	61.7	81.7	R1 - 7	61.7	P1.1
14000	1 35.8	79.9	81.2	81.0	61.9	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.J	82.0	62.0	F 0
12000	36.8	81.6	82.9	83.3	83.6	83.7	83.8	83.8	83.8	83.8	8.7.8	A3.8	83.8	93.8	83.8	+3.0
10000	37.9	84.8	86.2	86.7	87.0	87.1	87.2	87.2	87.2	87.2	87.2	87.2	87.2	A7.2	87.2	87.2
9000	11 3A.Z	85.2	86.6	87.1	87.4	87.5	87.5	87.5	87.5	87.6	87.6	87.6	87.6	87.6	87.6	81.6
8 8000	39.1	87.6	89.0	89.5	49.9	90.0	90.1	90.1	90-1	90.1	90.1	90.1	90.1	1.00	90.1	96.1
E 7000	39.4	88.2	89.7	91.2	90.5	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	96.1
E 6000	11 39.7	89.1	90.0	91.2	91.5	01.6	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
500	40.1	90 - 1	91.7	92.3	92.7	92.8	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.4
	46.1	90.5	92.1	92.7	93.1	93.2	93.3	93.3	93.3	93.4	93.4	93.4	93.4	93.4	93.4	93.4
	40.2		93.3	93.9	94.3	94.5	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
	40.6		94.1	94.8	95.2	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
F 3000	11 40.7	93.3	95.1	95.8	96.2	96.4	96.5	96.5	96.5	96.6	96.6	96.6	96.6	96 • 6	96.6	96.6
E 2500	1 40.B	93.6	95.4	96.1	96.5	96.7	96.8	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96 • 9	96.9
E 2000	1 40.9	94.0	95.8	96.5	96.9	97-1	97.2	97.5	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
E 1860	11 41.0	94.1	95.9	96.6	97.0	97.2	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
	41.2		96.4	97.1	97.5	97.7	97.8	97.9	97.9	98.C	98.0	98.0	98.0	96.0	48 • O	90.0
E 1700	11 41.3	94.9	96.8	91.5	98.0	98.2	98.3	98.4	98.4	98.5	98.5	98.5	98.5	98 • 5	98.5	96.5
1000	1 41.3	95.2	97.1	97.9	98.4	98.6	98.7	98.9	98.9	98.9	98.9	98.9	99.9	98.9	48.9	96.9
E 900	31 41.4	95.3	97.3	98.0	98.6	98 • 5	98.9	99.1	99.1	99.1	99.2	99.2	99.2	99.2	99.2	99.2
	1 41.4		97.4	98.2	98.8	98.9	99.1	99.2	99.2	99.3	99.3	99.3	99.3	99.3	99.3	94.3
	1 41.4		97.5	98.2	98.8	99.0	99.2	99.3	99.4	99.4	99.4	99.4	99.4	99.4	79.4	99.4
ב אטר	11 41.4	95.4	97.5	98.3	98.9	99.1	99.3	99.4	99.4	99.5	99.5	99.5	99.5	99.5	99.5	94.5
	1 41.4		97.6	98.4	99.0	39.2	99.4	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	94.6
	41-4		97.6	90.5	99.1	99.3	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	64.8
	41.4	95.5	97.6	98.5	99.1	99.3	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	95.9
	41.4		97.6	98.5	99.1	99.3	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9
£ 10f	11 41.4	95.5	97.6	98.5	99.1	99.3	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	101.0
	41.4	95.5	97.6	96.5	99.1	99.3	99.6	99.7	99.8	99.9	99.9	99.9	49.9	99.9	99.9	100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

S 1	FATION N	IUMBER:	724505	STATI	ON NAME:	#CC0	NYELL A	FB KS				PERIOD MONTH	OF PEC			P000-05	LU
• •		•••••	• • • • • • • •	• • • • • •	• • • • • • • •	• • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •				• • • • • •		• • • • • • •	• • • • • •	• • • • • •	
	ILIMG						_			IN STATE		-					
		GE	GE	GE	GE	GŁ	GE	GE	GΕ	GE	GE	GŁ	G E	3 E	GE	GŁ	UE .
		10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	
• •	• • • • • • •	• • • • • •	• • • • • • • •	• • • • • •	• • • • • • • •	• • • • • •	• • • • • • •		• • • • • • •	• • • • • • •		• • • • • • •			• • • • • •		
N (CEIL I	29.7	69.1	70.9	72.2	72.5	72.5	72.5	72.5	72.5	72.6	72.6	72.6	72.6	72.6	12.6	1
	_																
	500001		74 - 3	76.0	77.3	77 • 7	77.7	77.7	77.7	77.7	77.8	77.8	77.8	77.8	77.8	77.8	17.0
	Telau!		74.3	76 • Ü	77.3	77.7	77.7	77•7	77.7	17.7	77.8	77.8	77.8	71.8	77.8	17.8	11.5
	100001		74 - 4	76.1	71.4	77.8	77.8	77.8	77.8	77.8	78 • C	78.0	78.U	78.0	78.0	75.0	7t.u
	140001		75.9	77.6	70.9	79.4	79.4	79.4	79.4	79.4	79.5	79.5	79.5	19.5	79.5	79.5	74.5
ĿΕ	156901	32.0	77.0	78.7	8 C • O	80.4	8C - 4	80 • 4	80.4	80.4	80.5	30.5	80.5	80.5	80.5	#C.5	FL.5
LE	100001	33.1	81.5	83.2	84.5	84.9	84.9	84.9	84.9	84.9	85.1	85.1	85.1	85.1	85.1	05.1	85.1
υE	90001	33.1	81.5	83.2	94.5	04.9	84.9	84.9	84.9	84.9	R5.1	85.1	85.1	85.1	A5.1	84.1	F5.1
űE	80001	34.2	84 . 6	86.3	97.6	88.1	88.1	88 - 1	88.1	68.1	68.2	88.2	88.2	88.2	R8.2	68.2	88
υE	70001	34.7	86.1	87.8	89.1	89.6	89.6	89.6	89.6	69.6	89.7	89.7	89.7	59_7	89.7	89.7	44.7
GΕ	. 6001	34.7	86.6	89.3	89.6	90.0	90.0	90.0	90.0	90.0	90.1	90.1	90 - 1	90.1	90.1	.0 1	96.1
GΕ	5 Դև Ու	35.2	P8 . 2	89.9	91.5	91.9	91.9	91.9	91.9	91.9	92.0	92.0	92.0	92 • 0	92.0	92.0	9
ijΕ	45001	35.5	88.6	90.3	91.7	92.4	92.4	92.4	92.4	92.4	92.5	92.5	92.5	92.5	92.5	92.5	94.5
6 E	40001	55.6	90.2	92.0	93.4	94.1	94.1	94.1	94 - 1	94.1	94.2	94.2	94.2	94.7	94.2	94.2	44
G F.	3*001	35.6	90.5	92.6	94.1	94.7	94.7	94.7	94.7	94.7	94.8	94.8	94.8	94.8	94.6	94.8	94.6
٥E	30001	35.6	91.2	93.2	94.7	95.4	95.4	45.4	95.4	95.4	95.6	95.6	95.6	95.6	95.6	95.6	45.6
							. 5 - 1	,,,,,,		, , , , ,		,,,,	. , , ,	. , ,	2.0	7. . 0	. , , ,
€ن	25001	15.6	91.2	93.2	94.7	95.4	95.4	95.4	95.4	95.4	95.6	95.6	95.6	95.6	95.6	45.6	45.6
űĒ			91.2	93.2	94.7	95.4	95.4	95.4	95.4	95.4	95.6	9. 6	95.6	95.6	95.6	y t . b	95.6
G E			91.2	93.2	94.7	95.4	95.4	95.4	95.4	95.4	95.6	95.6	95.6	95.6	95.0	45.6	45.6
G E	1500	35.6	91.4	93.4	94.9	95.7	95.7	95.7	95.1	95.7	95.9	95.9	95.9	95.9	95.9	y5.9	45.4
ÚΕ			91.6	93.7	95.4	96.1	96.1	96 • 1	96.1	96.1	96.3	96.3	96.3	26.3	96.3	¥6.3	46.5
					, , , ,		, , , ,	,,,,		,,,,	.0.,	70.03		,,,	.0.	,0.,	
G.E.	10001	45.7	92.4	94.7	96.6	97.3	97.3	97.3	97.5	97.3	97.5	97.5	97.5	97.5	97.5	97.5	97.5
Ú.E		35.7	92.4	94.7	96.6	97.3	97.3	97.3	97.3	97.3	97.5	97.5	97.5	97.5	97.5	97.5	91.5
6 E		35.7	92.4	94.9	96.8	97.5	97.5	97.5	97.5	97.5	97.7	97.7	97.7	97.7	97.7	97.7	41.1
GE		35.7	92.9	95.5	97.3	98.1	98.1	98.1	98.1	98.1	98.3	94.3	98.3	98.3	98.3	41.1	40.5
L F		35.7	93.1	95.8	97.6	4R.4	96.4	98.4	98.4	98.4	98.7	98.7	98.7	98.7	98.7	98.7	46.7
01			,,,,,	,,,,	71.0	70.4	30.44	30.4	70,4	70.4	~ A . /	40.1	98.1	45.1	40.7	70.1	46.1
GΕ	son t	35.7	95.5	96.0	98.0	98.8	96.8	98.8	98.8	48.8	79.1	99.1	60 .	99.1			
6 E		35.7	93.5	96.2	90.2	99.0	99.0	99.0	99.0	99.0	99.5	39.5	99.1 99.5	99.5	99.1	99.1	99.1
GE		35.7	93.5	96.2	98.2	99.0	90.0	99.0	99.0	99.0	99.5	99.5	99.5	99.5	99.5	49.5	99.5
G.E.		35.7	93.5	96.2	98.2	99.0	99.0	99.1	99.1	99.0	99.8	97.8	99.5	99.8	99.8	49.8	44.5 44.4
U.F		35.7	93.5	96.	96.2	99.0	99.0		99.1	99.1	99.8	99.9				130.0	
	1001	23.1	73.3	10.00	10.2	7740	77.U	99.1	44.7	77.1	44.8	44.4	99.4	99.9	99.9	140.0	100.0
6 E	σl	35.7	93.5	96.2	90.2	99.0	99.0	99.1	99.1	99.1	99.8	99.9	99.9	79.9	99.9	100.0	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VFRSUS VISIHICITY FROM HOURLY OBSERVATIONS

STATICS NUMBER: 724505 STATION NAME: MCCONNELL AFRIKS PERIOD OF RECORD: 77-86 MONTH: AUG HOURS(LST): 67.6-7500 VISIBILITY IN STATUTE MILES
GE GE GE GE
2 1 1/2 1 1/4 1 CEILING

IN | SE
FEET | 15 ... 6E 6E 6E CE GE 3 GE G.F Sif c F 3 2 1/2 6/16 1.0 3/4 1/2 1/4 5/8 40 CETE 1 27.6 65.8 67.6 69.0 69.1 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 74.4 74.4 UE 200001 29.1 74.4 74.4 of 18000 29.1 of 16000 29.1 of 14000 29.1 70 • 4 7u • 4 72.4 72.4 71.5 73.5 73.8 73.8 73.9 73.9 74.4 74.4 74.4 74.4 74.4 74.4 74.4 14.4 14.4 74.4 74.4 74.4 74.4 74.4 74.4 74.4 74.4 74.4 12.1 74.7 73.6 7 5 - 4 74.1 74.2 74.7 74.7 74.7 74.7 74.7 74.7 14.7 74.7 75.6 15.6 GE 120001 29.2 75.6 6F 190001 30.2 6F 90001 30.2 6F 80001 32.0 6F 70001 32.5 77.0 77.1 81.9 82.5 78.4 78.5 79.0 79.0 79.0 79.0 79.0 79.0 79.3 79.0 79.0 75.1 79.9 90.4 7 to -3 78.5 63.3 63.9 74.1 79.1 79.1 79.1 79.1 79.1 76.6 79.1 79.1 79.1 14.1 83.4 84.0 84.1 54.1 54.5 84.1 84.1 04.1 84.1 84.1 84.1 A4.1 A4.6 84.6 84.6 84.6 84 - 6 84.6 84.6 82.8 94.3 50001 32.9 40001 33.9 40001 33.9 35001 33.9 87.5 84.9 85.3 87.5 87.8 A . . 3 87.5 t, t P 6 - 7 B 8 - 4 B 5 - 2 ∪ **E** ∪ **F** 83.1 67.0 87.1 87.8 87.8 8.18 87.8 67.8 87.8 87.8 57.8 +1.5 84.8 85.3 87.L 88.8 89.8 88.9 89.7 90.6 89.7 89.7 89.7 89.7 89.7 89.7 R9.7 69.7 90.6 41.1 87.A 89.9 90.6 90.6 90.6 90.6 90.6 94.49 9. . . 92.5 42.5 25001 33.4 27001 33.8 15001 33.8 15001 33.9 91.9 92.9 93.2 93.3 93.9 92.9 92.9 92.4 92.7 91.7 67.2 67.2 87.3 91.9 92.0 92.5 93.2 93.3 93.9 ii f 89.4 91.4 92 • 2 92 • 3 93.1 93.2 93.2 93.2 93.3 93.2 93.2 93.2 93.2 45.3 93.2 93.3 41.9 , f 90.2 91.9 92.7 93.8 93.9 25.9 93.4 93.9 05.9 93.4 9 . . 6 44.6 90.8 93.4 94.6 94.6 94.6 94.6 74.6 94.6 44.6 44.0 1000| 34.1 960| 34.1 PGC| 34.1 44.2 94.4 95.7 95.7 95.8 95.8 95 • 8 95 • 6 95.8 95.8 95.8 95.8 95.8 93.5 95.8 95.8 95.8 91.4 88.1 93.5 94.2 94.8 95.0 45.A 44.0 95.6 88.4 88.5 96.5 96.8 96.5 96.8 96.5 96.8 96.5 96.8 94.0 95.1 96.3 96.5 96.5 96.5 96.5 40.5 96.8 91.6 96.8 96.8 95.6 29.1 94.1 95.6 97.7 97.3 47. 1 97.5 41.5 1381 34.1 92.6 94.9 98.0 98.2 98.3 98.5 98.3 90.3 96.2 98.1 4001 34.1 7001 34.1 89.1 89.1 92.5 95.3 95.5 96.3 96.6 96.9 98.3 98.6 98.5 98.8 98.5 98.8 99.6 99.0 98.7 99.1 98 • 1 99 • 1 98.7 99.1 98.7 98.7 40.1 úξ 96.7 1.06 99.1 6,1 2001 34.1 89.4 93.1. 95.6 96.8 97.0 98.7 98.4 98.9 99.1 47.4 99.4 49.4 99.4 40.4 44.4 1601 34.1 95.1 95.6 98.7 98.9 99.5 99.5 99.6 47.7 (, **{** 49.6 46.8 98.9 21 49.1 P9.4 9 1 . 1 95.6 96.8 97-6 48.7 98.4 98.9 99.1 99.5 99.5 49.6 99.6 99.7 100.

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: AUG HOURS(LST): D630-0800 CEILING VISIBILITY IN STATUTE MILES st 6€ 5 GE 1 1 GE GE GE 6 5 GΕ GE GΕ GE GE GE 2 1 1/2 1 1/4 Gε I٨ GE GE 3 2 1/2 3/4 1/2 5/16 1/4 NO CEIL | 22.0 54.6 57.7 59,2 60.0 60.4 60.8 60.8 60.8 60.6 60.8 60.8 60.9 60.9 69.5 69.7 69.5 69.7 69.9 10.2 GE 200001 24.1 62.4 67.8 68.6 69.0 69.5 69.5 69.5 69.6 69.6 69.5 GE 180001 24.1 GE 160001 24.1 GE 140001 24.2 62.4 62.6 66.1 66.3 66.4 69.2 69.7 70.9 69.7 69.7 70.0 69 • 7 70 • 0 69.8 68.8 69.8 76 69.1 69.6 70.0 70.0 70.0 10.1 70.1 63.2 67.1 69.1 69.9 70.3 70.8 70.8 70.8 70.8 70.8 70.8 70.9 70.9 71.0 71. GE 125001 24.7 71.9 UE 100001 26.3 77.3 77.3 69.2 76.8 77.2 GE 90001 26.5 80001 27.8 69.7 73.5 75.8 76.9 77.3 77.7 77.7 77.7 77.7 82.0 77.7 82.0 77.8 82.2 77.8 78.0 82.3 82.0 70001 28.3 82.7 ĿΕ 60001 29.6 78.9 81.4 82.6 83.0 83.5 83.5 83.5 83.5 83.7 83.7 63.8 63. 5000| 29.1 77.4 78.1 86.2 86.2 86.9 88.3 86.3 87.0 86.5 87.1 86.6 87.2 88.7 86.7 87.3 88.8 69.6 86.3 86.5 87.1 86.6 82.4 83.5 86.5 84.8 86.0 67. 79.0 79.2 88.6 88.7 89.5 6 E 4000 30.0 86.0 87.8 88.3 88.5 88.5 88.6 3"001 30.0 89.0 89.0 89.2 89.5 ьE 84.2 86.8 88.2 88.6 89.2 89.4 85. 90.9 91.7 91.7 z500| 30.1 2000| 30.1 1800| 30.1 90.0 90.8 90.8 91.0 91.8 91.8 6 E 90.4 90.4 90.6 90.6 90.9 91. 80 - 1 88 .2 89.6 GE 80.3 88.7 90.1 90.i 90.5 90.5 91.1 91.2 91.4 91.5 91.6 91.6 91.7 86.0 91. 91. 86.0 15001 30.2 80.8 89.2 90.8 91.3 91.8 92.2 92.3 97.4 92.5 92.5 42.6 93.1 93.4 93. 6 E 12001 30.2 81.3 9 u . 1 91.6 93.2 93.3 93.3 92.7 93.1 94.1 94.4 94.8 96.1 ÜF 10001 30.2 81.8 82.2 88.3 96.9 91.2 93.2 93.7 94.U 94.4 94.1 94.5 94.3 94.7 94.5 94.9 94.5 94.9 94.6 95.1 94.6 94.7 95.2 94. 95. 95.1 96.3 96.7 95.6 95.9 96.2 96.6 FOO! 30.2 7001 30.2 82.5 82.7 91.9 94.6 95.8 96.1 6 F 88.8 96.0 96.2 96.3 96.5 90. 1, 5 89.0 96.3 96.5 96.7 96.8 96.6 96. 89.2 6001 30.2 95.3 96.8 96.9 97.0 97.1 97.2 97. 97.2 98.4 5001 30.2 95.3 95.6 95.7 96.5 97.0 97.2 94.7 82.8 82.9 92.5 92.6 97.6 97.8 96.0 98.3 98.2 98.6 98.5 98.5 98. 89.4 98.4 98.6 3001 30.2 82.9 92.7 98.8 99.0 98.8 99.0 60 2001 30.2 82.9 89.4 92.7 95.3 95.8 97.3 98.0 98.4 98 . B 99.0 99.2 99.2 99.4 99. 99.5 99.6 1001 30.2 89.4 92.7 95.3 95.8 Ŀξ 82.9

TOTAL NUMBER OF OBSERVATIONS:

82.9

89.4

01 30.2

930

95.3

92.7

95.8

97.4

98.1

98.5

98.9

99.2

99.2

99.5

99.5

99.6 100.

GLOBAL CLIMATOLOGY BRANCH USAFLTAC

PENCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

AIR WEATHER SERVICE/MAC PEPIOD OF RECURD: 77-66

MONTH: AUG HOURS(LST): 69-0-1166 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB MS CEILING GE CE 3 2 1/2 6 6 IN L GE FEET 1 10 GE 1/2 5/16 1/4 NO CETE 1 26.3 62.9 63.3 63.5 63.8 63.8 63.8 63.8 63.8 63.8 63.9 63.9 63.9 63.4 71.4 71.4 72.3 71.6 71.6 72.5 72.0 72.0 72.9 74.0 69.6 69.8 71.0 71.0 71.6 71.6 71.9 71.9 71.9 71.9 71.9 71.9 71.9 72.0 12.0 12.0 7 . . . 71.9 72.8 73.9 71.9 71.9 72.9 72.4 UF 180001 28.7 71.9 72.8 GE 140001 28-7 GE 140001 29-1 70.€ 71.8 72.5 73.5 72.8 73.9 72.8 72.8 72 · 9 74 • 0 7 . . 9 73.9 73.9 74.0 72.9 73.3 73.5 71.7 12000 29.8 79.2 79.8 83.1 79.9 GE 130001 31.4 79.5 19.5 79.6 79.8 79.8 9000| 31.5 8000| 32.4 80.3 81.7 60.4 63.8 55.1 86.4 #3.8 #5.1 77.8 80.9 79.4 82.6 60.0 63.3 96.0 83.3 80.3 AU.3 83.7 80.3 83.7 80.3 83.7 80.3 83.7 83.4 83.8 GΕ # . GR A3.0 ьE 70001 33.0 81.7 83.5 84.4 84.6 84.6 84.9 84.9 64.9 A4.9 84.9 84.9 85.1 85.1 85.9 86.2 86.2 86.2 A6.2 85.2 86.2 ٥E 60001 33.3 82.9 84.7 85.6 85.9 86.3 86.3 86.3 5000| 33.3 4500| 33.4 4500| 33.4 3500| 33.4 83.9 84.0 84.7 97.4 87.5 88.6 87.4 87.5 88.6 88.9 67.5 87.6 88.7 89.0 85.7 85.8 86.8 86.9 87.4 87.5 87.5 87.6 58.7 87.1 87.2 87.5 87.5 86.7 89.0 88.3 86.8 86.3 86.3 88.3 88.6 88.9 6E 88.6 88.6 88.6 88.7 88.9 88.9 89.0 99.0 84.6 ĿΕ 30001 33.4 86.1 88.4 90.0 96.0 90.3 9.1.3 90.3 90.5 90.1 90.1 90.4 90.4 43.4 96.4 2001 33.4 2001 33.4 19001 33.5 91.1 91.6 91.9 92.9 91.7 91.7 92.0 93.3 91.2 91.7 92.6 90.8 91.3 91.6 91.2 91.2 91.0 91.3 92.3 91.6 91.9 92.9 94.5 91.6 91.9 92.9 91.6 91.9 92.9 86.7 89.2 90.4 90.8 91.6 91.9 91.6 91.9 L F 92.0 92.0 93.0 93.0 91.6 92.9 ÚΕ 15001 33.9 87.4 90.3 92.6 92.9 93.1 91.7 93.8 17001 34-1 96.7 97.2 97.8 1"00| 34.1 700| 34.1 800| 34.1 94.7 95.3 95.7 95.9 96.5 97.0 96.7 97.2 97.8 96.7 97.2 91.8 96.7 97.2 91.8 96.7 97.2 97.8 96.8 97.3 98.0 89.8 90.1 93.2 GF GF 91. . 2 91.2 96.8 97.3 96.8 97.3 96.8 97.8 48.0 90.3 94 C 98.0 20.1 υŧ 700 | 34.1 95.9 97.5 98.1 98.1 98.2 98.2 98.2 48.2 98.8 96.8 i.F 6001 34.1 90.6 94.3 96.5 98.1 98.7 98 . 7 98.8 *00| 34.1 400| 34.1 91.0 94.7 94.8 94.8 98.4 98.4 99.4 94.5 99.6 99.6 99.7 99.4 99.4 49.6 99.8 99.5 99.7 99.9 99.5 44.5 44.7 45.4 ŭΕ 96.9 98.6 99.4 99.4 49.5 94.6 99.4 99.5 CE 1001 34.1 91.1 97.0 98.7 98.7 99.8 99.9 99.6 7601 34.1 91.1 94.6 97.0 98.4 99.8 99.9 99.9 49.9 99.8 99.8 1001 34-1 97.0 98.7 99.5 99.6 49.7 99.8 130.0 100.0 100.0 100.0 0 | 34.1 97.0 130.0 170.0

PERCENTAGE FREWMENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER	: 724505	STATI	ON NAME:	MCCO	NNELL AF	B KS					OF REC			1200-14	co
CEILIMG	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • •	• • • • • • •			IN STAT			• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
IN I GE	GE	GE	GE	GE	GE	GE	GE	GE	58	GE	GE	GE	GE	GE	CE
FEET 1 11		5	4		2 1/2			1 1/4	1	3/4	5/8	1/2	5/16	1/4	u
									-						
NO CETE 1 27.1	65.3	66.1	66.6	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66,7	66.7	66•7	66.7
GE 200001 31.	73.8	74.6	75.1	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2
GE 18000 31.5		7 8	75.3	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
GE 160001 31.9	74.1	74.9	75.4	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5
uf 140001 32.	75.3	76.1	76.6	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7
GE 120001 33.5	77.4	78.3	76.7	78.8	78.8	78.8	78.5	78.8	78.8	78.8	78.6	78.8	78.8	78.8	70.8
GE 100001 35.	81.5	82.4	82.8	82.9	82.9	H2.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	02.9	82.9
uf 90001 35.6		82.9	83.3	83.4	83.4	83.4	83.4	83.4	A3.4	83.4	83.4	83.4	83.4	83.4	83.4
SE 80001 35.0	84.9	86.1	86.6	86.7	86.7	86.7	86.7	86.7	B6.7	86.7	86.7	86.7	86.7	86.7	86.7
of 70001 35.	85.1	86.2	86.8	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	84.9
UE 65001 36.1	86.0	87.	87.1	87.8	87.8	87.8	87.8	8.78	87.8	87.8	87.8	87.8	87.8	87.8	87.8
		_													
us 5mapl 36.1	97.2	88.5	89.0	89.1	89.1	89.1	89.1	89-1	89.1	89.1	89.1	89.1	89.1	09.1	89.1
UE 45001 36.	87.2	86.5	89.0	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
UE 4001 36.5	98.5	89.8	90.3	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90 • 4	90.4	90.4	90.4
GE 35001 36.9	89.7	91.3	91.8	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
UE 30001 37.0	90.8	92.5	93.0	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
UF 25001 37.0	91.4	93.1	95.8	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
6F 2000 37•0	92.2	94.1	94.7	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
GE 1800 \$ 57.	92.8	94.7	95.4	95.8	95.8	95.8	95.8	95.B	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 15001 37.4	94.0	96.0	96.7	97.1	97.1	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GF 12001 37.5	94.9	97.1	97.7	98.2	96.2	98.3	98.4	48.4	98.4	98.4	98.4	98.4	98.4	98.4	96.4
GE 10001 37.1	95.2	97.3	90.0	98.5	96.5	98.6	98.7	98.7	98.7	98.7	98.7	98 • 7	98.7	98.7	98.7
6E 900 37.	95.6	97.7	98.4	98.9	98.9	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	95.1
UE 8J01 37.6	95.9	98 - 1	9 4 . 7	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
UE 7001 37.6		98.2	98.8	99.4	99.4	49.6	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8
LE fuel 37.0	95.9	98.2	96.8	99.4	99.4	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9
UF 500 37.4		98.2	98.8	99.4	99.4	99.6	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	101.0
DE 4001 37.0		98.2	5.89	99.4	99.4	49.6	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	106.0
oF ₹00 37.6		98.2	98.8	99.4	99.4	49.6	99.7	99.9	100 • 0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2001 37.0		98.2	9 5 . 8	99.4	99.4	99.6	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
OE 1301 37.0	95.9	98.2	98.8	99.4	99.4	99.6	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	106.C
GE 01 37.1	95.9	98.2	98.8	99.4	99.4	99.6	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	106.6

PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

CTATION NUMBER. TOURNE STATION NAME. MCCONNELL ARE MC

STATIO	N N	JMPLR:	724505	STATE	N NAME:	4000	NNELL A	FB KS					OF REC		-86 (LST):	1500-17	00	
																		.
CEILIN	6									IN STAT								
IN			ĢĒ	GE	GE.	GE	GE	GE	GE	3.0	GE.	GE	GE	GE	GE	GE	GE	
FEET	ı	10	ь	5	4		2 1/2	2	1 1/2		1	3/4	5/8	1/2	5/16	1/4	Ü	
	• • • •		• • • • • •	• • • • • • •	•••••		• • • • • • •	• • • • • •		•••••	• • • • • •	• • • • • •	•••••	•••••	•••••	• • • • • • •		•••
NO CEI	ı ı	28.4	69.2	69.4	76.4	70.4	70.4	70.4	70.4	70.4	70-4	70.4	70.4	70.4	70.4	70.4	76.4	
PE 500	וממ	32.8	78.6	78.7	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	
GE 180			78.6	78.7	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79 - 8	
GE 160			78.8	78.9	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	
GE 140	uol	33.2	79.6	79.7	80.6	80.8	80.8	80.8	80.6	8.06	80.8	80.8	80.8	8.08	80.8	8.06	80.8	
0E 15C	001	34.0	81.7	81.8	83.0	83.0	83.0	83.0	83.0	83.O	#3.O	83.0	83.0	83.0	83.0	83.0	83.G	
GE lar			85.4	85.5	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	96.7	86.7	86.7	
		36.2	86.0	86.1	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	
		36.5	87.4	87.5	86.7	88.7	88.7	88 • 7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	86.7	86.7	
		36.7	87.6	87.7	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	80.9	
0E 60	301	36.9	68.5	88.6	8 4 • 8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	84.8	
GE SM	001	37.2	9n.4	90.5	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	
GE 45	001	37.3	90.9	91.0	92.2	92.3	92.3	92.3	92.3	92.3	92.3	97.3	92.3	92.3	92.3	92.3	9 3	
GE 4P	001	37.7	92.8	92.9	94.1	94.3	94.3	94.4	94.4	94 - 4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	
		38.D	93.5	93.7	94.8	95.1	95.1	95.2	95.2	95.2	95.2	95.2	95 • 2	95.2	95.2	95.2	95.2	
GE 30	1 90	38.3	95 • 3	95.5	96.7	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	
GE 25	on I	38.4	95.7	96.1	97.3	97.6	97.6	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	
		38.4	95.8	96.2	97.4	97.7	97.7	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	
SE 18	uol	38.4	96.0	96.5	97.6	98.0	98.0	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98 • 1	96.1	
GE 15	001	3R.4	97.2	97.7	98.9	99.2	99.2	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	
GE 12	001	38.4	97.4	98.0	99.2	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 10	:.n.l	38.4	97.4	98.0	99.2	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	94.7	
		38.4	97.4	98.C	99.2	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 9	100	38.4	97.4	98.0	99.2	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 7	001	38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	106.6	
GE 6	100	38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
6E 5	nn I	38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100 • n	100.0	100.0	
		38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
		38.4	97.4	98.D	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
		38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	130.0	100.0	
		38.4	97.4	98.0	99.2	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
	0.1	38.4	97.4	98 . ti	99.2	99.9	99 5	100 0	100.0	100.0	100.0	100.0	100 0	100.0	100.0	100	lee e	
GE	• • • •	,n. 4	71.7	70.0	77.6	,,,,,	77.7			100.0								

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUM			_		-							HOURS	(LST):	1900-20	០០
CEILING		• • • • • • •	•••••	• • • • • •	• • • • • • • •			IN STATE			• • • • • • •	•••••		• • • • • • • •	
IN 1 FEET 1	10 6	GE 5	GE 4		6€ 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	36 3	5E 3/4	GE 5/8	GE 1/2	GE 5/16	GE 1/4	r. CE
NO CEIL Í 2	9.2 69.6	70.5	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6
GE 20000 3 GE 18000 3 GE 16000 3 GE 14000 3 GE 12000 3	3.3 81.0 3.3 81.2 4.1 82.0	82.4 82.5 82.7 83.5 86.2	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.6 84.6 87.3	83.4 83.5 83.8 84.6 67.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.6 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3	83.4 83.5 83.8 84.6 87.3
GE 100001 3: GE 90001 3: GE 80001 3: GE 70001 3: GE 60001 3	6.2 86.7 6.6 87.3 7.0 89.1 7.2 89.4	88.2 88.8 90.6 90.9 91.7	89.4 90.0 91.8 92.0 92.9	89.4 90.0 91.8 92.0	89.4 90.0 91.8 92.0 92.9	89.4 90.0 91.8 92.0 92.9	89.4 90.0 91.8 92.0	89.4 90.0 91.8 92.0	89.4 90.0 91.8 92.0	89.4 90.0 91.8 92.0	89.4 90.0 91.8 92.0 92.9	89.4 90.0 91.8 92.0	89.4 90.0 91.6 92.0 92.9	89.4 90.0 91.8 92.0 92.9	89.4 90.0 91.8 92.0 92.9
GE SOOT 31 GE 45001 31 GE 45001 31 GE 35001 31 GE 35001 31	91.9 8.3 92.2 8.4 93.7 8.7 94.3	93.4 93.7 95.2 95.8 96.5	94.6 94.8 96.3 97.0 97.6	94.6 94.8 96.3 97.0 97.6	94.6 94.8 96.3 97.0 97.6	94.6 94.8 96.3 97.0 97.6	94.6 94.8 96.3 97.0	94.6 94.8 96.3 97.0 97.6	94.7 94.9 96.5 97.1	94.7 94.9 96.5 97.1	94.7 94.9 96.5 97.1	94.7 94.9 96.5 97.1	94.1 94.9 96.5 97.1 97.7	94.7 94.9 96.5 97.1 97.7	94.7 94.9 96.5 97.1
GE 25001 30 GE 20001 30 GE 16001 30 GE 15004 30 GE 12001 30	8.8 95.1 8.8 95.5 8.8 96.2	96.6 96.6 97.0 97.7 97.8	97.7 97.7 98.2 98.9 99.0	97.8 97.8 98.3 99.0 99.1	97.8 97.8 98.3 99.0 99.1	97.8 97.8 98.3 99.0	97.8 97.8 98.3 99.0 99.1	97.8 97.8 98.3 99.0	98.0 98.0 98.4 99.1 99.2	98.0 98.1 98.5 99.2 99.4	98.0 98.1 98.5 99.2 99.4	98.0 98.1 98.5 99.2 99.4	98.0 98.1 98.5 99.2 99.4	98.0 98.1 98.5 99.2 99.4	98.0 98.1 98.5 99.2 99.4
GE 1000 30 GE 900 30 GE 800 30 GE 700 30 GE 600 38	96.5 9.9 96.5 9.9 96.5	98.0 98.0 98.0 98.0 98.0	99.1 99.1 99.1 99.1	99.4 99.4 99.7 99.7	99.4 99.4 99.7 99.7	99.4 99.4 99.7 99.7 99.7	99.4 99.4 99.7 99.7 99.7	99.4 99.4 99.7 99.7 99.7	99.5 99.5 99.8 99.8	99.7 99.7 100.0 100.0	99.7 99.7 100.0 100.0	99.7 99.7 100.0 100.0	99.7 99.7 100.0 100.0	99.7 99.7 100.0 100.0	99.7 106.6 106.0 106.0
GE SGO 38 GE 400 31 GE 300 34 GE 200 31 GE 140 31	8.9 96.5 9.9 96.5 9.9 96.5	98.0 98.0 98.0 98.0 98.0	99.1 95.1 95.1 95.1 99.1	99.7 99.7 99.7 99.7 99.7	99.7 99.7 99.7 99.7 99.7	99.7 99.7 99.7 99.7 99.7	99.7 99.7 99.7 99.7 99.7	99.7 99.7 99.7 99.7 99.7	99.8 99.8 99.8 99.8	100.0 100.0 100.0 100.0	100 • U 100 • U 100 • U 100 • U 100 • U	100.0 100.0 100.0 100.0	100.0 100.0 100.0 100.0	100.0 100.0 100.0 100.0	100.0 100.0 100.0 100.0
6E 01 31	8.9 96.5	98.0	99-1	99.7	99.7	99.7	99.7	94.7	99.8	100.0	100.0	100.0	100-0	100-0	106.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

			• • • • • • •														
CE I	LING		_					V151	BILITY	IN STAT	UTF MIL	E S					• -
:	IN I	GŁ	GE	GE	GΕ	GE	GE	GŁ	Ġ٤	GE	GE	GE	GĘ	GE	GE	GE	GΕ
FE	E1 [10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	٥
٠.		• • • • • •	• • • • • • •	*****		•••••	• • • • • • •	• • • • • • •		• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • •
N 0	CEIL	30.4	73.5	74.7	75.3	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5
	200001		79.7	81.4	81.9	62.3	82.3	82.4	82.4	62.4	A2 - 4	87.4	82.4	82.4	12.4	82.4	62.4
	180001		79.7	81.4	81.9	82.3	92.3	82.4	82.4	82.4	82.4	87.4	82 • 4	82.4	92.4	82.4	82.4
	16000		79.7	81.4	81.9	82.3	82.3	82.4	82.4	82.4	82.4	82.4	82.4	82.4	P2.4	82 • 4	82.4
	140001		80.1	81.8	82.4	82.7	82.7	82.8	82.8	82.9	82.8	82.8	82.8	82.8	P2.8	82.8	82.8
υE	150001	33.1	65.4	84.1	84.6	84.9	84.9	85.1	85.1	85.1	A5.1	85.1	85.1	85.1	85.1	85.1	85.1
υE	iorool	34.4	84.9	86.7	87.2	87.5	97.5	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
	10016		85.1	86.8	87.3	87.6	87.6	87.7	87.7	67.7	87.7	87.7	87.7	87.7	97.7	87.7	87.7
	80001		86.8	88.5	84.0	89.4	89.4	89.5	89.5	89.5	89.5	89.5	89.5	89.5	P9.5	89.5	84.5
υĒ	70001		88.C	89.7	9 L . Z	90.5	90.5	90.6	90.6	90.6	90.6	97.6	90.6	90.6	90.6	40.6	90.6
Ę	60001	36.D	P8.3	90.6	90.6	91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
E	5000	36.5	90.2	92.0	92.7	93.2	93.2	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
E	4500 l		90.4	92.5	92.9	93.4	93.4	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5
E.	40001		91.6	93.4	94.1	94.6	94.6	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
E	35001		92.8	94.6	95.3	95.8	95.8	95.9	95.9	95.9	96.0	96.0	96 • ú	96.0	96.0	96.0	96.0
ı E	30001	36.6	93.4	95.4	96.1	96.7	96.7	96.8	96.6	96.8	96.9	96.9	96.9	96.9	96.9	96.9	96.4
£	25001	36.6	93.4	95.4	96.1	96.7	96.7	96.9	96.9	96.9	97.0	97.0	97.0	97.0	97.0	97.0	97.0
ιĒ	2000	36.6	93.5	95.5	96.2	96.8	96.8	97.0	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1
Œ	10091	36.6	93.8	95.A	96.6	97.1	97.1	97.3	97.3	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4
E	15001		94.4	96.5	97.2	97.7	91.7	98.0	98.U	98.0	98.1	94.1	98 - 1	98.1	98 - 1	96 - 1	98.1
ιE	15001	36.6	94.6	96.8	97.5	98.1	98.1	98.3	98.3	98.3	98.4	98.4	98.4	98.4	98.4	98.4	98.4
E	10001	36.6	94.7	96.9	97.6	98.2	98.2	98.4	98.4	98.4	98.5	98.5	98.5	98.5	98.5	98.5	98.5
E	900	36.6	94.8	97.0	97.7	98.3	98.3	48.5	98.5	98.5	98.6	98.6	98.6	98.6	98.6	98.6	98.6
ı	Punl	36.6	94.6	97.2	98.0	98.6	98.6	98.8	98 . 8	98.8	98.9	98.9	98.9	98.9	9.80	98.9	96.9
Æ	7001	36.6	95.5	97.8	90.6	99.2	99.2	99.5	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	94.0
E	4001	36.6	95.€	98.0	90.7	99.4	99.4	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	94.7
E	sun I	36.6	95.6	98.0	98.7	99.5	99.5	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	49.8	99.8
ŧ	4001	36.6	95.6	98.℃	96.7	99.7	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100-0	130.0	101.0
E		36.6	95.6	98.0	98.7	99.7	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	166.0
E		36.6	95.6	98.0	96.7	99.7	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	130.0	100.0
ŧ	1001	36.6	95.6	98.0	98.7	99.7	99.7	99.9	99.9	99.9	100.0	100.0	100.3	100.0	100.0	100.0	100.0
r		36.6	95.6	98.0	96.7	99.7	99.7	99.9	99.9				100.0				106.0

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CFILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

ILIK6 IN GE ELT 10 CEIL 27-6 20000 30-4 18000 30-4 18000 30-4 14000 31-9 12000 31-9 12000 31-8 9000 33-8 7000 33-8 7000 34-8 4500 34-8 4500 35-7 5000 35-5 1500 35-5 1500 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7 700 35-7	27.6 (30.4 30.4	GE 6	GE 5	G E	GE		w 1 S 1									
CEIL 27.6 2000 30.4 1800 30.4 1800 30.4 1800 30.4 1800 31.9 1200 31.4 1000 32.8 900 33.0 800 33.8 700 34.2 600 34.5 500 34.8 4500 35.0 400 35.7 500 35.7 1000 35.7 900 35.7 1000 35.7 1000 35.7 1000 35.7 1000 35.7 1000 35.7 1000 35.7 1000 35.7	27.6 (30.4 30.4				r: c				IN STATE		-					
CEIL 27.6 20001 30.4 18001 30.4 18001 30.4 16000 30.4 14001 31.9 12000 31.4 10001 32.6 9000 33.8 7001 34.8 4500 35.0 4001 35.2 3500 35.4 2500 35.5 1800 35.5 1800 35.5 1800 35.7 900 35.7 900 35.7 900 35.7 900 35.7	27.6 6 30.4 30.4		5			GE	GE	GE	GE	GE	GE	GE	GE	GE	G E	CE
CEIL 27.6 20001 30.4 18001 30.4 16001 30.4 16001 30.4 14001 30.9 12001 31.4 10001 32.6 9001 33.0 8001 33.8 7001 34.8 4501 35.0 47001 35.7 47001 35.4 37001 35.4 37001 35.4 37001 35.5 18001 35.5 18001 35.5 18001 35.7 9001 35.7 9001 35.7 9001 35.7 9001 35.7 9001 35.7 9001 35.7 9001 35.7	27.6 (30.4 30.4	•••••		4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	L
200001 30.4 180001 30.4 160001 30.4 140001 31.9 120001 31.4 100001 32.8 90001 33.8 70001 34.2 6001 34.8 45001 35.0 40001 35.2 35001 35.4 25001 35.4 25001 35.5 10001 35.5 10001 35.7 10001 35.7 10001 35.7	30.4 30.4		• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •
18ruči 30.4 16ruči 30.4 14ruči 30.4 14ruči 30.9 120001 31.4 10ruči 32.8 9ruči 33.0 8ruči 33.0 8ruči 34.8 4ruči 34.5 5ruči 34.8 4ruči 35.0 4ruči 35.0 4ruči 35.4 2ruči 35.4 2ruči 35.4 2ruči 35.5 2ruči 35.5 2ruči 35.5 18001 35.7 9uči 35.7 9uči 35.7 9uči 35.7 6001 35.7	30.4	66 - 1	67.5	68.4	68.7	68.7	68.8	68.8	68.8	68.8	6P.8	68.8	68.9	68.9	68.9	60.7
160001 30.4 141001 31.9 120001 31.4 100001 32.6 90001 33.8 70001 34.2 60001 34.2 60001 34.5 40001 35.2 35.001 35.4 25.001 35.4 25.001 35.5 18.001 35.5 18.001 35.7 9.001 35.7 9.001 35.7		73.7	75.3	76.3	76.5	76.6	76.8	75.8	76.8	76.8	76.8	76.8	76.8	76.8	76.8	76.4
14 nool 33.9 12 nool 31.4 10 nool 32.8 9 nool 33.0 8 nool 33.8 7 nool 34.2 6 nool 34.5 5 nool 34.8 4 nool 35.0 4 nool 35.4 5 nool 35.4 5 nool 35.4 5 nool 35.5 2 nool 35.5 1 nool 35.7 9 nool 35.7 6 nool 35.7 6 nool 35.7		73.6	75.4	76.4	76.6	76.7	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
120001 31.4 10001 32.8 90001 33.0 80001 33.8 70001 34.2 60001 34.5 5001 34.8 45001 35.0 40001 35.2 35001 35.4 25001 35.4 25001 35.5 20001 35.5 18001 35.5 18001 35.7 9001 35.7 6001 35.7 6001 35.7		74.0	75.0	76.6	76.8	76.9	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.2
100001 32.8 90001 33.0 80001 33.8 70001 34.2 60001 34.5 50001 34.8 45001 35.2 37001 35.4 37001 35.4 37001 35.5 20001 35.5 20001 35.5 15001 35.5 15001 35.7 9001 35.7		74.8	76.4	77.4	17.7	77.8	77.9	17.9	77.9	78.U	79.0	78.6	78.0	78.0	79.C	7n
90001 33.0 80001 34.2 60001 34.2 60001 34.5 50001 34.5 50001 35.0 40001 35.2 37001 35.4 25001 35.5 20001 35.5 20001 35.5 18001 35.5 18001 35.7	31.4	76 • 6	78.2	79.2	79.5	79.5	79.7	19.7	79.7	79.7	79.7	79.7	79.B	79.8	79.8	74.0
8 000 33.8 7000 34.2 6000 34.5 5000 34.8 4500 35.2 3700 35.4 3700 35.5 2000 35.5 2000 35.5 1800 35.5 1800 35.5 1800 35.7 900 35.7 900 35.7 600 35.7 500 35.7	32.8	80.2	81.9	82.9	83.2	83.3	83.4	83.4	8 . 4	83.5	83.5	83.5	83.5	R3.5	83.5	A 3.5
7000 34.2 6000 34.8 4500 25.0 4000 35.2 3500 35.4 3600 35.4 3600 35.5 2600 35.5 2600 35.5 1500 35.5 1500 35.6 1700 35.7 900 35.7 600 35.7	33.0	80.6	82.2	83.3	83.6	93.7	83.8	83.8	83.8	B 3 . B	87.8	83.8	83.9	A3.9	03.9	63.9
50001 34.8 45001 35.0 40001 35.2 37001 35.4 37001 35.4 25001 35.5 27001 35.5 18001 35.5 18001 35.7 10001 35.7 9001 35.7 6001 35.7	33.8	83.4	85.1	86.2	86.5	86.6	86.8	86.8	86.8	86.8	86.8	86.8	86.9	96.9	66.9	H6.4
\$0001 34.8 45001 35.0 40001 35.2 37001 35.4 37001 35.5 27001 35.5 27001 35.5 18001 35.5 18001 35.7 9001 35.7 9001 35.7 6001 35.7 5001 35.7	34.2	84 . C	85.6	A 6 . 9	87.3	87.3	87.5	87.5	87.5	87.5	87.5	87.5	87.6	87.6	87.6	41.6
45001 35.0 47001 35.2 37001 35.4 37001 35.4 25001 35.5 27001 35.5 18001 35.6 12001 35.7 9001 35.7 9001 35.7 6001 35.7 6001 35.7	34.5	84.8	86.5	87.7	88.0	88.1	88.3	88.3	88.3	A8.3	8 4 . 3	88.3	88.5	A8.3	88.4	50.4
4 00 0 1 35.2 3 00 0 1 35.4 3 00 0 1 35.5 2 00 0 1 35.5 1 0 0 1 35.5 1 0 0 1 35.6 1 2 0 0 1 35.7 9 0 0 1 35.7 9 0 0 1 35.7 6 0 0 1 35.7	34.8	86.5	88.3	89.6	90.0	90.1	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	40.4
35.00 35.4 35.00 35.5 25.00 35.5 25.00 35.5 18.00 35.5 15.00 35.6 17.00 35.7 9.00 35.7 9.00 35.7 6.00 35.7 5.00 35.7 5.00 35.7		86.8	88.6	89.4	90.3	90.3	90.6	90.6	90.6	90.6	90.6	93.6	90.6	90.6	40.6	4L.7
30001 35.4 25001 35.5 20001 35.5 18001 35.5 18001 35.7 10001 35.7 9001 35.7 9001 35.7 6001 35.7 6001 35.7		A8.2	90.1	91.3	91.8	91.9	92.1	92.1	92.1	92.1	92.1	92.1	92.2	92.2	72.2	9
25001 35.5 20001 35.5 18001 35.5 15001 35.6 17001 35.7 9001 35.7 9001 35.7 6001 35.7		88.8	90.9	92.2	92.6	92.7	92.9	92.9	92.9	93.0	93.0	53.U	93.0	93.0	93.0	93.1
2001 35.5 18001 35.5 18001 35.6 12001 35.7 9001 35.7 9001 35.7 6001 35.7	35.4 6	89.8	92.0	93.3	93.9	93.9	94.2	94.2	94.2	94.2	94.3	74 . 3	94.3	94.3	94.3	94.3
18001 35.5 15.01 35.6 12001 35.7 9001 35.7 9001 35.7 7001 35.7 6001 35.7		90.1	92.3	93.6	94.2	94.3	94.6	94.6	94.6	94.6	94.7	94.7	94.7	94.7	94.7	94.7
15001 35.6 17001 35.7 10001 35.7 9001 35.7 9001 35.7 7001 35.7 6001 35.7		90.2	92.6	93.9	94.5	94.6	94.9	94.9	94.9	95.U	95.0	95.⊔	95.1	95.1	95.1	95 · i
1700 35.7 1000 35.7 900 35.7 900 35.7 700 35.7 600 35.7 500 35.7		90.5	92.8	94.2	94.7	94.9	95.1	95.2	95.2	95.3	95.3	95.3	95.3	95.3	95.3	95.3
10001 35.7 9001 35.7 9001 35.7 7001 35.7 6001 35.7		91.1	93.5	94.9	95.5	95.7	96.0	96.0	96.0	96.1	96.1	96.1	96.1	96.1	96.2	96.2
9001 35.7 9001 35.7 7001 35.7 6001 35.7	35.7	91.6	94.1	95.6	96.2	96.3	96.7	96.7	96.7	96.8	96.8	96.8	96.9	96.8	46.9	96.9
POD 35.7 700 35.7 600 35.7 500 35.7		92.0	94.7	96.2	97.0	97.1	97.5	97.5	97.5	97.6	97.6	97.6	97.7	97.7	97.7	97.7
700 35.7 600 35.7 500 35.7		92.1	94.8	96.4	97.2	97.3	97.6	97.7	97.7	97.8	97.8	97.8	97.8	97.8	47.9	97.9
600 35.7 500 35.7		92.3	95.1	96.7	97.6	97.7	98.1	98.2	98.2	98.3	98.3	98.3	98.3	98.3	9A.3	46.3
5001 35.7		92.5	95.3	96.9	97.9	98.0	98.4	98.5	98.5	98.6	98.6	98.6	98.7	98.7	98.7	98.1
	35.7 9	92.6	95.5	97.2	98.1	98.2	98.7	98.7	98.8	98.9	98.9	98.9	99.0	99.0	99.0	99.0
4001 15 7		92.7	95.6	97.3	98.3	98.4	98.9	99.0	99.1	99.2	99.2	99.2	99.2	99.2	99.3	94.3
		92.8	95.7	97.4	98.4	98 • 6	99.1	99.2	99.3	99.4	99.5	99.5	99.5	99.5	49.6	94.6
300 35.7		92.6	95.7	97.4	98.5	98.6	99.2	99.3	99.4	99.6	99.7	99.7	99.7	99.7	99.7	94.7
700 35.7	55.1 9	92.8	95.7	97.4	98.5	98.6	99.2	99.4	99.4	99.7	99.7	99.7	99.8	99.8	99.8	99.8
1601 35.7		92.8	95.7	97.4	98.5	98.6	99.2	99.4	99.5	99.7	99.8	99.8	99.9	99.9	99.9	99.9

PERCENTAGE FREQUENCY OF OCCUMPENCE OF LETVING VERSUS VISIBILITY FROM HOURLY GOSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PLETON OF PROOFER BY AR MONTHS SEE HOURSCLUTS: G -Day CEILING VISIBILITY IN STATUTE MILES 5.3 5/16 1/4 5/8 172 NO CETE | 32.0 68.2 69.1 69.3 69.7 69.7 69.7 64.8 69.8 69. H 64.4 49.H . 4. 4 67.6 GE 2J0001 33.7 74.2 74.2 74.8 74.5 74.5 74.9 75.7 14.5 14.5 14.5 72.7 73.7 73.9 74.2 74.2 74.3 74.3 14.5 74.5 GE 180001 33.7 GE 160001 33.7 72.7 73.2 73.7 74.2 73.9 74.2 74.8 74.5 74.9 75.7 74.3 74.9 75.7 74.4 74.4 75.7 74.2 74.8 74.3 14.9 74.3 74.4 74.7 74.3 74.9 75.7 74.3 74.4 GE 140001 33.9 74.0 75.6 75.6 75.6 15.7 11.0 15.1 GE 120001 34-2 75.2 76.3 11.0 11.0 77.0 78.0 78.2 GE 100001 34.3 76.8 77.0 78.6 76.8 81.6 78.6 78.6 78.8 81.6 70.7 78.7 24. 7 10.1 7 H . 7 14 7 20.1 10.1 90001 34.4 76.9 R1.7 R3.0 76.4 81.2 78.4 10.9 01.7 78.8 10.4 78.9 71. . 'n. ¥ 14.4 GF 80001 34.4 79.7 81.0 81.6 81.7 67.3 87.6 P1 • 1 #1.7 #3.7 91.1 n1.7 70001 34.6 80.7 GE 82.0 82.6 82.9 82.9 82.9 83.0 я (... n3... 9 4 . (*) F : . . 60001 34.9 83.7 83.7 83.8 9 3 _ H 85.7 87.2 89.2 85.7 87.2 89.3 85.9 87.4 89.6 84.9 87.4 84.5 90.0 50001 35.4 83.1 85.9 81.4 89.6 84.6 85.3 85.7 85.4 87.4 GΕ 45001 36.0 40001 36.6 84.7 86.6 86.1 80.9 87.2 89.2 87.4 49.6 93.0 67.4 97.4 r7.4 07.4 89.5 90.0 84.6 ρψ.υ 35001 36.8 61 87.0 88.6 A 9 . 3 89.7 99.7 90.0 90.0 90.0 90.0 42.U 42.1 ٠,٠. 90.4 91.3 91.8 91.8 91.9 92.1 92.1 6 E 6 E 92.3 92.9 92.9 93.4 92.7 93.2 93.2 25001 37.0 89.1 91.0 91.9 92.3 92.9 92.4 93.0 92.7 91.2 93.2 93.8 92.7 91.7 91.2 91.8 92.7 43.2 95.2 9...1 9.... 9.... 43.1 43.2 2000 | 37.1 1900 | 37.1 89.1 89.1 92.4 91.6 93.2 93.2 91.6 92.9 93.0 93 1.5 1500L 37.1 90.2 93.0 93.6 93.8 91.8 91.4 93.8 ψ ₹. μ 12001 37.1 90.9 92.6 10001 37.1 91.9 92.6 93.9 95.3 95.7 95.9 96.4 95.3 95.1 95.7 91.7 46.2 9001 37.1 PUDI 37.1 95.1 94.1 45.6 95.7 95.4 45.9 46.4 ه ۲۰ 95.4 45,9 25.4 92.4 94.7 95.7 95.1 € E 96.1 96.4 96.2 46.4 41.0 96.4 16.4 11.5 46.4 700 96.8 97.u 91.0 91.0 97.7 ų E 6L01 37.1 9h.3 40.5 98.3 <90 | 37.1
460 | 37.1
760 | 37.1</pre> 96.6 91.0 94.2 98.6 94.2 94.3 98.6 98.8 99.1 99.4 98.4 99.4 99.4 48.6 4 A . A 9 P . 4 96.8 ΰĒ 94.0 96.2 91.3 98.7 99.8 98.7 99.0 99.2 99.3 99.4 y 0 . 5 44.4 44.4 GI 98.6 99.6 ĞF 2ugl 37.1 94.0 99.6 1 . 49 97.4 44.0 99. 130.0 100.6 100.0 12000 1.00.00 1. . . . 100.0 99.0 94.0 96.5 49.3 99.6 130.0 100.0 100.0 GE CI 57.1 99.6 94.6 96.1 97.4 99.0 99.1. 49.3 99.6 100.6 100.0 100.0 100.0 100.0 100.0 100.0

PENCENTAGE FREQUENCY OF OCCURRENCE OF CETLING VERSUS VISIBILITY FROM HOURLY OUSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: SEP HOURS(EST): 0300-0500 STATION NUMBER: 724565 STATION NAME: MCCONNELL AFE KS

																0 100 0 5	00
			• • • • • • •	• • • • • • •	• • • • • • •		• • • • • •						• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	
CEI	LING							V151	BILITY	IN STATE	JTF MILE	5					
1	IN I	GŁ	61	G E	GE	GE	C.E	GE	GE	υŁ	3.0	GE	GE	GE	GE	GE	ĿΕ
	ET I		6	, s	- 4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	ن
															,, 10	.,,	Ü
• • •	• • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •		• • • • • • •		• • • • • • •	• • • • • • •		• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • •
NO	CEIL I	30.4	65.1	65.6	65.9	66.4	66.4	66.7	67.u	67.0	67.1	67.4	67.4	67.6	67.6	67.6	67.6
												-	-				
									*** **	***	• • •		•				
	Socool		69.0	69.4	69.8	70.3	76.3	10.6	10.9	70.9	71.0	71.5	71 - 3	71.4	71.4	71.4	71.4
	180001		69.0	69.4	64.8	70.3	7L.3	70.6	70.9	70.9	71.0	71.3	71.3	71.4	71.4	71 - 4	71.4
GΕ	160001	31.3	69.3	69.6	76.1	70.7	70.7	70.9	71.2	71.2	71.3	71.7	71.7	71.8	71.8	71.8	71.8
6 F	140001	31.3	69.7	70.1	70.4	71.0	71.0	71.2	71.6	71.6	71.7	72.0	72.C	12.1	72.1	72.1	72.1
	120001		70.3	70.9	71.2	71.6	71.6	72.0	72.3	72.3	72.4	72 · 8	72.8	72.9	72.9	72.9	72.9
:12	1,1001	21.0	10.3	70.7	11.2		11.0	1.5 + 23	12.03	12.5	12.5	1	72.0	12.7	, , , ,	,,,,	, , ,
GE	100001	31.8	72.4	73-1	73.0	74.1	74.1	74.3	74.1	74.7	74.8	75.1	75.1	75.2	75.2	75.2	75.2
GE	90001	31.8	72.6	73.4	73.9	74.4	74.4	74.7	75 • U	75.0	75.1	75.4	75.4	75.6	75.6	15.6	15.6
GΕ	80001	32.1	75.2	76.2	76.8	71.3	77.3	77.6	77.9	77.9	78.0	78.3	78.3	78.4	78.4	78.4	76.4
GE	70001		76.3	77.3	77.9	78.4	76.4	78.7	79.0	79.0	79.1	79.4	79.4	79.6	79.6	79.6	74.6
_																	
ĢΕ	60001	32.3	76.9	77.9	78.4	79.0	74.U	19.2	79.6	79.6	79.7	80.0	80.0	80.1	80 - 1	00.1	8L.1
GE	50001	37.4	79.6	80.6	81.1	81.7	81.7	81.9	82.3	62.3	82.4	82.8	82.0	82.7	82.9	62.9	8 4
GE	4500		80.6	81.7	82.2	62.8	82.8	83.0	83.4	63.4	A3.6	83.9	83.9	84.0	84.0	84.0	P4.0
ĢΕ	4000		82.4	83.6	84.2	84.9	84.9	85 - 1	A5.6	45.6	P5.7	86.0	86.0	86.1	86.1	86.1	86.1
G £	35001	34.7	82.4	83.6	R4.2	84.9	84.9	85.1	85.6	85.6	85.7	86.0	86.0	56.1	86.1	86.1	Ft.l
üΕ	30001	35.2	85.0	86.3	87.1	87.8	87.8	88.0	88.4	80.4	A8.6	89.0	89.0	89.1	89.1	59.1	R9.1
														•			
GΕ	25001	16 7	A5.6	86.9	81.7	88.3	88.3	89.6	89.0	69.0	89.1	89.6	89.6	89.7	89.7	89.7	84.1
UΕ	50001		86.9	88.3	89.2	89.9	89.9	90.1	90.6	90.6	90.7	91.1	91.1	91.2	91.2	71.2	11.2
υ£	1800		87.2	88.6	84.1	90.3	90.3	90.6	91.6	91.0	91.1	91.6	91.6	91.7	91.7	91.7	91.7
5€	1,001	35.3	88.0	89.6	96.4	91.1	91.1	91.3	91.8	91.B	91.9	97.3	92.3	92.4.	92.4	12.4	9 4
i F	17601	15.1	89.7	91.2	94.2	97.9	92.9	43.1	93.6	93.6	93.7	94.1	94.1	94.2	94.2	94.2	94.2
٠.	,	2	3,	,			,										
_																	
5 €	1001		90.3	92.0	63.7	93.8	93.6	94.0	94.4	94.4	94.6	95.D	95.0	95.1	95.1	55 · 1	95 - 1
į, r		35.3	90.3	92.0	93.1	93.9	93.9	94.1	94.6	94.6	94.7	9 c . 1	95.1	95.2	95.2	45.2	45.2
Úξ	•uo	55.3	90.9	97.6	93.7	94.6	94.6	94.8	95.2	45.2	95.3	95.8	95.8	95.9	95.9	45.9	95.4
6.t	1001	35.3	91.6	92.9	94.3	95.3	95.3	95.6	96.1	96.1	96.2	96.7	96.7	96.8	96.8	46.8	96.8
5.5		35.3	91.1	93.0	94.4	95.7	95.7	95.9	96.4	96.4	96.6	97.0	97.0	97.1	97.1	97.1	97.1
٠,		J , • ,	71.1	73.0	74.4	97.1	73.7	* / • *	,,,,	,	.0.0	7.4.0	* 7 • 5	,,			*, • •
Ģ €		35.3	91.4	93.3	94.8	96.2	96.2	96.6	97.1	97.1	97.2	97.7	97.7	97.8	97.8	¥7.8	97.8
G F	4301	35.3	91.4	93.6	95.1	96.9	96.9	97.3	97.9	47.9	98.1	94.6	98.6	98.7	98.7	48.7	96.7
G.E		35.3	91.6	93.7	95.3	97.1	97.4	98.0	98.8	90.A	29.1	99.6	99.6	99.7	99.1	99.7	99.7
Ü.E		35.3	91.6	93.7	95.3	97.1	97.4	0.89	96.8	98.8	99	99.8	99.8	99.9	99.9	49.9	69.9
														-			-
6€	1001	35.3	91.6	93.7	95.3	97.1	97.4	98.0	98.9	98.9	99.3	99.9	99.9	100.0	100.0	100.0	11 0.0
G.E	01	35.3	91.6	93.7	95.3	97.1	97.4	98.0	98.9	98.9	99.3	49.9	99.4	100.0	120.0	100.0	100.0

PERCENTAGE FREQUENCY OF GCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 77-86
MONTH: SEP HOURSILST): D600-08C0 VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 GE GE 3 2 1/2 GE GE 4 ε ε GE GE GE 2 1 1/2 1 1/4 GE 1 1.0 3/4 5/8 1/2 5/16 1/4 () NO CETE | 26.0 59.8 62.0 62.2 62.3 62.3 62.4 58.7 66.8 61.6 61.7 61.8 61.9 62.4 62.7 62.7 GE 200001 28.0 GE 180001 28.1 63.7 65.9 66.8 67.1 67.2 67.6 67.8 67.9 67.7 67·9 68.0 68.0 68.1 68.1 68.4 66.4 65.1 65.2 66.3 66.1 68.2 69.3 68.2 68.3 68.3 66.7 UE 160001 28.1 66.2 67.1 67.2 67.6 64.0 68.0 68.2 68.8 66.8 69.U 68 • 2 140601 48.8 65.1 67.2 10.6 120001 29.7 69.7 70.7 71.0 71.3 71.6 71.6 71.9 71.9 72.0 72.0 72.3 74.7 75.2 78.3 75.0 75.6 75.0 75.6 76.7 75.1 75.7 100001 30.4 70.2 70.8 71.7 72.2 75.2 75.8 75.0 78.1 90001 30.4 75.3 74.2 77.3 74.3 77.4 74.7 77.8 75.4 75•7 78•8 76.1 79.2 4 E 76.1 6001 31.3 78.6 78.7 79.2 79.2 79.8 ŭ₽ 70001 31.8 73.9 77.3 77.9 78.0 78.3 78.7 78.9 79.1 79.2 79.3 79.3 79.8 60001 32.0 77.6 80.6 G E 76.3 78.6 78.7 5000| 32.1 400| 32.1 4000| 32.4 78.1 78.8 80.4 80.7 81.4 83.3 8C.8 81.6 83.6 81.2 82.0 84.1 81.6 82.3 84.4 81.8 82.6 84.7 82.8 82.8 84.9 82.1 82.9 85.0 82.2 83.0 85.1 G.E 76 . 2 82.1 82.9 85.0 82.2 82.7 76.9 8G.2 82.1 83.0 85.1 83.4 83.4 85.6 U.F 3 001 32.4 81.U 84.2 85.1 85.3 85.6 85.7 85.7 85.8 85.8 86.2 30001 32.4 83.6 85.1 85.4 86.0 86.4 86.7 86.9 87.0 87.0 87.1 87.1 87.6 82.2 63.4 83.7 87.0 88.2 87.2 88.4 87.4 88.7 87.6 88.8 87.7 88.9 2*001 32.4 20001 32.8 79.4 80.7 84.1 85.3 85.7 86.0 87.2 86.6 87.8 86.1 64.3 86 . 9 Gξ 19001 32.8 81.1 85.8 67.3 87.7 88.2 88.7 88.9 89.1 89.2 90.4 89.2 89.3 89.3 89.8 84.8 90.6 90.3 1,1 15001 32.8 82.2 85.1 87.0 88.6 88.9 89.4 89.9 90.1 90.4 90.6 91.0 91.0 89.7 90.6 93.0 93.7 94.6 10001 32.8 84.U 84.1 84.3 91.9 92.9 87.2 87.6 87.9 89.1 89.7 90.2 91.3 90.9 93.8 9001 32.8 8001 32.8 91.6 92.9 92.6 93.4 93.1 93.3 93.6 93.7 93.8 UF GF 94.2 94.2 95.A 7001 32.R 84.7 88.3 96.0 93.2 93.7 95.1 95.3 95.6 95.7 95.7 95 . R 96.2 96.2 96.3 95.6 96.1 96.2 96.2 96.3 96.8 91.0 93.4 96.8 6.8 €001 32.8 84.9 88.6 94.0 100| 32.8 440| 32.8 300| 32.8 85.0 85.2 85.2 88.9 89.1 89.1 91.4 92.1 92.1 97.0 98.3 98.6 98.6 97.1 98.4 98.7 94.0 94.6 95.4 96.3 96.7 97.1 97.2 97.2 97.7 97.7 98.0 98.2 98.2 98.4 űŧ 94.9 95.6 95.6 96.6 97.7 98.6 98.8 98.6 98.8 99.2 99.0 (, t 89.1 92.1 99.4 99.7 2001 32.8 P5.2 98.9 1001 32.8 89.1 92.1 95.1 95.8 96.8 97.9 98.2 98.6 98.9 99.0 99.1 99.1 99.7 106.0 95.1 99.0 01 32.8 92.1 97.9 98.2 98 . 6 98.9 99.1 99.1 99.7 100.0

TOTAL NUMBER OF OPSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER:	724505	STATI	ON NAME:	. MCE0	NNELL AF	FB KS				PEPIOD	OF REC	ORO: 77	-86			
										MONIH	: SEP	HOURS	(LS1):	0900-11	UC	
CEILIMG	•••••		• • • • • • • •					IN STATE			••••					
IN I GE	GE	GE	6E	GE	ÇΕ	GE	ĢĒ	GE.	GE	GE	GE	GE	GE	GE	CE	
FEET 1 10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	ü	
			• • • • • • •		• • • • • •		• • • • • • •				• • • • • • •		• • • • • •	• • • • • •		٠.
NO CEIL 19.0	61.9	62.6	62.9	63.0	63.U	63.0	63.0	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	
GE 200001 31.4	68.5	70.a	76.4	70.6	70.6	70.6	70.6	10.7	70.7	70.8	7D.6	70.8	73.8	70.8	76.8	
GE 180001 31.7	69.0	70.2	76.7	70.8	70.8	70.8	70.8	70.9	70.9	71.0	71.0	71.0	71.0	71.0	71.5	
UE 16F001 31.8	69.1	70.3	76.8	70.9	70.9	70.9	70.9	71.0	71.0	71.1	71.1	71.1	71.1	71.1	71.1	
GE 140001 32.0	69.9	71.1	71.6	71.7	71.7	71.7	71.7	71.8	71.6	71.9	71.9	71.9	71.9	71.9	71.9	
6E 12rool 32.7	71.6	72.8	73.2	73.3	73.3	73.3	73.3	73.4	73.4	73.6	73.6	73.6	73.6	73.6	73.6	
or 15(An) 25*1	,1.0	12.0	1 2 42	13.3	,,,,	, , , ,		13.4			.,	,,,,,		. 3.0		
GE 100001 33.4	74.8	76 - 1	76.7	76.8	76.8	76.8	76.8	76.9	76.9	77.0	77.C	77.3	77.0	17.0	77.0	
GE 90001 33.9	75.3	76.7	77.2	77.3	77.3	77.3	77.3	77.4	77.4	77.6	77.6	77.6	77.6	17.6	17.0	
GE 80001 34.3	78.1	79.7	8 U . 2	80.3	80.3	80.3	80.3	80.4	80.4	80.6	80.6	80.6	80.6	60.6	€5.6	
GE 70001 34.8	78.5	80.4	81.2	81.3	81.3	81.3	81.3	81.4	81.4	81.6	81.6	81.6	81.6	61.6	81.6	
GE 60001 34.9	79.3	80.9	81.8	81.9	81.9	81.9	81.9	82.0	82.0	82.1	82.1	82.1	82.1	87.1	62.1	
		***	0.00											•	• -	
GE 50001 34.9	79.7	81.2	82.3	82.4	82.4	82.4	82.4	82.6	82 • 6	87.7	82.7	82.7	82.7	82.7	8 7	
GE 4500 35 - 0	80.0	81.6	82.7	82.8	92.8	82.8	82.8	82.9	82.9	83.0	83.0	83.0	B3.0	83.0	85.0	
SE 40001 35.2	81.4	83.0	84.1	84.2	84.2	84.2	84.2	84.3	84.3	84.4	84.4	34.4	84.4	84.4	84.4	
GE 35001 35.2	81.8	83.6	84.7	84.8	84.6	84.8	84.5	84.9	84.9	85.0	85.0	85.0	85.0	0.0	65.0	
GE 3000 35.2	83.C	84.9	86.3	86.7	36.7	86.8	86.8	86.9	86.9	87.0	87.0	87.0	87.0	67.0	87.0	
GE 25001 35.3	84.2	86.1	87.6	87.9	87.9	88.0	88.0	68.1	88.1	88.2	88.2	88.2	68.2	88.2	90.2	
GE 2001 35.6	84.7	86.6	88.0	88.3	88.3	88.1	88.4	88.6	98.6	88.7	88.7	88.7	98.7	88.7	66.7	
LE 1700 35.7	85.7	87.6	84.0	89.3	89.3	89.4	89.4	89.6	89.6	89.7	89.7	89.7	89.7	89.7	89.7	
GE 15001 35.9	87.4	89.3	91.0	91.3	91.3	91.4	91.4	91.6	91.6	91.7	91.7	91.7	91.7	91.7	91.7	
GE 12001 35.9	88.1	90.0	91.7	92.0	92.0	92.1	92.2	42.3	92.3	92.4	92.4	92.4	92.4	92.4	9 c . 4	
GE 10001 35.9	89.0	91.1	97.8	93.2	93.3	93.4	93.9	94.1	94.2	94.3	94.3	94.3	94.3	94.3	94.3	
GF 900 35.9	89.4	91.7	93.3	93.8	93.9	94.0	94.4	94.7	94.8	94.9	94.9	94.9	94.9	94.9	94.9	
CE PUOJ 35.9	89.7	92.G	93.8	94.7	94.8	94.9	95.4	95.7	95.8	95.9	95.9	95.9	95.9	95.9	95.9	
GE 700 35.9	89.9	92.3	94.4	95.6	95.6	95.9	96.4	96.7	96.9	97.0	97.0	97.0	97.0	97.0	97.3	
GE EUR! 35.9	90.1	92.8	95.0	96.2	96.6	96.7	97.2	97.4	97.7	97.8	97.8	97.8	91.8	47.8	97.8	
GE 4001 35.9 GE 4001 35.9	90.3 90.3	93.1 93.2	95.4	96.8 97.1	97.1 97.4	97.3 97.7	98.2 98.7	98.4 99.1	98.7	98.8 99.4	98 - 8 99 - 4	98.8	98.8	98.8 99.4	95.8	
GE 3001 35.9	90.3	93.2	95.8 95.9	97.2	97.6	98.0	99.0	99.4	49.8	99.9	99.9	99.4	99.4	99.9	99.4	
	90.3	93.3	95.9	97.2	97.6	98.0	99.0	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	
GE 2001 35.9 GE 1001 35.9	90.3	93.3	95.9	97.2	97.6	98.0	99.0	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	
0c 1001 32• A	4U • 3	73.3	73.7	71.2	71.0	4c • 0	77.0	77.0	77.7	100.0	100.0	100.0	100.0	100.0	. 50 • 0	
GE 01 35.9	90.3	93.3	95.9	97.2	97.6	98.0	99.0	99.6	99.9	100.0	100.0	100.0	100.0	1.30.n	100	
0. 01 3349	70.03	73.3	, , , , , , , , , , , , , , , , , , ,	,,,,			77.00				•	100.0				

PERCENTAGE FREGUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFR KS PERIOD OF RECORD: 77-86 MONTH: SEP HOURS (LST): 1200-1400 VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 GF 3/4 5/8 1/2 5/16 1/4 NO CETE | 31.3 64.2 65.1 65.3 65.4 65.4 65.4 74.3 GE 200001 35.0 GE 180001 35.3 73.2 74 • 1 74 • 7 74.4 74.4 75.0 74.4 74.4 74.4 75.0 74.4 75.0 75.0 74.4 75.0 74.4 74.4 75.0 75.0 75.0 75.9 73.8 75.0 75.0 75.0 75.0 75.0 75.0 75.0 75.ú 75.ú GE 160001 35.3 GE 140001 35.9 73.8 74.7 74.9 75.8 75.0 75.0 75.0 75.0 75.0 75.0 75.0 75.6 75.9 74.7 75.9 75.9 75.9 77.2 75.9 15.9 75.9 75.9 75.9 75.9 75.9 GE 120001 36.2 17.2 77.2 77.2 77.2 17.2 77.2 77.2 77.2 77.2 GE 100001 36.4 GE 92001 36.7 79.6 80.1 79.8 8G.3 79.9 80.4 79.9 80.4 83.U 79.9 80.4 79.9 80.4 79.9 80.4 79.9 80.4 79.9 80.4 83.0 79.9 80.4 79.9 83.4 79.9 80.4 79.9 86.4 79.9 86.4 63.J 78.4 78.9 80001 36.9 82.9 81.2 63.0 ΰĒ 83.C 82.6 83.0 83.D 83.U 83.0 93.0 83.3 83.0 7000| 37.0 81.9 83.2 83.6 83.7 63.7 85.7 83.7 83.7 83.7 83.7 £3.7 03.7 GE 60001 37.2 82.2 83.6 83.9 84.0 84.0 84.0 84.0 64.0 84.0 84.0 94.0 64.0 5000| 37.3 4500| 37.6 4000| 37.8 83.4 84.0 85.0 GE GE 84.8 85.3 85.1 85.7 85.2 85.8 65.2 85.8 85.2 85.5 85.2 85.8 R5.2 85.8 85.2 85.8 85.2 85.8 85.2 85.8 85.2 85.8 85.2 85.8 85.2 85.8 86.8 86.8 89.0 ĿΕ 86.3 80.7 86.8 86.8 86.0 b6•8 86.8 86.8 86.8 Ft.0 35001 38.0 87.8 86.1 88.0 98.0 88.0 0.88 88.0 88.0 88.0 6.80 06.0 3000 1 38.1 87.6 89.2 89.9 20.0 90 - 1 yU.1 93.1 9... 25001 38.6 20001 38.8 18001 39.0 15001 39.2 90.6 91.3 92.0 G E G E 91.3 92.1 92.8 89.0 91.1 91.2 91.4 92.2 92.9 91.4 91.4 91.4 91.4 91.4 91.4 91.4 41.4 91.4 89.8 90.4 92.2 92.2 92.9 92.2 92.9 92.2 92.9 92.2 92.9 92.2 92.9 92.2 92.9 92.2 92.9 9...5 ίĘ 92.6 92.7 91.8 93.4 6E 94.0 94.2 94.3 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 12001 39.7 6E 92.6 45.8 95.8 95 B 95.8 95.8 95.8 95.8 45.8 45.0 1000| 39.2 900| 39.2 PuO| 39.2 93.7 93.8 93.6 95.6 95.8 96.1 96.4 96.7 97.2 96.9 97.1 97.7 97.2 97.4 98.0 97.4 97.8 98.3 97.4 97.8 98.3 97.4 97.8 98.3 97.4 97.6 U.E 97.4 C 7 . 4 96.4 97.8 98.3 97.8 98.3 98.3 90.3 98 . 3 90.5 7001 39.2 6001 39.2 93.9 6.E 96.4 97.2 97.7 98.1 98.4 98.8 98.9 06.9 91.2 96.4 98.3 98.1 99-11 99.0 99.0 99.1 99.1 99.1 99.1 99.1 6E 6E 99.0 99.0 99.1 5anl 39.2 96.8 96.8 97.6 98.1 98.1 99.7 94.7 99.8 99.9 99.7 94.2 98.7 99.8 99.8 99.8 99.8 4001 39.2 94.2 98.7 99.9 99.9 99.9 99.9 99.9 99.9 ьŧ 96.9 97.7 98.2 98.8 99.9 99.9 100.0 100.0 100.0 100.0 100.0 100.0 2001 39.2 96.9 91.7 99.1 49.9 94.2 98.8 99.9 39.9 100.0 100.0 100.0 190.0 100.0 166.0

99.1

99.9

99.9

100.0

99-9 100-0 100-0 100-0 100-0 100-0 100-0

TOTAL NUMBER OF OBSERVATIONS: 960

97.7

98.2

1601 32.2

01 39.2

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: SEP HOURS(LST): 1500-1700 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS GE GE GE VISIBILITY IN STATUTE MILES CFILING IN | GE | FEET | 10 6E 5 GE GF GE 2 1 1/2 1 1/4 GE 1 GE GŁ GΕ GE 5/16 Ł 3/4 5/8 1/2 1/4 NO CEIL | 28.9 63.G 63.4 63.4 63.4 61.7 65.1 63.1 63.4 63.4 63.4 63.4 63.4 63.4 £3.4 63.2 GF 20000[33.0 GE 18000[33.1 GE 16000[33.1 74 + 0 74 + 4 74 + 6 75.8 76.2 76.3 75.6 76.2 76.3 75.3 75.4 75.4 75.6 75.8 75.8 75.8 76.2 76.3 75.8 76.2 76.3 75.8 76.2 75.8 75.8 75.8 75.9 75.9 76.0 75.9 76.0 76.G 76.1 76.2 76.3 76.2 76.3 76.2 76.3 76.2 10.3 76.3 77.2 79.6 6E 12Capl 34.4 79.1 79.2 79.6 79.6 79.6 79.6 79.6 79.6 19.6 74.0 80.2 #2.u #2.3 87.3 82.7 100001 35.0 81.7 82.1 82.3 82.3 82.7 82.3 82.7 82.7 9000 | 35.1 8000 | 35.2 82.C 82.3 82.7 82.7 82.7 82.7 82.7 84.7 82.7 80.6 82.4 84.C 84.7 84.7 84.7 84.7 70001 35.3 85.4 85.4 85.4 F5.4 82.9 84.8 85.1 85.1 85.2 85.4 85.4 85.4 85.4 85.4 85.4 86.2 86.2 86.2 86.2 66.2 Ł 6 . . 86.G 86.2 6E 5000| 36.2 4000| 36.3 4000| 37.0 υE 87.4 87.7 87.7 87.7 87.7 87.7 85.1 87.C 87.3 87.3 87.7 87.7 67.7 87.7 88.2 67.7 85.7 87.7 87.9 95.1 88.2 90.4 88.2 90.4 υE 87.6 87.9 86.0 88.2 88.2 88.2 R8.2 88.2 88.2 90.4 90.4 90.4 90.4 93.4 90.4 89.6 98.2 90.4 6£ 90.1 90.4 90.4 91.3 91.3 30001 37.7 89.9 91.8 92.4 92.8 92.8 92.8 92.8 92.8 92.8 92.8 92.6 25001 38.1 20001 38.3 90.8 93.4 94.3 93.6 93.8 93.8 94.7 93.8 94.7 93.8 93.8 93.8 93.8 94.7 93.8 94.7 S F 92.7 93.3 93.3 üξ 94.4 18001 38.3 91.7 93.6 94.2 94.6 94.7 94.9 94.9 94.9 94.9 94.9 95.4 94.9 94.9 94.9 94.9 94.9 95.4 95.4 1'001 38.4 92.2 94.1 94.8 95.1 95.2 95.4 95.4 95.4 95.4 95.4 95.4 45.4 90.0 46.6 97.3 97.4 97.7 97.7 96.1 97.0 900| 38.4 800| 38.4 96.2 97.8 97.A 97.8 97.8 97.6 98.7 97.8 94.0 97.1 97.6 97.8 47.8 57.6 98.7 94.6 98.0 98.3 95.4 98.7 98 - 7 96.7 90.7 98.8 98.8 700 | 38.4 94.7 97.2 98.4 98.8 98.6 98.8 90.5 99.2 49.2 FOO! 38.4 97.6 99.2 99.2 99.2 99.2 (F 95.0 98.4 98.8 99.4 99.2 49.2 99.2 99.0 COD | 38.4 95.2 95.2 97.9 97.9 99.0 99.3 99.6 99.8 99.4 99.8 99.8 99.8 99.8 99.8 99.5 400 38.4 99.3 99.6 99.R 99.9 99.9 99.9 99.9 99.9 υE 99.0 99.9 99.9 υE 3001 38.4 95.2 97.9 99.3 99.6 99.8 99.9 100.0 100.0 100.0 100.0 100.0 106.4 100.0 2601 38.4 99.9 100.0 95.2 97.9 99.0 99.3 99.6 99.8 100.0 100.0 130.0 106.0 100.0 99.9 100.0 100.0 1.0.0 99.6 01 38.4 97.9 99.0 99.3 99.9 99.9 99.9 100.0 lng.g 100.0 100.0 100.0 100.0 υE 95.2 99.8

PERCENTAGE FREWDENCY OF OCCURRENCE OF CETALING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

TATEON NUMBER - TOREGE STATION NAME. MCCONNELL AFR NO

		_		STATIO	ON NAME:							MONTH	OF REC	HOURS	(LST):	1800-20	CC
	LIti6		• • • • • • • •		• • • • • • • •	• • • • • •	• • • • • • •			IN STATE			••••		• • • • • • •	• • • • • •	• • • • • • • • • •
1		GŁ	GE	υE	ĿΕ	GE	GF	GŁ	G.E	0 f	6E -	G.E	GF	GÉ	GΕ	68	_ل و
-	ET Ì	10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5 / 8	1/2	5/16	1/4	J
٠.,																	
N 0	CEIL I	29.2	65.9	66.7	67.0	67.1	67.2	67.2	67.2	61.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2
GE	zurdel	33.4	76.8	77.7	78.0	78.1	78.2	78.2	78.2	78.2	78.2	79.2	78.2	78 - 2	78.2	76.2	70.2
i√E	166601	33.4	76.9	77.e	78.1	78.2	78.3	18.3	78.3	76.3	78.3	78.3	78 . 3	78.3	78.3	78.3	78.3
υE	160001	33.4	77.2	78.1	76.4	78.6	78.7	78.7	78.7	76.7	78.7	79.7	78.7	78.7	76.7	7 F - 7	70.7
G E	140001	33.7	77.8	78.7	79.0	79.1	74.2	79.2	79.2	74.2	79.2	79.2	19.2	79.2	79.2	79.2	74.2
∪ F	120001	35.0	80.6	81.4	81.8	81.9	82.0	0.58	82.0	37.0	82.0	62.D	82.0	82.0	82.0	82.0	H2.L
f	iarobl	35, R	83.2	84.1	84.4	84.6	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	94.7	84.7	F4.7
G.F	90001		84.6	85.4	85.8	85.9	86.0	86.0	86.0	86.0	96.0	85.0	86.0	56.9	ن ، ي م	56.0	P L . U
L E	81001		97.L	67.9	88.2	88.3	38.4	88.4	88.4	88.4	88.4	88.4	88.4	89.4	68.4	58.4	40.4
GE	75761		97.4	88.4	88.0	89.9	34.0	89.0	89.0	89.0	89.C	89.0	89 · u	89.0	#9.U	a4.0	M9.3
i. E	engol		P7.8	88 • B	99.1	89.2	85.3	69.3	89.3	69.3	69.3	89.3	89.3	89.3	89.3	59.3	89.3
01	0.001	,,,,		0., 0.,	, , , ,	0 / • 1	.,,,	0,0,		0.05							
o F	50001	16 6	88.9	90.0	96.3	90.4	96.6	90.6	93.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	40.6
51	4+30		89.2	90.3	96.7	90.6	90.9	90.9	9(].9	90.9	90.9	90.9	90.9	93.9	93.9	90.9	40.9
G E	40001		90.1	91.4	91.9	92.0	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	97.1	92.1	9 1
51	36001		91.3	92.3	71.7	92.9	93.0	93.0	93.5	93.0	93.0	93.0	93.0	93.0	93.3	13.3	93.0
ű E	30001		91.6	93.3	93.6	93.9	94.0	93.0	94.1	94.1	94.1	94.1	94.1	94.1	74.1	94.1	44.1
u t	36 50 1	3/•1	41.0	* > • 3	43.0	73.7	74.0	74.5	74.1	74.1	74.1	74.1	44.1	,4.1	,,,,	7	
							0. 3			n., *	24.3	94.3	94.3	94_3	74. 7		
o t	25001		92.6	93.6	94.0	94.1	94.2	94.2	94.3 95.0	94.3 95.0	95.0	94.0	95.0	95.0	95.3	94.3 95.0	9 4 a . 4 5 a c.
GE	2001		92 • 1	94.2	94.7	94.8	94.9	94.9		95.2	95.2	95.2	95.2	95.2	95.2	95.2	45.0
GF	16001		92.9	94.4	94.9	95.0	95.1	95.1	95.2								
٥Ē	1,001		93.1	94.7	95.1	95.2	95.3	95.3	95.4	95.4	95.6	9. • 6	95.6	95.6	95.6	¥5.6	45.0
G.E	1700	37.3	94.2	95.8	96.3	96.4	96.6	96.6	96.7	96.7	96.8	96.8	96.8	76.8	96.8	+6.8	9 L + S
			_	_												,	
υf	tunat		94.6	86 - 1	96.7	96.8	96.9	96.9	97 • U	97.G	97.1	97.1	97.1	97.1	97.1	• ? • }	57.1
ı, E		37.3	94.8	96.6	97.1	91.2	97.3	97.3	97.4	97.4	97.6	97.6	97.6	97.6	97.6	+7.6	.7.6
G.E.		37.3	95.1	46.4	97.6	97.A	97.9	97.9	98.0	98.0	1.80	98.1	98 • 1	98.1	66.1	75.1	40.1
() F		37.3	95 • 3	97.1	91.8	94.1	96.2	98 • 2	98.3	98.3	98.4	90.4	98 • 4	48.4	98.4	18.4	96.4
GE	1001	37.3	95.3	97.1	91.9	98.4	98.6	98.6	90.7	98.7	8.89	98.8	98.0	98.8	98.0	, R . H	٠٠.٠
				_									5.0.				
G E		51.3	95.4	97.2	90.1	48.9	99.0	99.0	99.1	99.1	99.2	99.2	99.2	39.2	34.5	9.9.7	
GE		37.3	95.4	97.2	98.1	48.9	99.0	99 • 7	99.1	99.3	99.4	99.6	99.6	99.6	24.6	10.6	99.6
6 F		37.3	95.6	97.3	90.2	99.0	39-1	99.3	99.7	99.7	99.8	100.0	100.0	130.0	100.0	1 - n • 0	11.0.0
6F		37.3	95.6	97.3	90.2	99.0	99.1	99.3	99.7	99.7	99.8	100.0	100 • 0	100.0	100.0	100.0	100.0
ŭ€.	1001	37.3	95 • 6	97.3	95.2	99.0	99.1	99.3	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	1.0.0
GΕ	0.1	37.3	95.6	97.5	90.2	99.0	99.1	99.3	99.7	99.7	99.8	190.0	100.0	100-0	193.0	1.0.0	100.0

TOTAL NUMBER OF ORSERVATIONS:

o c

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CF LING VFRSUS VISIBILITY FROM HOURLY OBSERVATIONS

TATI	ON NO	JMBER:	724505	STATIO								MONTH	OF REC	HOURS	(LSI):	2
EILI	NG	• • • • • •	• • • • • • • •	•••••	• • • • • • •	•••••	• • • • • • • •		BILITY					• • • • • • •	• • • • • • •	•
IN	1		GE	GE	6E	GE	GE	GE	GE	G E	GE	GE	GE	GE	GE	
FEET	-	10	6	5	4	3	2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	
• • • •	••••	• • • • •	• • • • • • •	•••••	• • • • • • •	•••••	• • • • • • •	• • • • • •	•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• •
O CE	11. 1	32.7	70.2	70.4	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	
E 20	1000	34.4	77.4	77.7	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	
E 18	1000	34.6	77.6	77.8	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	
E 16	0001	34.6	77.9	78.1	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	
E 14	0001	34.8	78.1	78.3	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	
E 12	C00	35.0	79.0	79.2	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79,8	
E 10	0001	35.4	81.3	81.6	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	87.1	62.1	
E 9	0001	35.4	81.6	81.8	82.3	82.3	82.3	82.3	82.3	62.3	82.3	87.3	82.3	82.3	82.3	
E 8	1000	36.3	85.1	85.3	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	
E 7	cool	36.3	85.4	85.8	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	A6.6	
E 61	0 00 (36.3	86.0	86.3	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	97.1	
£ 5	1 000	36.8	87.9	88.2	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89-1	89.1	89.1	89.1	
E 4	00	36.9	80.4	88.8	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	69.1	
		37.3	90.6	90.9	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.5	91.8	91.8	
		37.7	91.3	91 - 7	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	
E 3	0001	37.7	92.9	93.2	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	
E 2	5001	37.7	92.9	93.4	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	
E 21	0001	37.9	93.9	94.4	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	
		37.9	93.9	94.4	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	
		37.9	94.1	94.7	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	
E 1	700	37.9	94.9	95.4	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	
		37.9	95.4	96 • ()	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	
		37.9	95.6	96.3	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	
		37.9	96.1	96.9	97.8	98.0	98.0	98.0	98.0	98.0	98.C	90.0	98.U	98.0	98.0	
		37.9	96.1	96.9	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	
Ε	eno 1	37.9	96.2	97.D	97.9	98.6	98.6	98.8	98.8	98.8	98.8	99.8	98 • 8	98.8	98.8	
		37.9	96.2	97.1	98.0	99.0	99.0	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	
		37.9	96.3	97.2	96.1	99.2	99.3	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
		37.9	96.4	97.3	98.2	99.4	99.6	99.9	100.0	100.0	100.0	100.0	130.0	100.0	100.0	
		37.9	96.4	97.3	98.2	99.4	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
Ε	1001	37.9	96.4	97.3	98.2	99.4	99.6	99.9	100.0	100-0	100.0	100.0	100.0	100.0	100.0	
E	0	37.9	76.4	97.3	98.2	99.4	94.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	

scc

9.4

'-

9 - . 9 - . 9 - .

99

1. u 1. u 1. u

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFRIKS PERIOD OF RECORD: 77-86
MONTH: SEP HOURS(ES HOURS (LST): ALL VISIBILITY IN STATUTE MILES CEILING GE GE GE 4 3 2 1/2 IN | GE FEET | 10 GE GE GE GE 2 1 1/2 1 1/4 GΕ GL GE GF 1 5/16 C 6 5 1/4 5/8 1/2 1/4 NO CETE 1 29.9 64.5 65.3 65.7 65.9 66.0 66.0 66.1 66.1 66.2 66.2 66.2 66.3 56.3 66.3 tt.3 73.3 73.5 73.7 73.8 74.0 74.2 74.9 73.8 74.0 74.2 73.9 74.1 74.3 75.1 73.9 74.1 74.3 75.1 73.9 74.1 74.4 75.1 71.9 72.8 73.5 73.6 73.9 74.1 74.0 GE 200001 32.5 73.7 73.8 74.0 72.2 72.4 73.1 74.2 74.4 75.1 GE 187001 37.7 GE 167001 32.7 73.1 74.U 74.5 13.7 73.8 74.2 74.0 74.0 74.7 74.4 75.1 74.1 74.4 75.0 75.1 14r001 33.0 74.0 ⊎€ 120001 33.6 74.7 75.7 76.1 76.3 76.4 76.5 76.6 76.6 76.7 16.7 76.9 76.8 76.6 100001 34.1 90001 34.2 80001 34.6 79.0 79.5 82.3 83.1 77.2 77.7 PD.3 78 - 2 78 - 7 70.7 79.2 92.0 79.1 79.6 19.2 19.1 19.2 19.8 79.3 79.9 82.7 79.4 79.9 79.4 79.9 62.7 d:.6 79.3 79.8 19.4 19.9 74.4 74.4 8..7 79.5 19.9 79.5 82.3 81.5 82.4 82.5 82.5 82.7 82.7 82.7 82.6 70001 34.8 90.9 82.8 83.1 83.2 83.3 93.4 83.5 83.5 e3.5 83.0 60001 34.9 61.5 8 3 . 4 83.7 83.5 A4.1 ωE 84.0 84.U 84.1 84.1 84.1 24.2 50001 35.3 45001 35.5 83.0 83.7 85.3 85.8 85.0 85.7 87.5 85.3 86.0 87.8 88.5 85.6 86.5 85.8 86.5 88.3 85.6 86.5 88.3 85.8 86.5 88.3 85.8 86.6 88.3 85.4 85.5 85.7 85.B 86.1 87.8 88.5 86.5 86.2 86.4 86.4 86.6 88.7 UF 4rnn1 36.0 86.7 вя•2 88•Я R8., 50.3 89.0 86.1 35001 36.1 86.1 88.8 90.8 GE 30001 36.3 A7.3 88.9 8 5 . 8 90.2 96.3 90.5 93.6 90.7 90.7 90.9 90.4 93.9 90.9 96.9 91.5 97.4 97.8 93.7 91.5 92.4 92.8 91.6 92.5 92.8 93.7 G.E 25001 36.4 97.9 89.6 96.5 40.9 91.6 91.2 91.3 91.4 92.3 91.4 91.5 91.5 91.6 2000 | 36.6 1900 | 36.7 1500 | 36.7 90.4 92.4 92.8 91.4 91.9 92.4 üΕ 88.7 89.1 91.8 92.4 92.6 93.6 92.8 ij E G E 92.2 92.6 89.9 93.2 91.6 92.6 93.1 93.5 93.7 93.7 93.7 12001 36.8 94.5 10001 36.8 93.5 95.1 95.4 95.8 96.5 95.9 96.6 91.6 94.6 95.2 95.6 96.3 96.8 95.6 95.7 96.0 96.1 96.8 97.4 96.3 97.3 97.6 91.8 93.6 94.3 94.9 95.4 94.2 96.3 ſ.F 90-1 36.8 96.0 96.2 96.2 96.3 96.3 G.F 8G0 | 36.8 91.5 91.U 97.6 97.1 96.8 97.3 97.6 7001 36. A 92.3 94.5 95.6 96.6 97.0 97.6 97.6 GE €331 36.8 92.5 94.€ 96.1 97.1 97.3 97.6 98.0 96.1 98.2 98.2 98.2 98.2 96.2 1.39 4.5 4.84 4.84 98.5 99.0 99.3 99.3 98.7 99.2 99.6 99.7 98.8 99.3 99.7 99.8 Sun 1 36.9 92.7 95.5 96.4 97.6 97.8 98.6 98.8 98.8 98.8 98.9 60.5 400 | 36.9 300 | 36.9 92.8 95.2 97.9 96.1 96.3 96.3 99.3 99.7 99.8 99.4 99.4 99.4 44.4 96.6 ſ.F 96.7 98.0 98.1 99.4 99.7 99.8 99.8 2001 36.8 95.2 99.8 92.8 96.7 1601 36.8 49.5 99.7 99.9 150.0 100.0

99.5

99.3

99.7

99.8

99.9

99.9 100.0 1(.0

99.9

TOTAL NUMBER OF DESERVATIONS: 1200

92.6

95.2

96.7

98.1

98.3

98.9

01 36.8

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

{ IL 1 % b	• • •		•••••		• • • • • • •		• • • • • • •			IN STATU			• • • • • • •	• • • • • • •	• • • • • •		• • • • • • •
IN	ı	SE	GE	GE	GΕ	GE	GE	GE	GE	GE	GE	GŁ	GΕ	GE	3.0	GE	GE
FEET		10	6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	Ü
• • • • • •	• • •	• • • • •	•••••	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •
ה כבונ	1	55.2	65.1	65.1	65.2	65.5	65.6	65.6	65.8	65.8	65 • 8	65.8	65.8	65.8	65.8	65.8	66.0
20000	1	36.1	68.9	69.0	69.1	69.5	69.6	69.6	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	70.0
19500	١į.	36.3	69.1	69.2	69.4	69.7	69.8	69.8	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	76.2
f 16000	٦į	36.5	69.5	69.6	69.7	70.0	70.1	70.1	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	76.5
E Lando	11.	56.6	7G • C	70.1	70.2	70.5	70.6	70.6	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9	71.1
E 12007	11	36.9	70.5	70.8	76.9	71.2	71.3	71.3	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.7
r ibron	: 1	37.3	72.2	72.4	72.5	72.8	72.9	72.9	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.3
E 9ndo			72.2	72.4	72.5	72.8	72.9	72.9	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.1	73.3
i andr			74.6	74.8	74.9	75.3	75.4	75.4	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6
1000	ni -	38.9	75.5	75.5	75.6	75.9	76.0	76.0	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.5
r brad	1	38.9	75.5	75.7	75.8	76.1	76.2	76.2	76.5	76.5	76.5	76.5	76.5	76.5	76.5	76.5	76.7
E Shac	1 :	4.61	77.7	78.1	78.2	78.5	78.6	78.6	78.8	78.8	78.8	79.8	78.8	78.8	78.6	78.6	79.0
4500			78.1	78.4	78.5	78.8	78.9	78.9	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.4
E 4000	1	39.9	79.1	79.5	79.6	0.08	80.1	1.08	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.5
F 3500	11	39.9	79.7	89.1	8 C + 2	80.6	80.8	80.9	81.0	81.0	81.0	81.0	81.0	81.0	91.0	61.0	61.2
3000	1.	59.9	91.0	81.4	81.6	82.0	82.2	82.2	82.4	82.4	92.4	87.4	82.4	82.4	82.4	82.4	82.6
E 2*00	11	40.0	81 - 7	82.6	82.8	83.3	83.4	83.4	83.7	83.7	83.7	83.7	83.7	83.7	83.7	63.7	83.9
2000			82.3	83.5	8 2 . 9	84.5	84.6	84.6	84.8	84.8	84.8	84.9	84.9	84.9	84.9	84.9	85.2
1800			82.4	83.7	84.0	84.6	84.7	84.7	84.9	84.9	84.9	85.1	85.1	85.1	85.1	85.1	85.3
E 1°00	1	10.9	83.7	84.9	85.3	86.0	86.1	86.1	86.3	86.3	86.6	86.7	86.7	86.7	86.7	86.7	86.9
1200	1	40.9	84.1	85.8	86.1	87.0	87.1	87.1	87.3	67.3	87.5	87.6	87.6	87.6	87.6	87.6	87.8
1000	11 4	10.9	84.9	86.8	87.2	88.4	88.5	88.5	88.7	88.7	88.9	89.0	89.0	89.0	89.0	89.0	84.2
		9.04	85.2	87.3	87.8	89.2	89.5	89.6	89.8	89.8	90 • C	90 • I	90.1	90.1	90.1	90.1	96.3
PU0) 4	40.9	85.7	88.U	88.5	89.9	90.2	90.4	90.6	40.6	90.9	91.0	91.0	91.0	91.0	91.0	91.2
E 700) [4	0.9	86.0	88.5	89.0	90.4	90.8	91.0	91.2	91.2	91.4	91.5	91.5	91.5	91.5	91.5	91.7
600	1 4	+0.9	87.1	89.8	90.6	92.0	92.4	92.7	92.9	92.9	93.1	93.2	93.2	93.3	93.3	93.3	93.5
		10.9	87.4	90.3	91.6	93.4	93.9	94.5	95.2	95.3	95.5	95.6	95.6	95.7	95.7	95.7	95.9
		10.9	88.1	91.1	92.4	94.5	94.9	95.6	96.5	96.6	96.9	97.1	97.1	97.2	97.2	97.2	97.4
		10.9	88.2	91.2	92.5	94.9	95.5	96 • 1	97.U	97.1	97.4	97.6	97.6	97.7	97.7	97.8	96.1
E 200		10.9	88.2	91.2	92.5	95.1	95.6	96.5	97.5	97.6	98.5	98.9	98.9	99.0	99.0	99.1	99.4
							0.5 /	0/ 5	07.6	07 (99.1		
100) [4	10.9	88.2	91.2	92.5	95 • 1	95.6	96.5	97.5	97.6	98.5	98.9	98.9	99.0	49.1	99.2	94.5

PERCENTAGE FREQUENCY OF OCCURPENCE OF CFILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LST): 0300-0500 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS CEILING VISIBILITY IN STATUTE MILES IN | GE FEET | 10 GE GE GE GE GE GE 2 1 1/2 1 1/4 GE G E 5 / 8 GE GE GΕ GΕ 10 ъ 3 2 1/2 1/2 5/16 NO CEIL | 32.9 59.7 60.2 61.0 61.1 61.3 61.4 61.4 61.4 61.7 66.2 60.6 60-6 64.0 GE 200001 34.1 63.7 64.3 64.3 64.1 64.4 64.4 65.2 62.7 62.7 63.2 64.4 64.4 64.6 64.6 64.6 GE 18000| 34.1 63.2 63.8 64.0 64.4 64.7 65.1 GE 16000 34.1 63.2 63.2 63.7 64.4 64.7 65.1 65.1 65.4 65.4 65.5 6E 140001 34.2 63.4 64.0 64.0 64.4 64.5 64.7 64.8 65.2 65.2 65.8 63.8 65.1 66.1 GE 120001 34.3 64.3 64.3 64.8 66.1 66.3 69.0 66.9 67.1 69.8 66.9 67.1 69.8 GE 100001 35.1 GE 90001 35.1 67.1 67.2 67.5 65.7 66.2 66.5 66.6 66.8 66.9 67.1 69.4 66.8 67.0 67.3 67.3 67.4 67.7 65.9 67.1 69-1 6 E 80001 36.6 68.0 68.9 68.6 69.8 68.3 69.7 70.0 70.1 70.1 70.3 70.4 7000 | 36.6 68.9 GE 60001 37-0 69.0 69.7 69.7 70.1 70.2 70.4 70.5 70.8 70.9 70.9 70.9 71.1 71.2 71.6 71.8 73.0 72.0 73.2 75.7 76.8 72.2 73.3 72.4 73.5 72.5 73.7 74.4 5000| 37.1 4500| 37.4 70.3 71.3 71.5 72.7 72.4 73.5 71.9 74.4 75.4 72.0 72.5 72.9 73.3 74.5 74.9 76.0 75.4 76.5 75.8 76.5 77.1 76.0 77.1 76.1 77.2 76.6 77.6 GE 40001 37.7 73.8 75.2 75.5 75.8 16.9 76.9 76.9 35001 38.0 74.7 16.2 G.E. 76.6 79.2 30001 38.2 BU. u 2500| 38.3 2000| 38.5 1800| 38.6 77.3 78.7 78.9 80.0 81.4 81.8 80.3 81.7 82.2 80.3 81.7 82.2 80.5 81.9 82.4 81.1 82.5 82.9 GE 78.3 79.7 78.8 79.4 79.9 80.2 80.3 80.5 80.6 82.0 GE 8U.2 8U.5 80.8 81.2 81.0 81.3 81.6 81.7 82.2 80.0 GE 81-4 84.7 15001 39.2 81.6 82.4 83.0 83.2 83.5 83.7 83.9 84.0 84.0 84.0 84.2 94.2 K4.3 85.8 85.6 56.1 86.6 úΕ 12001 39.4 81.6 83.1 84.0 84.8 85.1 85.4 85.5 85.7 85.8 86.0 86.U 87.2 87.6 88.7 10001 86.3 86.9 87.6 86.9 87.4 87.1 87.6 87.2 87.8 87.4 88.1 87.5 88.2 900| 39.4 82.3 82.6 84.2 84.6 86.1 86.7 86 · 8 87 · 3 85.1 85.5 GΕ 85.3 86.2 86.2 87.4 88.5 89.8 88.7 89.5 GE 2001 39.5 83.1 88.2 88.3 88.7 88.9 88.9 99.0 700 | 39.5 89.4 90 0 90.0 90.0 6 E 83.4 8.8A GE 6001 39.6 90.8 91.6 91.7 92.0 92.3 92.3 92.3 92.5 92.7 93.1 95.5 96.7 98.2 94.5 94.5 95.7 94.5 95.7 97.2 94.7 95.9 97.4 94.7 95.9 97.4 88.4 92.8 93.8 94.0 94.3 95,4 94.9 5001 85.1 96.1 93.9 96.1 97.6 98.3 94.6 94.2 94.6 94.7 4001 39.6 3001 39.6 85.2 85.5 94.8 94.9 95.8 GΕ 89.1 91.0 94.1 96.5 97.2 97.2 97.6 97.B 98.1 46.8 G.F 2001 39.6 85.5 89.1 91.0 94.2 95.6 96.0 98.1 100 | 39.6 85.5 89.1 91.0 95.6 100.0 G F 01 39-6 85.5 89.1 91.0 94.2 94.7 96.2 96.9 98.0 98.2 98.2 98.4 98.4 98.6

PERCENTAGE FREGUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LST): U600-0600 VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 G E 5 / B GE 1/2 5/16 1/4 55.5 55.2 GE 200001 31.2 GE 180001 31.2 57.4 57.5 59.0 59.1 59.6 59.7 59.7 58.1 58.8 58.8 58.9 59.1 59.9 59.8 60.0 60.0 60.3 60.1 60.9 58.2 59.9 59.9 60.1 60.1 60.2 60.2 61.U 56.3 58.9 59.2 60.0 60.1 GE 160001 31.2 56.3 57.5 58.2 58.9 58.9 59.1 59.2 60.0 60 - 1 GE 140001 31.3 57.3 5A . 5 59.1 59.9 59.9 60.1 60.2 60.6 60.9 61.0 61.1 61.1 61.1 61.2 GE 120001 31.7 60.3 61.1 58.4 61.1 61.4 61.5 61.9 62.2 62.3 62.4 62.4 62.5 63.2 UE 10000| 32.6 GE 9000| 32.6 GE 8000| 34.0 62.9 63.0 65.1 60.9 62.3 64.8 64.9 67.0 64.9 65.1 67.1 64.9 65.1 67.1 64.9 65.1 67.1 63.7 63.8 64.1 64.2 64.5 64.6 64.7 64.8 65.2 63.7 64.0 65.8 65.9 GE 63.0 64.3 65.8 66.7 68.3 65.8 66.1 66.2 66.9 66.0 70001 34.5 65.4 66.1 66.9 67.2 67.7 68.0 6R.1 68.2 68.2 64.5 6 Duol 35.1 65.1 66.7 67.4 68.2 68.2 68.5 68.6 69.0 69.2 69.4 69.5 69.5 69.5 69.6 50001 35.5 45001 35.8 68.2 69.4 66.9 70.1 69.7 70.9 69.7 70.9 70.1 71.3 70.5 71.7 70.8 71.9 66.6 67.6 70.0 71.2 7n.9 72.0 71.0 72.2 74.3 74.9 71.0 72.2 74.3 71.0 71.1 71.8 73.0 G.F 40001 36.6 35001 36.6 69.7 71.4 72.2 72.9 73.0 73.3 73.4 73.9 74.1 74.7 74.2 74.8 74.3 71.9 70.1 ΰE 73.5 73.7 74.0 74.1 74.5 74.9 75.1 75 - K 30001 37.0 76.1 76.2 76.3 76.3 77.2 6 E 6 E 25001 37.2 20001 37.4 75.7 77.6 73.9 74.6 75.8 77.0 77.1 77.2 79.1 79.6 77.2 79.1 79.6 71.9 73.8 76.1 76.8 77.3 70.1 75.7 76.0 76.5 76.8 77.7 76.2 78 • 1 78 • 5 78.7 79.0 79.5 79.2 79.7 78.3 78.9 79.1 86.0 74.1 18001 37.4 78 - 1 78.7 79.4 79.6 AL.4 G E G E 15001 37.6 78.1 78.9 80.3 80.5 81.0 81.2 A1.8 81.9 82.0 82.0 92.0 84.4 1200 | 37.8 78.9 76.6 79.8 81.2 81.4 81.9 82.2 82.6 82.8 82.9 83.0 83.0 es. 4 6 E 6 E 6 E 82.5 83.3 85.2 84.2 85.1 87.0 8P.6 84.3 85.2 87.1 10001 38.n an.n 81.0 82.7 83.2 83.4 83.9 84.1 84.3 85.2 84 • 3 85 • 2 85.3 9001 38.0 80.6 81.6 83.5 85.5 84.3 84.7 84.9 86.9 84.1 86.0 8001 38.0 78.9 86.2 87.7 81.8 83.2 86.0 86.7 87.1 A7.2 87.3 P6.1 79.4 7001 38.0 82.9 84.5 86.6 86.9 87.5 88.2 88.5 88.7 88.8 88.9 89.0 84.8 ٥E 6001 38.0 79.6 83.2 89.8 91.0 5001 38-0 85.6 87.0 87.2 90.0 91.0 93.7 94.7 91.4 88.6 90.5 91.2 89.2 91.5 92.7 95.5 96.9 91.7 91.8 91.9 91.3 94.4 GE 4001 38.1 80.6 84.6 92.4 93.1 93.0 93.8 94.2 94.3 95.5 94.5 95.8 94.6 94.7 96.0 GE 3001 38.1 80.8 2001 38.1 80.8 84 . 6 87.2 91.3 92.0 93.2 93.9 95.2 96.0 96.5 96.6 96.8 97.1 97.2 1001 38.1 84.8 92.0 91.3 93.2 95.3 96.5 96.9 97.0 97.3 91.6 ¥7.8 99.5 GE 01 38.1 80.8 84.5 87.2 91.3 92.0 93.2 94.0 95.3 96.5 96.9 97.0 97.4 97.1 98.0 100.0

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
HONTH: OCT HOURS(LST): 0900-1100 STATION NUMPER: 724505 STATION NAME: MCCONNELL AFB KS HONTH: OCT VISIBILITY IN STATUTE MILES GE GE GE GE 2 1 1/2 1 1/4 1 CEILING. GE 02 3 2 1/2 GE GE GE 5 4 5E 1/4 FEET | GE 1 3/4 5/16 ь 5/8 1/2 0 NO CEIL | 31.8 54.1 54.9 55.2 55.5 55.7 55.8 56.0 56.0 56.1 56.1 56.2 56.2 56.2 56.5 62.6 61.1 61.2 62.2 62.3 62.4 62.4 62.5 62.4 62.5 62.4 62.5 GE 200001 33-2 60.2 61.9 62.2 60.3 61.9 62.D 62.3 62.4 62.5 62.6 o€ 160001 33.3 60.3 61.2 61.5 61.8 62.0 62.2 62.4 62.4 62.5 62.6 62.6 62.6 62.7 UE 140001 33.3 60.9 61.7 62.0 62.4 62.6 62.7 62.9 62.9 63.0 63.1 63.1 63.1 63.2 63.3 6E 120001 33.5 GE 100001 34.1 66.2 68.0 66.5 66.6 68.3 64.6 65.8 66.3 66.7 66.7 66.8 66.8 66.9 66.9 66.9 67.0 64.7 65.6 65.9 66.5 66.8 66.8 66.9 66.9 67.0 67.0 c٤ 90001 34.2 67.0 67.1 67.2 8000) 35.1 68.7 68.A 66.9 6 E 69.6 70001 35-8 67.4 68.3 68.6 68.9 69.1 69.2 69.5 69.6 69.7 69.9 60401 36.0 68.1 68.9 69.2 69.6 69.8 69.9 70.1 70.1 70.2 70.2 70.3 70.3 70.3 70.4 76.5 5000| 36.3 4500| 36.5 4000| 36.6 71.1 71.5 72.7 71.3 71.7 72.9 73.1 71.4 71.8 73.0 73.2 71.4 71.8 73.0 71.5 71.9 73.1 73.3 71.5 71.9 73.1 71.5 71.9 73.1 71.6 72.0 73.2 69.1 70.1 70.4 70.8 71.0 71.7 69.6 70.4 7U.9 71.9 71.4 72.2 70.5 71.5 71.2 6 E 72.9 73.1 3,001 36.8 73.2 70.6 73.3 6.F 30001 37.2 73.5 74.0 74.8 75.1 75.2 75.5 74.6 77.2 77.8 76.2 79.0 79.7 25601 37.6 73.5 75.1 77.7 76.0 76.2 79.0 76.3 79.1 76.3 79.1 79.8 76.5 79.2 79.9 76.6 79.4 GE GE 2500| 37.6 2000| 38.2 1800| 38.2 78.7 76.0 78.4 78.8 79.2 79.9 79.2 79.5 79.0 GΕ 76.6 78.4 79.4 79.5 79.7 79.8 79.9 60.0 80.1 15001 38.5 78.4 79.8 81.1 81.4 81.7 81.9 ωE 86.3 81.5 81.7 81.8 81.8 81.9 81.9 82.0 82.2 84.2 86.7 88.7 90.6 10001 38.9 86.0 86.2 86.5 86.5 86.6 86.6 86.7 86.7 86.8 86.9 88.8 85.4 88.5 68.5 90.3 88.6 90.5 88.6 90.5 86.9 G F 9001 38.9 83.0 86.2 87.3 88.0 88.3 88.7 88.7 Pu01 39.0 86.9 90.6 83.9 89.8 90.1 90.6 90.8 υŧ 88.1 69.1 91.6 GΕ 7001 39.0 87.7 90.1 91.7 91.8 91.9 6001 39.0 (, E 88.6 90.2 91.8 92.5 92.9 93.1 93.1 93.3 93.3 93.4 93.4 93.4 93.5 95.7 94.8 97.2 97.7 1001 37.0 4001 39.0 89.0 89.7 92.7 94.0 93.4 94.7 94.5 96.5 94.5 96.6 94.8 97.2 GΕ 85.3 85.6 91.0 94.1 94.7 97.0 94.8 97.2 95.6 91.7 97.7 85.6 89.8 91.6 96.8 97.4 6 E 300| 39.0 94.3 95.1 97.0 97.6 97.7 97.8 98.0 2001 39.0 94.4 95.3 96.1 98.9 99.1 94.4 97.3 98.5 98.6 98.7 49.5 GE 100 | 39.0

98.3

98.5

98.6

99.0

99.2

100.0

97.3

TOTAL NUMBER OF ORSERVATIONS: 930

85.6

89.9

01 39.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

																1200-14	
ILING		••••		• • • • • • •	••••	• • • • • •	• • • • • •	1214	BILITY	IN STAT	UTF MIL	ES.	•••••		•••••	• • • • • • •	•••••
IN EET	1 (10	GE 6	GE 5	4 4	GE 3	GE 2 1/2	S PE	6E 1 1/2		GE 1		GE 5/b	GE 1/2	GE 5/16	GE 1/4	GE D
CEIL			58.5	58.8	56.8	59.0	59.0	59.0	59.ن	59.0	59•0	59.0	59.0	59.0	59.0	59.0	59.0
20000			64.7	65.1	65.1	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
18000			64.9	65.3	65.3	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
16000			61.1	65.5	65.6	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9
14000			65.6	66.0	66.1	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5
12000	1 3 3	7.2	67.4	67.8	68.0	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	66.3
10000			69.5	69.9	76.0	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	74.3
9000			69.5	69.9	76.0	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	74.3
8000			71.1	71.5	71.6	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9
7000	1 38	8.7	71.6	72.0	72.2	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5
6000	36	8.7	71.9	72.4	72.5	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8
5000	1 38	8.7	72.5	72.9	73.1	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4
4500	11 36	8.7	72.5	72.9	73.1	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4
4000	1 39	9.2	73.3	73.8	74.1	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
3500	1 39	9.7	74.1	74.5	74.8	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2
3000	1 40	0.2	77.6	78.3	78.6	79.0	79.8	79.0	79.0	79.0	79.0	19.0	79.0	79.0	79.0	19.0	74.0
2500	1 45	9 • C	78.9	79.6	79.9	80.4	80 - 4	80.4	80.4	80.4	80.4	80.4	80.4	80.4	80.4	50.4	88.4
2000	4 1	1.0	80.9	81.6	81.9	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	62.5	82.5
1800	1 41	1.4	81.6	82.5	82.9	83.4	83.4	83.4	83.4	83.4	83.4	83,4	83.4	83.4	83.4	53.4	83.4
1500	1 41	1.5	83.7	84.7	85.5	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86 - 3	86.3	46.3	86.3
1200	1 43	1.9	86.1	87.4	88.2	89.1	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
1000	1 41	1.9	87.6	89.2	90.3	91.7	91.9	92.2	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
900	41	1.9	88.2	89.9	91.0	92.4	92.6	92.8	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
800	1 41	1.9	89.4	91.4	92.7	94.2	94.4	94.6	94.7	94.7	94.7	94.7	94 - 7	94.7	94.7	94.7	94.7
	1 41		99.4	91.7	93.1	94.6	94.8	95.1	95.2	95.2	95.3	95.3	95.3	95.3	95.3	95.3	95.3
600	4 1	1.9	90.8	93.2	94.8	96.5	96.7	96.9	97.2	97.2	97.3	97.3	97.3	97.3	97.3	97.3	97.3
	1 41		91.2	93.9	95.5	97.3	97.5	98.0	98.4	98.4	98.5	98.5	98.5	98.5	98.5	98.5	98.5
400	1 41	1.7	91.2	94.1	95.7	97.7	98.0	98.5	99.2	99.2	99.5	99.5	99.5	99.5	99.5	99.5	99.5
	1 41	1.9	91.3	94.2	95.8	98.0	96.2	98.7	99.5	99.5	99.9	99.9	99.9	99.9	99.9	99.9	94.9
	1 41		91.3	94.2	95.8	98.0	98.2	98 - 7	99.6	99.6	100.0	100.0	100.0	100.0	100.0	100.0	106.0
100	1 41	1.9	91.3	94.2	95.8	98.0	98.2	98 • 7	99.6	99.6	100.0	100.0	100-0	100.0	100.0	190.0	100.0
0	1 41	1 0	91.3	94.2	95.8	98.0	98.2	98.7	99.6			100.0					

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VFRSUS VISIBILITY FROM HOUPLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LST): 1500-1700 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES

GE GE GE GE GE GE GE GE

5 4 3 2 1/2 2 1 1/2 1 1/4 1 3/4 CEILING IN 1 GE GE FEET 1 10 6 GE 1/4 5/8 1/2 5/16 O 59.6 NO CEIL | 32.8 59.5 59.5 54.5 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 59.6 68.7 GE 200001 36.2 GE 180001 36.3 68.2 68.5 68.5 68.7 68.7 68.7 68.7 68.7 68.8 68.7 68.8 68.7 68.7 68.7 66.7 68.8 69.0 69.7 68.8 69.0 69.7 68.3 68.6 68.6 68.8 68.8 68.8 GE 160001 36.3 GE 140001 36.5 68 • 5 69 • 0 68 • 8 69 • 5 66.8 69.0 69.7 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.7 69.5 69.7 69.7 69.7 69.7 69.7 69.7 69.7 120001 36.9 70.3 70.8 71.1 71.1 71.1 71.1 71.1 71.1 71.1 71.1 71.1 10000| 37.6 9000| 37.7 8000| 38.1 73.4 73.8 74.7 75.4 73.8 74.1 73.8 74.1 73.8 74.1 73 · 8 74 · 1 73.4 73.8 73.8 74.1 72.8 73.0 74.1 74.1 G.F 74.1 74.1 74.1 74.1 74.1 74.7 75.1 75.1 75.2 75.2 75.2 70001 38-4 75.4 75.7 75.7 75.8 75.8 75.8 75.8 75.8 75.8 75.9 75.8 75.8 75.8 74.8 75.6 76.6 60001 38.5 76.0 76.0 76.0 76.0 76.0 GF 75.9 76.0 76.0 76.0 76.0 75.7 75.9 76.9 77.1 17.0 17.2 SCOOL 38.8 77.0 77.0 77.0 77.0 77.0 77.0 77.0 76.7 76.8 77.2 77.2 77.2 78.1 77.2 78.1 77.2 78.1 4500| 38.8 77.1 77.2 77.2 4000 I 38.9 78.0 78.3 78.1 78.4 78.1 78.1 78.1 G E 76.8 78.0 76.1 3500| 39.0 3000 | 39.8 80.8 81.9 82.4 82.4 82.4 82.4 82.4 82.4 82.4 82.4 25001 39.9 20001 40.4 84.4 67.0 84.4 87.0 84.5 87.1 GE GE 82.7 85.1 83.9 84.0 84.3 84.4 87.0 84.4 87.0 84.5 87.1 84.5 87.1 84.5 87.1 84.5 87.1 84.5 87.1 86.9 87.5 87.6 18001 40.4 87.1 87.4 87.5 87.5 87.5 87.6 87.6 87.6 87.6 87.6 86.9 90.2 GE 15001 40.6 86.9 88.9 89.4 90.1 90.1 90.2 90.2 90.3 90.3 90.3 90.3 90.3 96.3 12001 40.9 92.6 93.3 GE 10001 40.9 91.2 91.3 91.9 93.2 93.3 93.3 89.0 93.2 93.3 93.4 94.9 95.9 93.4 94.9 96.0 92.0 93.4 93.4 93.5 95.1 93.5 95.1 6 E 900 | 40.9 89.6 93.3 93.5 93.5 93.5 93.5 94.9 96.0 95.1 95.1 FUCT 40.9 89.5 91.8 94.6 95.3 94 . 8 95.1 95.1 GE 700 | 40.9 95.6 96.0 96.1 97.8 98.0 6 E 600 40.9 91.1 96.9 98.0 98.0 98.0 98.0 99.U 99.4 99.6 GE FOO! 40.9 91.7 94.5 95.8 97.7 98.0 98.2 98.4 98.8 99.0 99.4 99.1 99.5 99.1 99-1 99.1 99.1 99.1 4001 40.9 2001 40.9 94.6 99.0 99.5 GĒ 96.0 99.4 91.8 99.4 99.9 GE 96.2 98.2 98.6 100.0 100.0 100.0 100.0 100.0 100.0 99.6 99.6 99.9 100.0 ĠΕ 2001 40.9 96.2 98.2 99.2 100.0 100.0 130.0 91.9 94.8 98.6 100.0 100.0 100.0 100.0 100.0

99.2

99.6

98.6

100.0 100.0 100.0

100.0 100.0 100.0

TOTAL NUMBER OF OBSERVATIONS: 93

91.9

96.2

98.2

01 40.9

ь€

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: OCT HOURS(LS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HOURS(LST): 1800-2000 VISIBILITY IN STATUTE MILES CEILING GE GE 3 2 1/2 GE GE GE 2 1 1/2 1 1/4 GE GE 1 3/4 IN 1 GE FEET 1 11 GE GE GE GE 5/8 1/2 5/16 1/4 0 64.6 NO CEIL | 35.1 65.1 65.2 65.4 65.4 65.4 65.4 65.4 65.4 65.4 65.4 65.4 65.4 65.4 65.4 72.4 72.7 72.7 73.4 71.9 72.3 12.2 12.5 72.4 72.7 72.4 72.7 72.4 72.7 12.4 12.7 72.4 72.7 72.4 72.7 72.4 72.7 72.4 72.7 72.4 72.7 72.4 72.7 72.4 72.7 6E 20000| 37.2 71.5 71.8 GE 180001 37.3 GE 160001 37.3 GE 140001 37.3 72.3 73.0 72.7 73.4 72.7 73.4 72.7 73.4 72.7 73.4 72.7 73.4 72.7 73.4 72.7 73.4 72.7 73.4 72•7 73•4 71.8 72.5 72.7 72.7 72.5 73.2 73.4 73.4 GE 120001 38.2 75.1 75.1 77.0 77.1 77.8 77.2 77.3 GE 100001 39.0 GE 80001 39.1 GE 80001 39.5 77.2 77.3 78.1 17.2 17.3 76.8 76.9 77.6 77.2 77.3 77.2 77.3 77.2 77.3 77.2 77.3 76.2 76.3 77.0 77.3 77.3 78.1 77.3 77.3 77.3 78.1 78.1 78.1 78.1 70.1 78.1 78.1 70001 39.5 77.7 78.5 78.7 78.9 78.9 78.9 78.9 78.9 78.9 78.9 78.9 7A.9 74.0 78-9 7 K - 9 79.0 60001 39.5 79.0 79.0 79.0 79 . U GE 78.6 78.8 79.0 50001 40.0 18.8 79.6 79.8 79.8 80.0 80.0 80.0 80.0 80.0 80.0 80.0 80.2 80.0 80.0 80.0 80.0 84.0 45001 40.0 40001 40.2 78 - 8 80 - 3 80.0 80.2 80.2 80.2 80.2 80.2 80.2 80.2 80.2 90.2 60.2 80.2 G.F 81.4 81.6 82.9 81.8 81.8 81.8 81.8 81.8 81.8 81.8 81.8 81.8 81.8 61.8 3500 | 40.3 81.2 GΕ 83.1 83.1 83.1 83.1 30001 40.5 84.2 84.7 84.7 84.7 84.7 84.7 84.7 2500| 40.8 2000| 41.0 1800| 41.0 1500| 41.2 83.7 85.5 85.4 87.4 87.6 86.0 86.1 86.1 86.1 86.1 88.4 86.1 88.4 86.1 88.4 86.1 86.1 88.4 86.1 88.4 86.1 GE B 7.6 38.4 80.4 88.3 88.3 88.4 88.4 88.4 88.6 89.6 88.6 88.6 88.6 85.7 87.8 88.5 88.5 88.6 88.6 88.6 48.6 88 - 6 GΕ 86.3 88.6 88.9 89.8 89.8 89.9 89.9 89.9 89.9 89.9 90.6 10001 41.3 93.3 93.3 93.3 93.3 93.3 93.3 93.2 93.3 93.3 6 E 89.1 91.6 91.9 93.1 GE 900| 41.3 800| 41.3 89.6 92.0 92.6 92.4 93.9 94.0 94.1 94.1 94.7 94.1 94.1 94.7 94.1 94.1 94.7 94.1 94.1 94.1 94.1 700 | 41.3 90.4 93.2 93.7 95.7 96.5 96.5 96.5 96.5 96.5 96.5 96.5 96.5 97.4 97.4 G.E 97.4 97.4 AUD1 41.3 90.9 93.7 94.3 96.2 96.6 97.1 97.4 97.4 500 | 41.3 93.9 94.5 96.7 97.6 97.5 97.8 97.8 99.0 97.8 97.8 97.A 97.A 97.8 97.8 99.1 99.1 99.1 99.1 99.1 99.1 400| 41.3 99.1 91.2 94.6 95.1 95.2 98.0 98.3 98.9 99.2 99.4 6E 94.1 98.6 99.4 99.6 99.6 99.8 98.0 99.5 99.6 99.6 99.6 99.6 99.7 99.8 99.8 2001 41.3 91.4 99.1 99.8 98.4 99.0 6E 94.4 100.0 100.0 100.0 99.6 01 41.3 99.9 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 91.4 94.4 95.2 98.1 98.4 99.0 99.4

TOTAL NUMBER OF ORSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

CTATION NUMBER. TOURISE CLATION NAME. MCCONNELL

STATION I	NUMBER:	724505	S1411	ON NAME:	MCCO	NNELL A	FB KS				PERIOD	OF REC		-86 (LST): .	210N~23	nn
														• • • • • • •	• • • • • •	
EILING									IN STAT							
	GŁ	GΕ	GE	GE	GE	GE	GE	ĿΕ	GE	GE	GE	GE	GE	GĘ	₽ .	ĿΕ
	10	6	5	4		2 1/2	_	1 1/2		1	3/4	5/8	1/2	5/16	1/4	U
			•••••	• • • • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •	•••••		•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • •	
O CEIL	36.5	67.1	67.4	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	66.1
E 200001	27 /	71.5	71.6	12.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.5
E 18000		71.8	72.2	72-5	72.5	72.5	72.5	72.5	12.5	72.5	72.5	72.5	72.5	72.5	72.5	72.8
£ 16000		72.2	72.5	72.6	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	73.1
E 14000		72.2	72.5	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	73.1
E 12000		73.0	73.3	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	74.0
t 120001	71.0	13.0	13.2	13.1	13.1	73.1	13.1	73.1	13.1	13.1	1341	73.7	13.1	13.1	13.1	, 4 . 0
£ 10000	38.6	75.2	75.5	75.8	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	76.2
E 9000	38.6	75.3	75.6	75.9	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.3
E 80001	39.5	76.7	77.0	77.3	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.7
E 7root	39.6	77.5	77.8	78-2	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.6
E 6000 (39.6	77.6	78.0	76.3	78.5	78.5	78.5	78.5	78.5	78.5	7R.5	78.5	78.5	78.5	78.5	78.8
E Sena	39.7	78.6	79.1	79.7	19.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	86.2
	39.7	79.0	79.4	79.9	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.4
	40.2	80.3	80.6	81.2	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.7
	40.3	80.6	81.0	81.5	81.7	81.7	81.7	81.7	81.7	B1.7	81.7	81.7	81.7	81.7	81.7	82.0
	40.3	81.9	82.6	83.1	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.7
							•									
E 25001	40.6	84.3	85.2	86.0	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.8
E 2000	40.6	85 • 2	86.0	86.9	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.6
E 1800	40.6	85.2	86.0	86.9	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.6
E 1500	40.6	86.1	87.4	88.3	88 - 7	88.7	88.7	88.7	68.7	88.7	88.7	88.7	88.7	98.7	88.7	89.0
1200	40.6	87.2	88.7	89.7	90 . l	90 • 1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.4
10001	1 40.6	88.2	89.9	91.1	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.9
	40.6	88.7	90.5	91.7	92.4	92.4	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.8
	40.6	88.9	90.9	92.5	93.2	93.2	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.7
	40.6	89.0	91.2	92.9	94.0	94.0	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.6
	40.6	89.4	91.5	93.2	94.5	94.5	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	95.3
. 6001	40.0	07.7	7113	73.2	74.3	74.5	74.0	,,,,	7447	****	7747	77.7	77.7	74.7	,,,,	,,,,
	40.6	90.0	92.4	94.2	95.9	96.G	96.3	96.1	96.9	96.9	96.9	96.9	96.9	96.9	96.9	97.2
	40.6	90.3	92.7	94.6	96.5	96.6	97.1	97.6	97.8	97.8	98.0	98.U	98.0	98.0	98.0	96.3
	40.6	90.3	92.7	94.6	96.6	96.7	91.2	97.8	98.1	98.2	98.3	98.3	98.3	98.3	98.3	96.6
	40.6	90.3	92.9	94.8	96.9	97.1	97.6	98.3	98 • 5	98.6	99.1	99.1	99.4	99.5	99.5	99.8
E 100 l	40.6	90.3	92.9	94.8	96.9	97.1	97.6	98.3	98.5	98.9	99.2	99.2	99.5	99.6	99.6	99.9
E ni	40.6	90.3	92.9	94.8	96.9	97.1	97.6	98.3	98.5	98.4	99.2	99.2	99.5	99.6	99.6	106.0
																•••••

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIAILITY FROM HOLPLY OBSERVATIONS

STATION NUMBER: 724565 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86 MONTH: OCT HOURS (LST): CEILING VISIBILITY IN STATUTE MILES GE GE IN | GE FEET | 10 GE GE GE 5 GE GE GE 2 1 1/2 1 1/4 GE 1 GE GE GE G.F G.F 6E 4 3 2 1/2 10 3/4 5/16 1/4 8 5/8 1/2 NO CETE 1 33.5 60.1 60.5 60.7 61.0 61.0 61.3 61.3 61.4 61.3 61.3 61.6 GE 200001 35.3 GE 180001 35.4 GE 160001 35.4 66.9 66.0 66.7 66.9 65.5 66.2 66.5 66.8 65.7 66.3 66.5 66.7 66.9 66.7 66.8 66.9 67.0 67.0 67.2 67.0 67.2 67.1 67.2 67.1 67.1 67.3 67.1 67.4 67.6 67.B 67.9 GE 140001 35.5 66.4 66.9 67.1 67.4 67.5 67.6 67.7 67.8 67.A 67.8 67.8 66.1 68.7 68.7 GE 120001 35.8 69.0 GE 100001 36.5 GE 90001 36.6 GE 80001 37.5 69.5 69.7 71.3 70.9 71.0 72.7 73.5 70.2 70.4 70.7 70.8 71.0 71.0 71 - 1 71.1 71.2 71.2 71.2 71.4 71.2 70.3 70.5 70.9 70.9 72.6 71.1 71.2 72.9 73.7 71.3 71.3 71.3 71.5 71.2 71.3 70001 37.7 73.0 73.5 74.0 73.6 68 73.7 GF 60001 37.9 72.5 73.4 74.2 74.5 50001 38.2 45001 38.3 75.2 75.7 GE GE 74.4 74.9 75.8 74.7 75.1 75.5 75.6 77.1 77.7 75.8 77.2 77.9 75.9 76.0 76.0 74.1 75.8 75.9 75.9 76.0 76.0 76.6 GE 4000| 38.7 75.5 76.3 77.0 77.2 77.3 77.4 77.4 77.4 77.4 77.4 77.5 77.7 6.5 35001 38.8 76.0 76.9 77.6 77.8 78.0 78.0 7 R . N 78.1 78.1 78.1 78.1 76.4 30001 39.1 79.0 GE 78.0 80.1 80.2 80.2 BD.3 60.4 80.4 80.6 80.3 2500| 39.4 2000| 39.6 1800| 39.7 80.8 82.7 83.1 81.5 83.4 83.8 81.6 83.5 83.9 81.7 83.6 84.0 81.8 83.7 84.1 81.9 83.8 84.2 6E 79.3 80.4 81.4 83.3 81.8 81.9 81.9 81.9 82.0 8D.9 81.2 83.7 84.1 83.9 82.6 83.7 84.2 84.2 84.2 84.5 ΰĒ 15001 40.0 85.9 **66.3** GF 12001 40.2 84.2 86.0 86.6 87.5 87.6 87.8 87.9 88.0 88.1 88.1 88.1 88.1 88.1 88.2 B6 . 4 89.6 90.4 91.7 1000| 40-2 87.9 88.5 89.6 89.5 90.4 91.7 89.7 90.6 89.7 90.6 96.8 G E G E 85.0 85.5 87.1 87.7 89.0 89.8 89.2 90.0 89.4 90.3 89 • 7 90 • 5 89.8 99.8 89.8 90.6 90.6 91.9 90.7 91.3 GΕ POD | 40.3 86.2 88.6 91.0 91.5 91.8 91.9 01.0 92.2 92.6 92.7 7001 40.3 89.2 90.3 91.9 92.8 92.9 93.0 93.0 93.1 93.1 93.1 93.3 υE 86.4 GE 5001 40.3 87.7 92.3 94.8 95.4 95.9 97.2 97.7 96.2 96.2 96.2 90.5 GE 90.7 95.8 96 . D 96.1 96.1 96.5 97.7 98.4 400 | 40.3 300 | 40.3 88.0 91.2 92.9 95.3 95.6 95.8 97.0 97.4 97.5 97.6 98.2 97.6 98.3 97.6 98.3 6 E 97.9 GE 98.6 2001 40.3 88.1 93.1 95.8 96.2 97.0 97.7 98.0 98.6 98.8 98.9 99.0 99.0 99.1 00.4 99.0 99.2 99.2 99.3 99.7 GE 1001 40.3 88.1 91.4 93.1 95.8 96.2 97.0 97.7 98.0 98.7 99 . n 99.4 100.0 GE 0 | 40.3 91.4 93.1 95.8 96.2 97.0 97.7 98.0 98.7 99.0 99.2 99.3 88 - 1 99.0

PERCENTAGE FREQUENCY OF OCCUMPENCE OF CEILING VERSUS VISIPILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
HONTH: NOV HOURS(LST): 0030-0200 VISIBILITY IN STATUTE MILES CEILING VISIBILITY IN STRUCTS

GE GE GE GE GE GE

3 2 1/2 2 1 1/2 1 1/4 1 3/4 IN | GE FEET | 10 GE 5 GE GE GΕ 4 6 5/8 1/2 5/16 1/4 (1) NO CEIL | 23.7 54.4 55.4 55.8 55.9 55.9 56.0 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.2 56.2 GE 200001 25.6 GE 180001 25.7 GE 160001 25.7 59.9 61.3 61.6 61.6 61.7 61.7 60.4 61.2 61.3 61.4 61.6 61.6 61.6 61.6 61.6 61.7 61.7 62.0 60.1 60.7 61.4 61.6 61.6 61.8 61.8 61.9 61.9 61.8 61.8 61.9 60.7 61.8 61.8 61.8 61.8 61.9 62.1 62.1 GE 140001 25.9 60.4 61.0 61.9 62.1 62.1 62.1 62.1 62.1 62.2 61.8 63.6 GE 12000 26.1 61.9 62.4 63.2 63.3 63.3 63.4 63.6 63.6 63.6 63.6 63.6 63.6 63.7 63.7 GE 10000| 26.9 GE 9000| 26.9 GE 8000| 27.3 65.7 65.9 67.3 63.8 64.0 64.6 65.4 65.7 67.1 65.4 65.7 67.1 65.8 65.8 67.2 65.7 65.9 67.3 65.7 65.9 67.3 65.7 65.9 67.3 65.7 65.9 67.3 65.3 65.7 65.9 67.3 65.6 65.9 66.0 66.0 65.4 66.2 67.4 GE 70001 28.0 66.9 67.7 66.4 68.6 68.6 68.7 68.8 68.8 68.8 68.8 68.8 68.8 68.8 68.9 60.9 69.4 69.4 60001 29.2 67.6 69.2 69.4 69.4 68.3 69.1 69.2 ЬE 5000 | 28.3 4500 | 28.7 4000 | 28.7 3500 | 29.4 GE GE 68.1 69.0 70.4 68.9 69.8 71.2 69.9 70.8 70.0 70.9 70 · 1 71 · 0 70.2 71.1 72.6 70.2 71.1 72.6 70.0 70.2 10.2 70.2 70.2 70.2 70.3 74.3 70.9 72.3 74.1 71.1 71.1 71.1 71.1 72.6 71.1 11.2 71.2 GΕ 72.2 72.3 74.1 72.4 74.3 74.3 74.3 30001 29.8 76.6 76.8 76.8 77.0 77.1 77.1 77.1 77.1 77.1 77.1 77.1 17.2 77.2 GE GE 25001 30.3 20001 30.7 76.3 77.7 79.U 80.9 79.0 80.9 79.0 80.9 79.0 80.9 79.0 80.9 19.3 79.0 79.1 81.0 77.2 79.0 AD . 9 8 G • 2 8 U • 8 80.6 81.1 80.9 80.6 80.8 £1.0 81.4 81.4 81.4 81.4 82.9 P1.4 82.9 81.e GE 18001 30.7 78.1 79.6 81.1 81.3 81.4 81.4 -1.6 79.6 81.6 P2.9 82.9 63.0 G€ 15001 30.9 82.2 62.6 82.6 83.0 12001 30.9 81.1 85.7 1000 30.9 84.3 84.7 85.7 87.1 87.8 88.9 87.3 88.0 89.2 87.4 88.1 89.4 87.7 88.3 89.7 87.8 88.4 89.8 82.U 87.1 87.8 H7.8 86.4 88.1 89.4 90.9 82.2 82.7 AB . 3 A9 . 7 88.3 P9.7 88.3 88.3 89.7 80.4 67.6 G€ PCD | 30.9 88.0 89.0 GΕ 700 | Ğξ 30.9 82.9 86.2 84.2 90.3 90.4 90.7 90.9 91.2 91.2 91.2 91.2 91.2 91.3 91.3 89.4 91.5 91.3 91.8 GE 600 L 31.0 83.1 86.4 90.8 90.9 91.1 91.8 91.8 91.8 91.8 41.9 41.9 92.4 93.1 93.6 92.6 93.3 93.8 93.2 94.4 95.1 93.8 95.1 96.1 94.3 95.8 97.1 5001 31-0 83.8 94.8 93.9 94.3 94 - 3 94.3 94.3 400 | 31.0 300 | 31.0 84.1 84.1 87.9 91.1 96.4 95.8 95.8 95.8 95.8 95.9 95.9 GE 96.9 97.1 97.9 88.1 96.9 GE 2001 31-0 84.1 91.3 93.6 93.8 95.1 96.1 98.2 96.7 1001 94. 9A . 7 99.0 49.2 94.7

96.1

95.1

97.6

96.9

98.2

98.2

98.7

99.0

TOTAL NUMBER OF OBSERVATIONS:

91.3

900

88.1

93.6

93.8

n1 31.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

ATH BENTHEN SENTICETORS

S T	ATION N	UMBER:	724505	STATIO	A NAME:	HCCG	NNELL AF	BKS				PERIOD	OF RECO	RD: 77	-86		
												HONTH	: NOV	HOURS	(LŠT): (300-05	LO
		• • • • • •		•••••	• • • • • • •	• • • • • •							• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • • • • • • •
	ILING IN I	GE	GE	GΕ	68	GE	GE	05	GE	IN STATI	GE	. 2 E	GE	GE	GE	GE	6E
	IN J		6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	0.0
												• • • • • • •	•			• • • • • •	
••		•••••							••••								
N O	CEIL I	23.0	53.0	54.9	55.6	56.0	56.0	56.3	56.3	56.3	56.4	56.4	56.4	56.4	56.4	56.6	56.6
6 E	200001	24.0	56.6	58.4	\$9.2	59.7	59.7	60.0	60.0	60.0	60.1	60.1	60.1	60 • 1	60.1	60.2	60.2
GΕ	180001	24.0	56.6	58 • 4	59.2	59.7	59.7	60.0	60.0	60.0	60.1	60.I	60.1	60 • 1	60.1	60.2	60.2
GE	160001	24.0	56.6	58.4	59.2	59.7	59.7	60.0	60.0	60.0	60.1	60.1	60.1	60 • 1	60.1	60.5	60.2
	140001		56.6	58.4	59.2	59.7	59.7	60.0	60.0	60.0	60.1	60.1	60.1	60.1	60.1	60.5	60.2
υE	120001	24.0	57.4	59.3	6 C - 1	60.6	60.6	60.9	60.9	60.9	61.0	61.0	61.0	61.0	61.0	61.1	61.1
	100001		59.4	61.3	62.2	62.7	62.7	63.0	63.0	63.0	63.1	63.1	63.1	63.1	63.1	63.2	63.2
6 E			59.4	61.3	62.2	62.7	62.7	63.0	63.0	63.0	63.1	63.1	63.1	63.1	63.1	63.2	63.2
GE			60.6	62.4	63.4	63.9	63.9	64.2	64.2	64.2	64.3	64.3	64.3	64 • 3	64.3	64.4	64.4
GE			61.4	63.3	64.3	64.8	64.8	65.1	65.1	65.1	65.2	65.2	65.2	65.2	65.2	65.3	65.3
ίE	60001	25.6	62.1	64.0	65.1	65.6	65.6	65.9	65.9	65.9	66.0	0.66	66.0	66.0	66.0	66.1	66.1
GE	50001	26.1	64 - 1	66.1	67.4	67.9	67.9	68.2	68.2	68.2	68.5	68.3	68.3	68. 7	68.3	68.4	60.4
GΕ	45001	26.3	65.0	67.0	68.3	68.8	68.8	69.1	69.1	69.1	69.2	69.2	69.2	69 • 2	69.2	69.3	64.3
G €	40001	26.6	66.2	68.2	69.6	70.0	76.0	70.3	70.3	70.3	70.4	70.4	70.4	70.4	70.4	70.6	76.6
GE	3500 (27.0	67.3	69.3	76.7	71.1	71.1	71.4	71.4	71.4	71.6	71.6	71.6	71.6	71.6	71.7	71.7
٥E	30001	27.0	68.1	70.1	71.4	71.9	71.9	72.4	72.4	72.4	72.6	72.6	12.6	12.6	72.6	72.7	77
3.6	25001	27.6	70.2	72.2	73.6	74.0	74.0	74.6	74.6	74.6	74.7	74.7	74.7	74.7	74.7	74.8	74.8
GE			71.7	73.A	75.1	75.6	75.6	76.1	76.1	76.1	76.2	75.2	76.2	76.2	76.2	76 - 3	76.3
GE	18001		72.6	74.7	76.0	76.4	76.4	77.0	77.0	77.0	77.1	77.1	77.1	77.1	77.1	77.2	11.3
GE	1 4 00 1	28.6	74.6	76.6	78.2	78.8	78.8	79.3	79.3	19.3	19.4	79.4	79.4	79.4	79.4	19.6	78.6
GE	12001	28.6	16.2	78.6	8 C - 1	80.7	AC.7	81.2	81.2	81.2	81.3	61.3	81.3	81.3	P1 + 3	al • 4	81.4
GE	10001	28.8	77.7	80.1	82.2	83.D	93.0	83.6	A3.6	83.6	84.0	84.0	841	84.0	84.0	04.1	F4.1
6 E	0001	29.1	78.9	81.6	83.7	84.6	84.6	85.1	85.1	85.1	R5.6	85.6	85.6	85.6	A5.6	65.7	95.7
GΕ	8601	29.1	80.0	83.6	86.0	86.9	87.0	87.6	87.7	67.7	88.1	88.1	88.1	88.1	A8 . 1	88.2	A6.2
GΕ	760 (29.1	80.6	34-1	86.7	87.6	87.7	88.3	88.4	88.4	9.84	98.9	88.9	88.9	A8.9	89.0	E9.0
GE	6001	29.1	80.9	84.8	87.9	89.1	99.2	89.9	90.1	90.2	90.7	90.7	90.7	90.7	90.7	4U*8	46.8
GE	5001	29.1	81.0	85.1	R8.4	90.3	90.1	91.3	91.7	91.8	92.2	97.2	92.2	92.2	92.2	92.3	92.3
ΰĒ		29.1	81.1	85.2	88.6	91.2	91.7	92.9	94.2	94.7	95.2	95.2	95.2	95.2	95.2	95.3	95.3
GE		29.1	81.1	85.3	88.8	91.8	92.4	94.1	95.7	96.1	96.7	96.7	96.7	97.0	97.0	^ * • 1	97.3
δE	2001	29.1	81.2	85.6	84.6	92.0	92.7	94.4	96.1	91.0	98.0	98.0	98.0	98.3	98.3	98.4	98.9
GE	1001	29.1	81.2	85 • 6	8 9 . 0	92.0	92.7	94.4	96.2	97.1	98.1	98.3	98.3	98.7	98.7	98.8	99.1
GE	n I	29.1	81.2	85.6	89.0	92.0	92.7	94.4	96.2	97.1	98.1	98.4	98.4	98.9	98.9	99.J	106.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

					• • • • • • •		• • • • • • •							• • • • • • •			• • • • • •
	LING								BILITY				_				
1		GE	GE	G E	6 E	GE	GE	GE	30	GE	GE	GE	Gε	GE	GE	0.E	6∙ F
_	_	10		5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	c/16	1/4	÷
•	• • • • •	• • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •		• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •
0	CEIL	20.4	45.6	47.1	48.7	50.0	50.0	50.3	50.4	50.4	50.4	5n.4	50.4	50.6	50.6	55.7	51.1
,	cere	200	73.0	****	40.7	30.0	30.0	30.3	30.4	30.4	30.4	20.7	70.4	30.0	30.0	3	31.1
	20000	21.4	49.2	50.9	52.6	53.9	53.9	54.2	54.3	54.3	54.3	54.3	54.3	54.4	54.4	54.7	55.2
	18000	21.4	49.2	50.9	52.6	53.9	53.9	54.2	54.3	54.3	54.3	54.3	54.3	54.4	54.4	54.7	55.2
Ε	16000	21.6	49.3	51.0	52.7	54.0	54.0	54.3	54.4	54.4	54.4	54.4	54.4	54.6	64.6	54 + 8	55.3
	14000	1.6	49.6	51.2	52.9	54.2	54.2	54.6	54.7	54.7	54.7	54.7	54.7	54.8	54.8	55.0	55.6
	12000	21.9	49.9	51.6	53.2	54.6	54.6	54.9	55.0	55.0	55.0	55.0	55.0	55.1	55.1	55.3	50.0
		22.4	51.4	53.3	55.0	56.4	56.4	56.8	56.9	56.9	56.9	56.9	56 • 9	57.0	57.0	57.2	51.9
Ē		22.4	51.4	53.3	55.0	56.4	56.	56.8	56.9	56.9	56.9	56.9	56.9	57.0	57.0	57.2	57.9
E		23.4	54.4	56 • 3	5 8 • 0	59.6	59.6	59.9	60.0	60.0	60.0	60.0	60.0	60 - 1	60.1	6C.3	61.0
		23.7	55.3	57.2	5 € • 9	60.4	60.4	60.8	60.9	60.9	60.9	60.9	60.9	61.0	61.0	61.2	61.9
-	6000	24.0	55.8	57.7	59.3	61.0	61.0	61.3	61.4	61.4	61.4	61.4	61.4	61.6	61.6	61.8	64
	scoo	24.6	57.4	59.4	61.1	63.0	63.0	63.3	63.4	63.4	63.4	63.4	63.4	63.6	63.6	63.4	64.4
		24.6	58.0	60.0	61.7	63.6	63.6	63.9	64.0	64.0	64.0	64.0	64.0	64.1	64 - 1	. 4 . 3	64.6
	4000	24.6	58.7	60.7	62.3	64.3	64.3	64.7	64.8	64.8	64.8	64.8	64.8	64.9	64.9	65.1	65.6
	3100	24.9	59.4	61.6	63.2	65.2	65.2	65.6	65.7	65.7	65.7	65.7	65.7	65.8	65.8	66.0	66.7
	30001	25.8	61.3	63.4	65.1	67.1	67.1	67.4	67.6	67.6	67.6	67.6	67.6	67.7	67.7	67.9	60.0
	35.01														•	10.	
		25.1 26.8	63.6 66.2	65.7 68.6	61.3 70.2	69.3	69.4 72.3	69.8 72.7	69.9 72.8	69.9 72.8	69.9 72.8	69.9 72.8	69.9 72.8	70.0 72.9	70.0 72.9	70.2 73.1	76.9 73.6
		26.9	67.1	69.6	71.4	73.4	73.6	73.9	74.0	74.0	74.0	74.0	74.0	74.1	74.1	74.3	75.5
		27.7	68.9	71.6	73.4	75.6	75.7	76.1	76.4	76.6	76.6	76.6	76.6	76.7	76.7	76.9	77.6
-		27.8	71.0	73.9	76.3	78.6	78.7	79.3	79.7	79.8	79.8	79.8	79.8	79.9	79.9	00.1	h U • B
	1100	2 ,		, , , ,	, 0.5		,	.,.,	,,,,,	,,,,	,,,,	. , . 0		, , , ,	, , ,	00.1	00.0
	1000	27.8	72.3	75.3	77.9	80.3	80.6	81.3	81.7	81.8	A1.8	81.8	81.6	81.9	91.9	82.1	82.0
	900	28.0	73.2	76.4	79.6	82.3	82.8	83.6	83.9	84.D	84.1	84.2	84.2	84.3	84.3	84.6	P.
	8001	28.0	74.7	78.3	81.7	85.2	85.9	86.9	87.2	87.3	87.6	87.7	87.7	87.8	87.8	88.U	60.7
Ξ		28.0	75.4	79.1	82.7	86.2	87.0	88.1	88.4	86.6	88.8	88.9	89.0	89.1	A9.1	59.3	96.0
	6001	28.0	76.1	79.8	83.4	87.1	88.0	89.3	89.8	90.0	90 • 2	90.3	90.4	90.6	9.00	4C.8	91.4
	Son I	28.0	76.3	80.1	83.8	87.8	88.8	90.3	91.2	91.4	91.7	91.9	92.0	92.1	92.1	42.3	93.0
		28.0	76.6	80.4	84.2	88.3	89.6	91.3	92.9	93.3	93.7	93.9	94.0	94.1	94.1	94.4	95.1
		29.0	76.7	80.6	84.8	88.9	90.3	92.2	94.1	94.7	95.3	95.6	95.7	95.9	95.9	96.2	91.0
		28.0	76.7	80.6	84.8	88.9	90.3	92.2	94.3	95.2	96.2	96.7	96.8	97.2	97.2	91.6	98.4
		28.0	76.7	80.6	84.8	88.9	90.3	92.2	94.3	95.3	96.3	96.9	97.0	97.6	97.6	98.0	98.9
			- •													•	
	0.1	28.0	76.7	80.6	84.8	88.9	90.3	92.2	94.3	95.3	96.3	96.9	97.0	97.6	97.6	98.1	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: NOV HOURS(LST): 09UD-110D STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES CEILING GE GE GE GE GE 2 1 1/2 1 1/4 IN | GE FEET | 10 3 2 1/2 5 5/8 4 1/2 1/4 U 6 1 3/4 5/16 NO CEIL | 21.2 47.2 48.6 49.1 49.6 49.6 49.7 49.8 49.8 49.8 49.8 49.8 49.8 49.8 49.9 GE 200001 23.3 53.4 54.8 55.7 56.1 56.2 56.3 56.7 56.6 56.6 56.9 56.6 56.6 56.7 56.7 56.6 56.6 56.6 GE 18000 | 23.4 GE 16000 | 23.4 53.8 55.1 56.9 57.0 57.0 56.0 56.4 56.6 56.9 56.9 56.9 56.9 56.7 57.6 56.9 57.8 56.4 56.9 57.8 56.9 57.8 56.9 56.9 56.0 56.6 56.9 14000| 23.4 56.0 57.9 56.9 57.4 GE 120001 23.6 55.0 56.6 57.9 58.0 58.1 58.3 58.3 58.3 58.3 58.4 56.4 10000| 24.3 58.6 59.1 59.4 60.0 60.1 60.7 60.3 56.9 57.4 59.9 60.3 60.3 60.3 60.3 60.4 60.3 60.3 9000| 24.4 8000| 25.0 7000| 25.8 GE 61.0 61.0 60.4 60.6 60.9 60.9 59.7 61.3 62.2 62.9 63.0 63.1 63.3 63.3 63.3 63.3 63.3 63.3 63.4 63.4 GE 60.8 62.4 63.3 64.0 64.3 64.1 64.2 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.6 64.6 64.9 60001 25.9 64.6 64.9 64.9 65.0 65.0 66.0 66.4 68.1 66.3 66.8 68.4 66.3 66.8 68.4 66.3 66.8 68.4 66.3 66.6 68.4 66.8 66.8 66.9 68.6 GE 50001 26.1 62.0 63.8 64.8 65.6 65.7 66.8 66.3 66.8 66.4 GE 4500 | 26.1 4000 | 26.6 62.2 64.2 65.2 66.0 67.7 66.1 66.9 66.9 68.4 68.4 68.6 3500 68.2 68.9 69.0 69.0 68.9 68.9 68.9 68.9 GE 30001 26.9 64.9 67.0 68.0 68.8 69.6 69.6 69.6 69.6 69.6 69.6 69.7 64.7 67.9 70.3 69.0 69.8 72.4 73.9 69.9 72.6 70.2 72.9 74.3 70.6 73.2 70.6 73.2 70 • 6 73 • 2 70.6 73.2 74.7 77.3 70.6 73.2 74.7 25001 27.3 65.8 68.0 70.6 73.2 70.6 73.2 70 · 7 70.7 GE 73.3 74.8 77.4 1800| 29.0 1500| 28.3 69.4 74.7 GF 71.8 73.1 74.0 74.7 74.7 74.7 74.7 74.8 GE 77.3 74.3 75.7 76.4 76.6 76.9 77.2 77.3 77.3 77.3 17.4 12001 6 E 1000| 28.7 80.7 80.8 79.0 81.7 82.1 82.1 82.1 82_1 87.2 82.2 82.1 82.1 83.7 85.1 G E G E 900| 28.7 75.8 79.2 81.1 83.0 84.2 84.1 85.7 84.8 84.8 84.8 84.6 86.3 84.8 84.8 84.9 79.8 86.4 76.2 84.4 86.3 86.3 86.4 GE 76.8 85.7 86.1 87.7 87.4 88.2 88.2 88.4 90.7 7001 28.7 80.9 86.9 88.2 88.2 88.3 88.3 88.4 6001 28.7 90.7 90.3 90.4 81.6 84.3 88.7 90.4 90.6 90.6 93.3 96.1 98.2 G E G E 5001 28.7 4001 28.7 77.8 77.9 82.4 82.7 85.4 85.9 88.3 89.0 88.9 90.2 91.2 91.7 93.1 93.0 95.3 93.2 95.8 93.2 95.9 93.2 96.0 93.3 96.1 93.4 96.2 93.4 96.2 3001 24.7 82.9 82.9 86.1 89.3 89.3 89.9 89.9 91.7 91.8 96.7 97.3 97.4 98.2 98.4 98.4 78.0 94.0 97.9 98.1 98.2 2001 28.7 94.4 98.8 99.0 99.4 78.0 99.2 99.4 99.2 78.0 98.3 99.1 99.6 GE 1001 28.7 82.9 89.3 98.9 99.9 100.0 01 28.7 78.0 86.1 98.3 98.9 91.8 94.4

TOTAL NUMBER OF OBSERVATIONS:

....

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

S T	ATION N	UMPER:	724505	STATIO	ON NAME:	MCCO	NNELL AI	BKS				PEP100 MONTH		ORD: 77- HOURS	-86 (LST): 1	1200-14	ro
		•••••	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • •	• • • • • • •						• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	•
	ILING									IN STATE							
		GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GΕ	GE	GE	GE	GE	0E _
	EET		6	5	4		2 1/2			1 1/4	1	3/4	5/8	1/2	5/16	1/4	G
• •	• • • • • •	•••••	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • •		•••••	• • • • • •	•••••	•••••		• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	•••••
NO	CETL 1	24.4	54.2	54.6	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7
11.5	200001	26.7	60.0	60.7	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	64.9
	180001		61.1	61.8	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
	160001		61.4	62.1	62.3	62.3	62.3	62.3	62.3	62.3	62.3	67.3	62.3	62.3	62.3	62.3	62.3
	140001		61.7	62.3	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
GΕ	120001	27.6	62.6	63.2	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
6 E	100001	28.1	63.9	64.6	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64 - 8	64.8	64.8	64.8	64.8
GΕ	90001	28.3	64.2	64.9	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.1
G E	80001	28.4	65.7	66.3	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6
GE	70001	29.0	67.3	68.0	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	66.3
6 E	60001	29.2	67.9	68.6	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	66.9
GE	50001		70.0	70.7	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.D	71.0	71.0	71.0
GE	4500 (29.9	70.0	70.8	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71-1
GΕ	4000		71.6	72.3	12.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	12.7	72.7
Ģ€	3500		71.8	72.6	72.9	72.9	73.0	73.0	73.0	73.0	73.0	73.0	73.D	73.0	73.0	73.0	73.0
G€	3000 [30.7	72.4	73.2	73.6	73.7	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8
ĢΕ	2500		73.7	74.4	74.8	74.9	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
3.0	2000		76.3	77.2	77.6	77.7	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8
GE	1000		77.2	78.1	78.6	78.7	78.8	78.8	78 · B	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8
GΕ	1500		80.0	81.0	81.7	81.8	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	61.9
GĒ	1200	32.1	82.0	85.3	84.1	84.6	84.7	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
GE	10001	32.3	83.4	84.9	85.7	86.6	86.7	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
GE		32.3	84.4	86.2	87.0	88.0	88.2	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4
GE		32.4	85.2	87.0	88.3	89.8	90.0	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
GE		32.4	85.4	87.6	89.4	91.1	91.6	91.9	91.9	92.2	92.2	92.2	92.2	92.2	92.2	92.2	94.2
υĒ		32.4	85.6	87.9	89.9	91.7	92.2	92.9	93.2	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6
																	•
GΕ	5001	32.4	85.7	88.0	90.0	92.2	92.8	93.7	94.9	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
ĞĒ		32.4	85.7	88 • C	90.0	92.6	93.1	94 . 3	96.0	97.1	97.3	97.4	97.4	97.4	97.6	97.8	97.8
Gε	300 [32.4	85.7	88.0	96.0	92.9	93.4	94.8	96.6	91.7	98.3	98.6	98.6	98.6	98.7	98.9	98.9
GĒ		32.4	85.7	88.0	90.0	92.9	93.4	94.8	96.9	98.1	99.0	99.3	99.3	99.3	99.4	99.7	99.7
GE	100	32.4	85.7	88.0	90.0	92.9	93.4	94.8	96.9	98.1	99.C	99.3	99.3	99.3	99.4	99.8	99.8
GΕ	01	32.4	85.7	88.0	90.0	92.9	93.4	94.8	96.9	98.1	99.0	99.3	99.3	99.3	99.4	99.8	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

5 1 /	ATION N	UMRER:	724505	STATI	ON NAME:	: MCC0	INNELL AI	FB KS				PERIOD MONTH	OF REC		-86 (LST):	1500-17	00
	L ING	•••••	•••••	• • • • • •	• • • • • • •	• • • • • •	•••••			IN STATE			• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •
		GE	GE	GΕ	GE	GΕ	39	GE	GE	GE GE	GE GE	GE	GF	GE	G€	GE	G€
FE		10	6	5	4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	ū
• • •	· • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	•••••	• • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • •		• • • • • •	•••••
N O	CEIL I	24.4	53.8	54.2	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3
GE	200001	28.1	62.2	63.1	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2
	180001		63.1	64.0	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64 • 1	64.1	64.1	64.1
	160001		63.3	64.2	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
	14000		63.4	64.3	64.4	64.4	64.4	64.4	64 - 4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
GE	12000	28.9	65.1	66.D	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1
GΕ	100001	29.8	66.6	67.4	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6
GΕ	90001	30.0	66.8	67.7	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.B	67.8
GE	80001	30.4	68.0	68.9	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.B	69.6
GE			68.9	69.8	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9
ĢΕ	60001	30.6	69-1	70.0	76.1	70 - 1	70.1	70.1	70-1	70.1	70.1	70.1	70.1	70.1	70.1	70-1	70.1
GE	50001	31.0	70.3	71.2	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71 - 3	71.3	71.3	71.3
GE	45001		70.9	71.8	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9
GE	40001	31.4	72.7	73.6	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
ĿΕ	35001	32.0	73.7	74.6	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7
6 E	3000	32.3	75.6	76.4	76.7	76.7	76.7	76.7	76.7	76.7	76 - 7	76.7	76.7	76.7	76.7	76.7	76.7
GE	25001	32.8	77.4	78.4	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	76.7
GE	20001		79.2	80.6	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	84.8
GE	10041	33.1	80.1	81.7	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9
GE	15001	33.3	81.9	83.6	84.0	84.3	84.3	84.3	84 - 3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3
GE	12001	33.3	83.0	84.9	85.6	86.0	86.0	86 • O	86.0	86.0	0.68	86.0	86.0	86 • D	86.0	86.0	86.0
ĠΕ	10001	33. 1	83.8	86.1	86.9	87.4	87.4	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
GE		33.3	84.3	87.1	88.1	88.7	89.0	89.3	89.6	89.6	89.6	89.7	69.7	89.7	89.7	89.7	89.7
GE	1004	33.3	84.6	87.6	89.0	89.7	90.0	90.3	90.8	90.9	90.9	91.0	91.0	91.0	91.0	91.0	91.0
ьE	700 [33.3	85.D	88.2	89.9	90.8	91.1	91.4	92.2	92.3	92 • 3	92.4	92.4	92.4	92.4	92.4	92.4
ĿΕ	4001	33.3	85.1	88.7	90.4	91.7	92.0	92.3	93.6	93.7	93.7	93.8	93.8	93.8	93.8	93.8	93.8
GE	5001	33.3	85.3	89.3	91.2	92.7	93.1	94.0	96 • 1	96.6	96.7	96.8	96.8	96.8	96.8	96.8	96.8
GE		33.3	85.3	89.3	91.2	92.7	93.1	94.1	96.7	97.6	97.9	98.1	98.1	98.1	98.1	98.1	98.1
GE	300	33.3	85.3	89.3	91.2	92.8	93.2	94.2	96.8	97.7	98.7	99.2	99.2	99.2	99.2	99.2	99.2
bΕ	200 [33.3	85 • 3	89.3	91.2	92.8	93.2	94.2	96.8	97.7	98.7	99.3	99.3	99.4	99.4	99.4	99.4
GE	1001	33.3	85.3	89.3	91.2	92.8	93.2	94.2	96.8	97.7	98.7	99.3	99.3	99.4	99.4	99.7	100.0
GE	01	33.3	85.3	89.3	91,2	92.8	93.2	94.2	96.8	97.7	98.7	99.3	99.3	99.4	99.4	99.7	100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERIOD OF RECORD: 77-86
MONTH: NOV HOURSILS HOURS(LST): 1800-2000 VISIBILITY IN STATUTE HILES •••••• CEILING 6 GE GE GE NO CEIL | 29.1 60.8 61.2 61.2 61.2 61.2 61.2 61.2 GE 20000| 30.4 GE 18000| 30.6 GE 16000| 30.6 66.9 66.9 66.2 66.9 66.9 66.9 66.9 66.9 66.9 66.9 66.9 56.9 66.4 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.1 67.6 67.1 67.1 67.1 140001 30.6 66.9 67.6 67.6 67.6 67.6 67.6 67.6 67.6 67.6 67.6 67.6 67.6 67.6 GE 120001 31.0 68 - 4 69.1 69.1 69.1 GE 100001 31.2 GE 90001 31.2 69.7 69.8 71.1 70.3 70.4 71.8 76.3 70.3 70.3 70.4 71.8 70.3 70.4 71.8 70.3 70.3 70.4 71.8 70.3 70.3 70.3 70.4 71.8 72.3 70.3 70.4 71.8 70.3 70.3 70.3 70.4 70.4 70.4 71.8 72.3 70.4 70.4 71.8 70.4 70.4 70.4 8000 L 31.3 71.8 71.8 70001 31.3 71.7 72.3 72.3 72.3 72.3 12.3 72.3 6C001 31.4 71.8 72.4 72.4 72.4 72.4 72.4 72.4 72.4 72.4 6 E 6 E 6 E 50001 31.8 45001 32.1 40001 32.1 73.1 73.7 75.1 73.8 74.4 75.9 73.8 74.4 75.9 77.3 73.8 74.4 75.9 77.3 73.8 74.4 75.9 73.8 74.4 75.9 77.3 73.8 74.4 75.9 77.3 73.8 74.4 15.9 77.3 73.8 74.4 75.9 77.3 73.8 74.4 75.9 77.3 73.8 74.4 75.9 71.3 73.8 74.4 75.9 77.3 73.8 74.4 75.9 77.3 74.4 74.4 75.9 75.9 3500 32.4 77.3 77.3 77.3 GE 30001 32.6 2500| 32.9 2000| 33.2 1600| 33.6 1500| 33.7 8D.4 82.4 82.9 81.4 83.7 84.2 81.8 84.2 64.8 81.8 84.2 81.8 81.8 84.2 84.8 81.8 84.2 84.8 81.8 84.2 81 · 8 84 · 2 81.8 84.2 84.8 81.8 84.2 81.8 84.2 84.8 84.2 84.8 84.2 84.2 G.F 84.8 84.8 84.8 84.8 84.8 84.8 84.8 6 E 85.4 83.6 84.9 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 86.7 85.6 86.7 85.6 85.6 GE 1700 | 33.7 86 - 7 86.7 86.7 86.7 86.7 86.7 86.7 1000| 33.7 900| 33.7 800| 33.7 G E 85.1 88.2 89.8 91.8 88.2 89.6 88 • 2 89 • 8 88.3 69.9 92.0 88.3 89.9 88.3 89.9 92.0 88.3 89.9 92.0 88.3 89.9 92.0 86.9 88.3 88.3 89.9 88.3 89.9 88.3 88.6 89.4 89.9 89.9 86 - 1 91.6 91.8 91.9 92.0 92.0 92.0 93.7 7001 33.7 GE 86.6 89.1 90.0 92.9 93.1 93.1 93.3 93.7 93.7 93.7 93.7 93.7 93.7 90.7 GΕ 93.8 94.1 94.3 95.0 95.0 95.0 95.0 95.0 95.0 95.0 95.0 6 E 6 E *00| 33.7 400| 33.7 300| 33.7 86.9 86.9 86.9 89.7 90.0 90.0 94.1 94.7 94.8 94.4 95.1 95.3 96.4 95.9 97.0 97.1 96.2 97.6 97.8 90.7 96.4 97.8 96.4 97.8 96.4 97.8 96.4 97.8 96.4 97.8 96.4 97.8 98.2 99.1 96.4 97.8 91.0 98.2 95.2 96.6 98.2 99.1 98.2 98.2 98.2 98.2 2001 33.7 91.0 90.0 94.9 97.4 98.2 98.8 98.9 98.9 99.1 99.1 90.0 6 F 1001 33.7 86.9 99.11 GE pl 33.7 90.0 98.2 98.9 99.0 99.0 99.2 99.2 99.4 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: NOV HOURS(LST): 2100-2300 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES

OF GE GE GE CEILING E GE GE 2 1 1/2 1 1/4 GE 4 GE IN (3 2 1/2 5/16 1/4 ō 10 6 1 3/4 5/8 1/2 NO CEIL 1 27.4 59.4 59.9 60.0 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 60.1 65.3 65.3 65.4 65.4 65.4 65.6 65.6 65.6 65.6 65.6 65.6 65.7 65.6 65.6 65.6 65.6 65.6 GE 20000 | 28.9 GE 18000 | 28.9 64.9 64.9 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.7 65.6 65.7 GE 160001 28.9 65.6 65.6 65.6 6E 140001 28.9 65.0 65.4 65.6 65.7 65.7 65.7 66.8 68.3 69.6 67.6 67.6 68.8 68.1 68.1 69.3 68.2 68.2 69.4 68.3 GE 100001 29.2 68.3 68.3 68.3 68.3 68.3 68.3 68.3 68.3 68.3 GE 90001 29.2 80001 29.7 68.3 68.3 68.3 68.3 68.3 68.3 69.6 68.3 68.3 68.3 68.3 66.3 69.6 69.6 70001 30.3 70.0 70.6 70.7 70.8 70.8 70.8 70.8 70.8 70.8 70.8 70.8 70.8 70 . B 70.8 7µ.8 GE 60001 30.9 70.7 71.2 71.3 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 5000| 31.2 4500| 31.6 4000| 31.6 72.9 73.3 74.9 72.9 73.3 74.9 72.1 72.4 74.0 72.9 73.3 74.9 72.9 73.3 72.9 73.3 72.9 73.3 74.9 72.9 73.3 74.9 G E G E 72.7 73.0 72.9 73.3 72.9 73.3 72.9 73.3 72.8 74.9 GE 74.6 74.8 74.9 76.1 74.9 74.9 74.9 74.9 74.9 76.1 76.1 76.1 76.1 76.1 76.1 76.1 GE 35001 31.9 75.0 75.8 76.1 76.1 76.1 76.1 78.7 30001 32-3 80.1 82.4 82.9 80.0 82.2 82.7 80.1 82.4 82.9 80 • 1 82 • 4 82 • 9 80.1 82.4 82.9 GE 25001 32.6 78.4 80.1 80.1 80.1 80.1 GE GE 2000| 32.8 1800| 33.0 80.6 81.0 82.0 82.4 82.4 82.4 82.9 82.4 82.9 82.9 82.4 82.9 82.4 82.9 82.4 82.4 82.9 GE 15001 33.0 81.7 83.6 84.1 84.6 84.6 84.6 84.6 84.6 84.6 84.6 84.6 84.6 84.6 84.6 86.2 86.2 86.2 GE 12001 33.1 82.7 86.1 86.2 GE GE GE 1000| 33.2 900| 33.2 800| 33.2 83.9 84.6 85.2 86.9 87.7 89.0 87.9 88.9 90.3 87.9 88.9 90.3 87.9 88.9 90.3 87.9 88.9 90.3 88.0 89.1 90.6 87.7 AR - O 88.0 AR.D 88.0 86.0 86.9 89.0 89.1 90.6 89.1 90.6 89.1 89.1 90.6 89.1 88.7 90.1 7001 33.2 85.9 88.9 90.0 GE GF 6001 33.3 92.9 93.0 93.1 93.2 93.2 95.3 96.9 97.7 95.1 96.7 97.2 97.3 95.3 95.3 96.9 95.3 96.9 G E 500| 33.3 95.0 95.1 96.7 95.2 96.8 95.3 96.9 95.3 94.1 95.1 95.4 96.9 4001 33.3 86.4 90.1 91.7 96.3 96.9 97.7 97.7 3001 33.3 86.4 90.3 91.9 96.8 97.2 97.4 97.7 97.7 97.6 98.0 98.3 98.6 98.6 98.6 96.6 G.F 2001 33.3 86.4 90.3 91.9 04.4 95.4 96.8 1001 33.3 GE 86.4 90.3 6 E 01 33-3 86.4 90.3 91.9 94.4 95.4 96.8 97.4 97.7 98.1 98.8 99.0 99.0 99.1 99.2 100.0

TOTAL NUMBER OF OBSERVATIONS:

900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CFILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

				• • • • • • •							MONTH	. 404		(LST):	ALL	
ILING							V 1 5 1	BILITY	IN STATE	UTE MIL	ES					
IN	GE	GE	GE	GE	GE	GE	GΕ	GE	GE	GE	GE	GE	GΕ	GE	G£	GE
EET	10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	
•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • •	•••••	•••••	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • •	• • • • •
CEIL	24.2	53.6	54.4	54.9	55.2	55.2	55.3	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.5	55.
200001	26.1	59.1	60.1	60.6	60.9	61.0	61.1	61.1	61.1	61.1	61.1	61.1	61.2	61.2	61.2	61.
18000	26.2	59.4	60.4	61.0	61.3	61.3	61.4	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.6	61.
160001	26.2	59.5	60.5	61.1	61.4	61.4	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.7	61.
14000	26.3	59.8	60.8	61.4	61.7	61.7	61.8	61.8	61.8	61.9	61.9	61.9	61.9	61.9	61.9	62.
12000	26.5	60.8	61.8	62.4	62.7	62.7	62 • 8	62.9	62.9	62.9	62.9	62.9	62.9	62.9	63.0	63.
100001	27.0	62.4	63.5	64.1	64.4	64.4	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.7	64.
9000	27.1	62.6	63.7	64.3	64.6	64.6	64.7	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.9	65.
8000	27.5	64.2	65.3	65.9	66.3	66.3	66 • 4	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66,6	66.
7000	28.0	65.3	66.4	67.0	67.4	67.4	67.5	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.7	67.
60001	28.2	65.7	66.9	61.5	67.9	67.9	68.0	68.1	68.1	68 - 1	68.1	68.1	68.1	68.1	68.2	66.
5000 [28.6	67.2	68.3	69.0	69.4	69.4	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.8	69.
	28.8	67.7	68 • 9	69.6	70.0	70.0	70.2	70.2	70.2	70.2	70.2	70.2	70.3	70.3	70.3	70.
	29.0	69.1	70.3	71.0	71.4	71.4	71.6	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.8	71.
	29.4	70 . D	71.3	72.0	72.4	72.5	72.6	72.7	72.7	72.7	12.7	12.7	12.7	72.7	72.8	72.
3000	29.7	71.6	73.0	73.7	74.2	74.2	74.4	74.4	74.4	74.4	74.4	74 - 4	74.5	74.5	74.5	74.
	30-1	73.2	74.6	75.4	75.9	75.9	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.3	76.
	30.4	75.3	76.9	77.8	78.2	78.3	78.5	78.5	78.5	78.5	78.5	78.5	78.6	78.6	78.6	78.
	30.6	76 - 1	77.8	78.7	79.1	79.2	79.4	79.4	79.4	79.4	79.4	79.4	79.5	79.5	79.5	79.
	30.9	77.7	79.6	86.6	81.2	81.2	81.4	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.7	81.
1 200 (31.0	79.1	81.3	82.5	83.2	83.3	83.5	83.6	83.6	83.7	83.7	83.7	83.7	83.7	83.7	83.
	31.1	80.3	82.6	84-1	85.1	85.2	85.5	85.7	85.7	85.8	85.8	85.8	85.8	85.8	85.9	86.
	31.2	81.1	83.8	85.3	86.6	86.8	87.1	.87.3	87.3	87.5	87.5	87.5	87.5	87.5	87.6	87.
-	31.2	81.8	84.8	86.7	88.3	88.6	88.9	89.2	89.3	89.4	89.5	89.5	89.5	89.5	89.5	89.
	31.2	82.3	85.5	87.6	89.5	89.9	90.3 91.4	90.6 91.9	90.8 92.1	90.9 92.3	91.0 92.3	91.0 92.4	91.0 92.4	91.0	91.1 92.5	91.
6001	31.2	82.7	86.0	88.3	90.4	90.8	71.4	71.7	92.1	42.3	92.3	72.4	72.4	92.4	42.5	42.
	31.2	82.9	86.5	89.0	91.4	91.9	92.9	93.8	94.2	94.4	94.4	94.5	94.5	94.5	94.6	94.
	31.2	83.0	86.7	89.2	92.0	92.6	93.9	95.2	95.9	96.3	96.4	96.4	96.4	96.4	96.6	96.
	31.2	83.0	86.8	89.4	92.3	93.0	94.4	95.9	96.8	97.4	97.6	97.7	97.8	97.8	97.9	98.
	31.2	83.0	86.8	89.4	92.3	93.0	94.5	96.2	97.3	98.0	98.4	98.5	98.7	98.7 99.0	98.8 99.3	99.
1001	31.2	83.U	86.8	89.4	92.3	93.0	94.5	96 • 2	97.3	98.1	98.6	98.7	98.9	44.U	44.3	99.
C I	31.2	93.0	86.8	89.4	92.3	93.0	94.5	96.2	97.3	98 • 1	98.6	98.7	98.9	99.0	99.3	100.

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

ST	ATION N	UMBER:	724505	STATIO	N NAME:	MCCO	NNELL A	FB KS				PERIOD Month	OF REC		-86 (LST): (nono-os	00	
	IL ING	•••••	• • • • • • • •	•••••	•••••	• • • • • •	• • • • • • •			IN STAT			• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	••••••	• •
		GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GĘ	GE	GE	GE	GE	
	EET I		٠.	5	4	3			1 1/2		1	3/4	5/8	1/2	5/16	1/4	ם	
			_								. .				,,,,,,			
••	•••••		• • • • • • • •	• • • • • • •	•••••	•••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	•••••	•••••	• • • • • • •	• • • • • •	• • • • • • •	•••••	••
NO	CE IL I	25.5	57.3	58.4	58.6	59.0	59.0	59.2	59.4	59.4	59.5	59.5	59.5	59.5	59.6	59.6	66.0	
3.0	200001	26.7	60.2	61.5	61.8	62.3	62.3	62.5	62.6	62.6	62.7	62.7	62.7	62.7	62.8	62.8	63.2	
ĞĒ	180001	26.7	60.3	61.6	61.9	62.4	62.4	62.6	62.7	62.7	62.8	67.8	62.8	62.8	62.9	62.9	63.3	
GE	160001	26.7	60.3	61.6	61.9	62.4	62.4	62.6	62.7	62.7	62.8	62.8	62.8	62.8	62.9	62.9	63.3	
	140001		6p.5	61.8	62.2	62.6	62.6	62.8	62.9	62.9	63.0	63.0	63.0	63.0	63.1	63.1	63.5	
	120001		61.5	62.8	63.1	63.5	63.5	63.8	63.9	63.9	64.0	64.0	64.0	64.0	64.1	64.1	64.5	
•-				02.0					030,	03.	5,,,	• • • • •	0		••••		5.15	
r. F	100001	27.7	62.6	63.9	64.2	64.6	64.6	64.8	64.9	64.9	65.1	65.1	65.1	65.1	65.2	65.2	65.6	
ĞÈ			62.6	63.9	64.2	64.6	64.6	64.8	64.9	64.9	65.1	65.1	65.1	65 - 1	65.2	65.2	65.6	
GE			63.7	64.9	65.3	65.7	65.7	65.9	66.0	66.0	66.1	66.1	66.1	66.1	66.2	66.2	66.7	
GE		28.6	64.5	65.8	66.1	66.6	66.6	66.8	66.9	66.9	67.0	67.0	67.0	67.0	67.1	67.1	67.5	
GΕ		28.6	65.1	66.3	66.7	67.1	67.1	67.3	67.4	67.4	67.5	67.5	67.5	67.5	67.6	67.6	68.1	
Ü.	00001	20.0	03.1	•••	00.	0	0,.1	0,.3	07.4	0/••	0,.3	07.03	0,.5	0113	01.0	0,.0	00.1	
6E	50001	28.8	66.3	67.6	68.0	68.4	68.4	68.6	68.7	68.7	68.8	68.8	68.8	68.8	68.9	68.9	69.4	
GΕ	45001		67.2	68.5	68.8	69.2	69.2	69.5	69.6	69.6	69.7	69.7	69.7	69.7	69.8	69.8	70.2	
GE	40001		68.4	69.7	70.0	70.4	70.4	70.6	70.8	70.8	70.9	70.9	70.9	70.9	71.0	71.0	71.4	
GΕ	-	29.2	69.6	70.9	71.2	71.6	71.6	71.8	71.9	71.9	72.0	72.0	72.0	72.0	72.2	12.2	72.6	
G F		29.2	71.0	72.3	72.6	73.0	73.0	73.2	73.3	73.3	73.4	73.4	73.4	73.4	73.5	73.5	74.0	
O.L	30001						,,,,,	. , , , ,	,,,,,		. 3 • •	1304		,,,,,	, , , ,	,,,,,	7440	
GE	25001	29.6	72.0	73.3	73.7	74.1	74.1	74.3	74.4	74.4	74.5	74.5	74.5	74.5	74.6	74.6	75.1	
GΕ			73.4	74.7	75.3	76.0	76.0	76.2	76.3	76.3	76.5	76.5	76.5	76.5	76.6	76.6	77.0	
GE	18001	30.3	73.8	75.1	75.6	76.5	76.5	76.7	76.8	76.8	76.9	76.9	76.9	76.9	77.0	77.0	77.4	
ĿΕ	15001	31.1	76.3	77.7	76.3	79.1	79.4	79.6	79.7	79.7	79.8	79.8	79.8	79.8	79.9	79.9	80.3	
6 E	12001		78.7	80-1	81.1	82.2	82.4	82.8	83.1	83.1	83.3	83.3	83.3	83.3	83.4	83.4	83.9	
	,				• • • •			02.00				0503	.,,,	03.3		0	0307	
GE	10001	31.7	79.6	81.1	82.0	83.2	83.4	83.9	84.2	84.2	84.6	84.6	84.6	84.6	84.7	84.7	85.2	
GE		31.7	79.8	81.8	83.0	84.3	84.6	85.1	85.4	85.4	85.8	85.9	85.9	85.9	86.0	86.0	86.5	
٥E	1008	31.8	80.2	82.4	83.5	85.4	85.7	86 • 1	86.5	86.5	86.9	87.0	87.0	87.0	97.1	87.1	87.5	
GΕ	7001	31.8	80.5	83.0	84.5	86.8	87.2	87.6	88.0	88.0	88.4	88.5	88.5	88.5	88.6	88.6	89.0	
GE		31.9	81.7	84.3	86.0	88.8	89.2	89.7	90.0	90.0	90.5	91.0	91.0	91.0	91.1	91.1	91.5	
										,,,,,						,		
65	5001	31.9	81.9	84.9	86.7	89.6	90 - 1	90.5	90.9	98.9	91.6	92.0	92.0	92.0	92.2	92.2	92.6	
GE	4001	31.9	82.2	85.3	07.i	90.4	91-1	91.7	92.5	92.5	93.4	94.Õ	94.0	94.0	94.1	94.1	94.5	
GΕ	3001	31.9	82.2	85.3	87.4	91.5	92.2	93.0	94.1	94.2	95.6	96.1	96.1	96.2	96.3	96.3	96.8	
GE	200 1	31.9	82.2	85.3	87.4	91.5	92.2	93.0	94.2	94.6	96.1	96.9	96.9	97.0	97.2	97.3	98.1	
GE		31.9	82.2	85.3	87.4	91.5	92.2	93.0	94.2	94.6	96.3	97.1	97.1	97.4	97.6	98.0	99.9	
				,												•		
G.F	n I	71. g	02.2	95.3	0 7 - h	0 . 5	92.2	0.7.0	64.2	94.4	96.3	07.1	97.1	97.4	07.4	99.0	100.0	

GLOBAL CLIMATOLOGY BRANCH USAFETAC

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86

83.8 84.5 86.3 87.8 89.6

91.3 93.8

96.2

96.2

96.2

83.8 84.5 86.3 87.8

91.4 93.9

96.3

96.3

96.3

83.8 84.5 86.3 87.8

91.3 93.8 95.5

96.1 96.1

96.1

HOURS(LST): 0300-0500

83.9 84.6 86.5 88.0 89.7

91.5 94.0 95.7

96.7

97.6

83.8 84.5 86.3 87.8

91.4

95.6

96.3

96.6

96.6

84.8 86.7 86.2 89.9

91.8 94.3 96.0

97.2

100.0

MONTH: DEC

AIR WEATHER SERVICE/MAC

	IL IN	•••	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • • •	• • • • • • • • • • • • • • • • • • •	811117	IN STATE		• • • • • • • • • • • • • • • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •
	IN	ŭ	GE	GE	GE	٥E	GE	GE	GE			GE	GE	GE	GΕ	GE	GE	G.E.
	EET	i		6	5	-4		2 1/2		1 1/2		1	3/4	5/8	1/2	5/16	1/4	0
• •			• • • • • •		• • • • • • •	• • • • • • •	• • • • • •				• • • • • • • •		• • • • • •	• • • • • •	• • • • • • •		• • • • • •	• • • • • • • • • • • • •
NO	CEI	ı. I	25.7	56.6	57.2	57.8	58.2	58.2	58.3	58.3	58.3	58.4	58.5	58.5	58.5	58.5	58.6	56.8
																	-	
			26.2	58.9	59.6	6 U . 5	61 • 1	61.1	61.2	61.3	61.3	61.4	61.5	61.5	61.5	61.5	61.6	61.8
			26.2	58.9	59.6	60.5	61-1	61.1	61.2	61.3	61.3	61.4	61.5	61.5	61.5	61.5	61.6	61.8
			26.2	58.9	59.6	6 C . 5	61.1	61.1	61.2	61.3	61.3	61-4	61.5	61.5	61.5	61.5	61.6	61.8
GE	140	001	26.2	59.2	59.9	60.9	61.5	61.5	61.6	61.7	61.7	61.8	61.9	61.9	61.9	61.9	62.0	62.3
GE	120	001	26.5	59.9	60.6	61.6	62.3	62.3	62.4	62.5	62.5	62.6	62.7	62.7	62.7	62.7	62.8	63.0
GE	100	00 1	27.3	61.5	62.3	63.2	63.9	63.9	64.0	64.1	64.1	64.2	64.3	64.3	64.3	64.3	64.4	64.6
GE	90	00 İ	27.4	61.6	62.4	63.3	64.0	64.0	64.1	64.2	64 - 2	64.3	64.4	64.4	64.4	64.4	64.5	64.7
GE	80	00 İ	27.7	62.4	63.1	64.1	64.7	64.7	64.8	64.9	64.9	65.1	65.2	65.2	65.2	65.2	65.3	65.5
GE	7.0	na i	28.0	63.1	63.9	64.8	65.5	65.5	65.6	65.7	65.7	65.8	65.9	65.9	65.9	65.9	66.0	66.2
GE			28.2	64.2	64.9	65.9	66.6	66.6	66.7	66.8	66.8	66.9	67.0	67.0	67.0	67.0	67.1	67.3
GE	50	nn I	28.3	65.3	66.0	67.0	67.7	67.7	67.8	68.D	68.0	68.1	68.2	68 • 2	68.2	68.2	68.3	66.5
GE			28.3	66.1	66.9	67.8	68.6	68.6	68.7	68.8	68.8	68.9	69.0	69.0	69.0	69.0	69.1	69.4
GE			28.3	67.0	67.7	68.7	69.5	69.5	69.6	69.7	69.7	69.8	69.9	69.9	69.9	69.9	70.0	74.2
GE		•	28.6	68.0	68 - 8	69.8	70.5	70.5	70.6	70.8	70.8	70.9	71.0	71.0	71.0	71.0	71.1	71.3
GΕ			28.7	69.7	70.5	71.5	72.4	72.4	72.5	72.6	72.6	72.7	72.8	72.8	72.8	72.8	72.9	73.1
GĒ	25	on I	28.8	70.8	71.8	72.9	74.0	74.0	74.1	74.2	74.2	74.3	74.4	74.4	74.4	74.4	74.5	74.7
ĞĒ			29.4	72.4	73.8	74.8	76.1	76.1	76 • 2	76.3	76.3	76.5	76 6	76.6	76 • 6	76.6	76.7	76.9
GE			29.5	72.9	74.3	75.4	76.8	76.8	76.9	77.0	77.0	77.1	77.2	77.2	77.2	77.2	77.3	77.5
GE			30.1	74.7	76.6	78.0	79.5	79.5	79.6	79.7	79.7	79.8	79.9	79.9	79.9	79.9	80.0	80.2
GE			30.2	76.1	78.2	79.6	81.3	81.5	81.7	81.9	81.9	82.0	82.2	82.2	82.2	A2.2	82.3	82.5
				• •							,		~. •.					

83.5 84.3

86.1

90.8 92.7 93.9

94.2

83.5 84.3 86.1 87.6 89.1

90.9 93.3 94.7

95.1 95.1

95.1

83.7 84.4 86.2

87.7 89.5

91.2 93.7 95.3

95.6 95.6

95.6

TOTAL NUMBER OF OBSERVATIONS: 930

77.6 77.7 78.3 79.5

80.0

80.4 80.4 80.4

80.4

80 - 4

79.7 80.3

81.0 82.2 82.9

83.7 83.8 83.8

83.8

83.8

81.2 81.9 83.2 84.5

86.8 87.2 87,3

87.3

82.9 83.7

85.3

86.8

89.4 90.4

91.1

91.1 91.1

91.1

83.1 83.9 85.5 87.0

89.9 91.1 91.7

91.7 91.7

91.7

83.3 84.1 85.9

87.4

90.5 92.0 92.9

93.1 93.1

93.1

GE GE GE

GE

GΕ

GE

GE

GE

1000| 30.5 900| 30.5 800| 30.5

7001 30.5 6001 30.5

5001 30.5 4001 30.5 3001 30.5

200 | 30.5 100 | 30.5

01 30.5

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

5 1 4	ATION NUM	MBER:	724505	STATIO	ON NAME:	MCCO	NNELL A	BKS				PERIOD MONTH	OF REC		-86 (LST):	0600-08	00	
		• • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • •	• • • • • • •						• • • • • • •	• • • • • •	• • • • • •	• • • • • •	• • • • • • • • • • • • • • • • • • • •	٠
	LING			_				_	BILITY									
	N I		GE	GΕ	GE	GE	GE	GE	GE	GE	GE	GΕ	5€	GE	GE	GE	GE	
FE	ET	10	6	5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	5/16	1/4	a	
• • •		• • • • • •	• • • • • • •	••••	• • • • • • • •	• • • • • •	• • • • • • •	• • • • • •		• • • • • • •	• • • • • •	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • •	٠
N O	CEIL I A	24.3	52.6	53.4	5 3 . 9	54.2	54.3	54.5	54.8	54.8	54 - 8	55.1	55.1	55.2	55.2	55.3	55.5	
	200001									59.0	59.1	59.4	59.4	59.5	59.5	59.6	59.8	
	200001 2		56 • 5	57.4	56.0	58.3	58.4	58.7	59.0	59.1	59.2	59.5	59.5		59.6	59.7	59.9	
	180001 2		56 • 6	57.5	58.1	58.4	58.5	58.8	59.1					59.6				
	100001 5		56.6	57.5	58.1	58.4	58.5	58.8	59.1	59.1	59.2	59.5	59.5	59.6	59.6	59.7	59.9	
	140001 2		56.8	57.7	58.3	58.6	58.7	59.0	59.4	59.4	59.5	59.7	59.7	59.8	59.8	59.9	60.1	
GE	120001 2	25.7	57.5	58.5	59.0	59.4	59.5	59.8	60.1	60.1	60.2	60.4	60.4	60.5	60.5	60.6	60.9	
	100001 2		59.0	60.1	60.6	61.2	61.3	61.7	62.0	62.0	62.3	62.5	62.5	62.6	62.6	62.7	62.9	
GE	90001 2		59.1	60.2	66.8	61.3	61.4	61.8	62.2	62.2	62.4	67.6	62.6	62.7	62.7	62.8	63.0	
GE	80001 2		6C.D	61.1	61.8	62.4	62.5	62.9	63.2	63.2	63.4	63.7	63.7	63.8	63.8	63.9	64.1	
_	70001 2		60.5	61.6	62.4			63.4	63.8	63.8	64.0	64.2	64.2	64.3	64.3	64.4	64.6	
-			-			62.9	63.0		64.9			65.4	65.4		65.5			
GE	60001 2	(0.8	61.6	62.7	63.4	64.1	64.2	64.6	04.7	64.9	65.2	65.4	P. CO	65.5	62.3	65.6	65.8	
GΕ	50001 2	7.0	62.8	63.9	64.6	65.3	65.4	65.8	66.1	66.1	66.3	66.6	66.6	66.7	66.7	66.8	67.n	
GE	45001 2		63.1	64.2	64.9	65.6	65.7	66.1	66.5	66.5	66.7	66.9	66.9	67.0	67.0	67.1	67.3	
GE	40001 2		65.1	66.2	67.0	67.6	67.7	68.2	68.5	68.5	68.7	68.9	68.9	69.0	69.0	69.1	69.4	
GE	35001 2		66 • 2	67.5	68.3	68.9	69.0	69.5	69.8	69.8	70.0	70.2	70.2	70.3	70.3	70.4	70.6	
GE	30001 2		67.4	68.7	69.6	70.2	70.3	7n.8	71.1	71.1	71.3	71.5	71.5	71.6	71.6	71.7	71.9	
3.	20001 2		01.4	00.1	07.0	10.2	70.3	10.0	,,,,		,,,,	11.3	11.5		.1.0	,	11.7	
GE	25001 2	28.3	68.6	70.1	71.0	71.6	71.7	72.3	72.6	12.6	72.8	73.0	73.D	73.1	73.1	73.2	73.4	
GE	20001 2		70.6	12.3	73.4	74.2	74.3	74 . 8	75.2	75.2	75.4	75.6	75.6	75.7	75.7	75.8	76.0	
GE	18001 2		70.9	72.5	73.7	74.4	74.5	75.1	75.4	75.4	75.6	75.8	75.8	75.9	75.9	76.0	76.2	
ĿΕ	15001 2		71.7	73.3	74.6	75.6	75.7	76.2	76.6	76.6	76 . 8	77.0	77.0	77.1	77-1	77.2	77.4	
GE	12001 2		73.5	75.3	76.8	77.7	77.8	78.4	78.7	78.7	78.9	79.1	79.1	79.2	79.2	79.4	79.6	
GE	10001 2	29.7	75.1	76.8	78.4	79.4	79.5	80 - 1	80.5	80.6	80.9	81.1	81.1	81.2	81.2	81.3	81.5	
G€	9001 2	29.7	76.3	71 4	80.1	81.1	81.2	81.8	82.3	82.4	R2.6	82.9	82.9	83.B	83.0	03.1	83.3	
GΕ	euo I z	29.7	77.4	79.8	81.7	82.8	83.0	83.7	84.1	84.2	84.5	84.9	84.8	84.9	84.9	85.1	85.3	
GĘ	7001 2	9.7	78.2	80.6	82.9	84.4	84.6	85.3	85.7	85.B	86.2	86.6	86.6	86.7	86.8	86.9	87.1	
GE	600 2	29.7	78.4	81.0	83.8	85.9	A6.2	86.9	87.4	87.5	88.1	88.4	88.4	88.5	88.6	88.7	88.9	
												_						
GE	5001 2		78.6	81.6	84.5	87.3	87.6	89.0	89.7	90.0	90.6	91.1	91.1	91.4	91.5	91.6	91.8	
GE	4001 2		78.6	81.8	84.8	88.0	88.3	89.9	90.9	91.5	92.3	92.9	92.9	93.2	93.3	93.4	93.7	
GE	300 2		78.7	81.9	85.2	88.4	88.6	90.4	91.8	92.6	93.9	94.5	94.5	94.8	94.9	95.2	95.5	
ĢĒ	200 2		78.7	81.9	85.2	88.4	88.8	90.5	91.9	92.9	94.4	95.2	95.2	95.6	95.8	96.3	96.8	
GE	100 2	29.7	78.7	81.9	85.2	88.4	88.8	90.5	91.9	92.9	94.4	95.2	95.2	95.8	96.1	97.2	99.9	
GE	0 2	29.7	78.7	81.9	85.2	88.4	8.86	90.5	91.9	92.9	94.4	95.2	95.2	95.8	96.1	97.2	100.0	

TOTAL NUMBER OF OBSERVATIONS:

930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

-			724505		_							NTH	OF REC	HOURS	(LŠTI: 1		
	L ING	••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • •	• • • • • • •			IN STAT			• • • • • • •	• • • • • • •	•••••		
	IN E	GE 10	GE 6	G€ 5	G E 4	GE ,	6E 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	G ξ 5 ∕8	GE 1/2	GE 5/16	GE 1/4	⊌€ D
		-	• • • • • • •		• • • • • • • • •							-	••••••			• • • • • • •	
N O	CE1L	.3.9	49.9	50.3	56.5	50.8	50.8	50.9	50.9	50.9	50.9	50.9	50.9	50.9	51.0	51.2	51.5
	200001		56.8	57.3	57.5	58.0	58.0	58.1	58.1	58 • 1	58.1	58.1	58.1	58.1	58 • 2	58.4	58.7
GE	180001	27.3	57.0	57.5	51.7	58.3	58.3	58.4	58.4	58.4	58.4	58.4	58 • 4	58.4	58.5	58.7	59.0
GE	160001	27.3	57.0	57.5	51.7	58.3	56.3	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.5	58 • 7	59.0
GE	140001	27.3	57.2	57.7	58.0	58.5	58.5	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.7	58.9	59.2
٥E	12000	27.6	58.5	59.0	59.2	59.8	59.8	59.9	59.9	59.9	59.9	59.9	59.9	59.9	60.0	60.2	60.5
GE	100001	28.1	60.8	61.3	61.5	62.0	62.0	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.4	62.6	63.0
GE	9000 [28.3	61.4	61.9	62.2	62.7	62.7	62.9	62.9	62.9	62.9	62.9	62.9	62.9	63.0	63.2	63.7
GE	80001	29.0	63.7	64.2	64.4	65.2	65.2	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.5	65.7	66.1
GE	70001	29.2	64.4	64.9	65.2	65.9	65.9	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.2	66.5	66.9
GE	60001	29.6	65.2	65.7	65.9	66.7	66.7	66.9	66.9	66-9	66.9	66.9	66.9	66.9	67.0	67.2	67.6
6 E	Soon I	30.0	66.5	67.0	67.2	68.2	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.6	68.8	69.2
GΕ		30.0	67.D	67.5	67.7	68.7	68.8	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.1	69.4	69.8
GE		30.3	68.4	68,9	69.1	70 - 1	70.2	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.5	70.8	71.2
GE		30.4	68.5	69.0	69.4	70.3	70.5	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.9	71.1	71.5
GΕ	3000		68.9	69.5	69.9	70.9	71.1	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.4	71.6	72.0
GΕ	2cnn l	30.8	69.9	70.8	71.3	72.3	12.5	72.7	72.8	72.8	72.8	72.8	72.8	72.8	72.9	73.1	73.5
60		31.0	71.0	71.8	72.6	73.5	73.8	74.0	74.2	74.	74.3	74.3	74.3	74.3	74.4	74.6	75.1
GE		31.2	71.3	72.2	72.9	73.9	74.1	74.3	74.5	74.5	74.6	74.6	74.6	74.6	74.7	74.9	75.4
GΕ		31.9	73.4	74.5	75.6	76.8	77.0	77.2	77.4	77.4	77.5	77.5	77.5	77.5	77.6	77.8	78.3
GE		32.2	75.3	76.8	76.1	79.5	79.7	79.9	80.1	80.1	80.2	80.2	80.2	80.2	80.3	80.5	81.0
GE	10001	32.3	76.0	77.8	79.1	80.5	80.8	81.0	81.3	81.3	81.4	81.4	81.4	81.4	81.5	81.7	82.2
GE		32.3	76.9	78.8	80.5	82.3	82.5	82.7	83.0	83.0	83.1	83.1	83.1	83.1	83.2	83.4	83.9
GE		32.3	77.7	79.9	82.4	84.1	84.3	84.5	84.8	84.8	85.1	85.1	85.1	85.1	85.2	85.4	85.8
6£		32.3	78.5	81.2	83.9	86.0	86.3	86.7	87.2	87.2	87.6	87.R	87.8	87.8	88.0	88.2	86.7
											89.1		89.5				
GE	600 I	32.3	78.5	81.5	84.2	86.7	87.1	87.6	88.4	88.6	84.1	89.5	07.3	89.5	89.6	89.8	90.3
GE		32.3	78.7	81.7	84.5	87.3	87.8	88.5	89.5	90.1	90.6	91.0	91.1	91.3	91.4	91.7	92.3
GE		32.3	78.7	81.8	84.6	87.6	88 - 3	89.0	90.3	91.3	91.9	92.3	92.4	92.6	92.7	93.0	93.5
GE		32.3	78.7	81.8	84.6	87.7	88.6	89.4	90.9	91.8	94.0	94.5	94.6	94.8	94.9	95.4	96.0
GΕ		32.3	78.7	81.8	84.6	87.7	58.6	89.5	91.0	92.2	94.6	95.5	95.6	96 • l	96.3	96.9	97.5
GE	1001	32.3	78.7	81.8	84.6	87.7	88.6	89.5	91.0	92.2	94.6	95.5	95.6	96.3	96.8	98.2	99.9
GE	at	32. 3	78.7	81.8	84.6	87.7	88.4	A9+5	91.0	92.2	94.6	95.5	95.6	96.3	96.8	98.2	100.0

GLOBAL CLIMATOLOGY BRANCH USAFETAC

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/HAC PERIOD OF RECORD: 71-86
MONTH: DEC HOURSILS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HOURSILST): 1200-1400 VISIBILITY IN STATUTE HILES CEILING GE GE 3 2 1/2 IN | GE FEET | 10 SE GE 5 4 GE GE GE 2 1 1/2 1 1/4 GE GE 1 3/4 GE GE GE GE 10 5/8 1/2 5/16 1/4 ũ 52.5 52.5 NO CEIL 1 24.2 51.6 52.0 52.4 52.5 52.5 52.5 52.5 52.5 52.5 52.5 52.5 52.5 52.5 60.4 GE 200001 27.2 59.5 59.9 60.2 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 60.4 61.0 61.0 GE 180001 27.5 60.4 61.0 61.0 61.0 61.0 61.0 61.0 59.8 60.8 61.0 61.0 61.0 GE 160001 27.5 GE 140001 27.7 59.8 60.4 60.8 61.D 61.0 61.0 61.0 61.0 61.0 61.0 61.0 61.0 61.0 61.0 60.2 60.9 61.2 61.4 61.4 61.4 61.4 61.4 61.4 61.4 61.4 61.4 61.4 61.4 61.4 GE 120001 28.2 61.0 61.6 62.2 GE 100001 28.8 65.6 65.6 68.3 65.6 65.8 65.8 64.9 65.6 65.6 65.6 65.6 65.6 65.6 64.1 65.3 65.6 65.6 GE 9000| 28.8 8000| 29.1 65.2 65.5 65.8 65.8 65.8 65.8 65.8 65.8 65.8 65.8 65.8 65.8 66.8 68.3 68.3 68.3 70001 29.6 68.7 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.4 69.4 60001 29.7 67.8 68.7 69.0 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 5000| 30.0 4500| 30.0 69.7 70.0 70.1 70.5 70.6 10.6 10.6 70.6 70.9 71.5 10.6 70.6 70.5 70.6 70.6 70.6 70.6 76.6 70.6 70.9 70.9 70.9 GE 68.9 70.9 71.5 GE 40001 30.3 35001 30.8 71.5 72.6 69.6 70.4 70.8 71.3 71.5 71.5 71.5 71.5 71.5 71.5 71.5 72.6 72.4 72.4 72.6 72.6 72.6 72.6 74.0 70.4 71.3 71.8 72.6 72.6 3000 | 30.9 75.5 79.4 79.7 75.5 79.4 79.7 75.3 79.0 79.4 75.5 79.4 79.7 75.5 79.4 6 E 6 E 25001 31.1 72.7 75.7 76.0 73.8 75.3 75.5 75.5 79.4 79.7 75.5 79.4 79.7 79.4 79.7 79.4 79.7 20001 31.9 11.2 17.5 78.2 78.5 79.1 79.5 79.4 79.4 79.7 80.2 GE 15001 32.5 77.3 79.2 81.1 81.2 81.5 81.5 81.5 81.5 81.5 81.5 81.5 81.5 81.5 81.5 12001 32.7 83.7 80.8 83.7 83.7 78.5 81.7 83.1 83.3 83.7 83.7 1000| 32.7 900| 32.7 800| 32.7 700| 32.7 82.6 84.8 85.1 85.5 87.3 85.7 87.5 85.7 85.7 87.6 89.7 85.7 87.6 85.7 87.6 85.7 87.6 89.8 91.1 85.7 85.7 87.6 87.6 89.8 91.1 80.3 82.9 84.1 86.3 86.6 89.6 89.8 89.8 69.8 91.1 GΕ 81.3 88.8 89.6 89.8 90.8 90.9 89.7 90.8 GE 84.6 86.1 88.5 88.8 81.6 6001 32.7 89.9 91.0 92.5 93.8 95.5 91.5 93.4 94.9 96.2 5001 32.7 4001 32.7 3001 32.7 81.9 81.9 81.9 85.2 85.3 85.3 90.1 90.5 93.0 93.1 93.8 93.8 87.3 90.6 91.2 92.5 92.6 94.2 94.3 95.4 97.0 95.4 97.3 95.5 97.5 95.5 95.5 GF 2001 32.7 87.3 91.8 91.4 92.7 95.3 96.6 98.1 98.4 99.0 99.7 99.5 99.5 1001 32.7 98 . 5 100.0 GE 90.8 95.3 96.6 01 32.7 90.8 91.4 92.7 95.3 95.4 96.6 98.2 98.5 99.2 99.6 100.0 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOUPLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: DEC HOURS(LST): 1500-1700 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS VISIBILITY IN STATUTE MILES CEILING IN | GE FEET | 10 GE 4 GE GE GE 2 1 1/2 1 1/4 GE 6 GE GE GE 1 3/4 GE 5/16 GE 1/4 3 2 1/2 5/8 5 1/2 Ω 57.3 57.3 57.3 57.3 57.3 57.3 57.3 NO CEIL / 26.8 56.6 57.3 57.3 57.3 57.3 57.3 57.3 63.9 64.0 64.0 63.1 63.2 63.2 63.9 64.0 64.0 63.9 64.0 64.0 63.9 64.0 64.0 63.9 64.0 64.0 63.9 64.0 64.0 GE 200001 28.7 GE 180001 28.8 63.9 63.9 63.9 63.9 64.0 63.9 64.0 63.9 64.D 63.9 63.9 64.0 64.0 64.0 64 · O GE 14000 | 28.8 GE 14000 | 29.1 64.0 64.0 64.0 64.0 64 . D 64.0 64.7 64.7 64.7 14.7 64.7 64.7 GE 120001 30.8 65.9 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66 . 7 66.7 66.7 66.7 66.7 68.7 69.0 71.5 68.7 69.0 71.5 68.7 69.0 71.5 68.7 69.0 71.5 68.7 69.0 71.5 68.7 68.7 69.0 71.5 68.7 69.0 68.7 69.0 68.7 69.0 68.7 68.0 68.3 68.7 68.7 GE 10000 | 31.2 GE 9000 | 31.2 69.0 71.5 69.0 8000 | 31.3 70.8 71.5 71.5 71.5 71.5 71.5 72.5 72.8 72.5 72.8 72.5 72.8 72.5 G€ 70001 31.3 71.7 72.5 72.5 72.5 72.5 72.5 72.5 72.5 72.5 72.5 72.5 6000| 31.3 6 E 6 E 6 E 5000| 32.0 4500| 32.0 4000| 32.4 73.4 73.4 74.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 75.9 74.3 74.3 74.3 74.3 75.9 76.3 74.3 74.3 75.9 74.3 75.9 74.3 75.9 74.3 75.9 76 · 3 78 · 5 35001 32.5 77.3 78.5 30001 32.5 78.5 78.3 78.4 78.4 78.5 78.5 78.5 G E G E G E 79.2 82.0 82.8 79.4 82.2 82.9 25001 32.9 78.3 79.2 79.5 79.9 79.9 79.9 79.9 79.9 79.9 79.9 79.9 79.9 79.9 82.8 83.5 85.6 82.8 2000 | 33.4 82.8 83.5 62.8 83.5 82.8 82.8 82.8 83.5 82.8 80.9 81.5 82.0 82.8 82.8 82.8 82.3 83.0 1500 | 33.8 84.2 82.6 84.2 84.7 GE 85.1 85.6 85.6 85.6 85 . 6 85.6 12001 33-8 88.1 88.1 88.1 88.1 88.1 90.1 91.9 90.1 91.9 88.7 89.1 90.9 92.2 92.8 90.0 89.2 89.9 91.9 91.9 GE 9001 33.8 8001 33.8 86.2 86.6 91.7 93.2 91.7 93.3 91.9 93.7 88.5 91.8 91.9 91.6 93.5 93.7 93.7 93.7 89.5 G F 700 | 33.8 87.0 90.4 93.7 94.0 94.1 94.5 94.5 94.5 94.5 94.5 GE 91.0 96.3 89.8 97.3 98.7 99.4 87.1 87.2 87.2 89.8 89.9 89.9 91.2 91.2 91.2 91.2 93.0 93.4 93.4 93.7 94.1 94.1 95.5 96.3 96.3 96.2 97.3 97.4 6 E 500| 33.8 400| 33.8 96.5 97.1 97.2 97.2 97.3 97.3 97.3 98.5 99.0 99.4 98.6 99.2 99.7 98.6 99.2 99.7 97.7 98.7 99.4 98.7 98.7 300 | 33.8 GE 2001 33.8 1001 33.8 100.0 100.0

96.3

98.5

99.7

99.7

99.9

99.9

100.0 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86 STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HONTH: DEC HOURSILST1: 1800-2000 VISIBILITY IN STATUTE MILES CEILING GE GE 3 2 1/2 IN | GE FEET | 10 GE 6 GE 5 6**E** GE GE GE 2 1 1/2 1 1/4 GE GE 1 3/4 G ξ 5 / 8 GE 1/2 GE 5/16 6E 1/4 ∪€ 0 60.1 60.5 60.5 60.6 60.6 60.6 60.6 60.6 60.6 60.6 60.6 NO CETE 1 28.4 66.5 60.5 60.6 60.6 6E 16000| 30.0 6E 16000| 30.0 65.7 65.7 65.7 66.1 66.1 66.1 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.1 06.1 66.1 66.1 66.1 66.1 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 66.3 GE 140001 30.3 66.8 67.2 67.2 67.2 67.2 67.4 67.4 67.4 67.4 67.4 67.4 67.4 67.4 69.4 GE 120001 31.3 68.7 69.1 69.1 69.1 69.1 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 71.8 71.8 75.7 74.5 72.3 72.3 72.3 72.3 74.1 72.3 72.3 74.1 72.3 72.3 74.1 72.5 72.5 74.3 72.5 72.5 74.3 72.5 72.5 74.3 72.5 72.5 74.3 72.5 72.5 74.3 75.3 72.5 72.5 74.3 75.3 72.5 72.5 74.3 72.5 100001 32.1 72.5 72.5 72.5 74.3 75.3 72.5 90001 32.1 80001 32.1 70001 32.1 12.5 GΕ 74.1 74.3 15.0 75.0 75.1 75.3 75.3 75.3 75.3 75.3 GE 75.1 75.3 5000| 32.1 4500| 32.1 4000| 32.1 76.7 17.6 78.2 19.8 76.7 77.6 78.2 71.0 77.9 78.6 77.0 77.9 78.6 77.0 17.9 78.6 77.0 77.9 78.6 76.5 77.3 78.0 77.9 77.0 77.9 78.6 79.8 77.0 77.9 78.6 79.8 77.0 17.0 71.3 78.0 79.2 77.9 78.6 68 76.5 77.1 77.9 78.6 77.9 78.6 78.6 79.8 ĿΕ 3'001 32.3 78.3 79.2 79.4 19.8 79.8 79 - A 79.8 79.R 79.R 79.8 30001 32.6 80.9 81.3 81.3 81.3 8C.1 86.7 80.9 81.3 81.3 81.3 81.3 81.3 2500| 32.7 2000| 33.2 1800| 33.2 1500| 33.2 80.6 82.1 82.3 81.4 63.2 83.4 81.4 83.2 83.4 84.7 81.7 83.4 83.6 81.7 83.5 83.7 82.2 84.0 84.3 82.3 84.3 84.5 82.3 84.3 84.5 82.3 84.3 84.5 82.1 83.9 82.3 84.3 84.5 86.3 82.3 84.3 84.5 Я2.3 84.3 84.5 82.3 82.3 عد 6 € 84.3 84.3 84.1 5 E 83.1 86.3 84.4 45.4 85.5 86.0 86.3 86.3 86.3 i f 86.1 12001 33.2 85.7 86.1 87.9 87.9 A7.9 87.9 87.9 87.9 87.9 90.3 91.2 92.7 10001 33.2 9001 33.2 9001 33.2 89.A 90.6 90.3 91.2 92.7 90 · 3 91 · 2 85.4 86.4 88.9 86.8 91.2 90.0 91.2 92.7 91.2 86.6 89.4 91.0 91.2 92.7 -, € 90.8 88.0 90.9 91.9 92.1 92.7 91.5 91.7 92.7 93.4 93.4 7001 33.2 86.6 89.5 96.0 92.4 93.2 91.4 91.4 93.4 93.4 93.4 6001 89.8 90.6 90.6 91.9 92.8 92.9 93.7 94.6 94.7 94.2 95.0 95.1 96.5 98.1 98.6 96.5 98.1 98.6 0001 87.5 95.3 95.5 96.1 96.5 96.5 96.5 96.5 96.5 ا را د د 4001 33.2 88.G 88.G 96.2 96.4 96.8 97.2 97.6 98 • 1 98 • 5 98.I 98.5 98.1 98.1 98.5 98.1 98.5 98.8 92.9 99.1 99.1 99.1 99.2 99.2 1001 31.2 88.0 90.6 96.3 99.5 99.9 97.7 98.9 99.4 99.4 99.5 100.0 01 33.2 95.1 96.3 96.8

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PEPIOD OF RECORD: 77-86
MONTH: DEC HOURS(LS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HOURS(LST): 2100-2300 CEILING VISIBILITY IN STATUTE MILES
IN | GE GE GE GE GE GE GE GE GE
FEET | 10 6 5 4 3 2 1/2 2 1 1/2 1 1/4 1 3/4 5/8 5/16 1/4 1/2 ı.) 61.3 NO CEIL | 27.9 60.4 60.9 61.2 61.2 61.2 61.3 61.3 61.3 61.3 61.3 61.3 61.3 61.3 61.3 GE 20000| 29.1 GE 18000| 29.1 GE 16000| 29.1 64.9 65.2 65.7 66.2 66.2 66.5 66.2 66.5 66.5 66 • 2 66 • 5 66.2 66.5 66.2 66.5 66.5 65.9 65·9 66·1 65.9 66.2 66.2 66.2 66.1 66.5 66.5 66.1 66.1 66.5 66.5 65.2 66.1 66.5 66.5 67.0 65.9 66.1 66.5 66.5 66.5 66.5 66.5 66.5 GE 140001 29.4 67.0 67.0 67.0 67.0 66.7 67.0 67.0 66.5 66.7 GE 120001 30.0 67.0 68.3 68.3 68.3 68.3 68.3 70.3 70.3 71.3 70.7 70.7 GE 100001 31.1 69.4 69.4 70.3 70.3 70.3 71.3 70.3 70.3 71.3 70.7 70.7 71.6 70.7 70.7 71.6 70.7 70.7 71.6 70 • 7 70 • 7 70.7 70.7 70.7 70.7 70.1 90001 31.1 70.1 71.1 70.7 70.7 71.6 74.7 80001 31.2 71.6 71.6 71.6 71.6 71.6 GE 70001 31.2 72.4 72.6 72.9 72.9 72.9 72.9 72.9 72.9 72.9 72.9 72.9 73.5 73.5 73.5 13.5 GΕ 60001 31.2 72.2 73.1 73.1 73.5 5000| 31.3 4500| 31.3 4000| 31.5 74.0 74.2 75.6 74.3 74.5 76.2 74.3 74.5 76.2 74.6 74.9 76.5 74.6 74.9 76.5 74.6 74.9 76.5 77.5 74.6 74.9 76.5 74.6 74.9 76.5 77.5 74.6 74.9 76.5 73.2 73.5 74.9 74.6 74.6 74.9 74.9 74.9 76.1 76.5 77.5 76.5 76.5 6. F 35001 31.5 75.6 77.1 77.1 77.5 GE 76.4 30001 31.6 78.4 78 - 4 78.4 78.4 78.4 78.4 79.5 81.4 82.0 79.0 79.0 79.4 79.5 79.5 81.4 79.5 79.5 79.5 81.4 82.0 83.4 2000| 32.3 1900| 32.3 79.0 79.3 80.5 80.8 81.3 80.8 81.3 81.3 81.4 82.0 81.4 82.0 81.4 82.0 81.4 42.0 81.4 82.0 79.8 81.4 GE 80.3 82.0 GΕ 15001 32.6 79.9 81.1 81.9 82.5 82.5 83.2 83.4 83.4 83.4 83.4 83.4 83.4 63.4 83.4 GE 12001 32.7 81.9 83.1 83.9 84.7 84 - 7 85.3 85.7 85.7 85.7 85.7 82.4 82.7 83.7 83.7 84.4 85.5 86.9 87.7 89.5 86.9 87.7 89.5 1000| 32.9 84.7 85.3 85.4 86.1 85.4 86.1 86 • 1 86 • 7 86.7 87.5 86.9 87.7 89.5 86.9 87.7 ЬE 86.7 86.9 87.7 86.9 86.9 87.7 87.5 86.5 87.5 89.5 89.5 GE POOL 32.9 87.5 87.5 88.3 89.1 89.3 89.5 84.5 700 I 89.0 89.0 90.8 91.0 91.0 91.0 91.0 91.0 91.0 91.0 93.1 93.1 GE 6001 32.9 85.1 A 7 . A 88.9 90.6 90.6 91.7 92.6 42.8 93.0 93.1 93.1 93.1 93.1 85.4 85.9 91.5 92.7 94.2 93.7 94.0 95.5 94.3 95.8 94.3 95.8 (, F + 0.0 | 13-0 86.1 89.5 91.5 92.7 94.2 94.3 94.3 94.3 94.3 400 33.0 88 . 7 90.2 95.7 95.8 95.8 95.8 85.9 85.9 92.9 94.6 95.3 96.8 97.5 96.8 97.7 96.8 97.8 96.8 98.0 GE 300 | 33.0 88.8 90.3 93.0 95.7 96.0 96.7 96.8 96.8 97.8 96.0 97.4 GΕ 2001 33.0 88.9 96.6 93.4 96.3 96 • 7 97.6 90.6 98.3 01 33.0 96.7 97.5 97.6 98.0 98.1 98.2 98.3 100.0 93.4 95.3 GE 85.9 96.6 93.3 96.3 88.9

PERCENTAGE FREQUENCY OF OCCURPENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: 77-86
MONTH: DEC HOURSILS STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS HOURS (LST): CEILING VISIBILITY IN STATUTE MILES GE 4 GE GE GE 6 IN | GE FEET | 10 GΕ 5 GE GE GE 2 1 1/2 1 1/4 GE 1 GE GE GE 3 2 1/2 3/4 1/2 NO CEIL | 25.8 56.3 56.7 56.7 56.9 56.9 56.9 56.9 57.D 55.6 56.5 62.3 62.4 62.4 61.4 61.6 61.6 62.3 62.5 62.5 62.3 62.5 62.5 GE 200001 27.6 60.7 61.7 62.0 62.0 62.6 62.2 62.2 62.5 62.6 GE 18000| 27.7 GE 16000| 27.7 60.8 60.8 61.9 62.2 62.2 62.3 62.4 62.4 62.5 GE 140001 27.8 61.3 62.8 62.9 63.0 63.0 63.0 63.0 63.2 GE 120001 28-4 62.5 63.3 63.6 63.9 63.9 64.0 64.1 64.2 64.2 64.2 64.2 64.3 10000| 29.1 9000| 29.1 8000| 29.4 7000| 29.6 65.4 65.6 67.2 65.8 65.9 67.6 66.1 66.2 67.9 66.4 66.6 68.3 69.1 66.4 66.6 68.3 64.6 66.1 66.3 66.5 66.3 66.5 68.2 66.3 66.4 66.6 68.2 69.1 66.5 66.5 66.5 66.7 66.7 66.6 66.7 66.3 67.9 68.1 68.3 69.2 GE 66.4 68.2 68.3 68.3 68.5 69.0 69.1 69.2 GE 67.2 68.4 69.D 69.0 69.1 68.1 68.8 68.8 5000| 29.9 4500| 30.0 4000| 30.2 69.0 69.5 70.7 69.9 70.3 71.6 70.7 71.1 72.4 70.7 71.2 72.4 70.9 71.4 72.7 71.2 71.7 72.9 73.9 76.2 70.7 71.9 71.U 71.5 71.0 71.5 71.1 71.6 71.0 71.5 71.1 71.6 72.8 71 • 1 71 • 6 72 • 8 GE GE 71.6 72.8 71.8 72.7 72.7 72.8 12,9 GE 73.1 GE 35001 30.4 73.3 73.4 73.6 73.7 73.7 73.7 73.8 73.8 73.8 73.8 30001 30.5 GE 74.7 75.0 76.3 78.6 79.0 76.4 78.7 79.1 76.4 78.7 79.2 76.4 78.8 79.2 76.5 78.8 79.3 GE GE 2500| 30.7 2000| 31.3 73.8 75.6 74.8 76.8 75.4 77.5 75.9 78.2 75.9 78.2 76.5 78.8 79.3 76.6 78.9 79.4 1800| 31.4 1500| 31.8 76.D 77.4 77.2 78.9 77.9 79.7 78.7 79.3 79.3 79.5 GF 78.6 81.3 81.4 81.5 GE 80.6 80.7 81.1 81.2 GE 1200| 32.0 79.1 80.7 83.6 83.7 83.8 85.4 86.8 88.5 1000 | 32.1 900 | 32.1 82.9 85.5 86.9 88.6 85.5 86.9 GE GE 80.8 80.8 81.5 81.8 82.8 83.7 84.2 85.5 84.4 85.7 85.2 86.6 85.3 85.5 86.9 85.6 87.0 88.7 85.5 86.9 86.3 87.8 88.6 GΕ 800 | 32.1 85.3 86.9 87.2 88.3 700 | 32.1 600 | 32.1 82.0 88.1 89.1 89.6 89.7 90.0 91.9 90.1 90.1 90.2 90.2 90.4 91.1 91.9 82.4 91.9 92.0 500| 32.1 400| 32.1 300| 32.1 85.6 85.9 85.9 87.8 88.1 86.3 93.2 94.8 96.1 93.5 95.3 96.7 93.8 95.5 97.1 G E G E 82.7 82.9 92.4 93.7 93.4 95.1 93.4 95.1 93.5 95.2 90.2 90.7 91.7 92.7 93.6 95.3 91.0 91.5 92.7 94.2 GE 82.9 91.3 91.8 93.2 94.4 96.5 96.6 96.7 96.9 94.7 97.6 2001 32.1 82.9 88.3 96.6 100 i 32.1 94.7 96.7 97.8 98.0 98.6 GE 01 32.1 82.9 93.3 94.7 95.4 96.7 97.3 97.4 97.8 100.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

												MONTH			(LST):	#LL	
	LING									IN STATE							
1		GE.	GE	GE,	GE	GE .	GE	GE	GE	GE	GE .	GE	GΕ	GE	GE	GE	6E
	ET		6		4		2 1/2		1 1/2			3/4 	5/8 •••••	1/2	5/16	1/4	
0	CEIL I	28.6	58.2	59.0	59.4	59.6	59.6	59.7	59.8	59.8	59.8	59.8	59.8	59.9	59.9	59.9	60.3
-	2 0 0 0 0 I	31.3	65.1	66.D	66.4	66.7	66.8	66.9	66.9	66.9	67.0	67.0	67.D	67.0	67.0	67.1	67.2
	180001		65.4	66.2	66.7	67.0	67.0	67.1	67.2	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.4
	1 6000 I	31.4	65.5	66.4	66.8	67.1	67.1	67.2	67.3	67.3	67.4	67.4	67.4	67.4	67.4	67.4	67.5
	14000 İ	31 - 6	65.9	66.8	67.3	67.5	67.6	67.7	67.7	67.8	67.8	67.8	67.8	67.8	67.9	67.9	66.0
	120001	32.1	67.1	68.0	68.5	68.8	68.8	68.9	69.0	69.0	69.0	69.1	69.1	69.1	69.1	69.1	69.2
	1 0000 I	33.0	69.7	70.6	71.1	71.4	71.5	71.6	71.6	71.7	71.7	71.7	71.7	71.7	71.7	71.8	71.9
		33.1	69.9	70.9	71.4	71.7	71.7	71.8	71.9	71.9	72.0	77.0	72.0	72.0	72.0	72.0	72.1
		33.8	72.2	73.2	73.7	74.0	74.1	74.2	74.2	74.2	74.3	74.3	74.3	74.3	74.3	74.4	74.5
		34.2	73.0	74.1	74.6	74.9	75.0	75.1	75.2	75.2	75.2	75.2	75.2	15.3	75.3	15.3	75.4
	60001	34.5	73.7	74.8	75.3	75.6	75.7	75.8	75.9	75.9	75.9	76.0	76.0	76.0	76.0	76.0	76.1
		34.9	75.2	76.3	76.9	77.3	77.3	77.4	77.5	77.5	77.6	77.6	17.6	77.6	17.6	11.1	17.8
	4500 [75 - 8	76.9	71.5	17.9	78.0	78.1 79.9	78.2	70.2 80.0	78.2	78.3	78.3	78.3	78.3	78.3	78 - 4
		35.5 35.8	77.4 78.3	78.6 79.6	79.3 80.3	79.7 80.7	79.8 80.8	80.9	80.0 81.0	81.0	80.0 81.1	80.1 81.1	80.1 81.1	80.1 81.1	80.1 81.1	80.1	80 - 2 81 - 2
		36.1	79.8	81.3	82.0	82.5	82.6	82.8	85.8	82.9	82.9	83.0	83.0	83.0	83.0	63.0	83.1
	25001	36.4	81.1	82.7	83.4	84.0	84.1	84.3	84.4	64.4	84.5	84.5	84.5	84.5	84.5	84.6	84.7
		36 - 7	82.5	84.2	85.0	85.6	85.7	86.0	86.1	86.1	86.2	86.2	86.2	86.2	86.2	86.3	86.4
		36.8	82.9	84.7	85.5	86.1	86.3	86.5	86.6	86.6	86.7	86.7	86.7	86.8	A6.8	86.8	86.9
		37.1	84.2	86.1	87.1	87.8	88.0	88.2	88.4	88.4	88.5	88.5	88.5	88.6	88.6	88.6	88.7
	12001	37.2	85.5	87.5	88.6	89.4	89.6	89.9	90.1	90 - 1	90 • 2	90.3	90.3	90.3	90.3	90.3	96.4
	10001	37.3	86 . 4	88.6	89.8	90.8	91.0	91.4	91.6	91.7	91.8	91.9	91.9	91.9	91.9	91.9	92.0
		37.4	86.8	89.2	90.5	91.6	91.8	92.3	92.5	92.6	92.7	92.8	92.8	92.8	92.8	92.9	93.0
		57.4	87.2	89.8	91.3	92.5	92.8	93.3	93.6	93.7	93.8	93.9	93.9	93.9	93.9	94.0	94.1
		37.4	87.5	90.2	91.8	93.2	93.5	94 - 1	94.4	94.5	94.7	94.8	94.8	94.8	94.8	94.9	95.0
	600	37.4	87.8	90.6	92.4	93.9	94.3	94.9	95.3	95.5	95.7	95.8	95.8	95.8	95.8	95.9	96.0
		37.4	87.9	90.9	92.8	94.5	94.9	95.7	96.2	96.4	96.7	96.8	96.8	96.8	96.9	96.9	97.0
		37.4	88.0	91.1	93.0	94.9	95.4	96.3	97.0	97.3	97.6	97.8	97.8	97.8	97.9	97.9	98.0
		37.4 37.4	88.0 88.0	91.1 91.2	93.1 93.1	95.1 95.2	95.6 95.7	96.6 96.7	97.4	97.8 97.9	98.3 98.5	98.4 98.8	98.5 98.9	98.6 99.0	98.6 99.1	98.7 99.2	98.8
		37.4	88.0	91.2	93.1	95.2	95.7	96.7	97.5	98.0	98.6	98.9	99.0	99.2	99.3	99.5	99.9

U S AIR FORUM ENVIRORMENTAL TECHNICAL APPLICATIONS CENTER

TOTAL SKY SOVER

Second Mays STATIONS IN PROCESS OF MARK, CART. SLW, EACHIN, CVSNOAST, & ORSOUNDE MARK USES AS INFUL FOR THE SETAL SKY SOVER.

CLEAR WAS CONVENTED IN 0/10

SUBTIFIED WAS JUNIER HE 10 3/15

BROKEN WAS CONVERTED IC 1/10

CVasta, T Sa Sell Comment IC 1771

CB (MACE) MAS CONVERTED TO 10/15

TATION NUMBER:	724505	STATION	NAME:	MCCONNEL					PERIO Mont	H: JAN				
••••••	• • • • • • •	• • • • • • • •	• • • • • • •	PERCE	NTAGE	FREQUE	ICY OF	ENTHS OF	TOTAL SK	Y COVER	· • • • • • • • • • • • • • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •
HOURS (LST)		0	1	2	3	4	5	6	7	8	9	10	MEAN	ORZ
00-02	36	1.7	• • • • • •	17	.9	* • • • • • •	• • • • • •	• • • • • • • • •	•••••	• • • • • •	13.0	30.4	4.7	925
03-05	1 41	-1		15	- 3						10-4	33.2	4.7	926
06-08	1 27	.9		2.3	. 8						12.4	36.0	5.4	926
09-11	1 19	. 9		30	. 7						17.7	35.7	6 • 1	926
12-14	1 13	1.7		31	.0						19.3	36.1	6.3	929
15-17	1 10	1.9		34	. 8						19.2	35.1	6.3	930
18-20	1 19	.4		31	. 7						16.6	32.4	5.7	930
21-23	1 39	. 2		20	•5						12-6	31.7	4.9	927
														7419
TOTALS	• • • • • • •	STATION	NAME:	•••••	.7	к 5	• • • • • •	• • • • • • •	PERIO	D OF RE	15.2 	33.8 77-86	5.5	
••••••	• • • • • • •	STATION		MCCONNEL	L AFB			TENTHS OF	HONT	H: FER	CORD:	• • • • • • • •		
••••••	724505	STATION		MCCONNEL	L AFB			TENTHS OF	HONT	H: FER	CORD:	• • • • • • • •	MEAN	
TATION NUMBER:	724505	STATION	• • • • • •	MCCONNEL PERCE	L AFB	FREQUE	CY OF		MONT TOTAL SK	H: FER	ECORD:	77-86	••••••	TOTAL
TATION NUMBER: HOURS (LST)	724505	STATION	• • • • • •	PERCE	L AFB	FREQUE	CY OF		MONT TOTAL SK	H: FER	CORD:	77-86 10	MEAN	OBS
TATION NUMBER: HOURS (LST)	724505	STATION	• • • • • •	PERCE 2 17	L AFB NTAGE 3	FREQUE	CY OF		MONT TOTAL SK	H: FER	CORD:	77-86 10 36.0	ME AN	TOTAL OBS
TATION NUMBER: HOURS (LST) OO-O2 03-OS	724505	STATION 0 3.7	• • • • • •	PERCE 2 17 23	L AFB	FREQUE	CY OF		MONT TOTAL SK	H: FER	9 12-4 13-0	77-86 10 36.0 36.6	ME AN	831 085 101AL
TATION NUMBER: HOURS (LST) 00-02 03-05	724505	STATION 0 3.7 3.1	• • • • • •	PERCE 2 17 17 23	L AFB NTAGE 3 .9 .2	FREQUE	CY OF		MONT TOTAL SK	H: FER	9 12.4 13.0	77-86 10 36.0 36.6 42.0	ME AN 5.3 5.4 6.1	101AL 0BS 831 830 829
TATION NUMBER: HOURS (LST) 00-02 03-05 06-08	724505	STATION 0 3.7 3.1 .1	• • • • • •	PERCE 2 17 23 23 26	L AFB NTAGE 3 .9 .2	FREQUE	CY OF		MONT TOTAL SK	H: FER	12.4 13.0 13.8 19.6	77-86 10 36.0 36.6 42.0	ME AN 5.3 5.4 6.1 6.7	701AL 0BS 631 83 ₀ 829
TATION NUMBER: HOURS (LST) 00-02 03-05 06-08 09-11 12-14	724505	STATION 0 3.7 3.1 3.1 3.1	• • • • • •	PERCE 2 17 17 23 23 26	L AFB NTAGE 3 .9 .2 .2 .6	FREQUE	CY OF		MONT TOTAL SK	H: FER	12.4 13.0 13.8 19.6	77-86 10 36.0 36.6 42.0 42.6 38.3	ME AN 5.3 5.4 6.1 6.7	701AL 0BS 631 830 829 843
TATION NUMBER: HOURS (LST) 00-02 03-05 06-08 09-11 12-14	724505	STATION 0 3.7 3.1 .1 .2 .1	• • • • • •	PERCE 2 17 23 23 26 30 30	L AFB NTAGE 3 .9 .2 .2 .6 .6	FREQUE	CY OF		MONT TOTAL SK	H: FER	12.4 13.0 13.8 19.6 20.9	77-86 10 36.0 36.6 42.0 92.6 36.3 37.4	ME AN	701AL 085 831 830 829 843 845

GLOBAL CLIMATOLOGY BRANCH USAFETAC

TOTALS |

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER FROM HOURLY OBSERVATIONS

AIR WEATHER SERVICE/MAC PERIOD OF RECORD: MONTH: MAR STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS 77-86 PERCENTAGE FREQUENCY OF JENTHS OF TOTAL SKY COVER HOURS ! TOTAL 5 0 ILST) İ 2 3 10 MEAN 088 927 00-02 | 37.0 15.5 11.8 35.7 5.1 03-05 1 33.6 17.7 12.1 36.7 929 06-08 1 23.8 926 20.6 18.3 925 39.6 09-11 I 21.9 22.1 6.6 16.4 930 12-14 14.7 25.2 18.4 41.7 930 6.9 15-17 | 11.5 24.5 22.6 41.4 930 18-20 | 13.7 28.2 18.0 40.2 6.5 21-23 | 31.9 17.1 11.7 39.2 5.5 930 39.0 7427 PERIOD OF RECORD: MONTH: APR STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS PERCENTAGE FREQUENCY OF TENTHS OF TOTAL SKY COVER TOTAL OBS HOURS ! 3 9 MEAN 0 2 5 6 10 (LST) | 899 00-02 | 30.3 34.0 21.1 14.6 5.0 03-05 (31.2 21.4 17.3 30.1 5.2 891 06-08 | 27.1 23.1 32.1 6.1 896 09-11 1 6.3 898 900 12-14 31.7 9.8 28.3 15-17 1 7.9 35.1 897 6.0 18-20 | 11.4 36.6 26.0 26.1 897 21-23 32.1 23.9 17.9 26.1 4.9

30.3

5.8

7176

TION NUMBER: 7	24505 ST	ATION NAI	HE: MCC	ONNELL AFT	3 KS				PERIO	OF RE	CORD:	77-86		
HOURS (LST)	0	1	2	PERCENTAGI 3	FREQU	ENCY OF	-	S OF	TOTAL SKY	COVER 8	9	10	MEAN	TOTAL
ua-az 1	26.8	• • • • • • •		25.8	· · · · · · · · · · · · · · · · · · ·	• • • • • • •	•••••	• • • • •	•••••	• • • • • •	15.0	32.5	5.4	927
03-05 1	21.1			26.1							20.5	32.3	5.9	926
06-08	8 • 5			27+0							29.4	35.0	7.0	925
89-11 i	7.1			29.0							30.6	33.2	7.0	930
12-14 1	4.1			34.1							32.8	29.0	6.9	930
15-17	4.0			37.8							32.5	25.7	6.6	930
18-20 l	5 • 6			39.8							30.2	24.4	6.4	930
21-23 l	25.4			26.1							19.0	29.5	5.4	930
TOTALS !	12.8			30.7							26.3	30 - 2	6.3	7428

STALTON NOWBER:	7245U:) 31A	IIUN NAME:	HLLU	NNELL AF	3 N S			MON	H: 10 0		77 00		
HOURS (LST)		0	1	2 2	ERCENTAGE	FREQUE	NCY OF T	ENTHS OF	TOTAL SI			10	MEAN	TOTAL
00-02	· · · · ·	8.0	•••••	••••	26.5		• • • • • • • •	• • • • • • •	•••••	• • • • • •	23.0	22.5	5-1	897
03-05	ι :	20.9			29.9						22.9	26+3	5.6	896
06-08	1	8.1			30.6						33.0	28.3	6.7	898
09-11	1	9.1			34.4						30 - 4	26 • 1	6.4	899
12-14	1	6.9			40.3						32.1	20 • 7	6 • 2	900
15-17	t	6.2			43.3						31.3	19.2	6.0	898
18-20	1	8.2			42.3						27.6	21.9	5.9	897
21-23	1 :	22.5			31.6						23.4	22.5	5.3	898
TOTALS	ı	13.7			34.9						28.0	23.4	5.9	7183

STATION NUMBER:	724505	STATIO	N KAME:	MCCO						DOIR ₃ 9 Honth	: JUL		77-86		
HOURS (LS7)	-	0	1	P 2		FREQUENC			OF	TOTAL SKY			10	MEAN	TOTAL OBS
00-02	1 38	.9	• • • • • • •	••••	30.5	••••••	• • • •	•••••	••••	• • • • • • • • • •	• • • • • •	16.4	19.3	3.6	929
03-05	1 30) • 1			34.0							19.5	16.5	4.4	930
06-08	1 19	5-1			38.4							28.6	17.9	5.5	929
09-11	1 17	. 1			42.4							26.4	13.5	5.0	927
12-14	1 10	.4			50.8							28.3	10.5	5.1	930
15~17	1 7	.9			56.1							29.5	6.5	5.0	928
18~20	1 13	.5			54.6							24.2	7.7	4.6	926
21-23	1 30	.9			41.5							15.5	12.1	3.9	927
TOTALS	1 50	1.6			43.5							23.6	12.4	4.7	7426

STATION NUMBER:	724505	STATION						PERIOD Month	: AUG		77-86		
HOURS (LST)		0 1			AGE FREQU			TOTAL SKY		9	10	MEAN	OBS
00-02	35	.4	• • • • • • • •	29.9)	••••	• • • • • • • • • •	••••••		16.7	18.1	4.2	924
03~05	1 33	.7		29.3	1					17.3	19.8	4.4	926
06~08	1 12	.4		37.5	,					30.1	20.1	5.8	921
09-11	1 13	3 • 2		41-1	l					29.6	16.1	5.5	925
12~14	1 8	••		46.8	1					31.2	13.9	5 - 6	9 3 0
15-17	1 5	• 9		56.7	,					27.9	9.5	5.2	929
18-20	1 11	.9		51.6	.					26.1	10.4	4.9	926
21-23	1 29	.4		38.6	•					16.8	15.3	4.2	923
TOTALS	1 18	•8		41.4						24.5	15.4	5.0	7404

STATION NUMBER:	724505	STATION	NAME:	MCCONNE	LL AFI	3 KS					OF RE	CORD:	17-86		
HOURS (LST)		0	ı	PERC 2	ENTAGI	FREQUENCY	0 F 5		5 OF 6	TOTAL SKY	COVER 8	9	10	MEAN	TOTAL OBS
00-02	1 38		• • • • • • •	2	4.1	• • • • • • • • • • •	•••	•••••	• • • •	• • • • • • • •	•••••	15.2	22.2	4.3	897
03-05	1 37	•8		2	3.3							15.9	23.0	4.4	888
U6-08	1 17	.3		3	6.1							22.0	24.6	5.5	683
09-11	1 17	•5		3	8.0							23.6	28.9	5.4	895
12-14] 13	.8		4	1.8							25.0	19-4	5.4	899
15-17	l 13	.0		•	0.1							28.1	18.8	5.6	900
18-20	1 18	.7		3	9.6							24.4	17.3	5 • 1	898
21-23	1 34	.9		Z	9.2							16.2	19.7	4.3	900
TOTALS	1 24	.0		3	4.0							21.3	20.7	5.0	7160

STATION NUMBER:	724505	STATION	NAME: MC	ONNELL AFB	KS			PERIOD Month		CORD:	77-86		
HOURS (LST)		σ 1	2	PERCENTAGE 3		oF 5	TENTHS OF	TOTAL SKY	COVER	9	10	MEAN	OB2
00-02	90	.8		19.5	•••••		• • • • • • • • • • • • • • • • • • • •	••••••		12.7	26.9	4.4	928
03-05	1 35	.8		21.4						14.2	28.6	4.8	918
06-08	1 25	•2		25.4						22.8	29.6	5 • 8	914
09-11	17	.7		29.0						23.7	29.6	6.0	923
12-14	1 18	• 3		29.9						24.5	27.3	5 • 6	930
15-17	1 18	•0		33.4						22.9	25.7	5 - 6	929
18-20	1 25	.3		33.3						19.4	22.0	4.9	928
21-23	1 39	.9		22.1						13.6	24.4	4.3	927
TOTALS	1 27	•3	••••	26.8	•••••			•••••		19-2	26.8	5+2	7397

STATION NUMBER:	724505 STA	TION NAME:	MCCONNELL AF	BKS				D OF RE	CORD:	77-86		
HOURS (LST)		1	PERCENTAG 2 3	E FREQUEN	CY OF TE	NTHS OF	TOTAL SK	Y COVER	9	10	HEAN	TOTAL OBS
00-05	1 35.0		14.9	••••••	• • • • • • •	• • • • • • • •	• • • • • • • •		15.4	34.7	5.3	898
03-05	j 32.9		19.0						12.7	35.4	5.3	896
06-08	1 19.9		24.3						18.9	36.9	6.1	896
09-11	12.7		29.6						18.4	39.3	6.5	900
12-14	11.9		31.6						20.7	35.8	6.4	899
15-17	12.8		31.7						23.4	32.1	6.3	900
18-20	1 22.1		31.3						16.7	29.9	5.4	900
21-23	i 34 • 2		19.7						15.2	30.9	5.0	900
TOTALS	22.7		25.3						17.7	34.4	5.8	7189

STATION NUMBER:	724505	NOITATE	NAME:	MCCONN	IELL AFB	KS			MONT	D OF REC H: DEC		77-86		
HOURS (LST)		0	1	P E F	CENTAGE 3	FREQUENCY	OF		TOTAL SK		9	10	MEAN	TOTAL
00-02	33	-1	• • • • • • •	• • • • • •	21.3	•••••	• • • •	• • • • • • • •	• • • • • • • • •		10.4	35.2	5.1	924
03-05	1 32	.7			21.0						11.1	35.2	5.1	929
06-08	1 22	.9			24.3						16.2	36.6	5.8	926
09-11	1 14	.8			26.3						21.8	37.0	6.5	926
12-14	j 15	. 3			25.2						22.9	36.7	6.5	930
15-17	1 13	•0			30.2						23.3	33.4	6.4	930
18-20	i 22	. 8			27.4						17.3	32.6	5 • 6	927
21-23	1 32	.4			22.0						10.4	35.2	5 - 1	926
TOTALS	1 23	.4			24.7						16.7	35.2	5 . 8	7418

STATION NUMBER: 724505	STATION NAME:	MCCONNELL AFB KS	PERIOD OF RECORD:	77-86
			MONTH: ALL	

	HOURS (LST)		0	1	2	ERCENTAGE 3	FREQUEN	ICY OF T	ENTHS OF	TOTAL SE	Y COVE	9	10	MEAN	TOTAL
					••••										
JAN	ALL	1	25.4			25.7						15.2	33.8	5.5	7419
FEB		ı	21.5			23.8						16.9	37.9	6.0	6713
MAR		1	22.4			21.7						16.9	39.0	6.1	7427
APR		i	20.0			28.1						21.7	30.3	5.8	1116
MAY		i	12.8			30.7						26.3	10.2	6.3	7428
JUN		J	13.7			34.9						28.0	23.4	5.4	7103
JUL		ł	20.6			43.5						23.6	12.4	4.7	7426
AUG		1	18.8			41.4						24.5	15.4	5.0	7404
SEP		ſ	24.0			34.0						21.3	20.1	5.0	1160
001		ı	27.3			26.8						19.2	26.8	5.2	7347
NOV		ı	22.7			25.3						17.7	34.4	5.8	7189
DEC		ı	23.4			24.7						16.7	35.2	5.6	7418
	TOTALS	1	21.1			30.1						20.7	28.3	5.6	67340

F

U S AIR FORCE ENVIRONMENTAL TECHNICAL APPLICATIONS CERTER

PART E

PSYCHROMETRIC SUMMARIES

In this section are presented various susmaries of dry- and vet-bulb temperatures, dev points, and relative lamidity. The order and somer of presentations follows:

- 1. Cumulative percentage frequency of occurrence derived from delly observations and presented by month and around for all years combined. These tabulations provide the cumulative percentage frequency to tenths of temperature by 5-degree Fabrenheit increments, plus menu temperature, standard deviations, and total number of observations in three separate tables as follows:
 - a. Daily maximum temperatures
 - b. Daily minimum temperatures
 - c. Daily mean temperatures

NOTE: Beginning in January 1964, daily maximum and minimum temperatures are routinely selected from hourly observations recorded on surface observing forms or from automated data collections for all Air Force operated stations. For those stations observing less than 24 hours per day, and where maximum and minimum temperatures are required but not recorded, these are also selected from hourly data from as early an January 1949 and later. Please refer to notations on summary pages and Station History for further information on reporting practices of individual stations.

- 2. Extreme values derived from daily observations with the extreme value selected for each year and month of record available. An annual (ALL MONTHS) value is nelected when all months for a year have valid extremes. Heans and standard deviations are computed for months and numual when four or more values are present for any column. Two tables of daily extremes are prepared:
 - a. Extreme maximum temperature
 - b. Extreme minimum temperature

NOTE: The following symbols, are used in the extreme data blocks:

- (1) * indicates the extreme was selected from a month with one or more days missing.
- (2) # indicates the extreme was selected from a month in which hourly temperatures were available for less than 2h hours for at least one day in the month.
- 3 Values for means and standard deviations do not include we universels for incomplete months.

Continued on Reverse

3. Bivariate percentage frequency distribution and computations of dry-bulb versus vet-bulb temperature.

These tables have been temporarily discontinued for the Russwo pending the advent of RUSSWO-2 in mid 1986.

- 4. Means and standard deviations These tubulations are derived from hourly observations and present the mean, standard deviation, and total number of observations for the eight standard 3-hour groups, by month and annual and again at the bottom for all hours combined. Records for all years combined are presented in the following three tables; DRY-BULB TEMPERATURE, WET-BULB TEMPERATURE, and DEW-FOIRT TEMPERATURE.
- 5. Cimulative percentage frequency of occurrence of relative humidity This summary is derived from hourly observations and presents the cumulative percentage frequency of occurrence of relative humidity by increments of 10% classes, plus the mean relative humidity and total number of observations in two tables.
 - a. Table 1 is prepared by menth and sumual, all years combined, with month being the vertical argument.
 - b. Table 2 is prepared by month by standard 3-hour groups, with the hour groups being the vertical argument and a separate page for each month. All years are also combined for this summary.

DAILY TEMPERATURES

LB-, B

CUMULATIVE	PERCENTAGE	FREQUENCY OF	OCCURRENCE
	FROM DAILY	OBSERVATIONS	

	'EMP "F	JAN	FEB	MAR	APR	MAY	אנונ	J. 1	AUG _	SEP	эдт <u></u>	NOV		ANN IA.
>	.15 -							. 7.	• •					• .
							•	i • 4.		• 4 -			•	• 1
2	<u>.</u>					•	· .	15.1	13.50	2				
2					• 1.	• .	بدوشة	41.0.	33.9.	1	• -		-	. 1
					•	1,	33.2.	37.4.	.د ۽ ٻنڌ	23.4.				1
					4 .2.	1	30.3.	43.0	7	43.1				
. ≥			a 1.	± . 1 .	13.4.	35 . 7.	10.5.	94.5.	21.2.	Sans	1000	• 4		22.1
, 2	<u>V</u>		1.4.		27.4.		71.2	23.44	1.2.	75.5	12.7			5 L
≥			7	.5.1.	44	75.4.	27.1	99.5.	3.3	20.1.	54.5	3	. د ه	4
-	2	1	١ .ن.	24.9.	61.	فيه شان	99.2.		1	42.50		22.0	4 * *	52.2
2	.	4.	13-1.		75.3.	25.4.	28 . 2.			11.0		· •	1 + 6	63.7
2	ہ ن	13.2.	22.	52.5.	1-42	13.7.	100.0			9.1.	62.4.	S	19.00	
>		24.1.	٠٠٠٠.	35.6.	73.9.	49.2.						22.00		15.5
2	4	. J. S Z.	51.9.	77.7.	97.9	1						7	43	A 5
•	-	٠٠٠.	4.	5.6.	99.1					1		90	ساقة ما دارد	
.*	: .	يراش بهدائين	15.6.		79.7						2.	24.4	77.4.	• i
*	~ .	4.	20.1	41.5	79.3							S - 4.	27	4
.*	~ _	25	و د مي	÷ . 3.	130.00							. 2 . 7 .	5000	· ? • -
			, i . 5.	46.5								4	6.7.	74.7
-	:	5.0.	والشاج أأأ وا	13.3.									. د د د د	9.4
.*			4 . d.	1									.4.5	- 3 • 6
:		9.7	1										's	69.5
.*	-												. 9	1
.*	-												المراقب المحارب	<u>:</u>
	-													
													_	
. *	_												-	
-														
:	**													
:	_												-	
,	_	,						,						
٠														
•													_	
•	-													
,														
	MEAN		ALLAN.		67.4.	15.44.	5: - 1.	32.3.	7.	£1.2.	14.3.	£4.4.	43.0.	د ب نه در
	S.D.	12.4661	4 - 27 - 1								74.13		2.191	.1.153

10'A1 OB5 1123 732 1023 99 1023 USAFETAC 021 5 (OL A) PEVIOUS EDITIONS OF THIS FORM ARE OBSOLUTE

DAILY TEMPERATURES

1.14.17

PAR DEIMS FOREGO PARCH DIRC SAT LA GIRATION WRO

STATE OF THE STATE OF

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
FROM DAILY OBSERVATIONS

TEMP OF JAN FEB MAR APR MAY JUN BIL AUG SEP * i 2 1.--27-1- 1--- 2-1 -1 01-5- 47-4- 17-- -4 27.1 85.0. 14.3. 30.0 ~ . ~ 97 A . 7 57.6 14.0 - ---146 · · 44. W. . W. .. 77. 1.70.00 100.0 37.7 79. . . . • • • 40.00 15. .. 57.0 Paga of the state 11. 76.5 - - 3 - - -----.... > • • • 40.00 7 1.7 '...2. . 70.0 24.0 . 2 . . . 15 🕶 27.6. 20.0 /9.6. 75.0 / 75.0 /2.8 /9.9. 41.4. 21 • 1 17 • 2 الشهائك العهيدات L . . 1. 51. 5.00 35.5. 47.1.1 1 ... 71.5. امر وسواد 1.9. 92 ml. 98 ml. 14.•7: 99 ml. نه 4 د د 7 د * • · · i . 9. التعسال المعلال الأمطار السا . a. . n . . > . . . 1. ... MEAN S D 1

USAFETAC 1 RM 0 21 5 (OL A)REVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

DAILY TEMPERATURES

A PAL CLIMATOLOS RANCH VIETIC STATER SERVICE MAC 17415 VOCONTELL AFFORMATE

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM DAILY OBSERVATIONS)

TEMP OF	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	oct	NOV	DEC	ANNUA
; -							• 1.						
					•		1.2.	. u .					
						• 4.	÷ 4.	_ 4.	• i.			_	
					•	7.	34.2.	24.7.	5	• 1.		-	
				•	J . i	. ۵ م ت .	∟5 . 0.	54.4.	19.7.	• 4.		-	1 .
				1	12	ين من	£7.6.	31.2.	20.4.	1.		18	20
			مميذ ه	. ت م	JL . C.	32.3.	97.4.	-5	59.1.	15.4.	• 4 -		3.2°
ن		• Å.	4	22.5.	∟£.	⊇ય ⊾3.	92.7.	9E.9.	.د ه 78	32.2.	1.5.	_	41
	٠	1.2.	1 3.	42.5.	79	99-1.	1-2.6.	100.0.	23.1.	53.4.	.ت. غ	. 2 .	4 _
_	• £.	4.1.	21.00	£2.3.	12.3.	150.2.			.د ه ت ي	5.	.نهـ1	2	5.5
		11.7.	34.0.	79.5.					49.4.	∴ 1 - û.	33	D . Y	5_
4	2 4 4.	22.3.	52.3.	9-46.	99.00.				29.3.	90.5.	12.0	17.0.	7.4
	<u>-2.3.</u>	34.	12.5.	95.7.	1-4				100.0.	92.9.	7 9.	34.3.	7.7
; .	4 7.	.2.5.	33.9	99.						. څخو د	35.4.	53.3.	ڭ ئ
· • -	51.E.	71.4.	32.3.	99.3						. 1.9.		74.5.	· · ·
2 .	13.9.	a2 🔐.	.5.3.	99.9.						1	7.5.	£4.6.	3~
2	79.	9	ني ۽ ي لا	. 15 - 5.							بهندي	-1	≎ 6-
	a . •2.	92.6.	ى 9 . ن.								. 2 . 9.	94.1.	غَ يَ
114 4	.5.4.	9.5.	¥3.9.				,				11 2.2.	18.3.	€ ≩
4 4	5.4.		150.0.									ذ. وا	3.4
	9.1.	1										9.7.	400
_	134.3												1
_													•
				_								_	
_					· ·							_	
-	•	•	•	•	•		•		•	•		-	
-	•	•	•	•	•			•	•	-		-	
	•	•	•	•	•							-	
-	•	•	•	•	•		•			•	•	-	
-	•	•	•	•	•		•		- •		,	-	
-	•	•	•	*	•		•	•	*	•	•	-	
-	•	•	•	•	•			•	•	•	•	-	
7	•	•		+		•	+		•	•	•	-	
-	•	•	•	•	•	- •				•	•	-	
**	•	•	•	•	*	•	•		•	•	•		
MFAN		F				⊤=+ ≠		RL_C.		•	•	35	

JSAFETAC 22 5 OL AJREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR MEATHER SERVICE/MAC

EXTREME VALUES OF MAXIMUM TEMPERATURE
(FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-86

1					•	HOLE DEGI	1-1-H-5-	KCMHETI					ALL
YEAR !	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	130	NO V	LEC	MONTH
53	• • • • • • • •	• • • • • • • •	• • • • • • •	• • • • • • •	•••••	••••	• • • • • • •	• • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • •	59	• • • • • • • •
54	67	83	79	90	87	104	114	106	104	96	77	65	11
55 l	64	65	86	91	92	91	102	101	98	86	77	81	10
56 l	68	8 🖸	87	94	98	105	104	107	101	90	77	67	10
57 [66	68	75	77	83	96	102	102	95	85	74	63	10
58	57	68	57	8.2	94	99	100	100	95	89	75	62	10
59 I	61	64	80	91	89	102	97	102	96	78	77	63	10
1 03	66	62	8 D	85	89	103	101	99	92	8.8	73	64	10
61	58	69	76	87	88	96	100	101	96	82	66	64	10
62 1	58	79	79	8 3	100	95	102	105	97	90	70	64	10
63 1	59	70	84	89	93	98	104	108	92	93	76	62	10
64 1	71	5 7	74	83	99	101	105	107	98	85	77	57	10
65 İ	69	68	76	85	87	94	100	98	92	92	75	66	10
66	63	61	8.3	8 2	91	95	105	104	91	90	76	74	10
67 I	74	72	88	87	99	92	96	100	89	68	70	61	10
68	66	61	81	84	90	97	103	109	92	89	72	60	10
69	55	69	74	82	90	99	103	107	95	89	72	64	10
70 J	63	78	15	89	8.8	100	106	106	102	83	71	69	10
71 1	70	65	78	84	90	99	104	96	101	89	72	61	10
72 I	56	82	82	97	89	98	102	99	96	89	67	67	10
73	63	62	72	7.8	86	103	99	103	92	86	73	66	10
74	58	68	86	77	91	105	107	100	90	81	69	58	10
75 l	5.5	5.5	75	8 2	85	92	100	101	99	93	77	73	10
76 l	67	84	86	86	85	97	101	105	101	90	71	66	10
77	56	74	79	8 3	86	97	104	98	92	87	70	67	10
78 I	57	49	86	84	8.8	99	106	103	103	92	79	66	10
79	45	61	80	18	86	96	101	100	95	94	6.8	63	10
80	60	6.5	6.8	85	90	108	110	110	100	93	82	65	11
81	73	79	79	90	83	102	107	100	94	86	70	65	10

NOTES * (BASED ON LESS THAN FULL MONTHS)

R (AT LEAST ONE DAY LESS THAN 24 OBS)

CONTINUED ON NEXT PAGE....

GLOBAL CLIMATOLOGY BRANCH USAFETAC AIR WEATHER SERVICE/MAC EXTREME VALUES OF MAXIMUM TEMPERATURE (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-86

						MHOLE DE	GREES FA	HRENHE I T			•••••	•••••	• • • • • • • • • • • • •
YEAR	MAL	FEB	MAR	APR	HAY	NUL	-N-T-H-S JUL	AUG	SEP	OCT	NOV	DEC	ALL MONTHS
83	62	69	76	77	88	92	106	107	98	88	77	51	107
84	62	7 1	70	8.2	8.6	99	165	110	105	82	6.8	68	110
85 (48	55	78	85	100	104	107	103	103	82	73	53	107
86	67	75	8 1	85	85	96	108	92	92	78	62	50	108
PEAN (61.9	68.5	78.5	85.0	89.8	98.4	103.4	102.9	96.6	87.7	72.9	63.9	105.1
5.D. I	6.605	8.639	6 . 266	4.747	4.788	4.330	3.699	4.245	4.493	4.477	4.241	6.646	3.391
TOTAL OBS	1023	932	1023	990	1023	990	1023	1023	990	1023	990	1054	12084

NOTES * (BASED ON LESS THAN FULL MONTHS) 8 (BT LEAST ONE DAY LESS THAN 24 OBS)

EXTREME VALUES OF MINIMUM TEMPERATURE (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-86

1	WHOLE DEGREES FAHRENHEIT -M-O-N-T-H-S-												
YEAR I	JAN	FEB	MAR	APR	HAY	JUN	JUL	AUG	432	OC 1	NOA	DEC	MONTHS
•••••••	•••••	• • • • • • • •	• • • • • • •	• • • • • • • •	• • • • • • • •	•••••	• • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •	7	• • • • • • • •
53 54	О	16	13	29	32	48	67	64	50	31	20	16	(
55 [11	3	8	35	50	50	67	60	51	32	9	5	ì
56	5	6	10	31	46	52	65	52	46	41	15	15	č
57	2	14	19	24	42	55	63	63	50	26	24	10	3
58	6	17	18	35	45	50	60	55	43	35	15	8	
59 1	-11	2	22	30	44	55	56	62	45	30	9	23	~1
60	- 11	5	0	33	34	55	58	60	49	30	20	12	
61 İ	4	10	28	32	38	53	57	53	43	37	24	-2	-
62 1	-10	2	3	22	44	57	5.9	58	46	36	25	-2	-10
63	-7	11	23	37	35	59	66	58	45	35	24	ĩ	- 7
64	-1	13	15	28	45	51	60	53	41	30	9	2	-:
65	10	i	13	35	47	57	59	59	43	35	19	20	
66 1	-2	6	16	27	38	51	67	57	44	30	18	ī	-
67 1	7	9	1	30	37	54	56	54	39	34	23	7	
68	-2	9	16	25	38	50	58	60	47	38	23	- 3	
69 1	8	18	6	35	45	50	63	63	54	31	1.9	17	
70 J	3	11	22	27	42	5.3	5 2	58	44	32	12	15	
71	4	- 4	15	29	43	61	54	60	44	35	23	23	
72	-4	4	16	24	46	5 <i>2</i>	54	60	37	27	23	3	~1
73 1	-1	16	30	27	40	5.3	62	59	42	31	28	1	-:
74 1	-3	13	15	33	44	5.3	64	56	43	36	21	15	-
75 [8	5	11	17	42	4 8	54	65	45	34	6	6	
76 (-2	9	14	29	33	5.3	62	59	42	21	8	- 2	~;
77	-2	13	23	3 3	49	5.8	63	58	\$5	36	21	5	~.
78	-4	-1	5	32	40	54	61	58	48	35	24	8	~1
79 1	-6	-5	24	29	40	5.3	64	58	50	36	20	5	~1
80)	8.	3	7	3 3	39	57	64	65	45	26	21	8	
81 I	15	- 3	28 19	39 27	41	54 5 <i>2</i>	62	58	45 45	32 32	27 19	13 14	~ :

NOTES # (BASEO ON LESS THAN FULL MONTHS)
IAT LEAST ONE DAY LESS THAN 24 OBS)

CONTINUED ON NEXT PAGE....

EXTREME VALUES OF MINIMUM TEMPERATURE (FROM DAILY OBSERVATIONS)

STATION NUMBER: 724505 STATION NAME: MCCONNELL AFB KS

PERIOD OF RECORD: 53-86

WHOLE DEGREES FAHRENHEIT -M-O-N-T-H-S-													ALL	
YEAR	1	JAN	FEB	MAR	APR	HAY	JUN	JUL	AUG	SEP	oc t	NO V	CΕC	MONTHS
83	ī	16	7	25	29	35	46	60	69	38	42	22	- R	
84	1	-1	14	20	3 3	38	57	61	59	37	33	25	14	-1
85	1	- 3	1	25	35	49	50	65	60	35	33	15	- i	- 3
86	1	9	8	23	32	47	58	62	5 3	52	37	8	19	8
MEAN	<i>i</i>	1.8	6.5	16.2	30.2	41.6	53.3	60.9	59.1	44.9	33.0	18.7	£.4	-1.3
S.D.	1	6.845	6.596	8.039	4.633	4 • 796	3.450	4.168	3.864	4.802	4.294	6.156	7.658	4.733
AL OBS	1	1023	932	1023	990	1023	990	1023	1023	990	1023	990	1654	12084

NOTES * (BASED ON LESS THAN FULL MONTHS)
(AT LEAST ONE DAY LESS THAN 24 OBS)

SLUBAL CLIMATOLOGY PRANCH UMAFETAC Alimeather Service/Mac

MEANS AND STANDARD DEVIATIONS

ERY-BULG TEMPERATURES DEG F FROM HOUPLY DESERVATIONS

724 .5	YCCONNELL - FB KS	77-86	
STATION	STATION NAME		VEADS

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			318	TICH NAME						TEARS				
HRS LST		JAN.	FEB	MAR	APR	MAY	אטנ	JUL	AUG	SEP	oct	NOV	DEC	ANNUAL
	MEAN	25.	38			60.2			74.3		54.9		31.1	52.3
0-02	SD	11.7 41	2.6541	13.137	9.495	6.9.2	6.367	5.364	6.D8D	9.073	3.962	10.4581	10.931	19.431
	TOTAL OBS	. 933.	c46.	930	. 9.26	. 93	920.	930.	930.	900.	936.	. 91 0 .	93.	10956.
•	MEAN	24.6	2 1	2 G . Q	4 / • 7	56.2	67.4	73.8	71.7	65.2	53	45.1	29.0	53
98 t = 15	S D	10.7251												18.968
	TOTAL OBS	230.					900.							10956
	MEAN			20.0							£2 (. 7.0		55.4
	5 D	23.	୍∂8•3	39.2						_	52.6			19.738
5 - 0 f	TOTAL OBS	1 66 1.	-											
		930.	z46.	930	. 9	سدك لا	. 920.	930.	930.	90 L.	930	. 90 0 .	9_0,	10756
	MEAN		32.8	45.9	57.9	67.2	77.1	84.6	81.7	73.7	64	44.3	33.0	57.3
1	5 D	11.5:71												
• •	TOTAL OBS	3.20.			. 9_D.		. מבפ							
	MEAN				. ,		· - · · •							
		13.4	30.0	52.3					88.2		66.8	5 . 3	38 • 9	
11 -:	S D.	13.1 31												
	TOTAL OBS	. 9.35.	ä 46 .	932.		934,	920.	930	233.	920.	930.	. 92 0 .	930.	10956
,	MEAN	1 مد 3	41.2	54.5	65•2	73.3	£3.8	92.9	89.6	81.0	67.9	51.	39 a s	64.8
17	\$. D	13.4771												22.371
	TOTAL OBS	930,	±46.		9 . 5.				930					
					. ,				•					
	MEAN	70.5							84.0				34.7	59 . 6,
- 2	S D	11.5 51	3.9471											21.641
	TOTAL OBS	23	5 46 .	934.	. 91D.	9 34.	900.	929.	9.30.	900.	930	. ∠ ΩΩ .	927.	10952
•	MEAN	27.7	. १२. र	45.6	55.0	63.4	73.2	F2	77.8	72	57.4	42.9	32.3	55.
1-23	S D	10.8311											10.850	19.987
	TOTAL OBS	- 23							93					
	MEAN					, , , , ,			0 : 0		50.		77	56.7
All	5 D	2:.5					75.3			72.5			33.6	
HOURS	TOTAL OBS	12.26 1												
		744	6768.		71_9	744~		7439	7492	<u> </u>	<u>7440</u> .	7200	7454	8764

USAF ETAC FORM 0-89-5 (OL A)

CLOSAL CLIM TOLOGY DRANCH TRAFETAC A.T - EATHER SERVICE/MAC

MEANS AND STANDARD DEVIATIONS

SETTALLE TEMPERATURES DEG F FROM HOURLY CASERVATIONS

724' 5 11CONNELL AFB KS 77-86

S'ATION	•		STA	ATION NAME						YEARS				
HRS LST		JAN.	FEB	MAR.	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
3-32	MEAN S.D. TOTAL OBS	23.7 10.0061 - 4.0	28.4 1.591 246	9.263	9 72	6.945	64.5 5.799 900	3.863	4.548	61.2 8.316 900	8.5501	10.048	28.5 10.495 930.	47.7 17.556 10949
55	MEAN S D TOTAL OBS	22. 10.1051 - 730		9.235		7.135	5.898	3.845		8.389	8.896	10.014		
3:	MEAN S.D. TOTAL OBS	21. 10.2031 93.	1.499	9.336	9.281	7.121	5.786	3.668	66.4 4.801 930	8.179	8.853	9.784	10.707	46.5 18.149 10 44 9
-:1	MEAN S D TOTAL OBS	16311	1.670	9.266	9. 94	7.043	5 . c 36	3.425		5.206	7.860	9.668	1 .551	
17-17	MEAN S D TOTAL OBS	10.9771	1.814	9.295	9.169	· 251	5.753	3.464	72.1 4.541	5.077	7.585	9.723		_
15-17	MEAN S D TOTAL OBS	27.9 10.8931 929		9.175	8.8.7	6 . 862	5.534	3.382	71.9 4.397 930	7.791	7.621	9.566	11.723	17.157
-2	MEAN S D TOTAL OBS	10.1021	1.534	8.870		5 . 846	5.521	3.597	75.2 4.349	7.803	7.77		123¢	
1-23	MEAN S D TOTAL OBS	9.9481		8.093	8.860	6.720	5.538	3.755	68 • 2 4 • 456 930	8.005	8.122	9.456	29.4 15.27 927	
All HOURS	MEAN S D TOTAL OBS	13.7071	1.980	9.685	9.566	7.523	6.180	4.216		8.36%	8.616		11.62t	

USAF ETAC FORM 0-89-5 (OL A)

MEANS AND STANDARD DEVIATIONS

CEX-POINT TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

7245 5 MCCONNELL AFE KS

STATION NAME

77-86

HRS LST JUN JAN FFB MAR APR. SEP MEAN 34.0 23.3 23.6 32.9 42.3 52.6 11.4 64.3 62.8 57.1 45.1 43.2 5.D 11.-72 12.6511.3.58413.559 6.235 6.596 5.396 5.584 9.36410.42911.62612.472

TOTAL OBS 3.70 684 6.596 5.396 5.5 18.785 3.30 246. 930. 8 99. 929. 900. 92ć. 932. 90 U. 930. 397 930 MEAN 17.1 22.6 31.9 41.6 51.6 60.6 63.7 62.5 56.7 44.7 33.4 22.7 50 12.2 212.94510.59110.737 8.269 6.596 4.871 5.624 9.0.010.36311.55712.810 TOTAL OBS 930 646 930 970 627 920 027 027 027 42.5 18.910 930, 846, 930, 900, <u>9</u>27, 910, 927, 930, 900, 930, 897, 10947 13.3 21.2 3..6 42.0 52.3 61.2 64.5 65.1 56.9 44.7 32.8 22.1 42.5 5 D 12-51712-9911.77913-653 6-429 6-636 4-624 5-639 9-59 10-36511-22512-620 TOTAL OBS 370 846 930 9 0 908 9 0 928 937 900 930 897 897 93 J-0 n 19.373 910. 646. 930. <u>910. 926. 910. 926. 930.</u> 900, 930 697 929, 145, 930, 929. 923. 929. 929. 955. 930. 700, 93U. MEAN 17.7 5.6 34.5 44.7 55.4 62.7 (4.5 64.4 5d. 40.5 35.1 24.7 12.62112.57411.16011.561 9.299 7.191.6.700 6.43410.36210.67011.65712.635 S D TOTAL OBS 920. 646. 930. 9.6. 93<u>0. 930. 930. 930. 96</u>0. 930. 4 C D j 10.4 2..2 34.5 44.4 55.1 62.6 63.6 63.2 57. 45.9 35.7 24.8 MEAN 5 D 12.14712.3.311.16411.469 9.215 7.274 6.289 6.64610.18911.12811.50912.595 18.476
TOTAL OBS 2.6 244 07 070 770 93... 9_0, 4Ç.Ş. 933, 930, <u>930,</u> <u>930</u> 930 900 930 929. 846. MEAN 14. 25.5 34.2 44.0 54.5 62.5 63.8 63.0 57.0 45.7 34.3 24.1 S.D. 11.95512.27913.74411.172 0.932 7.121 5.996 6.232 9.65410.50111.18312.323 16.525 TOTAL OBS 938. E45. 932. 948. 928. 920. 929, 930, 900, 93j 1:09 24.7 34.1 43.5 53.6 62.4 64.4 63.0 57.1 45.3 33.7 23.0 S.D. 11.85512.35410.32010.617 6..68 6.456 5.426 5.800 9.37610.29510.99112.311
TOTAL OBS 276 846 97 800 846. 93J. 899: 9 Zu. ¥22. 930. 936. 45C. 9.10. 899 MEAN " 13.4 24.2 33.4 43.3 53.7 62.0 64.3 63.3 57.3 45.5 34.1 23.6 ALL 5 D 12.34 12.7261 ... 83611 ... 67 8.821 6.8:7 5.476 6.026 9.59710.56311.40012.598 15.9 2. TOTAL OBS 7436 6766 7440 71.8. 7433 72:0. 7431 7439 7200 7440 71.0 7434 876.79

USAF ETAC FORM 0-89-5 (OL A)

GLUBAL CLIMATOLOGY FRANCH L. AFETAC T. WEATHER SERVICEM AC

RELATIVE HUMIDITY

7245 5 STATION	MUCCANELL AFB KS	77-60	- ···
STATION	STATION NAME	PERIOD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

MONTH	HOURS		PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									TOTAL
	(LST)	10%	20°6	30%	40%	50%	60°.	70°.	80°c	90%	RELATIVE	NO OF
13.4	3-52	1:0.5	155.5	;9.8	97.4	72.8	1.3	54.1	32.5	12.9	72.4	÷3.
	<u> -55</u>	137.5	1 5.0	93.c	97.4	97.3	-4.5	02.2	34.1	11.1	3.5	y 5.
	<u>c-</u>	0.024	35.3	1.9.7	93.5	53.2	.5.9	63.3	75.1	17.	74.4	7 ?
	-11	1.7.0	100.0	79.	94.7	.7.2	70.7	44.5	26.2	5.0	55.5	9,19
	<u> </u>	1.00	9.7	95.5	1.5.1	55.5	47.1	25.7	.4.5	.1 . 4	: . <u>.</u> .	ن ۲
	1:-17	100.0	15.4	94.	80.4	01.8	43.9	24.5	12.3	7.1	= 7.:	9.39
	2	107.7	75.5	72.4	93	3.	51.7	3 / • .	23.4		 65•2	~ ;
	1-73	1	170.0	49.	91.1	7 . 3	75.4	49	.7.		7	9.7
				ļ						· · · · · · · · · · · · · · · · · · ·	- 	
4	-			<u> </u>							<u> </u>	:
.			ļ			-			<u> </u>	-	· ·	
errene si												· •
101	TALS	140.2	9.5	93	1 2 - 1	7.3	59	4 = .4	26.5	•	67	74.74

SUBBAL CLIMATOLOSY BRANCH BAFETAC AI REATHER SERVITEZMAC

RELATIVE HUMIDITY

724T. 5 CONNELL AFE AS T7-EE STATION STATION NAME PERIOD	MONTH
--	-------

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTA	GE FREQUENC	Y OF RELATIV	E HUMIDITY (GREATER THAN	4		MEAN	TOTAL
MONTH	(L.S.T.)	10°	20°¢	30∘.	40%	50%	60℃	70°-	80°.	901	RELATIVE HUMIDITY	NO OF OBS
ES	U = n .	1.3.5	175.0	,;,	95.1	1	4.5	50 . 7	77.4	<u> 45.65</u>	.75.7	
	<u> </u>	105.0	175.0	,9.5	9:09	1006	39.5	65.5	45.5	17.0	77.	→
	-7		150.0	100.0	17.5	57.8	+1.3	70.7	46.7	17.4	7:.1	<u> 645</u>
	-11	1 0.7	170.3	19.5	97.	-3.4	71.0	48.9	23.5	17.	70.7	: = 4
	11-	162.3	-5.9	95.3	2 C	04.5	5.5	32.0	22.3	7.	51.5	54
	1 -17	1 5.0	17.5	9.0	95.0	22.2	4 < . 1	31.1	17.0	1.5	57.4	. 4 و
	20	10	,9.4	95.2	5 1	77.5	55	46.3	4.5	10.	05.0	54
	1-23	100.0	150.5	79.1	92	54.7	70.6	57.ε	32	1 7 . 5	72.4	- 4
	ļ ļ										: - 	•
	<u>.</u>										· ·	
							ļ				<u> </u>	
												•
101	TALS	1 0.0	9.5	97.	93.1	5.1	72.2	53.0	32.5	17.1	- 3	676:

DELTAL CLIMATOLOGY HRANCH LINIETAC All Eather Service MAC

DE	IΔT	IVE	ш	I AA I	DITY
KE	LAI	IVE	пu	m	viii

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTA	GE FREQUENC	Y OF RELATIV	E HUMIDITY G	REATER THAN	1		MEAN RELATIVE	TOTAL NO OF OBS.
MONTH 	(L.S.T.)	10%	20°∘	30°-	40%	50°•	60°∘	70°.	80°-	90 -	YTIDIMUH	
:	<u> </u>	100.0	175.3	.9 . 0	<u></u>	1.1.1	75.7	52.7	23.4	• .	71.1	_ <u> </u>
	<u>ن 2</u>	1	100.0	<u> </u>	20.1	54.5	32.03	<u> tl.1</u>	34	2	<u> </u>	<u> 5 :</u>
	L25	150.5	120.0	100.0	97.5	95.2	د 35 و	1.4.5	25.1	14.5	75	<u>, , , , , , , , , , , , , , , , , , , </u>
	11	120.0	100.0	75.4	92.	77.3	4.3	31.1	21	• /	74.	9
	1 - 1 -	155.9		30.4	<u>د و ع 7</u>	20.4	34.5	21.2	12.5	4.4	1 4	7 -
	117	1 2.5	+37.c	34.	ز. 51	43.		1	11.:	1 2.7	50 • t	; ≀
	<u>22</u>	100.0	c ç.1	92.4	F 1 .	01.5	35.1	21.6	13.7	3	67.4	23.
	1-23	100.0	106.5	- ₹ • 7	54.2	53.5	21.7	37.	1,.5	.7	55.	93
·	·	ļ										
			1				1					
- •												
tot	ALS	15	9.4	45.6	37.	7 + . 5	57.9	30.5	2.2	7.0	24.1	744

CLUMAL CLIMATOLOGY GRANCH LEAFETAC ALL REAT ER SERVICE/MAC

RELATIVE HUMIDITY

THE STATE OF THE S	7247_5 STATION	CCC NELL AFB NO.	77-56	MONTH
--	-------------------	------------------	-------	-------

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTA	GE FREQUENC	Y OF RELATIV	E HUMIDITY (GREATER THAN	ı		MEAN RELATIVE HUMIDITY	TOTAL NO OF OBS
MONTH	(L.S.T)	10%	20°c	30°₊	40°°	50%	60°,	70%	80%	90		
۵,	U-02	12 - 2	120.0	138.0	1 + 5 • 1	71.7	77.4	53.0	27.	1.0	-1 - :	έ ;
	:-5:	1	100.0	1 .	7 y • . `	5.2	-3.6	62.5	35.9	<u> </u>	74.5	y 5
	L :	100.0	170.0	49.	97.7	70.6	43.	50.4	34.1	•	74.3	· · · · · ·
	-11	100.5	100.0	48.5	2.4.	ε4.7	5.02	33.	17.4	4.3	52.	·
	114	1 :0	9	91.3	٤	¬→•1	33.s	20	5	2.3	1:3.4	٠
	1 -17	1 7.0	0 • 4	54.2	50.1	42.2	127.0	16.	7.	7	: :50.3	913
	: -20	168.0	9.0	94.1	7	39.6	+1.	<u>'</u> - •	1	?	₹ 6. -	
	1-23	1 %	100.0	, 0 . :	- L • L	- 0.2	54.5	43.5	122		67.	<u></u>
	· · · · · · · · · · · · · · · · · · ·		i					İ				•
	:								· 	+		
		ļ								·····	•	
									! !			
101	ALS	1	7.7	96.	20.7	73.5	57.6		23.			71

USAFETAC	FORM JUL 64	0-87-5 (OL A)	
			-

L PAL CLIM TOLDO HANGA PRESTAC AT REAT ER SERVICEMAR

RELATIVE HUMIDITY

STATION NAME 77-13	MONTH -
--------------------	---------

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	 · ·		PERCENTA	GE FREQUENC	Y OF RELATIV	VE HUMIDITY	GREATER THA			MEAN	TOTAL
MONTH	LST	10",	20^-	30.	40°a	50%	60°:	70	80	90	HUMIDITY	NO OF OBS
.211	عاد حقايم	M.I.	1	4-2-	· · · · · · · · · · · · · · · · · · ·	, , 7 . 5	2	7:.2	4 • 5		<u> </u>	. •
	= * · ·,	1:	و. بر	<u> </u>	<u> </u>	7	1.4		- + ' · · · ·	<u>L</u> . <u>.</u> .	• • • · · ·	
	; - f .	122	1 • •	1 -1		, y \ ,	····	7:		: !_	<u> </u>	-
	-:1	1-10	<u>, 110.0</u>		-4.5	<u>. 2.5</u>	<u> </u>	<u> </u>	. 1 <u>7</u> •.=	1	· :	
	1-1-	1_1_	, , , ,	,,7.:		127.1	- <u></u>	2. • *	1,•		. '• '	
	1 -1.7	10.	<u> </u>	÷ + + + + + + + + + + + + + + + + + + +	7 . ,	<u></u>	· · · · · · · · · · · · · · · · · · ·	. 1:	1.		. •	
		10.0	1		· · · · · · · · · · · · · · · · · · ·	' + •	<u></u>					
	. 1-53	1 .	1.12.5	1		•		•			***	
	•				•							
		.		·	•	+	•	- • •		•	•	
		•		- 		•	• =					
r · · · · -	• • •	≥: ‡ ————		- 	e t o see see	+	s: 4 ====	_ + ====	: : :	· •		ı
1	OTALS		1.1.1.	1.5		<u> </u>	· _ • i					-

DE PAE CLIMATCEODY HANCH LIGHTETAC A LEAT EN SERVICEZZAL

RELATIVE HUMIDITY

STATION CONNEC	E FE / STATION NAME	7 - i >	e e e e e e e e e e e e e e e e e e e
----------------	---------------------	---------	---------------------------------------

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)


	HOURS	•			PERCENTA	GE FREQUENC	Y OF RELATIV	E HUMIDITY C	GREATER THAN			MEAN	-, -4,
HINON	ις τ	10		20	30	40 -	50	60	70	80	90	· RELATIVE HUMIDITY	
	'	.1 .					1			3 2	:	· *±•;	
				• .		· · · · · · · · · · · · · · · · · · ·	. 1		<u></u>	1 • 1	· ·- <u>·</u>		
			Į.			· · · <u>· · · · · · · · · · · · · · · · </u>	17.5	1.	1.	7 . 7			
	- 1	į.	÷				?	4.5	2	11.	. 1.1 .		
	1-			· • I	. ::-		<u> </u>	<u> </u>	11	2 • 2			
	, -:·			7.0	2.	7	ر ۱۹۰۰	<u>, , , , , , , , , , , , , , , , , , , </u>	17.7		, . .		
	· ·	. •		7 •			. 4;	25.1	21.4	_ •			
	1-			. •	ļ	- · <u>•</u>	41.4	7	4 • -	1	, ·	•	
						1			+		-		
					; •	i •		ļ					
					-•	: +			=: +				
						_+			±4 °		ı		
10	TALS		~	, ·		· · · · · · · · · · · · · · · · · · ·	7 .3	• 1	, ,				

USAFETAC FORM 0-87-5 OL A

- - -

AD-A179 196 MCCONNELL AFB KANSAS REVISED UNIFORM SUMMARY OF SURFACE AND ALL OF

END



MICROCOPY RESOLUTION TEST CHART
MATIONAL BUREAU OF STANDARDS SWIFA

DE AL CLIMATOLOS HANGH SELTAC AT LA SERVIC MAC

RELATIVE HUMIDITY

STATION STATION NAME PERIOD	MONTH
-----------------------------	-------

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS		PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									
MONTH	(LST)	10%	20°	30%	40°.	50°∘	60°	70%	80	90	HUMIDITY	NO OF OBS
یا د	14-0.	1 1.2	112.5		72.4	. 7	==-1	-1.4	17.5	1 2 • 1	66.7	42c.
	<u>21-11</u>	1-24-	11111	· · · · · · · · · · · · · · · · · · ·	2100	192.3	- : i e l	5:.	27.5		71.7	r 7.
	. ^ .	12	124.5	100	- • 9	72.7	75.0	15.	23.4	· · · ·	 • • • • • • • • • • • • • • • • • • •	i
	11	1	y • C	+ 45	-, -,	3 .7	72.7	15	4.5	•	14.7	<u> </u>
·	1,-14	. غــــــــــــــــــــــــــــــــــــ	<u> </u>	79.1			1	5.5	<u> </u>	• 1	3.5	7
	1 -17		44	72.	4	11.	• 5	···	1		· • -	· · · · · · · · · · · · · · · · · · ·
		<u>_</u> 2 وزر نز	<u> </u>	<u> </u>	· •1	41.5	1 -1	7.0	2.,	•••	47.6	479
	1-23	1		· · · ·	· · · · ·	11.	+1.5	÷ 2. •	7.		<u>53.</u>	· · · - · _ · · ·
		.	- •· ·	<u> </u>		-	ļ			+	·+-···	.
	•			ļ		 	-		-	<u> </u>	-i	·
		•	•			ļ		· -	ļ	·		4
ı	• • • • • •	- •	- 	 			ļ		ļ	 	<u> </u>	
T	OTALS	↑	1	. 2 .	7 .	J	7.04	25.	1	<u> </u>	-6	747,

DE BAL CLIMATOLOGY BRANCH BYAFETAC AL LEATHER SERVIC: MAC

RELATIVE HUMIDITY

724 5	YUCONNELL AFB KS	77-50	
STATION	STATION NAME	PERIOD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	1	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									
MONTH	(L.S.T.)	10%	20°≎	30°∘	40°•	50°.	60°.	70°	80	90	RELATIVE HUMIDITY	NO OF OBS
<u> </u>	<u>5-7</u>	1.0.0	173.0	19.3	3	. 59.	J	4	24.	1.	£a.,	970
	205	137.0	155.0	, , , 4	0,	70.9	1 +1 -5	<u> </u>	134.5		73.0	<u></u>
	-::	0.0	172.0	. 7 . 4		 > • ÷	4	_ 60 .	32.3	3.1	73.1	. د خ
	-:1	1 0.5	9.=	93.7	9,.2	55.4	1.1	27.	11-1			, ,
	11-	130.0	.9.4	٠7٠.	5	11.3	7 3	11.1	4.1	i	47.0	·
	1 7	100.0	0 • t	75.	4	12.7	15.00	7.	1	·	. 64 . 1	7
	z .	100.0	9.7	71.	64	47.3	1.2	1.•	۱	• • • • • • • • • • • • • • • • • • • •	1 • •	 .
	1-23	190.9	1 5.5	,	G.	75.5		34.	15.5	• 1		٧:,
	i → — — —										_	
	ļ		<u> </u>								<u> </u>	i
											ļ	
					ļ							<u> </u>
10	TALS	127.0	9.7	93.5	92.1	67.4	F •5	32.7	15.1	1.2	: ,, ,,	7439

IL HAL CLIMATOLOGY HANCH L MILTAC AL NEATHER SERVICE MAL

RELATIVE HUMIDITY

724: 5 CCCNNELL AFO AS TATION NAME PERIOD

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTAC	E FREQUENC	Y OF RELATIV	E HUMIDITY G	REATER THAN	I		MEAN	TOTAL NO OF OBS
MONTH	(L S.T.)	10°6	20°∘	30%	40%	50%	60°€	70°	80°	90%	RELATIVE	
٠.٠	0-02	1 7.5	100.0	79.7	95.5	62.5	75.	50.2	2406	7.3	7::.2	· · · · · ·
	 <u> </u>	122.5	122.5	<u> 23.2</u>	C y	7.1	76.4	04.5	340:	t	74.7	5
		1: 1.0	nes.	132.6	7 - 3	.5.9	10.0	65.0	35.5	! 	7	·
	-11	1.0.0	105.5	79.	93	71.4	47.2	25	12.4	3	62 • 6	97
	11-	1_3.3	·9·7	38.	6:	39.8	31.5	13.2	3.5		<u> </u>	,
	: 12 -17	1	5.9	3.5	5	0.	17.5	10.4	5.1	1.5	44: • 4	4
	-2	1	169.	95.7	70.0	ر 3 و 5 ر	34.5	12.0	7 . i	<u> </u>	54.	9
	1-23	1 3.8	9.9	99.6	90.3	5 . 5	50.4	31.00	15.3		64.0	4.
	i i		_								·	:
	i L										<u> </u>	
											<u> </u>	
10	TALS	10r.s	9.6	95.4	94.4	7 5	53.0	35.5	17.7	4.	51.	7

JEURAL CLIMATOLOGY RRANCH L MELTAC TO WEATHER SERVICEMMAC

RELATIVE HUMIDITY

7245 STATION	"CCONNELL AFB KS STATION NAME	7.7 - 5.3	MONTH
STATION	STATION NAME	PERIOD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN										TOTAL
MONTH	(LST)	10°.	20°	30°∘	40°	50°.	60°-	70	80	90	RELATIVE HUMIDITY	NO OF OBS
41	<u> </u>	1 • 2	1-3.5) G . G	1 \$ -> 1	53.0	٠	1 54 64	21.3	• 1	• • •	
£	<u>-</u>	<u>167.5</u>	1 4.4	100.	.1	92.	1.1	54.5	24.4	11.5	<u>'4.7</u>	9 1
		10 1.0	120.0	poc.	****	43.4	١٠,٠٤	56.6	41.4	12.1	75.5	97.
	- ' 1	1 . ^	5.9	76. S		17.1	4.4	34.7	11	<u>, • ; </u>	4.5	+ 1
	-14	1 •	-7.3		54.7	47.5	, s • .	4.5.	12.	3	1:2-1	1.1.
<u></u>	-17	1	4.5	17	A	41.7	1. • 3	1 1	1	[• · ·		٠,
	- <u>:</u>	1	₹5.9	93.		03.7	4:.3	29	17.	····	5. S	73
	1-23	1	1.50.5	98.	51	: •t	51.5	47.	300.	1		y ²
			·								+	
		··•								ļ		.
	· · · · · · · · · · · · · · · · · · ·	ļ			. 							
												· •
101	ALS	:33.0	5 • 9	93.	84.5	72.1	51.7	42.5	24.5		63.7	744

PORM 0-87-5 (OL A)

DE HAL CLIMATOLOGY ERANCH L V ETAC AL HEATHER SERVICEYMA

RELATIVE HUMIDITY

STATION NAME

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS			PERCENTA	SE FREQUENC	Y OF RELATIV	E HUMIDITY O	REATER THAN	1		MEAN	TOTAL
MONTH	(LST)	10°°	20°:	30°-	40%	50%	60° c	70	80	90	RELATIVE	NO OF OBS
	المتعددة	<u>.1.2.5.</u>	1-1-1	<u> </u>	+ 92.3	75.9		52.0	· · · · · · · · · · · · · · · · · · ·	1:	. 29.5	. 3-1
	<u> 12-01</u>	101.0	100.0	135.	15	193.2	7.3	7. •	! + "= = "	<u> </u>	. ? 7	s 7
	1 - 1 - 1]1. u <u>•</u> \$_	100.0	130.:	152.5	79.1	21.1	74.	: 45.	17.4		. 5
_	L 1.1	<u> </u>	4:2.0	17.6	72.2	57.2	53.2	15.0	71.5	<u>, 4 : • 4 .</u>		
	11.	<u> 117.0</u>	9.9	75.	. • •	51.4	45.	22.4	1.7.	_ <u> </u>	·	
	1 -17	1.0.0	79.	73.	77.,	5à•à	39.9	27.3	11.1		7.	
	<u>e</u>	<u>ir 5 • 3</u>	-9."	7.,		:1.3	1.0	3- •.	 <u> 22.4</u>	1.2	nê.	
···	1-25	128.0	10.	9.7	7: • !	· .7	14.3	51.	i <u> </u>	1	1.	
	·		 					J			•	•
	<u> </u>						Ì		<u> </u>		·	
	•										•	•
τo	TALS	12 7.0	9.9	٠, ع د ا	۵).4	- 3 - 3	27	5. •4		11.		71

USAFETAC PORM (UL 64 0-87-5 (OL A)

IL :-AL CLIMATCLOGY HEANCH OUT TAC AL GEATHER SERVICE/MAC

RELATIVE HUMIDITY

7.2 4 1 5 STATION	STATION NAME	7.7 = 5 PERIOD	C MONTH
SIAHOM	STATION NAME	PEROD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

	HOURS	→	MEAN	TOTAL								
MONTH	(LST)	10%	20%	30%	40%	50°<	60°₹	70	80	90	RELATIVE HUMIDITY	NO OF OBS
,2 ° ,	10-04	1 ^.5	172.	+	9	y:.9	<u> </u>	<u> </u>	. 34 <u></u>	.11.9		. , , .
	i -:	p	1.12.2	100.0	- 7.5	75.7	· · · · · · · ·	63.1	7:.5	.11.	•	, , ,
	1	1.	121.5	<u>,</u>		1.5	-7.3	<u>-6.7</u>	41.9	<u>.</u>		, (
	-11	1 1.3	1	¥	1, .,	₹7.4	15006	46	7.	· · · · -	. t y . ?	,
	1 -1	1	۶.6	77.	F / • 5	.4.3	42.5	21.1	14	<u> </u>	· · · ·	, , ,
	<u>11</u>	1 .0	19.5	, , .		52.7	1 42.4	-+=	12.4	7	57.?	
		11	.9.7	94.6	,	03.0	6 .	· 		. *•	. 16.1	, ,
	1-73	137.7	100.0	.0.4	9 5 . 4	-1.7	7:09	<u> </u>		4	. '1.	
• .	•	ļ	- •		ļ		<u> </u>	i -	·		• -	
	.	<u> </u>	ļ		· 	ļ +	ļ	ļ	+ · · · · · · · · · · · · · · · · · · ·	• :=	•	
		 		<u> </u>				<u> </u>	, i	.		
	·								1			<u> </u>
το	TALS		ب پ	9	0	~*.1	65	47.2	27.7	,,	68.7	7434

USAFETAC	IUL 64	0-87-5 (OL A)		
		· Annual	_	

RELATIVE HUMIDITY

AL TOIMATOLOS FRANCOS TAC S FAT SA SINVIC FAC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

C VIEL AF AT STATION NAME PRIOD

MONTH	HOU	is .		PERCENTA	GE FREQUENC	Y OF RELATIV	E HUMIDITY C	GREATER THAN	 I		MEAN	TOTAL
	157	10	20	30	40°	50	60	70	80	90	RELATIVE	NO OF OBS
J	, t,		. y.ç	, ^{y 4} • 5		3	, 3¢ ;	. 47 • 4_	, 82 .		.67.	. 741.
5.2		427.2	. <u> </u>	. ;?	4.4.4	1	.14	<u>. 22 •</u>		. 4. • 1		. 57 mg .
~				, ** . _{2.}		74.0	·	<u></u>		· = i • •	4.	. 44
		2-1-0				<u> 1</u>	. 11.6	3°.		•:	1•.	71 5
		5.	122.4	↓: •_'		4.1	<u> </u>	.a3•a			. 22.	
J	•	12.00	<u> </u>	<u> </u>		7 . 3	1			• ;	• • • •	
٠		121.	t	, <u>5</u> 1	. 7	÷				•		
Α		::::0	5 · 1	↓ · ' · ± ±		67.4		<u>. 3.</u> •				**.*.
		.1 •	<u></u>	1 - 2	+	<u> </u>	<u> </u>	٠		. •	. 1.	
			- + +	, ·	+	7 -1	7.7	45	. 4.1	• · · · •	•	744
. %		140) c • "			6-1		∔ <u>.</u> •		. •	. 7.
, , , , ,		<u>ئەس</u> ىرلىدى	* • 5	144,			100.5	47	1.7.1	. ?		*
	TOTALS	j:∙5	7.6	<u> </u>	<u></u>	15.1	9. • 9	41.		1	· > • .	1.16 %

U S AIR FORCE ENVIRONMENTAL TECH TOAL APPLICATIONS CENTER

PART F

PRESSURE SUMMARY

Presented in this part are two tables giving the means, standard deviations, and total number of observations of station pressur: and sea-level pressure by month and annual for the local hourly observations corresponding to the eight 3-hourly synoptic times GCT. The same computations are also provided at the bottom of the page for all hours combined. All years of data available are combined in both of these tables, although the overall period is limited by service as indicated below.


NOTES: Station pressure not reported for all services until late in 1945.

Station pressure reported only at 6-hourly times for Air Force stations from Jan 64 - Jul 65.

METAR stations do not report Sea-level pressure for the period Jan 68 - Dec 70.

- 1. Station pressure is presented in the table in inches of mer uny.
- 2. Sen-level pressure is presented in millibars.

Provided below is a scale to convert station pressure values in indice of mercury or millibars to pressurealtitude in 1000's of feet. This scale is an enlarged motel of the pressure-altitude scale in the Emithsonian Meteorological Tables.



MEANS AND STANDARD DEVIATIONS

STATICA PRESSURE IN INCHES HE FROM HOURLY OBSERVATIONS

124 5	ان 'دا	CONN	ELL	AFS KS				77-86	5						
4 (**	`			STAT	ION NAME						YEARS				
HRS EST			N	FEB	MAR	APR	MAY	JUN	ĴΟŧ	AUG	SEP	ОСТ	NOV	DEC	ANNUAL
	MEAN	2. •	6742	8.6382	8 - 4942	86.4772	8 . 4592	8.4852	28 - 5232	c.5392	3.5462	5.5712	6.579.	8.631	2 - 549
2	5 0		2 1	.231	.234	.1'6	• 152	.124	د93.	.1~0	•157	.173	.224	.254	•19€
	TOTAL OBS		31	22.	310.	3 _2 ,	210.	.3 0 .	310,	310.	. ئا 30	310,	300	310	3651
	WEAN	 2 •	6717	8.5992	8.4872	28.4652	4472	8.4752	28•5192	8.5352	'&•5432	3.5652	28.5722	3. 25	26.542
	5 0		22	.231	.236	·1 6	· 15»	.127	.393	•1:3	•15 a	.175	.224	.259	.2 0
	101AC 085		31	2.2.	3 1 0.	3.5.	.13.	300.	31C.	310.	30C.	310	3 L O	31	3652
	MEAN	2 •	ь 652	E.6 12	8.4927	23.4762	8•4642	8.4932	28•5362	8.5502	8 .5 5.72	18.5752	86.5 72	8.621	26.553
	8.5		22	.220	.241	.1.9	· 151	.129	. 96	•1 ° 3	•15a	.181	.224	.26	• = 1 5
	TOTAL OBS		31 .	2.2.	312.	3 C.	.10 د	300.	310.	310.	300.	310	30 0 ,	31	3651
	MEAN	2:•	6562	E . 63 2	8.5182	28 • 4 49 2	20 • 4842	3 • 5 : 9 2	28•553 2	25.5662	16.58 L I	8.032	? 3 • 6€62	6.651	28.574
	s D		2 1		.244	. 234		-132		.1-5	.161	.195		.26	•. 3
	10141 080		31 .	22,	310,	215.	310.	3 Q.D.	31¢.	310.	300,	310	3 E,	31	3 o 53
	MEAN	" 2 •	5912	6.6292	8.5112	8 • 4 9° £	 6 • 4752	9.4962	28•53¢2	3.55.2	`8• 5 652	8.5982	86.5932	6.646	28.5±4
1	5.0	-		.226			• 159						.228	-	• . 23
	TOTAL OBS		31	£	. 10 د	3 LD.	_ 010,	300.	310.	310.	30°,	317,	300,	31	. 355⊾
	MEAN	- -	63:2	6.5742	8.4612	28 - 4 4 6 2		8.46	28 - 4981	8.5082	8.5142	2: . 5392	20.5442	h.601	28.519
	5 D						 154 				-		• ₹28		• 7 9 3
	TOTAL OBS		31	2_2.	310.	3 LD.	316.	300.	316.	316.	3	31 ö.	∃f D,	31.	3057
	MEAN	2 .	65.2	8.5812	8.4572	28 • 4 36 2	e.4192	8.435	28 • 4702	6.4:52	1 : • 5032	20.5382	20.5552	· .619	28.51
	5 D		224	•21	.233		. 149			•154	.163	.174		•2 5	• i • 9
	TOTAL OBS	-	316.	2_2.	.10	JLD.	310.	300.	315.	31	30 y.	210.	30Q,	3 L = .	3651
	MEAN	 2 •	66 2	6.6 42	8.4832	8.4 68 E	3.4462	8.466	28.5012			8.5672	20.5752	s.637	28.54.
1	5 D		22 -	.221	.231	• 1 - 5	147	•122	.194	.101	-159	.172	25	.243	•136
*	TOTAL OBS	-	315.	2_2.	310.	3 00.	214.	300.	310.	31	3£ 2.	315.	3 CC.	3C7.	3057
ALL	MEAN	· .	6692	6.6 32	8.488Z	28•469	8 • 4 5 P	8.477	28.5172	28.5322	20.5432	8.5682	88.57 5 2	8.629	28.544
HOURS	S D TOTAL OBS	•	2.2	.226	.238	• 1 · 7	• 157	•129	-	-	.161	. 179	.225		•2C1
	TOTAL OBS	2	<u>4D.</u>	2250.	2483.	24 CD.	2550.	2400	248	248	2400	2491	2420	2475	29214

SE MAD CLIMATOLOG CHANCE SETAC AT LEAT ER SEMVICEMMAC

MEANS AND STANDARD DEVIATIONS

CA LEVEL PRESSURE IN MBS FROM HOURLY OBSERVATION:

7241 5		CONNETE		S ATION NAME			77-8	5		YEARS				
H#5 , 5 T		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	001	Nov	C#41	Atura A
O	MEAN S.D. TOTAL OBS	1.22.5 c.543	6.813	8.683	6.462	5.574	4.573	3.473	3.709		6.455	c - 379		1016.3 7.6-5 305.
-	MEAN 5 () TOTAL OBS			8.769	7.229	5.644	4.677	3.422	3.713		6.017	0.267	7.706	1016.1 7.74 365.
	MEAN S D TOTAL OBS			8.955	7.316	5.739	4.753	3.498	3.8^6	5.916	6.725			1010.5 7.700 3000
	MEAN S D TOTAL OBS		8.66		7.445		4.615	3.575	3.851	5. 45	6.687	0.367		1017.4 7.619 3650
1	MEAN 5 D TOTAL OBS	0.792		9. 73		5.795		3.53₺	3.894	ڌه هن	6.776		1071.2 9.67i 31	1 10+7 7-876 3050
·	MEAN 5 D TOTAL OBS	8.673		6.847	7.244	5.66.	4.726	3.525	3.917	659	6.50	6.444	9.484	1.15.3 7.656 3652
	MEAN S Ü TOTAL OBS	5 . 4 3c		8.616	7. 45	5 • 492		3.496	3.881	6.107	5.472	8 • 392		7.74.
1	MEAN S D TOTAL OBS	1.22.4. 8.5.9	8.434	8.552	6.769	5 . 376	4.474	3.463	3.715	5.973	6.366	8.363	9.20€	1010+1 7+619 305-
Δ() HÖÇR' <u>:</u>	MEAN 5 D TOTAL OBS	1 - 22 • 4 • 623						1013.91 3.597						1.15.2

END DATE FILMED S-X8